## **APLIKASI ACTSPOT (M-ABSENSI)**

## APLIKASI ACTSPOT (M-ABSENSI Android MySQL Project

Kadek Diva Krishna Murti & Chandra Kirana Poetra

D4 Teknik Informatika, Politeknik Pos Indonesia



Kreatif Industri Nusantara

## Penulis:

Rolly Maulana Awangga

ISBN: 978-602-53897-0-2

### Editor

M. Yusril Helmi Setyawan

## Penyunting:

Syafrial Fachrie Pane Khaera Tunnisa Diana Asri Wijayanti

## Desain sampul dan Tata letak:

Deza Martha Akbar

## Penerbit:

Kreatif Industri Nusantara

## Redaksi:

Jl. Ligar Nyawang No. 2 Bandung 40191 Tel. 022 2045-8529

Email: awangga@kreatif.co.id

## Distributor:

Informatics Research Center Jl. Sariasih No. 54 Bandung 40151 Email: irc@poltekpos.ac.id

Cetakan Pertama, 2020

Hak cipta dilindungi undang-undang Dilarang memperbanyak karya tulis ini dalam bentuk dan dengan cara apapun tanpa ijin tertulis dari penerbit

'Jika Kamu tidak dapat menahan lelahnya belajar, Maka kamu harus sanggup menahan perihnya Kebodohan.' Imam Syafi'i

CONTRIBUTORS		

KADEK DIVA KRISHNA MURTI & CHANDRA KIRANA POETRA D4 Teknik Informatika.,

Politeknik Pos Indonesia, Bandung, Indonesia

## **CONTENTS IN BRIEF**

1	Persiapan	1
2	API	17
3	Mobile	51
4	Website	53
5	Web	87

## DAFTAR ISI

Daftar Gan	ıbar		xi
Daftar Tabe	el		xiii
Foreword			xvii
Kata Penga	ıntar		xix
Acknowled	lgments		xxi
Acronyms			xxiii
Glossary			XXV
List of Sym	nbols		xxvii
Introduction  Kadek Diva		Murti & Chandra Kirana Poetra	xxix
1 Pers	iapan		1
1.1	Persiap	oan dan pengenalan	1
	1.1.1	Instalasi Java	1
	1.1.2	Instalasi Android Studio	1
	1.1.3	Apa itu PHP?	7
			iv

## X DAFTAR ISI

		1.1.4	Sejarah PHP	7
		1.1.5	Sekilas tentang pembuat PHP: Rasmus Lerdorf	8
		1.1.6	Website yang menggunakan PHP	9
		1.1.7	Contoh Kode PHP	9
		1.1.8	Kelebihan PHP	9
		1.1.9	Kekurangan PHP	10
		1.1.10	Referensi belajar PHP	10
		1.1.11	Apa itu Framework?	11
		1.1.12	Mengapa harus menggunakan Framework?	11
		1.1.13	Pengenalan Codeigniter	12
		1.1.14	Konsep MVC (Model View dan Controller)	13
		1.1.15	Kelebihan dan Kekurangan Codeigniter	14
		1.1.16	Instalasi Codeigniter	14
2	API			17
	2.1	API		17
3	Mobi	le		51
	3.1	Perintah	n Navigasi	51
4	Webs	site		53
	4.1	API		53
5	Web			87
	5.1	Web		87
		5.1.1	Dapur Hosting	87

## DAFTAR GAMBAR

1.1	Android Studio Setup.	2
1.2	Instal Android AVD.	2
1.3	Lokasi instal Android Studio.	2
1.4	Membuat shorcut Android Studio.	3
1.5	Proses instalasi.	3
1.6	Proses instalasi selesai.	3
1.7	Jalankan Android Studio.	4
1.8	Import setting instalasi sebelumnya.	4
1.9	Splash screen Android Studio.	4
1.10		5
1.11		5
1.12		5
1.13		6
		хi

xii

1.14		6
1.15		6
1.16	Logo PHP	6
1.17	Creator PHP Rasmus Lerdorf	8
1.18	Website dengan bahasa PHP	9
1.19	Program Hello world yang ditulis dengan PHP	9
1.20	Framework PHP	10
1.21	Framework PHP	11
1.22	Logo Codeigniter	12
1.23	MVC Concept	13
1.24	Tampilan Xampp	14
1.25	Tampilan web Xampp jika berhasil instalasi	15
1.26	Website Codeigniter	15
1.27	Ekstrak File	15
1.28	Hasil Ekstrak File	15
5.1	Upload.	87
5.2	Login.	88
5.3	Upload file.	88
5.4	database file.	89
5.5	config file.	89
5.6	Tampilan	89

## DAFTAR TABEL

## Listings

17
17
18
18
18
19
19
20
20
21
21
22
22
38
38
38
39
39

## XVI LISTINGS

src/api/dosen/dosen_ubah.php	39
src/api/dosen/dosen.php	40
src/api/config.php	53
src/api/conn.php	53
src/api/mahasiswa/mahasiswa_login.php	54
src/api/mahasiswa/mahasiswa_registrasi.php	54
src/api/mahasiswa/mahasiswa_absensi.php	54
src/api/mahasiswa/mahasiswa_kegiatan.php	55
src/api/mahasiswa/mahasiswa_notifikasi.php	55
src/api/mahasiswa/mahasiswa_pembimbing.php	56
src/api/mahasiswa/mahasiswa_perusahaan.php	56
src/api/mahasiswa/mahasiswa_progress.php	57
src/api/mahasiswa/mahasiswa_progress_harian.php	57
src/api/mahasiswa/mahasiswa_ubah.php	58
src/api/mahasiswa/mahasiswa.php	58
src/api/dosen/dosen_login.php	74
src/api/dosen/dosen_mahasiswa.php	74
src/api/dosen/dosen_notifikasi.php	74
src/api/dosen/dosen_progress.php	75
src/api/dosen/dosen_progress_harian.php	75
src/api/dosen_ubah.php	75
src/api/dosen/dosen.php	76
src/web/config/config.php	89
src/web/config/database.php	102
src/web/controllers/ckelolauser.php	104
src/web/controllers/clogin.php	110
src/web/controllers/dashboard.php	111
src/web/models/mdatapeta.php	119
src/web/models/mdatauser.php	119
src/web/models/mlogin.php	139
src/web/models/mregister.php	139
src/web/views/chartview.php	140
src/web/views/dosen.php	141
src/web/views/index.php	160
src/web/views/login.php	185
src/web/views/vgrafik.php	186
src/web/views/vkelolauser.php	187
src/web/views/vregister.php	193

## **FOREWORD** Sepatah kata dari Kaprodi, Kabag Kemahasiswaan dan Mahasiswa

# KATA PENGANTAR Buku ini diciptakan bagi yang awam dengan pemrograman Android sekalipun. D. K. Murti & C. K. Poetra

Bandung, Jawa Barat Januari, 2020

## **ACKNOWLEDGMENTS**

Terima kasih atas semua masukan dari para rekan-rekan agar bisa membuat buku ini lebih baik dan lebih mudah dimengerti.

Terima kasih ini juga ditujukan khusus untuk team IRC yang telah fokus untuk belajar dan memahami bagaimana buku ini mendampingi proses Proyek 3.

D. K. M. & C. K. P.

## **ACRONYMS**

ACGIH American Conference of Governmental Industrial Hygienists

AEC Atomic Energy Commission

OSHA Occupational Health and Safety Commission

SAMA Scientific Apparatus Makers Association

## **GLOSSARY**

git Merupakan manajemen sumber kode yang dibuat oleh linus tor-

vald.

bash Merupakan bahasa sistem operasi berbasiskan \*NIX.

linux Sistem operasi berbasis sumber kode terbuka yang dibuat oleh Li-

nus Torvald

## **SYMBOLS**

- A Amplitude
- & Propositional logic symbol
- a Filter Coefficient
- B Number of Beats

## INTRODUCTION

KADEK DIVA KRISHNA MURTI & CHANDRA KIRANA POETRA

D4 Teknik Informatika Politeknik Pos Indonesia Bandung, Jawa Barat, Indonesia

## **BAB 1**

## **PERSIAPAN**

## 1.1 Persiapan dan pengenalan

## 1.1.1 Instalasi Java

## 1.1.2 Instalasi Android Studio

1. Kemudian klik dua kali pada installer yang telah di-download untuk memulai proses instalasi. Installer akan menampilkan Android Studio Setup seperti gambar berikut, lalu klik Next.



Gambar 1.1 Android Studio Setup.

2. Setelah itu kita diberi opsi untuk menginstal Android Virtual Device. Disini kita biarkan default setting-nya, lalu klik Next.



Gambar 1.2 Instal Android AVD.

3. Kemudian kita diminta untuk memilih lokasi tempat menginstal Android Studionya. Disini kita biarkan default setting-nya, lalu klik Next.



Gambar 1.3 Lokasi instal Android Studio.

4. Setelah itu, kita diberi opsi untuk membuat shortcut dari Android Studio. Disini kita biarkan default setting-nya, lalu klik Install.



Gambar 1.4 Membuat shorcut Android Studio.

5. Kemudian proses instalasi akan berjalan. Show details untuk menampilkan file yang diinstal.



Gambar 1.5 Proses instalasi.

6. Setelah proses instal selesai, klik Next.



Gambar 1.6 Proses instalasi selesai.

7. Kemudian centang Start Android Studio untuk membuka aplikasinya, lalu klik Finish.



Gambar 1.7 Jalankan Android Studio.

8. Ketika Android Studio dijalankan pertama kali, dialog Complete Installation akan muncul dan memberi opsi untuk mengimport setting dari instalasi sebelumnya. Disini kita pilih Do not import settings, lalu klik OK.



Gambar 1.8 Import setting instalasi sebelumnya.

9. Kemudian akan muncul splash screen dari Android Studio.



Gambar 1.9 Splash screen Android Studio.



Gambar 1.10

## 11. Pertama



Gambar 1.11

## 12. Pertama



Gambar 1.12



**Gambar 1.13** .

### 14. Pertama



**Gambar 1.14** .

## 15. Pertama



Gambar 1.15



Gambar 1.16 Logo PHP

## 1.1.3 Apa itu PHP?

PHP adalah bahasa pemrograman yang sering disisipkan ke dalam HTML. PHP memiliki kepanjangan yaitu PHP: Hypertext Preprocessor.Bahasa pemrograman ini menggunakan sistem server-side. Server-side programming adalah jenis bahasa pemrograman yang nantinya script/program tersebut akan dijalankan/diproses oleh server.

## 1.1.4 Sejarah PHP

Pada awalnya PHP merupakan kependekan dari Personal Home Page (Situs personal). PHP pertama kali dibuat oleh Rasmus Lerdorf pada tahun 1995. Pada waktu itu PHP masih bernama Form Interpreted (FI), yang wujudnya berupa sekumpulan skrip yang digunakan untuk mengolah data formulir dari web.

Selanjutnya Rasmus merilis kode sumber tersebut untuk umum dan menamakannya PHP/FI. Dengan perilisan kode sumber ini menjadi sumber terbuka, maka banyak pemrogram yang tertarik untuk ikut mengembangkan PHP.

Pada November 1997, dirilis PHP/FI 2.0. Pada rilis ini, interpreter PHP sudah diimplementasikan dalam program C. Dalam rilis ini disertakan juga modulmodul ekstensi yang meningkatkan kemampuan PHP/FI secara signifikan.

Pada tahun 1997, sebuah perusahaan bernama Zend menulis ulang interpreter PHP menjadi lebih bersih, lebih baik, dan lebih cepat. Kemudian pada Juni 1998, perusahaan tersebut merilis interpreter baru untuk PHP dan meresmikan rilis tersebut sebagai PHP 3.0 dan singkatan PHP diubah menjadi akronim berulang PHP: Hypertext Preprocessing.

Pada pertengahan tahun 1999, Zend merilis interpreter PHP baru dan rilis tersebut dikenal dengan PHP 4.0. PHP 4.0 adalah versi PHP yang paling banyak dipakai pada awal abad ke-21. Versi ini banyak dipakai disebabkan kemampuannya untuk membangun aplikasi web kompleks tetapi tetap memiliki kecepatan dan stabilitas yang tinggi.

Pada Juni 2004, Zend merilis PHP 5.0. Dalam versi ini, inti dari interpreter PHP mengalami perubahan besar. Versi ini juga memasukkan model pemrograman berorientasi objek ke dalam PHP untuk menjawab perkembangan bahasa pemrograman ke arah paradigma berorientasi objek. Peladen web bawaan ditambahkan pada versi 5.4 untuk mempermudah pengembang menjalankan kode PHP tanpa menginstal peladen perangkat lunak.

Versi terbaru dan stabil dari bahasa pemograman PHP saat ini adalah versi 7.4.3 yang dirilis pada tanggal 20 Februari 2020

## 1.1.5 Sekilas tentang pembuat PHP : Rasmus Lerdorf



Gambar 1.17 Creator PHP Rasmus Lerdorf

Rasmus Lerdorf merupakan seorang programmer yang berasal dari Denmark. Dia membuat dan membantu menginspirasi pengkodean bahasa PHP, terutama pada 2 versi awal yang kemudian dikembangkan secara grup bersama dengan Jim Winstead (Yang membuat blo.gs), Stig Bakken, Shane Caraveo, Andi Gutmans, dan juga Zeev Suraski. sampai sekarang ia terus berkontribusi pada projek.

Lerdorf lahir di pulau disko di daerah Greenland dan kemudian pindah ke Denmark pada awal hidupnya. kelaurganya pindah dari Kanada ke Denmark pada tahun 1980, lalu pindah lagi ke kota King di Ontario pada tahun 1983. Dia lulus dari SMA King City pada tahun 1988, dan pada tahun 1993 lulus dari Universitas Waterloo dengan gelar Bachelor of Applied Science di bidang teknik desain sistem. Dua juga ikut berkontribusi dalam Apache HTTP Server dan menambahkan clausa Limit pada mSQL DBMS.

Dari Septermber 2002 sampai November 2009, Lerdorf bekerja di perusahaan Yahoo sebagai Infrastructure Architecture Engineer. Pada tahun 2010 kemudian

bergabung ke perusahaan WePay untuk mengembangkan API (Application Programming Interface). dan pada tahun 2011 ia menjadi seorang konsultan untuk beberapa startup. Kemudian pada 22 Februari 2012 ia bergabung dengan Etsy, sebuah website e-commerce yang berfokus pada hal hal vintage. Dan pada tahun 2013, Rasmus bergabung dengan Jelastic sebagai Senior Advisor untuk membantu mereka mengembangkan teknologi baru.

Selain itu Lerdorf juga sering menjadi pembicara dalam konferensi open source di berbagai belahan dunia. Beberapa topik yang sering dia bahas diantaranya adalah security vulnerabilities dan juga tentang PHP.

Pada tahun 2003, ia di beri penghargaan oleh MIT Technology Review sebagai salah satu dari 100 inovator di dunia yang berada dibawah umur 35

## 1.1.6 Website yang menggunakan PHP



Gambar 1.18 Website dengan bahasa PHP

### 1.1.7 Contoh Kode PHP

```
<?php
    echo "Halo dunia";
?>
```

**Gambar 1.19** Program Hello world yang ditulis dengan PHP

#### 1.1.8 Kelebihan PHP

- Bahasa pemrograman PHP adalah sebuah bahasa script yang tidak melakukan sebuah kompilasi dalam penggunaannya.
- PHP dapat ditemukan di mana mana
- Dalam sisi pengembangan lebih mudah, karena banyaknya developer yang siap membantu dalam pengembangan.

### 10 PERSIAPAN


- Dalam sisi pemahamanan, PHP adalah bahasa scripting yang paling mudah karena memiliki referensi yang banyak.
- PHP adalah bahasa open source yang dapat digunakan di berbagai mesin (Linux, Unix, Macintosh, Windows) dan dapat dijalankan secara runtime melalui console serta juga dapat menjalankan perintah-perintah system
- Ringkas
- Maintenanace Mudah

## 1.1.9 Kekurangan PHP

- Banyak kompetisi, karena PHP adalah bahasa pemrograman yang paling umum
- Terkesan kurang prestigious
- Tidak ideal jika untuk pengembangan skala besar.
- Tidak dapat memisahkan antara tampilan dengan logik dengan baik (Meskipun penggunaan template bisa memperbaikinya)
- PHP mempunyai kelemahan security tertentu yang mana jika programmer tidak jeli dalam melakukan pemrograman dan kurang memperhatikan isu dan konfigurasi PHP

## 1.1.10 Referensi belajar PHP

- php.net
- sitepoint.com
- tutorialspoint.com/php/



Gambar 1.20 Framework PHP


## 1.1.11 Apa itu Framework?

Framework merupakan sebuah kerangka kerja, yang mana hal itu dapat memudahkan kita dalam melakukan pekerjaan. Akan tetapi, jika berkaitan dengan PHP, maka akan menjadi PHP Framework.

PHP Framework adalah suatu kerangka keja yang telah terpola dan memudahkan pengembang website dalam membuat web secara profesional, khususnya menggembangkan web menggunakan script PHP.

Namun perlu diketahui, bahwa PHP Framework berbeda jika dibandingkan dengan sebuah CMS (Content Management System). Meskipun pada dasarnya sama-sama memudahkan dalam pembuatan website. Tapi apabila menggunakan CMS, kita tidak perlu repot-repot dan pusing-pusing menulis script maupun sekumpulan kode. Dengan fitur CMS, semuanya telah dibuat instan dan kita hanya perlu sedikit mengatur bagian konten dan interface-nya saja.

Berbeda dengan Framework, kita tetap harus menuliskan script dan sekumpulan kode untuk dapat membangun sebuah web. Tanpa hal itu, pastinya website anda tidak pernah kelar



Gambar 1.21 Framework PHP

## 1.1.12 Mengapa harus menggunakan Framework?


- Mempercepat proses development
- Code yang terorganisir, reusable (bisa digunakan kembali), maintenable.
- Menghilangkan kekhawatiran tentang low-level security, sebab masing-masing framework telah di desain khusus untuk menangani masalah security yang umumnya menjadi masalah
- Menggunakan pola MVC (model view controller) yang memisahkan antara presentation dan logic
- Konsep web development modern seperti object oriented programming.



Gambar 1.22 Logo Codeigniter

# 1.1.13 Pengenalan Codeigniter

CodeIgniter merupakan aplikasi sumber terbuka yang berupa kerangka kerja PHP dengan model MVC (Model, View, Controller) untuk membangun situs web dinamis dengan menggunakan PHP. CodeIgniter memudahkan pengembang web untuk membuat aplikasi web dengan cepat dan mudah dibandingkan dengan membuatnya dari awal. CodeIgniter dirilis pertama kali pada 28 Februari 2006. Versi stabil terakhir adalah versi 3.1.11



Gambar 1.23 MVC Concept

## 1.1.14 Konsep MVC (Model View dan Controller)

Model View Controller merupakan suatu konsep yang cukup populer dalam pembangunan aplikasi web, berawal pada bahasa pemrograman Small Talk, MVC memisahkan pengembangan aplikasi berdasarkan komponen utama yang membangun sebuah aplikasi seperti manipulasi data, antarmuka pengguna, dan bagian yang menjadi kontrol aplikasi. Terdapat 3 jenis komponen yang membangun suatu pola MVC dalam suatu aplikasi yaitu:

- (a) View, merupakan bagian yang menangani logika presentasi. Pada suatu aplikasi web bagian ini biasanya berupa berkas templat HTML, yang diatur oleh controller. View berfungsi untuk menerima dan merepresentasikan data kepada pengguna. Bagian ini tidak memiliki akses langsung terhadap bagian model.
- (b) Model, biasanya berhubungan langsung dengan pangkalan data untuk memanipulasi data (insert, update, delete, search), menangani validasi dari bagian controller, tetapi tidak dapat berhubungan langsung dengan bagian view.
- (c) Controller, merupakan bagian yang mengatur hubungan antara bagian model dan bagian view, controller berfungsi untuk menerima permintaan dan data dari pengguna kemudian menentukan apa yang akan diproses oleh aplikasi.

## 1.1.15 Kelebihan dan Kekurangan Codeigniter


#### Kelebihan

- Performa sangat cepat: salah satu alasan tidak menggunakan kerangka kerja adalah karena eksekusinya yang lebih lambat daripada PHP from the scracth, tapi CodeIgniter sangat cepat bahkan mungkin bisa dibilang CodeIgniter merupakan kerangka kerja yang paling cepat dibanding kerangka kerja yang lain
- Konfigurasi yang sangat minim
- Banyak komunitas: dengan banyaknya komunitas CI ini, memudahkan kita untuk berinteraksi dengan yang lain, baik itu bertanya atau teknologi terbaru
- Dokumentasi yang sangat lengkap

### Kekurangan

- CodeIgniter tidak ditujukan untuk pembuatan web dengan skala besar.
- Library yang sangat terbatas.
- Tidak Adanya Editor Khusus.

## 1.1.16 Instalasi Codeigniter



**Gambar 1.24** Tampilan Xampp

- Persiapkan xampp dengan mendownloadnya terlebih dahulu di https://www.apachefrie
- Kemudian install Xampp



Gambar 1.25 Tampilan web Xampp jika berhasil instalasi



Gambar 1.26 Website Codeigniter

 Kemudian, dilanjutkan dengan instalasi codeigniter dengan cara mendownload terlebih dahulu codeigniter-nya di https://codeigniter.com/en/download



Gambar 1.27 Ekstrak File

- ekstrak file yang telah di download
- berikut adalah hasil ekstrak file



Gambar 1.28 Hasil Ekstrak File

# API

### 2.1 API

## Perintah navigasi direktori

```
1 <?php
2 define('hostname','localhost');
3 define('user','himatifp_actspot');
4 define('password','actspot2019');
5 define('db_name','himatifp_actspot');
6 ?>

1 <?php
2 require_once 'config.php';
3 class Connection
4 {
    private $connect;
    function __construct()
    {
        $this -> connect = mysqli_connect(hostname, user, password, db_name) or die("DB Connection error.");
    }
    public function get_connection()
```

```
18 API
```

14

```
return $this -> connect;
14
 ?>
1 <?php</pre>
include('mahasiswa.php');
a header('Content-Type: application/json');
 m = new Mahasiswa();
  if (isset($_POST['username'], $_POST['password'])) {
      $user = $_POST['username'];
      $pass = $_POST['password'];
        (!empty($user) && !empty($pass)) {
8
          $m->login_mahasiswa($user, $pass);
      } else {
          sison['status'] = 100;
          $json['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
14
 ?>
16
 <?php
 include ('mahasiswa.php');
  header('Content-Type: application/json');
 m = new Mahasiswa();
  if (isset($_POST['kode_otp'])) {
      $kode_otp = $_POST['kode_otp'];
      if (!empty($kode_otp)) {
          $m->registrasi_mahasiswa($kode_otp);
      } else {
          sison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo ison_encode($ison);
14
  }
15 ?>
1 <?php</pre>
include('mahasiswa.php');
3 header('Content-Type: application/json');
4 $m = new Mahasiswa();
 if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['
      id_dosen'], $_POST['latitude_absensi'], $_POST['longitude_absensi
      '], $_POST['imei_perangkat'], $_POST['id_kegiatan'], $_FILES['
      foto_absensi']['name'], $_POST['tgl_waktu'])) {
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa'];
      $id_dosen = $_POST['id_dosen'];
      $latitude_absensi = $_POST['latitude_absensi'];
      $longitude_absensi = $_POST['longitude_absensi'];
      $imei_perangkat = $_POST['imei_perangkat'];
      $id_kegiatan = $_POST['id_kegiatan'];
      tgl_waktu = POST['tgl_waktu'];
```

\$foto\_absensi = \$\_FILES['foto\_absensi']['name'];

```
$temp_foto_absensi = $_FILES['foto_absensi']['tmp_name'];
               $dir_absensi = "../images/absensi/";
1.9
               if (!empty($id_intern) && !empty($id_mahasiswa) && !empty(
19
               $id_dosen) && !empty($latitude_absensi)
              && !empty($longitude_absensi) && !empty($imei_perangkat) && !
20
               empty($id_kegiatan) && !empty($tgl_waktu)
              && !empty($foto_absensi)) {
                        $take_absensi = $m->ambil_absensi($id_intern, $id_mahasiswa,
               $id_dosen , $latitude_absensi , $longitude_absensi , $imei_perangkat
               , $id_kegiatan , $foto_absensi , $tgl_waktu);
                        if ($take_absensi) {
                                 $upload = move_uploaded_file($temp_foto_absensi,
24
               $dir_absensi.$foto_absensi);
                                 if (!$upload) {
                                           sistem = sistem size = sistem size = size 
26
                                           $json['message'] = 'Gambar gagal terupload';
                                           echo json_encode($json);
28
                                 }
                        }
               } else {
31
                        sison['status'] = 100;
                        $ison['message'] = 'Field tidak boleh kosong';
                        echo json_encode($json);
34
               }
        else {
36
               sison['status'] = 100;
               $ison['message'] = 'Field tidak boleh kosong';
39
              echo json_encode($json);
     }
40
 1 <?php</pre>
 include('mahasiswa.php');
 3 header('Content-Type: application/json');
 4 $m = new Mahasiswa();
 5 $m->list_kegiatan():
 6 ?>
 <?php
 include('mahasiswa.php');
 3 header('Content-Type: application/json');
 4 $m = new Mahasiswa();
     if (isset($_POST['id_intern'], $_POST['id_mahasiswa'])) {
               $id_intern = $_POST['id_intern'];
               $id_mahasiswa = $_POST['id_mahasiswa'];
               if (!empty($id_intern) && !empty($id_mahasiswa)) {
 8
                       $m->list_notifikasi($id_intern, $id_mahasiswa);
 0
               } else {
                        sison['status'] = 100;
                        $json['message'] = 'Field tidak boleh kosongs';
                        echo json_encode($json);
14
     } else {
15
               sistem = 100;
16
               $json['message'] = 'Field tidak boleh kosong';
```

```
20
```

```
echo ison_encode($ison);
19 }
1 <?php</pre>
include('mahasiswa.php');
header('Content-Type: application/json');
4 $m = new Mahasiswa();
5 $m->list_pembimbing();
6 ?>
<?php
include('mahasiswa.php');
3 header('Content-Type: application/json');
4 $m = new Mahasiswa();
5 if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['
      id_pembimbing'], $_POST['latitude_perusahaan'], $_POST['
      longitude_perusahaan'], $_FILES['foto_perusahaan']['name'])) {
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa']:
      $id_pembimbing = $_POST['id_pembimbing'];
      $latitude_perusahaan = $_POST['latitude_perusahaan'];
      $longitude_perusahaan = $_POST['longitude_perusahaan'];
      $foto_perusahaan = $_FILES['foto_perusahaan']['name'];
      $temp_foto_perusahaan = $_FILES['foto_perusahaan']['tmp_name'];
      $dir_perusahaan = "../images/perusahaan/";
14
16
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty(
      $id_pembimbing) && !empty($latitude_perusahaan) && !empty(
       $longitude_perusahaan) && !empty($foto_perusahaan)) {
          if ($m->get_distance($id_pembimbing) == false) {
              sison['status'] = 400;
18
              $json['message'] = 'Jarak kosong';
              echo json_encode($json);
          } else {
               $distance = $m->get_distance($id_pembimbing);
              $gap = $m->distance($latitude_perusahaan,
      $longitude_perusahaan , $distance['lat'], $distance['lon']);
               if (\$gap > 30) {
26
                   sison['status'] = 300;
                   $json['message'] = $gap.'Jarak terlalu jauh';
28
                   echo json_encode($json);
              } else {
30
                   $registrasi_perusahaan = $m->registrasi_perusahaan(
31
       $id_intern , $id_mahasiswa , $id_pembimbing , $latitude_perusahaan ,
      $longitude_perusahaan , $foto_perusahaan );
                   if ($registrasi_perusahaan) {
                       $upload = move_uploaded_file(
       $temp_foto_perusahaan , $dir_perusahaan . $foto_perusahaan ) ;
                       if (!$upload) {
                           sison['status'] = 400;
                           $json['message'] = 'Gambar gagal terupload';
36
                           echo json_encode($json);
38
```

```
}
40
          }
41
      } else {
          sison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosongs';
          echo ison_encode($ison);
45
46
    else {
      sison['status'] = 100;
      $ison['message'] = 'Field tidak boleh kosong';
      echo json_encode($json);
50
51
<?php
include('mahasiswa.php');
3 header('Content-Type: application/json');
4 $m = new Mahasiswa();
  if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['sort'
      1)) {
      $id_mahasiswa = $_POST['id_mahasiswa'];
      $id_intern = $_POST['id_intern'];
      sort = POST['sort'];
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty($sort))
          $m->progress_mahasiswa($id_intern, $id_mahasiswa, $sort);
10
      } else {
          sistem = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
14
    else {
16
      sison['status'] = 100;
      $json['message'] = 'Field tidak boleh kosong';
18
      echo json_encode($json);
19
  }
20
1 <?php</pre>
  include('mahasiswa.php');
3 header('Content-Type: application/json');
4 $m = new Mahasiswa();
  if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['tgl'])
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa'];
      tg1 = POST['tg1'];
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty($tgl))
          $m->progress_mahasiswa_perhari($id_intern, $id_mahasiswa,
      $tgl);
      } else {
          sistem ['status'] = 100;
          $json['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
14
16
```

17 ?>

API

```
<?php
include('mahasiswa.php');
3 header('Content-Type: application/json');
 $m = new Mahasiswa();
  $id_mahasiswa = $_POST['id_mahasiswa'];
    (isset($_POST['kelas'])) $kelas = $_POST['kelas'];
    (isset($_POST['kontak'])) $kontak = $_POST['kontak'];
    (isset($_POST['password'])) $password = $_POST['password'];
  if (isset($_FILES['foto']['name'])){
14
      $foto = $_FILES['foto']['name'];
      $temp_foto = $_FILES['foto']['tmp_name'];
16
      $dir_mahasiswa = "../images/mahasiswa/";
19
20
     (!empty($id_mahasiswa) && !empty($username)) {
     $m->ubah_username($id_mahasiswa, $username);
   elseif (!empty($id_mahasiswa) && !empty($nama)) {
     $m->ubah_nama($id_mahasiswa, $nama);
24
   elseif (!empty($id_mahasiswa) && !empty($kelas)) {
     $m->ubah_kelas($id_mahasiswa, $kelas);
    elseif (!empty($id_mahasiswa) && !empty($angkatan)) {
     $m->ubah_angkatan($id_mahasiswa, $angkatan);
2.8
   elseif (!empty($id_mahasiswa) && !empty($kontak)) {
     $m->ubah_kontak($id_mahasiswa, $kontak);
30
    elseif (!empty($id_mahasiswa) && !empty($password)) {
     $m->ubah_password($id_mahasiswa, $password);
    elseif (!empty($id_mahasiswa) && !empty($foto)){
      $result = $m->ubah_foto($id_mahasiswa, $foto);
34
      if ($result) {
         $upload = move_uploaded_file($temp_foto, $dir_mahasiswa.$foto
      );
         if (!$upload) {
             sistemath{ison['status'] = 400;
38
             $ison['message'] = 'Gambar gagal terupload';
39
             echo json_encode($json);
         }
   else {
44
      sistem ['status'] = 100;
      $ison['message'] = 'Field tidak boleh kosong';
46
     echo json_encode($json);
47
```

```
1 <?php
2 include ('../conn.php');
3 header('Content-Type: application/json');
4 class Mahasiswa
5 {</pre>
```

```
private $db;
6
       private $connection;
       public function __construct()
           this \rightarrow db = new Connection();
           $this -> connection = $this
               ->db
               ->get_connection();
       }
14
       public function ambil_absensi($id_intern, $id_mahasiswa,
       $id_dosen , $latitude_absensi , $longitude_absensi , $imei_perangkat
        $id_kegiatan, $foto_absensi, $tgl_waktu)
           $query = "INSERT INTO absensi(id_intern_absensi,
       id_mahasiswa_absensi, id_dosen_absensi,
           latitude_absensi, longitude_absensi, imei_perangkat_absensi,
       id_kegiatan_absensi,
           foto_absensi, tgl_waktu_absensi) VALUES ('$id_intern', '
20
       $id_mahasiswa',
       '$id_dosen', '$latitude_absensi', '$longitude_absensi', '$imei_perangkat', '$id_kegiatan',
           '$foto_absensi', '$tgl_waktu')";
           $result = mysqli_query($this->connection, $query);
2.4
           if ($result)
26
           {
               sison['status'] = 200;
               $ison['message'] = 'Berhasil melakukan absensi';
               echo json_encode($json);
               mysqli_close ($this -> connection);
               return true:
           else
34
           {
               sison['status'] = 400;
36
               $ison['message'] = 'Gagal melakukan absensi';
               echo json_encode($json);
               mysqli_close ($this -> connection);
30
               return false;
           }
41
42
       public function list_kegiatan()
44
45
           $query = "SELECT * FROM kegiatan";
46
           $result = mysqli_query($this->connection, $query);
           if (mysqli_num_rows($result) > 0)
49
           {
50
               $datas = array();
               while ($row = mysqli_fetch_array($result))
54
                    $datas[] = array(
55
```

```
"id_kegiatan" => $row['id_kegiatan'],
                        "nama_kegiatan" => $row['nama_kegiatan']
                    );
58
                }
59
                sison['status'] = 200;
                $json['message'] = 'Berhasil mengambil data';
62
                sison['data'] = sdatas;
63
64
                echo ison_encode($ison);
65
                mysqli_close ($this -> connection);
           }
67
           else
           {
                sison['status'] = 400;
                $ison['message'] = 'Gagal mengambil data';
                echo json_encode($json);
                mysqli_close ($this -> connection);
           }
74
       }
75
       public function list_pembimbing()
78
           $query = "SELECT * FROM pembimbing_perusahaan";
           $result = mysqli_query($this->connection, $query);
81
           if (mysqli_num_rows(sresult) > 0)
82
83
           {
                $datas = array();
85
                while ($row = mysqli_fetch_array($result))
87
                    $datas[] = array(
88
                        "id_pembimbing" => $row['id_pembimbing'],
                        "nama_pembimbing" => $row['nama_pembimbing'],
90
                        "nama_perusahaan" => $row['
0.1
       nama_perusahaan_perusahaan']
                    );
92
                }
94
                sistemath{ison['status'] = 200;
95
                $json['message'] = 'Berhasil mengambil data';
96
                $json['data'] = $datas;
97
                echo json_encode($json);
99
                mysqli_close($this->connection);
100
           }
101
           else
           {
                104
                $ison['message'] = 'Gagal mengambil data';
                echo json_encode($json);
106
                mysqli_close ($this -> connection);
107
           }
108
       }
```

```
public function get_distance($id_pembimbing)
           $query = "SELECT lat_pembimbing_perusahaan ,
       long_pembimbing_perusahaan FROM pembimbing_perusahaan";
           $result = mysqli_query($this->connection, $query);
           $row = mysqli_fetch_array($result);
           $data = array(
116
               "lat" => $row['lat_pembimbing_perusahaan'].
               "lon" => $row['long_pembimbing_perusahaan']
           if ($result)
           {
               return $data:
           }
           else
           {
126
               return false:
128
       public function registrasi_perusahaan($id_intern, $id_mahasiswa,
130
       $id_pembimbing , $latitude_perusahaan , $longitude_perusahaan ,
       $foto_perusahaan)
           $query = "UPDATE detail_intern SET id_pembimbing_dt_intern="
       $id_pembimbing', latitude_perusahaan='$latitude_perusahaan',
                   longitude_perusahaan='$longitude_perusahaan',
       foto_perusahaan='$foto_perusahaan'
                   WHERE id_intern_dt_intern = '$id_intern' AND
       id_mahasiswa_dt_intern = '$id_mahasiswa' ";
           $result = mysqli_query($this->connection, $query);
136
           if ($this
               ->connection->affected_rows > 0 && $result)
           {
140
               sison['status'] = 200;
               $ison['message'] = 'Berhasil melakukan registrasi
142
       perusahaan';
               echo json_encode($json);
143
               mysqli_close ($this -> connection);
               return true:
           }
           else
           {
148
               sistem [status] = 400;
149
               $json['message'] = 'Gagal melakukan registrasi perusahaan
150
               echo json_encode($json);
               mysqli_close($this->connection);
               return false:
           }
156
       public function progress_mahasiswa($id_intern, $id_mahasiswa,
       $sort)
```

```
158
           query = "SET @rank = 0;";
           mysqli_query($this -> connection, $query);
160
           switch ($sort)
162
                case 'hari':
164
                    query1 = "
165
                SELECT @rank:=@rank+1 AS rank, DAYOFYEAR(
       tgl_waktu_absensi) as date, ROUND(COUNT(*) / 3 * 100, 2)
                as percent FROM absensi WHERE id_intern_absensi=
       $id_intern AND id_mahasiswa_absensi = '$id_mahasiswa'
               GROUP BY DAYOFYEAR(tgl_waktu_absensi) ORDER BY rank ASC";
                    $result1 = mysqli_query($this->connection, $query1);
                    if (mysqli_num_rows(sresult1) > 0)
                    {
                         $datas = array();
                         while (\$row = mysqli_fetch_array(\$result1))
174
                         {
                             $datas[] = array(
                                 "sort" => "Hari ke-" . $row['rank'],
                                 "persen" => $row['percent']
178
                             );
                         }
180
181
                         sistem ['status'] = 201;
182
183
                         $ison['message'] = 'Berhasil mengambil data';
                         sison['data'] = sdatas;
185
                         echo json_encode($json);
186
                         mysqli_close ($this -> connection);
187
188
                    elseif (mysqli_num_rows($result1) == 0)
190
                    ł
                         sistem ['status'] = 300;
                         $json['message'] = 'Data tidak ada';
192
                         //$ison['data'] = [];
                         echo json_encode($json);
                         mysqli_close ($this -> connection);
                    }
196
                    else
197
198
                    {
                         sistem [status] = 400;
                         $ison['message'] = 'Gagal mengambil data';
200
201
                         echo json_encode($json);
202
                         mysqli_close ($this -> connection);
                break;
205
                case 'minggu':
206
                    query2 = "
207
               SELECT @rank:=@rank+1 AS rank, WEEK('tgl_waktu_absensi
       ',1) as week, ROUND(COUNT(*) / 21 * 100, 2)
                as percent FROM 'absensi' WHERE 'id_intern_absensi'=
209
       $id_intern AND 'id_mahasiswa_absensi ' = '$id_mahasiswa'
```

```
GROUP BY WEEK('tgl_waktu_absensi') ORDER BY rank ASC";
                    $result2 = mysqli_query($this->connection, $query2);
                    if (mysqli_num_rows($result2) > 0)
                    {
                        $datas = array();
                        while (\$row = mysqli_fetch_array(\$result2))
                            $datas[] = array(
                                 "sort" => "Minggu ke-" . $row['rank'],
                                 "persen" => $row['percent']
                            );
                        }
                        sison['status'] = 202;
                        $json['message'] = 'Berhasil mengambil data';
225
                        $json['data'] = $datas;
226
                        echo json_encode($json);
                        mysqli_close ($this -> connection);
230
                    elseif (mysqli_num_rows($result2) == 0)
                    {
                        sison['status'] = 300;
                        $json['message'] = 'Data tidak ada';
                        //$ison['data'] = [];
                        echo json_encode($json);
236
                        mysqli_close ($this -> connection);
                    }
                    e1se
                    {
                        sison['status'] = 400;
241
                        $json['message'] = 'Gagal mengambil data';
242
                        echo json_encode($json);
244
                        mysqli_close ($this -> connection);
246
               break:
247
               case 'bulan':
                    query3 = "
249
                    SELECT @rank:=@rank+1 AS rank, MONTH(
250
       tgl_waktu_absensi) as month, ROUND(COUNT(*) / 90 * 100, 2)
                    as percent FROM absensi WHERE id_intern_absensi=
251
                    AND id_mahasiswa_absensi = '$id_mahasiswa'
       $id_intern
                   GROUP BY MONTH(tgl_waktu_absensi) ORDER BY rank ASC";
                    $result3 = mysqli_query($this->connection, $query3);
                    if (mysgli_num_rows(sresult3) > 0)
254
                    {
                        $datas = array();
                        while (\$row = mysqli_fetch_array(\$result3))
258
                            $datas[] = array(
                                 "sort" => "Bulan ke-" . $row['rank'],
261
                                 "persen" => $row['percent']
262
                            );
263
```

```
265
                         sison['status'] = 203;
266
                         $json['message'] = 'Berhasil mengambil data';
267
                         sison['data'] = sdatas;
                        echo ison_encode($ison);
270
                         mysqli_close ($this -> connection);
                    elseif (mysgli_num_rows($result3) == 0)
                         sistem ['status'] = 300;
276
                         $ison['message'] = 'Data tidak ada';
                         //$ison['data'] = [];
                         echo ison_encode($ison);
                         mysqli_close ($this -> connection);
                    }
280
                    else
281
                    {
282
                         sison['status'] = 400;
283
                         $ison['message'] = 'Gagal mengambil data';
284
285
                         echo ison_encode($ison);
286
                         mysqli_close ($this -> connection);
                break:
289
           }
290
201
293
       public function progress_mahasiswa_perhari($id_intern,
       $id_mahasiswa, $tgl)
           $query = "SELECT tgl_waktu_absensi, nama_kegiatan,
295
       foto_absensi, pergeseran_absensi
           FROM absensi
296
           INNER JOIN detail_absensi ON absensi.id_absensi =
207
       detail_absensi.id_absensi_dt_absensi
           INNER JOIN kegiatan ON absensi.id_kegiatan_absensi = kegiatan
298
       .id_kegiatan
           WHERE id_intern_absensi = '$id_intern' AND
299
       id_mahasiswa_absensi = '$id_mahasiswa' AND
           DATE('tgl_waktu_absensi') = '$tgl'";
300
           $result = mysqli_query($this->connection, $query);
301
           if (mysqli_num_rows(sresult) > 0)
303
           {
                $datas = array();
304
305
                while (\$row = mysqli_fetch_array(\$result))
                    $datas[] = array(
308
                        "tgl_waktu" => $row['tgl_waktu_absensi'],
309
                        "kegiatan" => $row['nama_kegiatan'],
                        "foto_absensi" => $row['foto_absensi'],
                        "pergeseran" => $row['pergeseran_absensi']
312
                    );
314
```

```
sison['status'] = 200;
               $ison['message'] = 'Berhasil mengambil data';
317
               sison['data'] = sdatas;
318
               echo json_encode($json);
               mysgli_close ($this -> connection);
           elseif (mysqli_num_rows($result) == 0)
           {
               sison['status'] = 300;
               $json['message'] = 'Data tidak ada';
326
               //$ison['data'] = [];
               echo json_encode($json);
328
               mysgli_close ($this -> connection);
           }
           else
           {
               $json['status'] = $query;
               $json['message'] = 'Gagal mengambil data';
334
               echo json_encode($json);
336
               mysqli_close ($this -> connection);
           }
340
       public function login_mahasiswa($user, $pass)
341
           $query = "SELECT id_intern , id_mahasiswa , username , password ,
        nama_mahasiswa, kelas_mahasiswa,
           angkatan_mahasiswa, foto_mahasiswa, nama_prodi, id_dosen,
           nama_dosen, nama_perusahaan_perusahaan as nama_perusahaan,
       status_perusahaan , id_pembimbing_dt_intern as id_pembimbing
           FROM user
           INNER JOIN mahasiswa ON user.id_user = mahasiswa.id_mahasiswa
347
           INNER JOIN prodi ON mahasiswa.id_prodi_mahasiswa = prodi.
3/19
       id_prodi
           INNER JOIN detail_intern ON user.id_user = detail_intern.
       id_mahasiswa_dt_intern
           INNER JOIN intern ON detail_intern.id_intern_dt_intern =
350
       intern.id intern
           INNER JOIN dosen ON detail_intern.id_dosen_dt_intern = dosen.
       id_dosen
           INNER JOIN pembimbing_perusahaan ON pembimbing_perusahaan.
       id_pembimbing = detail_intern.id_pembimbing_dt_intern
           WHERE username='$user' AND password='$pass' AND user.
       role_user='mahasiswa'
           AND user.status_user='aktif' AND status_intern = 'berjalan'";
           $result = mysqli_query($this->connection, $query);
356
           $row = mysqli_fetch_array($result);
           $id_intern = $row['id_intern'];
358
           if (mysqli_num_rows($result) > 0 && ($row['id_pembimbing'] !=
        "" || $row['id_pembimbing'] != null) && $row['status_perusahaan'
       1 == "diterima")
360
```

```
361
               $query = "SELECT id_intern_dt_intern as id_intern,
362
       id_mahasiswa, username, password, nama_mahasiswa, kelas_mahasiswa
               angkatan_mahasiswa, foto_mahasiswa, nama_prodi, id_dosen,
        nama_dosen, nama_perusahaan_perusahaan as nama_perusahaan,
               status_perusahaan, nama_pembimbing,
364
       id_pembimbing_dt_intern as id_pembimbing FROM user
               INNER JOIN mahasiswa
               ON user.id_user = mahasiswa.id_mahasiswa
               INNER JOIN prodi
               ON mahasiswa.id_prodi_mahasiswa = prodi.id_prodi
368
               INNER JOIN detail_intern
369
               ON user.id_user = detail_intern.id_mahasiswa_dt_intern
               INNER JOIN intern ON detail_intern.id_intern_dt_intern =
       intern.id_intern
               INNER JOIN dosen
               ON detail_intern.id_dosen_dt_intern = dosen.id_dosen
               INNER JOIN pembimbing_perusahaan ON pembimbing_perusahaan
       .id_pembimbing = detail_intern.id_pembimbing_dt_intern
               WHERE username='$user' AND password='$pass' AND user.
       role_user='mahasiswa'
               AND user status user = 'aktif' AND status intern = '
       berjalan '";
               $result = mysqli_query($this->connection, $query);
378
               $row = mysqli_fetch_array($result);
380
               $data = arrav(
                   "id_intern" => $id_intern,
382
                   "id_mahasiswa" => $row['id_mahasiswa'],
                   "username" => $row['username'],
                   "password" => $row['password'].
385
                   "nama_mahasiswa" => $row['nama_mahasiswa'],
                   "kelas_mahasiswa" => $row['kelas_mahasiswa'],
387
                   "angkatan_mahasiswa" => $row['angkatan_mahasiswa'],
388
                   "foto_mahasiswa" => $row['foto_mahasiswa'],
                   "nama_prodi" => $row['nama_prodi'],
                   "id_dosen" => $row['id_dosen'].
                   "nama_dosen" => $row['nama_dosen'],
202
                   "nama_pembimbing" => $row['nama_pembimbing'],
393
                   "nama_perusahaan" => $row['nama_perusahaan']
394
395
               );
               sison['status'] = 201;
397
               $json['message'] = 'Login berhasil';
308
               sin('data') = sdata;
300
               echo ison_encode($ison);
               mysqli_close($this->connection);
402
           }
403
           elseif (mysqli_num_rows($result) > 0 && ($row['id_pembimbing'
404
       ] != "" || $row['id_pembimbing'] != null) && ($row['
       status_perusahaan'] == "" || $row['status_perusahaan'] == null))
           {
405
               data = array(
406
```

```
"id_intern" => $id_intern,
407
                    "id_mahasiswa" => $row['id_mahasiswa'],
408
                    "username" => $row['username'].
409
                    "password" => $row['password'],
410
                    "nama_mahasiswa" => $row['nama_mahasiswa'],
                    "kelas_mahasiswa" => $row['kelas_mahasiswa'],
                    "angkatan_mahasiswa" => $row['angkatan_mahasiswa'],
413
                    "foto_mahasiswa" => $row['foto_mahasiswa'].
414
                    "nama_prodi" => $row['nama_prodi'],
                    "id_dosen" => $row['id_dosen'],
                    "nama_dosen" => $row['nama_dosen'],
                    "nama_perusahaan" => $row['nama_perusahaan']
418
               );
419
420
               sison['status'] = 203;
               $ison['message'] = 'Login berhasil';
               sistemath{ison['data'] = sistemath{}data;
424
               echo ison_encode($ison):
               mysqli_close ($this -> connection);
426
           }
           else
428
               $query = "SELECT id_intern_dt_intern as id_intern,
       id_mahasiswa, username, password, nama_mahasiswa, kelas_mahasiswa
               angkatan_mahasiswa, foto_mahasiswa, nama_prodi, id_dosen,
431
        nama_dosen, kode_otp,
               status_perusahaan, id_pembimbing_dt_intern as
       id_pembimbing FROM user INNER JOIN mahasiswa
               ON user.id_user = mahasiswa.id_mahasiswa INNER JOIN prodi
               ON mahasiswa.id_prodi_mahasiswa = prodi.id_prodi INNER
434
       JOIN detail intern
               ON user.id_user = detail_intern.id_mahasiswa_dt_intern
435
               INNER JOIN intern ON detail_intern.id_intern_dt_intern =
436
       intern.id_intern
               INNER JOIN dosen
437
               ON detail_intern.id_dosen_dt_intern = dosen.id_dosen
               WHERE username='$user' AND password='$pass' AND user.
       role_user='mahasiswa'
               AND user.status_user='aktif' AND status_intern = '
440
       berjalan '";
441
               $result = mysqli_query($this->connection, $query);
               $row = mysqli_fetch_array($result);
443
               if (mysqli_num_rows($result) > 0 && ($row['id_pembimbing'
444
       ] == "" || $row['id_pembimbing'] == null) && ($row['
       status_perusahaan'] == "" || $row['status_perusahaan'] == null)
       && srow['kode_otp'] == '-')
445
                    data = array(
446
                        "id_intern" => $id_intern,
447
                        "id_mahasiswa" => $row['id_mahasiswa'],
                        "username" => $row['username'],
440
                        "password" => $row['password'],
450
                        "nama_mahasiswa" => $row['nama_mahasiswa'],
451
```

```
"kelas_mahasiswa" => $row['kelas_mahasiswa'],
452
                                                                       "angkatan_mahasiswa" => $row['angkatan_mahasiswa'
453
                      1,
                                                                        "foto_mahasiswa" => $row['foto_mahasiswa'],
454
                                                                       "nama_prodi" => $row['nama_prodi'],
                                                                       "id_dosen" => $row['id_dosen'],
                                                                       "nama_dosen" => $row['nama_dosen']
457
                                                           ):
458
                                                           sison['status'] = 202;
                                                           $ison['message'] = 'Login berhasil';
                                                           sin ['data'] = sdata;
462
463
                                                           echo json_encode($json);
464
                                                           mysgli_close ($this -> connection);
                                              }
166
                                              else
467
                                              {
468
469
                                                           sistem ['status'] = 400;
470
                                                           $ison['message'] = 'Username dan password salah';
                                                           echo json_encode($json);
472
                                                           mysqli_close ($this -> connection);
473
                                 }
475
                     }
476
477
                     public function registrasi_mahasiswa($kode_otp)
478
                                  $query = "SELECT kode_otp FROM mahasiswa WHERE kode_otp = "
480
                     $kode_otp '";
481
                                  $result = mysqli_query($this->connection, $query);
482
                                 $row = mysqli_fetch_array($result);
                                  if (mysqli_num_rows(sresult) > 0)
484
                                 {
485
486
                                              $query = "UPDATE mahasiswa SET kode_otp='-' WHERE
487
                      kode_otp='$kode_otp'";
100
                                              $result = mysqli_query($this->connection, $query);
489
                                              if (Sthis
490
                                                          ->connection->affected_rows > 0 && $result)
491
                                              {
                                                           \frac{1}{3} \frac{1}
493
                                                           $json['message'] = 'Registrasi berhasil';
494
495
                                                           echo json_encode($json);
                                                           mysqli_close ($this -> connection);
407
                                              }
498
                                              else
499
                                              {
500
501
                                                           sistemath{ison['status'] = 400;
502
                                                           $json['message'] = 'Registrasi gagal';
503
                                                           echo json_encode($json);
504
```

```
mysgli_close ($this -> connection);
505
               }
506
           }
507
           else
508
           {
               sison['status'] = 400;
511
               $ison['message'] = 'Registrasi gagal';
               echo ison_encode($ison);
               mysgli_close ($this -> connection);
           }
       }
       public function list_notifikasi($id_intern, $id_mahasiswa)
518
           $query = "SELECT id_intern , nama_pembimbing , pesan_notifikasi
       , nama_perusahaan_perusahaan , tgl_waktu_notifikasi FROM
       notifikasi
522 INNER JOIN pembimbing_perusahaan ON id_pembimbing =
       id_pembimbing_notifikasi
  INNER JOIN mahasiswa ON id_mahasiswa = id_mahasiswa_notifikasi
  INNER JOIN intern ON id_intern = id_intern_notifikasi
  WHERE id_mahasiswa_notifikasi='$id_mahasiswa' AND
       id_intern_notifikasi='$id_intern' ORDER BY tgl_waktu_notifikasi
       DESC":
526
527
           $result = mysqli_query($this->connection, $query);
           if (mvsqli_num_rows(sresult) > 0)
           {
530
               $datas = array();
               $kalimat1 = "melakukan absensi pada";
               $kalimat2 = "mengkonfirmasi absensi";
534
               $kalimat3 = "mendaftar ke perusahaan";
               $kalimat4 = "mengkonfirmasi pendaftaran";
536
               while (\$row = mysqli_fetch_array(\$result))
                    pesan = "";
540
                    if (preg_match("~\b" . $row['pesan_notifikasi'] . "\b
541
         , $kalimat1))
                        $pesan = "Anda " . $row['pesan_notifikasi'];
543
544
                    elseif (preg_match("~\b" . $row['pesan_notifikasi'] .
545
        "\b~", $kalimat2))
546
                        $pesan = ucwords(($row['nama_pembimbing'])) . " "
547
        . $row['pesan_notifikasi'] . " Anda pada";
548
                    elseif (preg_match("~\b" . $row['pesan_notifikasi'] .
        "\b~", $kalimat3))
550
```

```
$pesan = "Anda " . $row['pesan_notifikasi'] . " "
        . ucwords(($row['nama_perusahaan_perusahaan'])) . " pada";
                    elseif (preg_match("~\b" . $row['pesan_notifikasi'] .
553
        "\b~", $kalimat4))
                         $pesan = ucwords(($row['nama_pembimbing'])) . " "
        . $row['pesan_notifikasi'] . " Anda pada";
                    $datas[] = array(
                         "id_intern" => $row['id_intern'],
550
                         "pesan" => $pesan . " " . date_format(date_create
560
       (\text{srow}['tgl\_waktu\_notifikasi']), 'd F Y \p\u\k\u\1 G:i A'),
                         "tgl_waktu" => $row['tgl_waktu_notifikasi']
                    ):
563
                }
564
565
                sistemath{ison['status'] = 200;
                $ison['message'] = 'Berhasil mengambil notifikasi';
                sison['data'] = sdatas;
568
569
                echo json_encode($json);
                mysqli_close ($this -> connection);
           elseif (mysqli_num_rows($result) == 0)
574
           {
                sison['status'] = 300;
                $ison['message'] = 'Notifikasi tidak ada';
                echo json_encode($json);
                mysqli_close ($this -> connection);
579
           else
581
           {
                sison['status'] = 400;
583
                $ison['message'] = 'Gagal mengambil notifikasi';
584
                echo json_encode($json);
                mysqli_close ($this -> connection);
586
           }
587
       }
588
589
       public function ubah_username($id_mahasiswa, $username)
591
            $query = "UPDATE user SET username='$username' WHERE id_user
592
       ='$id_mahasiswa'";
           $result = mysqli_query($this->connection, $query);
595
           if (Sthis
596
                ->connection->affected_rows > 0 && $result)
597
           {
                sistemath{ison['status'] = 200;
599
                $json['message'] = 'Username berhasil diubah';
600
                echo json_encode($json);
601
```

```
mysgli_close ($this -> connection);
602
           }
603
           else
604
           {
605
                sison['status'] = 400;
                $ison['message'] = 'Username gagal diubah';
                echo ison_encode($ison);
608
                mysqli_close ($this -> connection);
609
610
           }
       }
611
       public function ubah_nama($id_mahasiswa, $nama)
613
614
            $query = "UPDATE mahasiswa SET nama_mahasiswa='$nama' WHERE
615
       id_mahasiswa='$id_mahasiswa'";
            $result = mysqli_query($this->connection, $query);
617
            if ($this
                ->connection->affected_rows > 0 && $result)
            {
                sison['status'] = 200;
622
                $json['message'] = 'Nama berhasil diubah';
623
                echo json_encode($json);
                mysqli_close ($this -> connection);
            }
626
           else
627
628
           {
                sison['status'] = 400;
                $json['message'] = 'Nama gagal diubah';
                echo json_encode($json);
631
                mysqli_close ($this -> connection);
           }
633
       public function ubah_kelas($id_mahasiswa, $kelas)
637
            $query = "UPDATE mahasiswa SET kelas_mahasiswa='$kelas' WHERE
638
        id_mahasiswa='$id_mahasiswa'";
            $result = mysqli_query($this->connection, $query);
640
641
642
            if ($this
                ->connection->affected_rows > 0 && $result)
            {
644
                sistem ['status'] = 200;
645
                $json['message'] = 'Nama berhasil diubah';
646
                echo json_encode($json);
                mysqli_close ($this -> connection);
           }
649
           else
           {
                sison['status'] = 400;
                $json['message'] = 'Nama gagal diubah';
653
                echo json_encode($json);
                mysqli_close ($this -> connection);
655
```

```
36
```

```
API
```

```
}
657
658
659
       public function ubah_angkatan($id_mahasiswa, $angkatan)
            $query = "UPDATE mahasiswa SET angkatan_mahasiswa='$angkatan'
        WHERE id_mahasiswa='$id_mahasiswa'";
662
            $result = mysqli_query($this->connection, $query);
            if ($this
               ->connection->affected_rows > 0 && $result)
666
           {
667
                sison['status'] = 200;
668
                $ison['message'] = 'Nama berhasil diubah';
                echo json_encode($json);
                mysqli_close ($this -> connection);
           }
672
           else
673
           {
                sison['status'] = 400;
675
                $ison['message'] = 'Nama gagal diubah';
                echo json_encode($json);
677
                mysqli_close ($this -> connection);
           }
680
681
682
       public function ubah_kontak($id_mahasiswa, $kontak)
            $query = "UPDATE mahasiswa SET kontak_mahasiswa='$kontak'
684
       WHERE id_mahasiswa='$id_mahasiswa'";
685
            $result = mysqli_query($this->connection, $query);
686
            if ($this
               ->connection->affected_rows > 0 && $result)
           {
690
                sison['status'] = 200;
691
                $json['message'] = 'Kontak berhasil diubah';
                echo json_encode($json);
693
                mysqli_close ($this -> connection);
694
           }
695
           else
696
           {
                sison['status'] = 400;
698
                $json['message'] = 'Kontak gagal diubah';
699
                echo ison_encode($ison);
700
                mysqli_close ($this -> connection);
701
           }
703
       public function ubah_foto($id_mahasiswa, $foto)
706
            $query = "UPDATE mahasiswa SET foto_mahasiswa='$foto' WHERE
707
       id_mahasiswa='$id_mahasiswa'";
708
```

```
$result = mysqli_query($this->connection, $query);
709
            if ($this
               ->connection->affected_rows > 0 && $result)
                sison['status'] = 200;
                $ison['message'] = 'Foto berhasil diubah';
                echo json_encode($json);
                mysqli_close ($this -> connection);
                return true:
           }
           else
720
           {
                sison['status'] = 400;
                $ison['message'] = 'Foto gagal diubah';
                echo json_encode($json);
                mysqli_close ($this -> connection);
                return false:
726
           }
       }
       public function ubah_password($id_mahasiswa, $password)
730
            $query = "UPDATE user SET password='$password' WHERE id_user
       ='$id_mahasiswa'";
           $result = mysqli_query($this->connection, $query);
734
            if ($this
               ->connection->affected_rows > 0 && $result)
           {
                sison['status'] = 200;
                $json['message'] = 'Password berhasil diubah';
740
                echo json_encode($json);
                mysqli_close ($this -> connection);
           }
           else
744
           {
745
                sistemath{ison['status'] = 400;
                $ison['message'] = 'Password gagal diubah';
747
                echo json_encode($json);
748
                mysqli_close ($this -> connection);
749
750
           }
       public function distance ($lat1, $lon1, $lat2, $lon2)
754
            if ((\$1at1 == \$1at2) \&\& (\$1on1 == \$1on2))
           {
                return 0:
           }
758
           else
           {
                \theta = 10n1 - 10n2;
761
                dist = \sin(\deg 2rad(\$lat1)) * \sin(\deg 2rad(\$lat2)) + \cos(
762
       deg2rad(\$lat1)) * cos(deg2rad(\$lat2)) * cos(deg2rad(\$theta));
```

```
38 API
```

```
dist = acos(dist);
               $dist = rad2deg($dist);
764
               miles = dist * 60 * 1.1515;
765
766
               return ($miles * 1.609344) * 1000;
767
          }
       }
769
 1 <?php</pre>
  include ('dosen.php');
  header('Content-Type: application/json');
  d = new Dosen();
  if (isset($_POST['username'], $_POST['password'])) {
       $user = $_POST['username'];
       $pass = $_POST['password'];
       if (!empty($user) && !empty($pass)) {
           $d->login_dosen($user, $pass);
10
       } else {
           $ison['message'] = 'Field tidak boleh kosong';
           echo json_encode($json);
  }
16
  ?>
  <?php
  include ('dosen.php');
  header('Content-Type: application/json');
 4 \text{ } \text{d} = \text{new Dosen();}
  if (isset($_POST['id_dosen'])) {
       $id_dosen = $_POST['id_dosen'];
       if (!empty($id_dosen)) {
           $d->list_mahasiswa($id_dosen);
 8
 o
       } else {
           $json['message'] = 'Field tidak boleh kosong';
           echo json_encode($json);
    else {
14
           sison['status'] = 100;
           $ison['message'] = 'Field tidak boleh kosong';
           echo json_encode($json);
18
  ?>
19
  <?php
  include ('dosen.php');
  header('Content-Type: application/json');
  d = new Dosen();
  if (isset($_POST['id_dosen'])) {
       $id_dosen = $_POST['id_dosen'];
```

if (!empty(\$id\_dosen)) {

} else {

9

\$d->list\_notifikasi(\$id\_dosen);

sistem = 100;

```
API
          $json['message'] = 'Field tidak boleh kosong';
          echo ison_encode($ison);
      }
  } else {
14
          sison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo ison_encode($ison);
18
19
include('dosen.php');
a header('Content-Type: application/json');
if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['sort'
      1)) {
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa'];
      sort = POST['sort'];
8
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty($sort))
          $d->progress_mahasiswa($id_intern, $id_mahasiswa, $sort);
      } else {
          sistemath{ison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
16
1 <?php</pre>
include('dosen.php');
3 header('Content-Type: application/json');
4 \text{ } \text{d} = \text{new Dosen();}
 if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['tgl'])
      ) {
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa'];
      tg1 = POST['tg1'];
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty($tgl))
          $d->progress_mahasiswa_perhari($id_intern, $id_mahasiswa,
      $tg1);
      } else {
```

```
1 <?php
2 include('dosen.php');
3 header('Content-Type: application/json');
4 \text{ } \text{d} = \text{new Dosen}();
6 $id_dosen = $_POST['id_dosen'];
7 if (isset($_POST['username'])) $username = $_POST['username'];
```

\$json['message'] = 'Field tidak boleh kosong';

sison['status'] = 100;

echo ison\_encode(\$ison);

14

16

}

```
40
```

```
if (isset($_POST['nama'])) $nama = $_POST['nama'];
              (isset($_POST['kontak'])) $kontak = $_POST['kontak'];
      if (isset($_POST['password'])) $password = $_POST['password'];
       if (isset($_FILES['foto']['name'])){
                   $foto = $_FILES['foto']['name'];
                   $temp_foto = $_FILES['foto']['tmp_name'];
1.4
                   $dir_dosen = "../images/dosen/";
       }
18
       if (!empty($id_dosen) && !empty($username)) {
10
20
                  $d->ubah_username($id_dosen, $username);
            elseif (!empty($id_dosen) && !empty($nama)) {
                  $d->ubah_nama($id_dosen, $nama);
           elseif (!empty($id_dosen) && !empty($kontak)) {
                  $d->ubah_kontak($id_dosen, $kontak);
2.4
           elseif (!empty($id_dosen) && !empty($password)) {
                  $d->ubah_password($id_dosen, $password);
26
            elseif (!empty($id_dosen) && !empty($foto)){
                   $result = $d->ubah_foto($id_dosen, $foto);
28
                   if ($result) {
29
                               $upload = move_uploaded_file($temp_foto, $dir_dosen.$foto);
30
                               if (!$upload) {
                                           sistem = sistem size = sistem size = size 
                                           $ison['message'] = 'Gambar gagal terupload';
                                           echo json_encode($json);
34
35
                               }
            else {
                   sistem ['status'] = 100;
38
                   $json['message'] = 'Field tidak boleh kosong';
30
                  echo json_encode($json);
40
41
```

```
1 <?php</pre>
include('../conn.php');
3 header('Content-Type: application/json');
4 class Dosen
  {
5
      private $db:
      private $connection;
      public function __construct()
           this \rightarrow db
                              = new Connection();
           $this -> connection = $this -> db-> get_connection();
      }
14
      public function list_mahasiswa($id_dosen)
           $query = "SELECT id_mahasiswa, nama_perusahaan_perusahaan,
      lama_internship, nama_mahasiswa, foto_mahasiswa,
           angkatan_mahasiswa, foto_perusahaan, kelas_mahasiswa,
      foto_mahasiswa, nama_prodi,
```

```
nama_pembimbing, lat_pembimbing_perusahaan,
18
      long_pembimbing_perusahaan, id_intern, COUNT(
      id_mahasiswa_dt_absensi) as jumlah_absensi
          FROM detail_intern
          INNER JOIN intern ON detail_intern.id_intern_dt_intern =
20
      intern.id_intern
          INNER JOIN pembimbing_perusahaan ON detail_intern.
      id_pembimbing_dt_intern = pembimbing_perusahaan.id_pembimbing
          INNER JOIN mahasiswa ON detail_intern.id_mahasiswa_dt_intern
      = mahasiswa.id_mahasiswa
          INNER JOIN prodi ON mahasiswa.id_prodi_mahasiswa= prodi.
      id_prodi
          INNER JOIN detail_absensi ON detail_intern.
24
      id_mahasiswa_dt_intern = detail_absensi.id_mahasiswa_dt_absensi
          WHERE id_dosen_dt_intern = '$id_dosen' AND status_intern = '
       berjalan '";
26
          $result = mysqli_query($this->connection, $query);
          if (mvsqli_num_rows(\$result) > 0) {
28
              $datas = array();
               while (srow = mysqli_fetch_array(sresult)) {
31
                   datas[] = array(
                   "id_intern" => $row['id_intern'],
                   "id_mahasiswa" => $row['id_mahasiswa'],
34
                   "nama_perusahaan" => ucwords($row['
       nama_perusahaan_perusahaan']),
                   "nama_mahasiswa" => ucwords($row['nama_mahasiswa']),
36
                   "foto_mahasiswa" => $row['foto_mahasiswa'],
                   "angkatan_mahasiswa" => $row['angkatan_mahasiswa'],
38
                   "foto_perusahaan" => $row['foto_perusahaan'],
                   "kelas_mahasiswa" => strtoupper($row['kelas_mahasiswa
40
      <sup>'</sup>]),
                   "foto_mahasiswa" => $row['foto_mahasiswa'],
                   "nama_prodi" => ucwords($row['nama_prodi']),
42
                   "nama_pembimbing" => ucwords($row['nama_pembimbing'])
                   "latitude_perusahaan" => $row['
      lat_pembimbing_perusahaan'],
                   "longitude_perusahaan" => $row['
45
      long_pembimbing_perusahaan'],
                   "presentase_internship" => round($row['jumlah_absensi
46
       ']/$row['lama_internship']*100,1)
              );
              }
48
              sistem = 200;
50
               $ison['message'] = 'Berhasil mengambil mahasiswa';
              sistemath{ison['data'] = sistemath{}datas;
              echo json_encode($json);
               mysqli_close ($this -> connection);
          } elseif (mysqli_num_rows($result) == 0) {
               57
              $json['message'] = 'Mahasiswa tidak ada';
58
59
```

61

62

63

67

68 69

70

81

23

85

87

88

0.1

93

97 98

```
echo ison_encode($ison);
               mysgli_close ($this -> connection);
           } else {
               sison['status'] = 400;
               $ison['message'] = 'Gagal mengambil mahasiswa';
               echo json_encode($json);
               mysgli_close ($this -> connection);
66
           }
       }
       public function login_dosen($user, $pass)
           query = SELECT
           username, password, id_dosen, nama_dosen, foto_dosen,
       id_intern , nama_prodi
          FROM user
74
           INNER JOIN dosen ON user.id_user = dosen.id_dosen
           INNER JOIN detail_intern ON user.id_user = detail_intern.
76
       id_dosen_dt_intern
           INNER JOIN intern ON detail_intern.id_intern_dt_intern =
       intern.id_intern
           INNER JOIN prodi ON dosen.id_prodi_dosen = prodi.id_prodi
78
          WHERE username = '$user' AND password = '$pass' AND
       status_user='aktif' AND role_user='dosen'":
           $result = mysqli_query($this->connection, $query);
82
           $row = mysqli_fetch_array($result);
           if (mysqli_num_rows(sresult) > 0) {
               data = array(
                   "username" => $row['username'],
                   "password" => $row['password'],
                   "id_dosen" => $row['id_dosen'],
                   "nama_dosen" => ucwords($row['nama_dosen']),
                   "foto_dosen" => $row['foto_dosen'],
90
                   "nama_prodi" => ucwords($row['nama_prodi'])
               );
               sison['status'] = 200;
0.5
               $json['message'] = 'Berhasil melakukan login';
               $json['data'] = $data;
               echo json_encode($json);
               mysqli_close ($this -> connection);
100
           } elseif (mysqli_num_rows($result) == 0) {
                   sistem = 300;
102
                   $ison['message'] = 'Username atau password salah';
                   echo json_encode($json);
105
                   mysqli_close ($this -> connection);
106
               } else {
               sison['status'] = 400;
               $json['message'] = 'Gagal melakukan login';
109
               echo json_encode($json);
```

```
mysgli_close ($this -> connection);
           }
       }
114
       public function progress_mahasiswa($id_intern, $id_mahasiswa,
116
       $sort)
       {
           squery = "SET @rank=0:":
118
           mysqli_query($this->connection, $query);
           switch ($sort) {
               case 'hari':
               query1 = "
               SELECT @rank:=@rank+1 AS rank, DAYOFYEAR(
       tgl_waktu_absensi) as date, ROUND(COUNT(*) / 3 * 100, 2)
               as percent FROM absensi WHERE id_intern_absensi='
       $id_intern ' AND id_mahasiswa_absensi = '$id_mahasiswa'
               GROUP BY DAYOFYEAR(tgl_waktu_absensi) ORDER BY rank ASC";
               $result1 = mysqli_query($this->connection, $query1);
126
               if (mysqli_num_rows($result1) > 0) {
                    $datas = array();
129
                    while (\$row = mysqli_fetch_array(\$result1)) {
130
                        $datas[] = array(
                        "sort" => "Hari ke-". $row['rank'],
                        "persen" => $row['percent']
               );
134
                    }
136
                    sison['status'] = 201;
                    $json['message'] = 'Berhasil mengambil progress';
138
                    sistemath{ison['data'] = sistemath{}datas;
139
140
                    echo ison_encode($ison);
141
                    mysqli_close ($this -> connection);
               } elseif (mysqli_num_rows($result1) == 0) {
                    sistem = 300;
                    $json['message'] = 'Progress tidak ada';
                    //$ison['data'] = [];
                    echo json_encode($json);
148
                    mysqli_close($this->connection);
149
               } else {
150
                    sison['status'] = 400;
                    $json['message'] = 'Gagal mengambil progress';
                    echo json_encode($json);
                    mysqli_close ($this -> connection);
154
               break:
               case 'minggu':
               query2 = "
158
               SELECT @rank:=@rank+1 AS rank, WEEK(tgl_waktu_absensi,1)
       as week, ROUND(COUNT(*) / 21 * 100, 2)
               as percent FROM absensi WHERE id_intern_absensi='
       $id_intern ' AND id_mahasiswa_absensi = '$id_mahasiswa'
               GROUP BY WEEK(tgl_waktu_absensi) ORDER BY rank ASC";
161
               $result2 = mysqli_query($this->connection, $query2);
162
```

```
if (mysqli_num_rows(sresult2) > 0) {
163
                                              $datas = array();
164
165
                                              while ($row = mysqli_fetch_array($result2)) {
166
                                                        $datas[] = array(
167
                                                        "sort" => "Minggu ke-". $row['rank'].
                                                        "persen" => $row['percent']
169
                                    ):
                                              }
                                              sison['status'] = 202;
                                              $json['message'] = 'Berhasil mengambil progress';
174
                                              sison['data'] = sdatas;
176
                                              echo ison_encode($ison);
                                              mysqli_close ($this -> connection);
                                    } elseif (mysqli_num_rows($result2) == 0) {
                                              sison['status'] = 300;
180
                                              $ison['message'] = 'Progress tidak ada';
181
                                              echo json_encode($json);
183
                                              mysqli_close ($this -> connection);
184
                                    } else {
185
                                              sison['status'] = 400;
186
                                              $json['message'] = 'Gagal mengambil progress';
                                              echo json_encode($json);
188
                                              mysqli_close ($this -> connection);
189
100
                                    break:
                                    case 'bulan':
                                              query3 = "
103
                                             SELECT @rank:=@rank+1 AS rank, MONTH(
                 tgl_waktu_absensi) as month, ROUND(COUNT(*) / 90 * 100, 2)
                                              as percent FROM absensi WHERE id_intern_absensi='
                 $id_intern ' AND id_mahasiswa_absensi = '$id_mahasiswa'
                                             GROUP BY MONTH(tgl_waktu_absensi) ORDER BY rank ASC";
106
                                              $result3 = mysqli_query($this -> connection, $query3);
197
                                              if (mysqli_num_rows(sresult3) > 0) {
198
                                                        $datas = array();
                                                        while ($row = mysqli_fetch_array($result3)) {
201
                                                                  $datas[] = array(
202
                                                                           "sort" => "Bulan ke-". $row['rank'],
203
                                                                            "persen" => $row['percent']
205
                                                                 );
                                                        }
206
207
                                                        sison['status'] = 203;
                                                        $json['message'] = 'Berhasil mengambil progress';
209
                                                        sin = sin 
                                                        echo json_encode($json);
                                                        mysqli_close ($this -> connection);
                                              } elseif (mysqli_num_rows($result3) == 0) {
214
                                                        sistem = 300;
                                                        $json['message'] = 'Progress tidak ada';
216
```

```
echo ison_encode($ison);
218
                        mysqli_close ($this -> connection);
                    } else {
                        sison['status'] = 400:
                        $ison['message'] = 'Gagal mengambil progress';
                        echo ison_encode($ison);
                        mysqli_close ($this -> connection);
224
               break:
           }
       }
228
       public function progress_mahasiswa_perhari($id_intern,
230
       $id_mahasiswa, $tgl)
           $query = "SELECT id_absensi, tgl_waktu_absensi,
       nama_kegiatan, foto_absensi, pergeseran_absensi
           FROM absensi
           INNER JOIN detail_absensi ON absensi.id_absensi =
234
       detail_absensi.id_absensi_dt_absensi
           INNER JOIN kegiatan ON absensi.id_kegiatan_absensi = kegiatan
       .id_kegiatan
           WHERE id_intern_absensi = '$id_intern' AND
       id_mahasiswa_absensi = '$id_mahasiswa' AND
           DATE(tgl_waktu_absensi) = '$tgl'";
           $result = mysqli_query($this->connection, $query);
238
230
           if (mysgli_num_rows(sresult) > 0) {
               $datas = array();
241
               while ($row = mysqli_fetch_array($result)) {
242
                    $datas[] =
                                array (
                        "id_absensi" => $row['id_absensi'],
244
                        "tgl_waktu" => $row['tgl_waktu_absensi'],
                    "kegiatan" => ucfirst($row['nama_kegiatan']),
246
                    "foto_absensi" => $row['foto_absensi'],
                    "pergeseran" => $row['pergeseran_absensi']." M"
248
               );
249
               sistem = 200;
               $json['message'] = 'Berhasil mengambil progress harian';
               sison['data'] = sdatas;
               echo json_encode($json);
256
               mysqli_close ($this -> connection);
           } elseif (mysqli_num_rows($result) == 0) {
               sison['status'] = 300;
               $json['message'] = 'Progress harian tidak ada';
261
               echo json_encode($json);
262
               mysqli_close ($this -> connection);
263
           } else {
               sistemath{ison['status'] = 400;
265
               $json['message'] = 'Gagal mengambil progress harian';
266
               echo json_encode($json);
267
```

```
mysgli_close ($this -> connection);
268
           }
260
       public function list_notifikasi($id_dosen){
274
           $query = "SELECT id_intern , nama_mahasiswa , nama_pembimbing ,
       nama_perusahaan_perusahaan , pesan_notifikasi ,
       tgl_waktu_notifikasi FROM notifikasi INNER JOIN
       pembimbing_perusahaan ON id_pembimbing = id_pembimbing_notifikasi
        INNER JOIN mahasiswa ON id_mahasiswa = id_mahasiswa_notifikasi
       INNER JOIN intern ON id_intern = id_intern_notifikasi WHERE
       id_dosen_notifikasi='$id_dosen' AND status_intern='berjalan'
       ORDER BY tgl_waktu_notifikasi DESC ":
           $result = mysqli_query($this->connection, $query);
278
           if (mvsali_num_rows(\$result) > 0) {
               $datas = array();
281
               $kalimat1 = "melakukan absensi pada";
282
               $kalimat2 = "mengkonfirmasi absensi";
283
               $kalimat3 = "mendaftar ke perusahaan";
               $kalimat4 = "mengkonfirmasi pendaftaran";
285
286
               while ($row = mysqli_fetch_array($result)) {
287
                    pesan = "";
288
                    if (preg_match ("~\b". $row['pesan_notifikasi']."\b~",
       $kalimat1)){
                        $pesan = ucwords($row['nama_mahasiswa'])." ".$row
290
       ['pesan_notifikasi'];
                    } elseif (preg_match ("~\b". $row['pesan_notifikasi']."\b
291
       ~", $kalimat2)){
                        $pesan = ucwords($row['nama_pembimbing'])." ".
292
       $row['pesan_notifikasi']." ".ucwords($row['nama_mahasiswa'])."
       pada":
                    }elseif(preg_match("~\b".$row['pesan_notifikasi']."\b
293
       ~", $kalimat3)){
                        $pesan = ucwords(($row['nama_mahasiswa']))." ".
294
       $row['pesan_notifikasi']." ".ucwords($row['
       nama_perusahaan_perusahaan'])." pada";
                    } elseif (preg_match ("~\b". $row['pesan_notifikasi']."\b
295
       ~", $kalimat4)){
                        $pesan = ucwords($row['nama_pembimbing'])." ".
296
       $row['pesan_notifikasi']." ".ucwords($row['nama_mahasiswa'])."
       pada";
                    }
                    $datas[] = array(
299
                    "id_intern" => $row['id_intern'],
300
                   "pesan" => $pesan." ". date_format(date_create($row['
301
       tgl_waktu_notifikasi']), 'd F Y \p\u\k\u\l G: i A'),
                    "tgl_waktu" => $row['tgl_waktu_notifikasi']
302
               );
303
304
```

```
305
306
               sison['status'] = 200;
307
               $json['message'] = 'Berhasil mengambil notifikasi';
308
               sison['data'] = sdatas;
311
               echo ison_encode($ison);
               mysqli_close ($this -> connection);
           } elseif (mysqli_num_rows($result) == 0) {
               sison['status'] = 300;
314
               $ison['message'] = 'Notifikasi tidak ada';
               echo json_encode($json);
               mysqli_close ($this -> connection);
318
           } else {
               sison['status'] = 400;
               $json['message'] = 'Gagal mengambil notifikasi';
               echo json_encode($json);
               mysqli_close ($this -> connection);
           }
324
       }
326
       public function ubah_username($id_dosen, $username){
           $query = "UPDATE user SET username='$username' WHERE id_user
       ='$id_dosen'";
           $result = mysqli_query($this->connection, $query);
330
           if ($this -> connection -> affected_rows > 0 && $result) {
               sison['status'] = 200;
               $json['message'] = 'Username berhasil diubah';
               echo json_encode($json);
               mysqli_close ($this -> connection);
336
           } else {
               sison['status'] = 400;
338
               $json['message'] = 'Username gagal diubah';
               echo json_encode($json);
340
               mysqli_close ($this -> connection);
341
           }
343
344
       public function ubah_nama($id_dosen, $nama){
345
           $query = "UPDATE dosen SET nama_dosen='$nama' WHERE id_dosen
       ='$id_dosen'";
347
           $result = mysqli_query($this->connection, $query);
348
349
           if ($this -> connection -> affected_rows > 0 && $result) {
               $json['message'] = 'Nama berhasil diubah';
352
               echo json_encode($json);
               mysqli_close ($this -> connection);
           } else {
               sistemath{ison['status'] = 400;
356
               $json['message'] = 'Nama berhasil diubah';
               echo json_encode($json);
358
```

```
mysgli_close ($this -> connection);
                          }
360
                 }
361
362
                 public function ubah_kontak($id_dosen, $kontak){
                           $query = "UPDATE dosen SET kontak_dosen='$kontak' WHERE
                 id_dosen='$id_dosen'";
365
                           $result = mysqli_query($this->connection, $query);
367
                           if ($this->connection->affected_rows > 0 && $result) {
                                     sistemath{ison['status'] = 200;
360
                                     $ison['message'] = 'Kontak berhasil diubah';
                                     echo json_encode($json);
                                     mysgli_close ($this -> connection);
                           } else {
                                     sistem = sistem size = sistem size = size 
                                     $json['message'] = 'Kontak gagal diubah';
                                     echo ison_encode($ison):
                                     mysqli_close ($this -> connection);
                          }
279
380
                 public function ubah_foto($id_dosen, $foto){
                           $query = "UPDATE dosen SET foto_dosen='$foto' WHERE id_dosen
382
                 ='$id_dosen'":
383
38/
                           $result = mysqli_query($this->connection, $query);
                           if ($this -> connection -> affected_rows > 0 && $result) {
386
                                     sistemath{ison['status'] = 200;
                                     $json['message'] = 'Foto berhasil diubah';
                                     echo ison_encode($ison);
389
                                     mysqli_close ($this -> connection);
                                     return true;
391
                          } else {
302
                                     sison['status'] = 400;
393
                                     $ison['message'] = 'Foto gagal diubah';
                                     echo json_encode($json);
                                     mysqli_close ($this -> connection);
206
                                     return false:
397
                          }
398
399
                 public function ubah_password($id_dosen, $password){
401
                           $query = "UPDATE user SET password='$password' WHERE id_user
402
                 ='$id_dosen'";
                           $result = mysqli_query($this->connection, $query);
404
405
                           if ($this -> connection -> affected_rows > 0 && $result) {
406
                                     407
                                     $ison['message'] = 'Password berhasil diubah';
                                     echo json_encode($json);
400
                                     mysqli_close ($this -> connection);
                           } else {
411
```

### **BAB 3**

# **MOBILE**

#### 3.1 Perintah Navigasi

Perintah navigasi direktori

## **WEBSITE**

#### 4.1 API

<?php

Perintah navigasi direktori

```
define('hostname', 'localhost');
define('user', 'himatifp_actspot');
define('password', 'actspot2019');
define('db_name', 'himatifp_actspot');
?>

??php
require_once 'config.php';
class Connection
{
    private $connect;
    function __construct()
    {
        $this -> connect = mysqli_connect(hostname, user, password, db_name) or die("DB Connection error.");
}
public function get_connection()
```

```
54 WEBSITE
```

```
return $this -> connect;
14
 ?>
1 <?php</pre>
include('mahasiswa.php');
3 header('Content-Type: application/json');
 m = new Mahasiswa();
  if (isset($_POST['username'], $_POST['password'])) {
      $user = $_POST['username'];
      $pass = $_POST['password'];
        (!empty($user) && !empty($pass)) {
8
          $m->login_mahasiswa($user, $pass);
      } else {
          sison['status'] = 100;
          $json['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
14
 ?>
16
 <?php
 include ('mahasiswa.php');
  header('Content-Type: application/json');
 m = new Mahasiswa();
  if (isset($_POST['kode_otp'])) {
      $kode_otp = $_POST['kode_otp'];
      if (!empty($kode_otp)) {
          $m->registrasi_mahasiswa($kode_otp);
      } else {
          sison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo ison_encode($ison);
14
  }
15 ?>
1 <?php</pre>
include('mahasiswa.php');
3 header('Content-Type: application/json');
4 $m = new Mahasiswa();
 if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['
      id_dosen'], $_POST['latitude_absensi'], $_POST['longitude_absensi
      '], $_POST['imei_perangkat'], $_POST['id_kegiatan'], $_FILES['
      foto_absensi']['name'], $_POST['tgl_waktu'])) {
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa'];
      $id_dosen = $_POST['id_dosen'];
      $latitude_absensi = $_POST['latitude_absensi'];
      $longitude_absensi = $_POST['longitude_absensi'];
      $imei_perangkat = $_POST['imei_perangkat'];
      $id_kegiatan = $_POST['id_kegiatan'];
      tgl_waktu = POST['tgl_waktu'];
      $foto_absensi = $_FILES['foto_absensi']['name'];
14
```

```
$temp_foto_absensi = $_FILES['foto_absensi']['tmp_name'];
               $dir_absensi = "../images/absensi/";
1.9
               if (!empty($id_intern) && !empty($id_mahasiswa) && !empty(
19
               $id_dosen) && !empty($latitude_absensi)
              && !empty($longitude_absensi) && !empty($imei_perangkat) && !
20
               empty($id_kegiatan) && !empty($tgl_waktu)
              && !empty($foto_absensi)) {
                        $take_absensi = $m->ambil_absensi($id_intern, $id_mahasiswa,
               $id_dosen , $latitude_absensi , $longitude_absensi , $imei_perangkat
               , $id_kegiatan , $foto_absensi , $tgl_waktu);
                        if ($take_absensi) {
                                 $upload = move_uploaded_file($temp_foto_absensi,
24
               $dir_absensi.$foto_absensi);
                                 if (!$upload) {
                                           sistem = sistem size = sistem size = size 
26
                                           $json['message'] = 'Gambar gagal terupload';
                                           echo json_encode($json);
28
                                 }
                        }
               } else {
31
                        sison['status'] = 100;
                        $ison['message'] = 'Field tidak boleh kosong';
                        echo json_encode($json);
34
               }
        else {
36
               sison['status'] = 100;
               $ison['message'] = 'Field tidak boleh kosong';
39
              echo json_encode($json);
     }
40
 1 <?php</pre>
 include('mahasiswa.php');
 3 header('Content-Type: application/json');
 4 $m = new Mahasiswa();
 5 $m->list_kegiatan():
 6 ?>
 <?php
 include('mahasiswa.php');
 3 header('Content-Type: application/json');
 4 $m = new Mahasiswa();
     if (isset($_POST['id_intern'], $_POST['id_mahasiswa'])) {
               $id_intern = $_POST['id_intern'];
               $id_mahasiswa = $_POST['id_mahasiswa'];
               if (!empty($id_intern) && !empty($id_mahasiswa)) {
 8
                       $m->list_notifikasi($id_intern, $id_mahasiswa);
 0
               } else {
                        sison['status'] = 100;
                        $json['message'] = 'Field tidak boleh kosongs';
                        echo json_encode($json);
14
     } else {
15
               sistem = 100;
16
               $json['message'] = 'Field tidak boleh kosong';
```

```
echo ison_encode($ison);
19
 }
1 <?php</pre>
include('mahasiswa.php');
header('Content-Type: application/json');
4 $m = new Mahasiswa();
5 $m->list_pembimbing();
6 ?>
<?php
include('mahasiswa.php');
3 header('Content-Type: application/json');
4 $m = new Mahasiswa();
5 if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['
      id_pembimbing'], $_POST['latitude_perusahaan'], $_POST['
      longitude_perusahaan'], $_FILES['foto_perusahaan']['name'])) {
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa']:
      $id_pembimbing = $_POST['id_pembimbing'];
      $latitude_perusahaan = $_POST['latitude_perusahaan'];
      $longitude_perusahaan = $_POST['longitude_perusahaan'];
      $foto_perusahaan = $_FILES['foto_perusahaan']['name'];
      $temp_foto_perusahaan = $_FILES['foto_perusahaan']['tmp_name'];
      $dir_perusahaan = "../images/perusahaan/";
14
16
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty(
      $id_pembimbing) && !empty($latitude_perusahaan) && !empty(
       $longitude_perusahaan) && !empty($foto_perusahaan)) {
          if ($m->get_distance($id_pembimbing) == false) {
              sison['status'] = 400;
18
              $json['message'] = 'Jarak kosong';
              echo json_encode($json);
          } else {
               $distance = $m->get_distance($id_pembimbing);
              $gap = $m->distance($latitude_perusahaan,
      $longitude_perusahaan , $distance['lat'], $distance['lon']);
               if (\$gap > 30) {
26
                   sison['status'] = 300;
                   $json['message'] = $gap.'Jarak terlalu jauh';
28
                   echo json_encode($json);
              } else {
30
                   $registrasi_perusahaan = $m->registrasi_perusahaan(
31
       $id_intern , $id_mahasiswa , $id_pembimbing , $latitude_perusahaan ,
      $longitude_perusahaan , $foto_perusahaan );
                   if ($registrasi_perusahaan) {
                       $upload = move_uploaded_file(
       $temp_foto_perusahaan , $dir_perusahaan . $foto_perusahaan ) ;
                       if (!$upload) {
                           sison['status'] = 400;
                           $json['message'] = 'Gambar gagal terupload';
36
                           echo json_encode($json);
38
```

```
}
40
          }
41
      } else {
          sison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosongs';
          echo ison_encode($ison);
45
46
    else {
      sison['status'] = 100;
      $ison['message'] = 'Field tidak boleh kosong';
      echo json_encode($json);
50
51
<?php
include('mahasiswa.php');
3 header('Content-Type: application/json');
4 $m = new Mahasiswa();
  if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['sort'
      1)) {
      $id_mahasiswa = $_POST['id_mahasiswa'];
      $id_intern = $_POST['id_intern'];
      sort = POST['sort'];
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty($sort))
          $m->progress_mahasiswa($id_intern, $id_mahasiswa, $sort);
10
      } else {
          sistem = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
14
    else {
16
      sison['status'] = 100;
      $json['message'] = 'Field tidak boleh kosong';
18
      echo json_encode($json);
19
  }
20
1 <?php</pre>
  include('mahasiswa.php');
3 header('Content-Type: application/json');
4 $m = new Mahasiswa();
  if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['tgl'])
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa'];
      tg1 = POST['tgl'];
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty($tgl))
          $m->progress_mahasiswa_perhari($id_intern, $id_mahasiswa,
      $tgl);
      } else {
          sistem ['status'] = 100;
          $json['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
14
16
```

```
17 ?>
 <?php
include('mahasiswa.php');
3 header('Content-Type: application/json');
 $m = new Mahasiswa();
  $id_mahasiswa = $_POST['id_mahasiswa'];
    (isset($_POST['kelas'])) $kelas = $_POST['kelas'];
    (isset($_POST['kontak'])) $kontak = $_POST['kontak'];
    (isset($_POST['password'])) $password = $_POST['password'];
  if (isset($_FILES['foto']['name'])){
14
      $foto = $_FILES['foto']['name'];
      $temp_foto = $_FILES['foto']['tmp_name'];
16
      $dir_mahasiswa = "../images/mahasiswa/";
19
20
     (!empty($id_mahasiswa) && !empty($username)) {
     $m->ubah_username($id_mahasiswa, $username);
   elseif (!empty($id_mahasiswa) && !empty($nama)) {
     $m->ubah_nama($id_mahasiswa, $nama);
24
   elseif (!empty($id_mahasiswa) && !empty($kelas)) {
     $m->ubah_kelas($id_mahasiswa, $kelas);
   elseif (!empty($id_mahasiswa) && !empty($angkatan)) {
     $m->ubah_angkatan($id_mahasiswa, $angkatan);
2.8
   elseif (!empty($id_mahasiswa) && !empty($kontak)) {
     $m->ubah_kontak($id_mahasiswa, $kontak);
30
    elseif (!empty($id_mahasiswa) && !empty($password)) {
     $m->ubah_password($id_mahasiswa, $password);
    elseif (!empty($id_mahasiswa) && !empty($foto)){
      $result = $m->ubah_foto($id_mahasiswa, $foto);
34
      if ($result) {
         $upload = move_uploaded_file($temp_foto, $dir_mahasiswa.$foto
      );
         if (!$upload) {
             sistemath{ison['status'] = 400;
38
             $ison['message'] = 'Gambar gagal terupload';
39
             echo json_encode($json);
         }
   else {
44
      sistem ['status'] = 100;
      $ison['message'] = 'Field tidak boleh kosong';
46
     echo json_encode($json);
47
```

```
1 <?php
2 include ('../conn.php');
3 header('Content-Type: application/json');
4 class Mahasiswa
5 {</pre>
```

```
private $db;
6
       private $connection;
       public function __construct()
           this \rightarrow db = new Connection();
           $this -> connection = $this
               ->db
               ->get_connection();
       }
14
       public function ambil_absensi($id_intern, $id_mahasiswa,
       $id_dosen , $latitude_absensi , $longitude_absensi , $imei_perangkat
        $id_kegiatan, $foto_absensi, $tgl_waktu)
           $query = "INSERT INTO absensi(id_intern_absensi,
       id_mahasiswa_absensi, id_dosen_absensi,
           latitude_absensi, longitude_absensi, imei_perangkat_absensi,
       id_kegiatan_absensi,
           foto_absensi, tgl_waktu_absensi) VALUES ('$id_intern', '
20
       $id_mahasiswa',
       '$id_dosen', '$latitude_absensi', '$longitude_absensi', '$imei_perangkat', '$id_kegiatan',
           '$foto_absensi', '$tgl_waktu')";
           $result = mysqli_query($this->connection, $query);
2.4
           if ($result)
26
           {
               sison['status'] = 200;
               $ison['message'] = 'Berhasil melakukan absensi';
               echo json_encode($json);
               mysqli_close ($this -> connection);
               return true:
           else
34
           {
               sison['status'] = 400;
36
               $ison['message'] = 'Gagal melakukan absensi';
               echo json_encode($json);
               mysqli_close ($this -> connection);
30
               return false;
           }
41
42
       public function list_kegiatan()
44
45
           $query = "SELECT * FROM kegiatan";
46
           $result = mysqli_query($this->connection, $query);
           if (mysqli_num_rows($result) > 0)
49
           {
50
               $datas = array();
               while ($row = mysqli_fetch_array($result))
54
                    $datas[] = array(
55
```

```
"id_kegiatan" => $row['id_kegiatan'],
                         "nama_kegiatan" => $row['nama_kegiatan']
                     );
58
                }
59
                sison['status'] = 200;
                $json['message'] = 'Berhasil mengambil data';
62
                sison['data'] = sdatas;
63
64
                echo ison_encode($ison);
65
                mysqli_close ($this -> connection);
            }
67
            else
            {
                sison['status'] = 400;
                $ison['message'] = 'Gagal mengambil data';
                echo json_encode($json);
                mysqli_close ($this -> connection);
            }
74
       }
75
       public function list_pembimbing()
78
            $query = "SELECT * FROM pembimbing_perusahaan";
80
            $result = mysqli_query($this->connection, $query);
81
            if (mysqli_num_rows(sresult) > 0)
82
83
            {
                $datas = array();
85
                while ($row = mysqli_fetch_array($result))
87
                     $datas[] = array(
88
                         "id_pembimbing" => $row['id_pembimbing'],
                         "nama_pembimbing" => $row['nama_pembimbing'],
90
                         "nama_perusahaan" => $row['
0.1
       nama_perusahaan_perusahaan']
                     );
92
                }
94
                sistemath{ison['status'] = 200;
95
                $json['message'] = 'Berhasil mengambil data';
96
                sison['data'] = sdatas;
97
                echo json_encode($json);
99
                mysqli_close ($this -> connection);
100
            }
101
            else
            {
                sistemath{ison['status'] = 400;
104
                $ison['message'] = 'Gagal mengambil data';
                echo json_encode($json);
106
                mysqli_close ($this -> connection);
107
            }
108
       }
```

```
public function get_distance($id_pembimbing)
           $query = "SELECT lat_pembimbing_perusahaan ,
       long_pembimbing_perusahaan FROM pembimbing_perusahaan";
           $result = mysqli_query($this->connection, $query);
           $row = mysqli_fetch_array($result);
           $data = array(
116
               "lat" => $row['lat_pembimbing_perusahaan'].
               "lon" => $row['long_pembimbing_perusahaan']
           if ($result)
           {
               return $data:
           }
           else
           {
126
               return false:
128
       public function registrasi_perusahaan($id_intern, $id_mahasiswa,
130
       $id_pembimbing , $latitude_perusahaan , $longitude_perusahaan ,
       $foto_perusahaan)
           $query = "UPDATE detail_intern SET id_pembimbing_dt_intern="
       $id_pembimbing', latitude_perusahaan='$latitude_perusahaan',
                    longitude_perusahaan='$longitude_perusahaan',
       foto_perusahaan='$foto_perusahaan'
                   WHERE id_intern_dt_intern = '$id_intern' AND
       id_mahasiswa_dt_intern = '$id_mahasiswa' ";
           $result = mysqli_query($this->connection, $query);
136
           if ($this
               ->connection->affected_rows > 0 && $result)
           {
140
               sison['status'] = 200;
               $ison['message'] = 'Berhasil melakukan registrasi
142
       perusahaan';
               echo json_encode($json);
143
               mysqli_close ($this -> connection);
               return true:
           }
           else
           {
148
               sistem [status] = 400;
149
               $json['message'] = 'Gagal melakukan registrasi perusahaan
150
               echo json_encode($json);
               mysqli_close ($this -> connection);
               return false:
           }
156
       public function progress_mahasiswa($id_intern, $id_mahasiswa,
       $sort)
```

```
158
           query = "SET @rank = 0;";
           mysqli_query($this -> connection, $query);
160
           switch ($sort)
162
                case 'hari':
164
                    query1 = "
165
                SELECT @rank:=@rank+1 AS rank, DAYOFYEAR(
       tgl_waktu_absensi) as date, ROUND(COUNT(*) / 3 * 100, 2)
                as percent FROM absensi WHERE id_intern_absensi=
       $id_intern AND id_mahasiswa_absensi = '$id_mahasiswa'
               GROUP BY DAYOFYEAR(tgl_waktu_absensi) ORDER BY rank ASC";
                    $result1 = mysqli_query($this->connection, $query1);
                    if (mysqli_num_rows(sresult1) > 0)
                    {
                         $datas = array();
                         while (\$row = mysqli_fetch_array(\$result1))
174
                         {
                             $datas[] = array(
                                 "sort" => "Hari ke-" . $row['rank'],
                                 "persen" => $row['percent']
178
                             );
                         }
180
181
                         sistem ['status'] = 201;
182
183
                         $ison['message'] = 'Berhasil mengambil data';
                         sison['data'] = sdatas;
185
                         echo json_encode($json);
186
                         mysqli_close ($this -> connection);
187
188
                    elseif (mysqli_num_rows($result1) == 0)
190
                    ł
                         sistem ['status'] = 300;
                         $json['message'] = 'Data tidak ada';
192
                         // $json['data'] = [];
                         echo json_encode($json);
                         mysqli_close ($this -> connection);
                    }
196
                    else
197
198
                    {
                         sistem [status] = 400;
                         $ison['message'] = 'Gagal mengambil data';
200
201
                         echo json_encode($json);
202
                         mysqli_close ($this -> connection);
203
                break;
205
                case 'minggu':
206
                    query2 = "
207
                SELECT @rank:=@rank+1 AS rank, WEEK('tgl_waktu_absensi
       ',1) as week, ROUND(COUNT(*) / 21 * 100, 2)
                as percent FROM 'absensi' WHERE 'id_intern_absensi'=
209
       $id_intern AND 'id_mahasiswa_absensi ' = '$id_mahasiswa'
```

```
GROUP BY WEEK('tgl_waktu_absensi') ORDER BY rank ASC";
                    $result2 = mysqli_query($this->connection, $query2);
                    if (mysqli_num_rows($result2) > 0)
                    {
                        $datas = array();
                        while (\$row = mysqli_fetch_array(\$result2))
                            $datas[] = array(
                                 "sort" => "Minggu ke-" . $row['rank'],
                                 "persen" => $row['percent']
                            );
                        }
                        sison['status'] = 202;
                        $json['message'] = 'Berhasil mengambil data';
225
                        $json['data'] = $datas;
226
                        echo json_encode($json);
                        mysqli_close ($this -> connection);
230
                    elseif (mysqli_num_rows($result2) == 0)
                    {
                        sison['status'] = 300;
                        $json['message'] = 'Data tidak ada';
                        //$ison['data'] = [];
                        echo json_encode($json);
236
                        mysqli_close ($this -> connection);
                    }
                    e1se
                    {
                        sison['status'] = 400;
241
                        $json['message'] = 'Gagal mengambil data';
242
                        echo json_encode($json);
244
                        mysqli_close ($this -> connection);
246
               break:
247
               case 'bulan':
                    query3 = "
249
                    SELECT @rank:=@rank+1 AS rank, MONTH(
250
       tgl_waktu_absensi) as month, ROUND(COUNT(*) / 90 * 100, 2)
                    as percent FROM absensi WHERE id_intern_absensi=
251
                    AND id_mahasiswa_absensi = '$id_mahasiswa'
       $id_intern
                   GROUP BY MONTH(tgl_waktu_absensi) ORDER BY rank ASC";
                    $result3 = mysqli_query($this->connection, $query3);
                    if (mysgli_num_rows(sresult3) > 0)
254
                    {
                        $datas = array();
                        while (\$row = mysqli_fetch_array(\$result3))
258
                            $datas[] = array(
                                 "sort" => "Bulan ke-" . $row['rank'],
261
                                 "persen" => $row['percent']
262
                            );
263
```

```
265
                         sison['status'] = 203;
266
                         $json['message'] = 'Berhasil mengambil data';
267
                         sison['data'] = sdatas;
                        echo ison_encode($ison);
270
                         mysqli_close ($this -> connection);
                    elseif (mysgli_num_rows($result3) == 0)
                         sistem ['status'] = 300;
276
                         $ison['message'] = 'Data tidak ada';
                         //$ison['data'] = [];
                         echo ison_encode($ison);
                         mysqli_close ($this -> connection);
                    }
280
                    else
281
                    {
282
                         sison['status'] = 400;
283
                         $ison['message'] = 'Gagal mengambil data';
284
285
                         echo ison_encode($ison);
286
                         mysqli_close ($this -> connection);
                break:
289
           }
290
201
293
       public function progress_mahasiswa_perhari($id_intern,
       $id_mahasiswa, $tgl)
           $query = "SELECT tgl_waktu_absensi, nama_kegiatan,
295
       foto_absensi, pergeseran_absensi
           FROM absensi
296
           INNER JOIN detail_absensi ON absensi.id_absensi =
207
       detail_absensi.id_absensi_dt_absensi
           INNER JOIN kegiatan ON absensi.id_kegiatan_absensi = kegiatan
298
       .id_kegiatan
           WHERE id_intern_absensi = '$id_intern' AND
299
       id_mahasiswa_absensi = '$id_mahasiswa' AND
           DATE('tgl_waktu_absensi') = '$tgl'";
300
           $result = mysqli_query($this->connection, $query);
301
           if (mysqli_num_rows(sresult) > 0)
303
           {
                $datas = array();
304
305
                while (\$row = mysqli_fetch_array(\$result))
                    $datas[] = array(
308
                        "tgl_waktu" => $row['tgl_waktu_absensi'],
309
                        "kegiatan" => $row['nama_kegiatan'],
                        "foto_absensi" => $row['foto_absensi'],
                        "pergeseran" => $row['pergeseran_absensi']
312
                    );
314
```

```
sison['status'] = 200;
               $ison['message'] = 'Berhasil mengambil data';
317
               sison['data'] = sdatas;
318
               echo json_encode($json);
               mysgli_close ($this -> connection);
           elseif (mysqli_num_rows($result) == 0)
           {
               sison['status'] = 300;
               $json['message'] = 'Data tidak ada';
326
               //$ison['data'] = [];
               echo json_encode($json);
328
               mysgli_close ($this -> connection);
           }
           else
           {
               $json['status'] = $query;
               $json['message'] = 'Gagal mengambil data';
334
               echo json_encode($json);
336
               mysqli_close ($this -> connection);
           }
340
       public function login_mahasiswa($user, $pass)
341
           $query = "SELECT id_intern , id_mahasiswa , username , password ,
        nama_mahasiswa, kelas_mahasiswa,
           angkatan_mahasiswa, foto_mahasiswa, nama_prodi, id_dosen,
           nama_dosen, nama_perusahaan_perusahaan as nama_perusahaan,
       status_perusahaan , id_pembimbing_dt_intern as id_pembimbing
           FROM user
           INNER JOIN mahasiswa ON user.id_user = mahasiswa.id_mahasiswa
347
           INNER JOIN prodi ON mahasiswa.id_prodi_mahasiswa = prodi.
3/19
       id_prodi
           INNER JOIN detail_intern ON user.id_user = detail_intern.
       id_mahasiswa_dt_intern
           INNER JOIN intern ON detail_intern.id_intern_dt_intern =
350
       intern.id intern
           INNER JOIN dosen ON detail_intern.id_dosen_dt_intern = dosen.
       id_dosen
           INNER JOIN pembimbing_perusahaan ON pembimbing_perusahaan.
       id_pembimbing = detail_intern.id_pembimbing_dt_intern
           WHERE username='$user' AND password='$pass' AND user.
       role_user='mahasiswa'
           AND user.status_user='aktif' AND status_intern = 'berjalan'";
           $result = mysqli_query($this->connection, $query);
356
           $row = mysqli_fetch_array($result);
           $id_intern = $row['id_intern'];
358
           if (mysqli_num_rows($result) > 0 && ($row['id_pembimbing'] !=
        "" || $row['id_pembimbing'] != null) && $row['status_perusahaan'
       1 == "diterima")
360
```

```
361
               $query = "SELECT id_intern_dt_intern as id_intern,
362
       id_mahasiswa, username, password, nama_mahasiswa, kelas_mahasiswa
               angkatan_mahasiswa, foto_mahasiswa, nama_prodi, id_dosen,
        nama_dosen, nama_perusahaan_perusahaan as nama_perusahaan,
               status_perusahaan, nama_pembimbing,
364
       id_pembimbing_dt_intern as id_pembimbing FROM user
               INNER JOIN mahasiswa
               ON user.id_user = mahasiswa.id_mahasiswa
               INNER JOIN prodi
               ON mahasiswa.id_prodi_mahasiswa = prodi.id_prodi
368
               INNER JOIN detail_intern
369
               ON user.id_user = detail_intern.id_mahasiswa_dt_intern
               INNER JOIN intern ON detail_intern.id_intern_dt_intern =
       intern.id_intern
               INNER JOIN dosen
               ON detail_intern.id_dosen_dt_intern = dosen.id_dosen
               INNER JOIN pembimbing_perusahaan ON pembimbing_perusahaan
       .id_pembimbing = detail_intern.id_pembimbing_dt_intern
               WHERE username='$user' AND password='$pass' AND user.
       role_user='mahasiswa'
               AND user status user = 'aktif' AND status intern = '
       berjalan '";
               $result = mysqli_query($this->connection, $query);
378
               $row = mysqli_fetch_array($result);
380
               $data = arrav(
                   "id_intern" => $id_intern,
382
                   "id_mahasiswa" => $row['id_mahasiswa'],
                   "username" => $row['username'],
                   "password" => $row['password'].
385
                   "nama_mahasiswa" => $row['nama_mahasiswa'],
                   "kelas_mahasiswa" => $row['kelas_mahasiswa'],
387
                   "angkatan_mahasiswa" => $row['angkatan_mahasiswa'],
388
                   "foto_mahasiswa" => $row['foto_mahasiswa'],
                   "nama_prodi" => $row['nama_prodi'],
                   "id_dosen" => $row['id_dosen'].
                   "nama_dosen" => $row['nama_dosen'],
202
                   "nama_pembimbing" => $row['nama_pembimbing'],
393
                   "nama_perusahaan" => $row['nama_perusahaan']
394
395
               );
               sison['status'] = 201;
397
               $json['message'] = 'Login berhasil';
308
               sin('data') = sdata;
300
               echo ison_encode($ison);
               mysqli_close ($this -> connection);
402
           }
403
           elseif (mysqli_num_rows($result) > 0 && ($row['id_pembimbing'
404
       ] != "" || $row['id_pembimbing'] != null) && ($row['
       status_perusahaan'] == "" || $row['status_perusahaan'] == null))
           {
405
               data = array(
406
```

```
"id_intern" => $id_intern,
407
                    "id_mahasiswa" => $row['id_mahasiswa'],
408
                    "username" => $row['username'].
409
                    "password" => $row['password'],
410
                    "nama_mahasiswa" => $row['nama_mahasiswa'],
                    "kelas_mahasiswa" => $row['kelas_mahasiswa'],
                    "angkatan_mahasiswa" => $row['angkatan_mahasiswa'],
413
                    "foto_mahasiswa" => $row['foto_mahasiswa'].
414
                    "nama_prodi" => $row['nama_prodi'],
                    "id_dosen" => $row['id_dosen'],
                    "nama_dosen" => $row['nama_dosen'],
                    "nama_perusahaan" => $row['nama_perusahaan']
418
               );
419
420
               sison['status'] = 203;
               $ison['message'] = 'Login berhasil';
               sistemath{ison['data'] = sistemath{}data;
424
               echo ison_encode($ison):
               mysqli_close ($this -> connection);
426
           }
           else
428
               $query = "SELECT id_intern_dt_intern as id_intern,
       id_mahasiswa, username, password, nama_mahasiswa, kelas_mahasiswa
               angkatan_mahasiswa, foto_mahasiswa, nama_prodi, id_dosen,
431
        nama_dosen, kode_otp,
               status_perusahaan, id_pembimbing_dt_intern as
       id_pembimbing FROM user INNER JOIN mahasiswa
               ON user.id_user = mahasiswa.id_mahasiswa INNER JOIN prodi
               ON mahasiswa.id_prodi_mahasiswa = prodi.id_prodi INNER
434
       JOIN detail intern
               ON user.id_user = detail_intern.id_mahasiswa_dt_intern
435
               INNER JOIN intern ON detail_intern.id_intern_dt_intern =
436
       intern.id_intern
               INNER JOIN dosen
437
               ON detail_intern.id_dosen_dt_intern = dosen.id_dosen
               WHERE username='$user' AND password='$pass' AND user.
       role_user='mahasiswa'
               AND user.status_user='aktif' AND status_intern = '
440
       berjalan '";
441
               $result = mysqli_query($this->connection, $query);
               $row = mysqli_fetch_array($result);
443
               if (mysqli_num_rows($result) > 0 && ($row['id_pembimbing'
444
       ] == "" || $row['id_pembimbing'] == null) && ($row['
       status_perusahaan'] == "" || $row['status_perusahaan'] == null)
       && $row['kode_otp'] == '-')
445
                    data = array(
446
                        "id_intern" => $id_intern,
447
                        "id_mahasiswa" => $row['id_mahasiswa'],
                        "username" => $row['username'],
440
                        "password" => $row['password'],
450
                        "nama_mahasiswa" => $row['nama_mahasiswa'],
451
```

```
"kelas_mahasiswa" => $row['kelas_mahasiswa'],
452
                                                                       "angkatan_mahasiswa" => $row['angkatan_mahasiswa'
453
                      1,
                                                                        "foto_mahasiswa" => $row['foto_mahasiswa'],
454
                                                                       "nama_prodi" => $row['nama_prodi'],
                                                                       "id_dosen" => $row['id_dosen'],
                                                                       "nama_dosen" => $row['nama_dosen']
457
                                                           ):
458
                                                           sison['status'] = 202;
                                                           $ison['message'] = 'Login berhasil';
                                                           sin ['data'] = sdata;
462
463
                                                           echo json_encode($json);
464
                                                           mysgli_close ($this -> connection);
                                              }
166
                                              else
467
                                              {
468
469
                                                           sison['status'] = 400;
470
                                                           $ison['message'] = 'Username dan password salah';
                                                           echo json_encode($json);
472
                                                           mysqli_close ($this -> connection);
473
                                 }
475
                     }
476
477
                     public function registrasi_mahasiswa($kode_otp)
478
                                  $query = "SELECT kode_otp FROM mahasiswa WHERE kode_otp = '
480
                     $kode_otp '";
481
                                  $result = mysqli_query($this->connection, $query);
482
                                 $row = mysqli_fetch_array($result);
                                  if (mysqli_num_rows(sresult) > 0)
484
                                 {
485
486
                                              $query = "UPDATE mahasiswa SET kode_otp='-' WHERE
487
                      kode_otp='$kode_otp'";
100
                                              $result = mysqli_query($this->connection, $query);
489
                                              if (Sthis
490
                                                          ->connection->affected_rows > 0 && $result)
491
                                              {
                                                           \frac{1}{3} \frac{1}
493
                                                           $json['message'] = 'Registrasi berhasil';
494
495
                                                           echo json_encode($json);
                                                           mysqli_close ($this -> connection);
407
                                              }
498
                                              else
499
                                              {
500
501
                                                           sistemath{ison['status'] = 400;
502
                                                           $json['message'] = 'Registrasi gagal';
503
                                                           echo json_encode($json);
504
```

```
mysgli_close ($this -> connection);
505
               }
506
           }
507
           else
508
           {
               sison['status'] = 400;
511
               $ison['message'] = 'Registrasi gagal';
               echo ison_encode($ison);
               mysgli_close ($this -> connection);
           }
       }
       public function list_notifikasi($id_intern, $id_mahasiswa)
518
           $query = "SELECT id_intern , nama_pembimbing , pesan_notifikasi
       , nama_perusahaan_perusahaan , tgl_waktu_notifikasi FROM
       notifikasi
522 INNER JOIN pembimbing_perusahaan ON id_pembimbing =
       id_pembimbing_notifikasi
  INNER JOIN mahasiswa ON id_mahasiswa = id_mahasiswa_notifikasi
  INNER JOIN intern ON id_intern = id_intern_notifikasi
  WHERE id_mahasiswa_notifikasi='$id_mahasiswa' AND
       id_intern_notifikasi='$id_intern' ORDER BY tgl_waktu_notifikasi
       DESC":
526
527
           $result = mysqli_query($this->connection, $query);
           if (mvsqli_num_rows(sresult) > 0)
           {
530
               $datas = array();
               $kalimat1 = "melakukan absensi pada";
               $kalimat2 = "mengkonfirmasi absensi";
534
               $kalimat3 = "mendaftar ke perusahaan";
               $kalimat4 = "mengkonfirmasi pendaftaran";
536
               while ($row = mysqli_fetch_array($result))
                    pesan = "";
540
                    if (preg_match("~\b" . $row['pesan_notifikasi'] . "\b
541
         , $kalimat1))
                        $pesan = "Anda " . $row['pesan_notifikasi'];
543
544
                    elseif (preg_match("~\b" . $row['pesan_notifikasi'] .
545
        "\b~", $kalimat2))
546
                        $pesan = ucwords(($row['nama_pembimbing'])) . " "
547
        . $row['pesan_notifikasi'] . " Anda pada";
548
                    elseif (preg_match("~\b" . $row['pesan_notifikasi'] .
        "\b~", $kalimat3))
550
```

```
$pesan = "Anda " . $row['pesan_notifikasi'] . " "
        . ucwords(($row['nama_perusahaan_perusahaan'])) . " pada";
                    elseif (preg_match("~\b" . $row['pesan_notifikasi'] .
553
        "\b~", $kalimat4))
                         $pesan = ucwords(($row['nama_pembimbing'])) . " "
        . $row['pesan_notifikasi'] . " Anda pada";
                    $datas[] = array(
                         "id_intern" => $row['id_intern'],
550
                         "pesan" => $pesan . " " . date_format(date_create
560
       (\text{srow}['tgl\_waktu\_notifikasi']), 'd F Y \p\u\k\u\1 G:i A'),
                         "tgl_waktu" => $row['tgl_waktu_notifikasi']
                    ):
563
                }
564
565
                sistemath{ison['status'] = 200;
                $ison['message'] = 'Berhasil mengambil notifikasi';
                sison['data'] = sdatas;
568
569
                echo json_encode($json);
                mysqli_close ($this -> connection);
           elseif (mysqli_num_rows($result) == 0)
574
           {
                sison['status'] = 300;
                $ison['message'] = 'Notifikasi tidak ada';
                echo json_encode($json);
                mysqli_close ($this -> connection);
579
           else
581
           {
                sison['status'] = 400;
583
                $ison['message'] = 'Gagal mengambil notifikasi';
584
                echo json_encode($json);
                mysqli_close ($this -> connection);
586
           }
587
       }
588
589
       public function ubah_username($id_mahasiswa, $username)
591
            $query = "UPDATE user SET username='$username' WHERE id_user
592
       ='$id_mahasiswa'";
           $result = mysqli_query($this->connection, $query);
595
           if (Sthis
596
                ->connection->affected_rows > 0 && $result)
597
           {
                sistemath{ison['status'] = 200;
599
                $json['message'] = 'Username berhasil diubah';
600
                echo json_encode($json);
601
```

```
mysgli_close ($this -> connection);
602
           }
603
           else
604
           {
605
                sison['status'] = 400;
                $ison['message'] = 'Username gagal diubah';
                echo ison_encode($ison);
608
                mysqli_close ($this -> connection);
609
610
           }
       }
611
       public function ubah_nama($id_mahasiswa, $nama)
613
614
            $query = "UPDATE mahasiswa SET nama_mahasiswa='$nama' WHERE
615
       id_mahasiswa='$id_mahasiswa'";
            $result = mysqli_query($this->connection, $query);
617
            if ($this
                ->connection->affected_rows > 0 && $result)
            {
                sison['status'] = 200;
622
                $json['message'] = 'Nama berhasil diubah';
623
                echo json_encode($json);
                mysqli_close ($this -> connection);
            }
626
           else
627
628
           {
                sison['status'] = 400;
                $json['message'] = 'Nama gagal diubah';
                echo json_encode($json);
631
                mysqli_close ($this -> connection);
           }
633
       public function ubah_kelas($id_mahasiswa, $kelas)
637
            $query = "UPDATE mahasiswa SET kelas_mahasiswa='$kelas' WHERE
638
        id_mahasiswa='$id_mahasiswa'";
            $result = mysqli_query($this->connection, $query);
640
641
642
            if ($this
                ->connection->affected_rows > 0 && $result)
            {
644
                sistem ['status'] = 200;
645
                $json['message'] = 'Nama berhasil diubah';
646
                echo json_encode($json);
                mysqli_close ($this -> connection);
           }
649
           else
           {
                sison['status'] = 400;
                $json['message'] = 'Nama gagal diubah';
653
                echo json_encode($json);
                mysqli_close ($this -> connection);
655
```

```
}
657
658
659
       public function ubah_angkatan($id_mahasiswa, $angkatan)
            $query = "UPDATE mahasiswa SET angkatan_mahasiswa='$angkatan'
        WHERE id_mahasiswa='$id_mahasiswa'";
662
            $result = mysqli_query($this->connection, $query);
663
            if ($this
               ->connection->affected_rows > 0 && $result)
666
           {
667
                sison['status'] = 200;
668
                $ison['message'] = 'Nama berhasil diubah';
                echo json_encode($json);
                mysqli_close ($this -> connection);
           }
672
           else
673
           {
                sison['status'] = 400;
                $ison['message'] = 'Nama gagal diubah';
                echo json_encode($json);
677
                mysqli_close ($this -> connection);
           }
680
681
682
       public function ubah_kontak($id_mahasiswa, $kontak)
            $query = "UPDATE mahasiswa SET kontak_mahasiswa='$kontak'
684
       WHERE id_mahasiswa='$id_mahasiswa'";
685
            $result = mysqli_query($this->connection, $query);
686
            if ($this
               ->connection->affected_rows > 0 && $result)
           {
690
                sison['status'] = 200;
691
                $json['message'] = 'Kontak berhasil diubah';
                echo json_encode($json);
693
                mysqli_close ($this -> connection);
694
           }
695
           else
696
           {
                sison['status'] = 400;
698
                $json['message'] = 'Kontak gagal diubah';
699
                echo ison_encode($ison);
700
                mysqli_close ($this -> connection);
701
           }
703
       public function ubah_foto($id_mahasiswa, $foto)
705
706
            $query = "UPDATE mahasiswa SET foto_mahasiswa='$foto' WHERE
707
       id_mahasiswa='$id_mahasiswa'";
708
```

```
$result = mysqli_query($this->connection, $query);
709
            if ($this
               ->connection->affected_rows > 0 && $result)
                sison['status'] = 200;
                $ison['message'] = 'Foto berhasil diubah';
                echo json_encode($json);
                mysqli_close ($this -> connection);
                return true:
           }
           else
720
           {
                sison['status'] = 400;
                $ison['message'] = 'Foto gagal diubah';
                echo json_encode($json);
                mysqli_close ($this -> connection);
                return false:
726
           }
       }
       public function ubah_password($id_mahasiswa, $password)
730
            $query = "UPDATE user SET password='$password' WHERE id_user
       ='$id_mahasiswa'";
           $result = mysqli_query($this->connection, $query);
734
            if ($this
               ->connection->affected_rows > 0 && $result)
           {
                sison['status'] = 200;
                $json['message'] = 'Password berhasil diubah';
740
                echo json_encode($json);
                mysqli_close ($this -> connection);
           }
           else
744
           {
745
                sistemath{ison['status'] = 400;
                $ison['message'] = 'Password gagal diubah';
747
                echo json_encode($json);
748
                mysqli_close ($this -> connection);
749
750
           }
       public function distance ($lat1, $lon1, $lat2, $lon2)
754
            if ((\$1at1 == \$1at2) \&\& (\$1on1 == \$1on2))
           {
                return 0:
           }
758
           else
           {
                \theta = 10n1 - 10n2;
761
                dist = \sin(\deg 2rad(\$lat1)) * \sin(\deg 2rad(\$lat2)) + \cos(
762
       deg2rad(\$lat1)) * cos(deg2rad(\$lat2)) * cos(deg2rad(\$theta));
```

```
74 WEBSITE
```

dist = acos(dist);

```
$dist = rad2deg($dist);
764
              miles = dist * 60 * 1.1515;
765
766
              return ($miles * 1.609344) * 1000;
767
          }
      }
769
 1 <?php</pre>
  include ('dosen.php');
  header('Content-Type: application/json');
  d = new Dosen();
  if (isset($_POST['username'], $_POST['password'])) {
      $user = $_POST['username'];
      $pass = $_POST['password'];
      if (!empty($user) && !empty($pass)) {
          $d->login_dosen($user, $pass);
      } else {
          $ison['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
  }
16
  ?>
  <?php
  include ('dosen.php');
  header('Content-Type: application/json');
  d = new Dosen();
  if (isset($_POST['id_dosen'])) {
      $id_dosen = $_POST['id_dosen'];
      if (!empty($id_dosen)) {
          $d->list_mahasiswa($id_dosen);
 8
 0
      } else {
          $json['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
    else {
14
           sison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
18
  ?>
19
  <?php
  include ('dosen.php');
  header('Content-Type: application/json');
  d = new Dosen();
  if (isset($_POST['id_dosen'])) {
      $id_dosen = $_POST['id_dosen'];
      if (!empty($id_dosen)) {
          $d->list_notifikasi($id_dosen);
      } else {
9
10
          sistem = 100;
```

```
75
                                                                  API
          $json['message'] = 'Field tidak boleh kosong';
          echo ison_encode($ison);
      }
  } else {
14
          sison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo ison_encode($ison);
18
19
<?php
include('dosen.php');
a header('Content-Type: application/json');
if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['sort'
      1)) {
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa'];
      sort = POST['sort'];
8
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty($sort))
          $d->progress_mahasiswa($id_intern, $id_mahasiswa, $sort);
      } else {
          sistemath{ison['status'] = 100;
          $ison['message'] = 'Field tidak boleh kosong';
          echo json_encode($json);
16
1 <?php</pre>
include('dosen.php');
3 header('Content-Type: application/json');
4 \text{ } \text{d} = \text{new Dosen();}
 if (isset($_POST['id_intern'], $_POST['id_mahasiswa'], $_POST['tgl'])
      ) {
      $id_intern = $_POST['id_intern'];
      $id_mahasiswa = $_POST['id_mahasiswa'];
      tg1 = POST['tg1'];
      if (!empty($id_intern) && !empty($id_mahasiswa) && !empty($tgl))
          $d->progress_mahasiswa_perhari($id_intern, $id_mahasiswa,
      $tg1);
      } else {
```

```
1 <?php
2 include('dosen.php');
3 header('Content-Type: application/json');
4 \text{ } \text{d} = \text{new Dosen}();
6 $id_dosen = $_POST['id_dosen'];
7 if (isset($_POST['username'])) $username = $_POST['username'];
```

\$json['message'] = 'Field tidak boleh kosong';

sison['status'] = 100;

echo ison\_encode(\$ison);

14

16

}

```
if (isset($_POST['nama'])) $nama = $_POST['nama'];
             (isset($_POST['kontak'])) $kontak = $_POST['kontak'];
      if (isset($_POST['password'])) $password = $_POST['password'];
       if (isset($_FILES['foto']['name'])){
                   $foto = $_FILES['foto']['name'];
                   $temp_foto = $_FILES['foto']['tmp_name'];
1.4
                   $dir_dosen = "../images/dosen/";
       }
18
       if (!empty($id_dosen) && !empty($username)) {
10
20
                  $d->ubah_username($id_dosen, $username);
            elseif (!empty($id_dosen) && !empty($nama)) {
                  $d->ubah_nama($id_dosen, $nama);
           elseif (!empty($id_dosen) && !empty($kontak)) {
                  $d->ubah_kontak($id_dosen, $kontak);
24
           elseif (!empty($id_dosen) && !empty($password)) {
                  $d->ubah_password($id_dosen, $password);
26
            elseif (!empty($id_dosen) && !empty($foto)){
                   $result = $d->ubah_foto($id_dosen, $foto);
28
                   if ($result) {
29
                               $upload = move_uploaded_file($temp_foto, $dir_dosen.$foto);
30
                               if (!$upload) {
                                          sistem = sistem size = sistem size = size 
                                          $ison['message'] = 'Gambar gagal terupload';
                                          echo json_encode($json);
34
35
                               }
            else {
                   38
                   $json['message'] = 'Field tidak boleh kosong';
30
                  echo json_encode($json);
40
41
```

```
1 <?php</pre>
include('../conn.php');
3 header('Content-Type: application/json');
4 class Dosen
  {
5
      private $db;
      private $connection;
      public function __construct()
           this \rightarrow db
                              = new Connection();
           $this -> connection = $this -> db-> get_connection();
      }
14
      public function list_mahasiswa($id_dosen)
           $query = "SELECT id_mahasiswa, nama_perusahaan_perusahaan,
      lama_internship, nama_mahasiswa, foto_mahasiswa,
           angkatan_mahasiswa, foto_perusahaan, kelas_mahasiswa,
      foto_mahasiswa, nama_prodi,
```

```
nama_pembimbing, lat_pembimbing_perusahaan,
18
      long_pembimbing_perusahaan, id_intern, COUNT(
      id_mahasiswa_dt_absensi) as jumlah_absensi
          FROM detail_intern
          INNER JOIN intern ON detail_intern.id_intern_dt_intern =
20
      intern.id_intern
          INNER JOIN pembimbing_perusahaan ON detail_intern.
      id_pembimbing_dt_intern = pembimbing_perusahaan.id_pembimbing
          INNER JOIN mahasiswa ON detail_intern.id_mahasiswa_dt_intern
      = mahasiswa.id_mahasiswa
          INNER JOIN prodi ON mahasiswa.id_prodi_mahasiswa= prodi.
      id_prodi
          INNER JOIN detail_absensi ON detail_intern.
24
      id_mahasiswa_dt_intern = detail_absensi.id_mahasiswa_dt_absensi
          WHERE id_dosen_dt_intern = '$id_dosen' AND status_intern = '
       berjalan '";
26
          $result = mysqli_query($this->connection, $query);
          if (mvsqli_num_rows(\$result) > 0) {
28
              $datas = array();
               while ($row = mysqli_fetch_array($result)) {
31
                   datas[] = array(
                   "id_intern" => $row['id_intern'],
                   "id_mahasiswa" => $row['id_mahasiswa'],
34
                   "nama_perusahaan" => ucwords($row['
       nama_perusahaan_perusahaan']),
                   "nama_mahasiswa" => ucwords($row['nama_mahasiswa']),
36
                   "foto_mahasiswa" => $row['foto_mahasiswa'],
                   "angkatan_mahasiswa" => $row['angkatan_mahasiswa'],
38
                   "foto_perusahaan" => $row['foto_perusahaan'],
                   "kelas_mahasiswa" => strtoupper($row['kelas_mahasiswa
40
      <sup>'</sup>]),
                   "foto_mahasiswa" => $row['foto_mahasiswa'],
                   "nama_prodi" => ucwords($row['nama_prodi']),
42
                   "nama_pembimbing" => ucwords($row['nama_pembimbing'])
                   "latitude_perusahaan" => $row['
      lat_pembimbing_perusahaan'],
                   "longitude_perusahaan" => $row['
45
      long_pembimbing_perusahaan'],
                   "presentase_internship" => round($row['jumlah_absensi
46
       ']/$row['lama_internship']*100,1)
              );
              }
48
40
              sistem = 200;
50
               $ison['message'] = 'Berhasil mengambil mahasiswa';
              sistemath{ison['data'] = sistemath{}datas;
              echo json_encode($json);
               mysqli_close ($this -> connection);
          } elseif (mysqli_num_rows($result) == 0) {
               57
              $json['message'] = 'Mahasiswa tidak ada';
58
59
```

```
echo ison_encode($ison);
                                    mysgli_close ($this -> connection);
 61
                          } else {
 62
                                   sison['status'] = 400;
 63
                                   $ison['message'] = 'Gagal mengambil mahasiswa';
                                   echo json_encode($json);
                                    mysgli_close ($this -> connection);
 66
                         }
 67
 68
 69
                public function login_dosen($user, $pass)
                          query = "SELECT"
                          username, password, id_dosen, nama_dosen, foto_dosen,
                 id_intern , nama_prodi
                         FROM user
 74
                         INNER JOIN dosen ON user.id_user = dosen.id_dosen
                         INNER JOIN detail_intern ON user.id_user = detail_intern.
 76
                 id_dosen_dt_intern
                         INNER JOIN intern ON detail_intern.id_intern_dt_intern =
                 intern.id_intern
                         INNER JOIN prodi ON dosen.id_prodi_dosen = prodi.id_prodi
 78
                         WHERE username = '$user' AND password = '$pass' AND
 70
                 status_user='aktif' AND role_user='dosen'";
                          $result = mysqli_query($this->connection, $query);
 81
 82
 23
                         $row = mysqli_fetch_array($result);
                          if (mysqli_num_rows(sresult) > 0) {
                                   data = array(
 85
                                             "username" => $row['username'],
                                             "password" => $row['password'],
 87
                                             "id_dosen" => $row['id_dosen'],
 88
                                             "nama_dosen" => ucwords($row['nama_dosen']),
                                             "foto_dosen" => $row['foto_dosen'],
 90
                                             "nama_prodi" => ucwords($row['nama_prodi'])
 0.1
                                   );
 93
                                   sison['status'] = 200;
 0.5
                                   $json['message'] = 'Berhasil melakukan login';
                                   sin = sin 
 97
 98
                                   echo json_encode($json);
                                    mysqli_close ($this -> connection);
100
                         } elseif (mysqli_num_rows($result) == 0) {
                                             sistem = 300;
102
                                             $ison['message'] = 'Username atau password salah';
                                             echo json_encode($json);
105
                                             mysqli_close ($this -> connection);
106
                                   } else {
                                   sison['status'] = 400;
                                   $json['message'] = 'Gagal melakukan login';
109
                                   echo json_encode($json);
```

```
mysgli_close ($this -> connection);
           }
       }
114
       public function progress_mahasiswa($id_intern, $id_mahasiswa,
116
       $sort)
       {
           squery = "SET @rank=0:":
118
           mysqli_query($this->connection, $query);
           switch ($sort) {
               case 'hari':
               query1 = "
               SELECT @rank:=@rank+1 AS rank, DAYOFYEAR(
       tgl_waktu_absensi) as date, ROUND(COUNT(*) / 3 * 100, 2)
               as percent FROM absensi WHERE id_intern_absensi='
       $id_intern ' AND id_mahasiswa_absensi = '$id_mahasiswa'
               GROUP BY DAYOFYEAR(tgl_waktu_absensi) ORDER BY rank ASC";
               $result1 = mysqli_query($this->connection, $query1);
126
               if (mysqli_num_rows($result1) > 0) {
                    $datas = array();
129
                    while (\$row = mysqli_fetch_array(\$result1)) {
130
                        $datas[] = array(
                        "sort" => "Hari ke-". $row['rank'],
                        "persen" => $row['percent']
               );
134
                    }
136
                    sison['status'] = 201;
                    $json['message'] = 'Berhasil mengambil progress';
138
                    sistemath{ison['data'] = sistemath{}datas;
139
140
                    echo ison_encode($ison);
141
                    mysqli_close ($this -> connection);
               } elseif (mysqli_num_rows($result1) == 0) {
                    sistem = 300;
                    $json['message'] = 'Progress tidak ada';
                    //$ison['data'] = [];
                    echo json_encode($json);
148
                    mysqli_close($this->connection);
149
               } else {
150
                    sison['status'] = 400;
                    $json['message'] = 'Gagal mengambil progress';
                    echo json_encode($json);
                    mysqli_close ($this -> connection);
154
               break:
               case 'minggu':
               query2 = "
158
               SELECT @rank:=@rank+1 AS rank, WEEK(tgl_waktu_absensi,1)
       as week, ROUND(COUNT(*) / 21 * 100, 2)
               as percent FROM absensi WHERE id_intern_absensi='
       $id_intern ' AND id_mahasiswa_absensi = '$id_mahasiswa'
               GROUP BY WEEK(tgl_waktu_absensi) ORDER BY rank ASC";
161
               $result2 = mysqli_query($this->connection, $query2);
162
```

```
if (mysqli_num_rows(sresult2) > 0) {
163
                                              $datas = array();
164
165
                                              while ($row = mysqli_fetch_array($result2)) {
166
                                                        $datas[] = array(
167
                                                        "sort" => "Minggu ke-". $row['rank'].
                                                        "persen" => $row['percent']
160
                                    ):
                                              }
                                              sison['status'] = 202;
                                              $json['message'] = 'Berhasil mengambil progress';
174
                                              sison['data'] = sdatas;
176
                                              echo ison_encode($ison);
                                              mysqli_close ($this -> connection);
                                    } elseif (mysqli_num_rows($result2) == 0) {
                                              sison['status'] = 300;
180
                                              $ison['message'] = 'Progress tidak ada';
181
                                              echo json_encode($json);
183
                                              mysqli_close ($this -> connection);
184
                                    } else {
                                              sison['status'] = 400;
186
                                              $json['message'] = 'Gagal mengambil progress';
                                              echo json_encode($json);
188
                                              mysqli_close ($this -> connection);
189
100
                                    break:
                                    case 'bulan':
                                              query3 = "
103
                                             SELECT @rank:=@rank+1 AS rank, MONTH(
                 tgl_waktu_absensi) as month, ROUND(COUNT(*) / 90 * 100, 2)
                                              as percent FROM absensi WHERE id_intern_absensi='
                 $id_intern ' AND id_mahasiswa_absensi = '$id_mahasiswa'
                                             GROUP BY MONTH(tgl_waktu_absensi) ORDER BY rank ASC";
106
                                              $result3 = mysqli_query($this -> connection, $query3);
197
                                              if (mysqli_num_rows(sresult3) > 0) {
198
                                                        $datas = array();
                                                        while ($row = mysqli_fetch_array($result3)) {
201
                                                                  $datas[] = array(
202
                                                                           "sort" => "Bulan ke-". $row['rank'],
203
                                                                            "persen" => $row['percent']
205
                                                                 );
                                                        }
206
207
                                                        sison['status'] = 203;
                                                        $json['message'] = 'Berhasil mengambil progress';
209
                                                        sin = sin 
                                                        echo json_encode($json);
                                                        mysqli_close ($this -> connection);
                                              } elseif (mysqli_num_rows($result3) == 0) {
214
                                                        sistem = 300;
                                                        $json['message'] = 'Progress tidak ada';
216
```

```
echo ison_encode($ison);
218
                        mysqli_close ($this -> connection);
                    } else {
                        sison['status'] = 400:
                        $ison['message'] = 'Gagal mengambil progress';
                        echo ison_encode($ison);
                        mysqli_close ($this -> connection);
224
               break:
           }
       }
228
229
       public function progress_mahasiswa_perhari($id_intern,
230
       $id_mahasiswa, $tgl)
           $query = "SELECT id_absensi, tgl_waktu_absensi,
       nama_kegiatan, foto_absensi, pergeseran_absensi
           FROM absensi
           INNER JOIN detail_absensi ON absensi.id_absensi =
234
       detail_absensi.id_absensi_dt_absensi
           INNER JOIN kegiatan ON absensi.id_kegiatan_absensi = kegiatan
       .id_kegiatan
           WHERE id_intern_absensi = '$id_intern' AND
       id_mahasiswa_absensi = '$id_mahasiswa' AND
           DATE(tgl_waktu_absensi) = '$tgl'";
           $result = mysqli_query($this->connection, $query);
238
230
           if (mysgli_num_rows(sresult) > 0) {
               $datas = array();
241
               while ($row = mysqli_fetch_array($result)) {
242
                    $datas [] =
                                array (
                        "id_absensi" => $row['id_absensi'],
244
                        "tgl_waktu" => $row['tgl_waktu_absensi'],
                    "kegiatan" => ucfirst($row['nama_kegiatan']),
246
                    "foto_absensi" => $row['foto_absensi'],
                    "pergeseran" => $row['pergeseran_absensi']." M"
248
               );
249
               sistem = 200;
               $json['message'] = 'Berhasil mengambil progress harian';
               sison['data'] = sdatas;
               echo json_encode($json);
256
               mysqli_close ($this -> connection);
           } elseif (mysqli_num_rows($result) == 0) {
               sison['status'] = 300;
               $json['message'] = 'Progress harian tidak ada';
261
               echo json_encode($json);
262
               mysqli_close ($this -> connection);
263
           } else {
               sistemath{ison['status'] = 400;
265
               $json['message'] = 'Gagal mengambil progress harian';
266
               echo json_encode($json);
267
```

```
mysgli_close ($this -> connection);
268
           }
260
       public function list_notifikasi($id_dosen){
274
           $query = "SELECT id_intern , nama_mahasiswa , nama_pembimbing ,
       nama_perusahaan_perusahaan , pesan_notifikasi ,
       tgl_waktu_notifikasi FROM notifikasi INNER JOIN
       pembimbing_perusahaan ON id_pembimbing = id_pembimbing_notifikasi
        INNER JOIN mahasiswa ON id_mahasiswa = id_mahasiswa_notifikasi
       INNER JOIN intern ON id_intern = id_intern_notifikasi WHERE
       id_dosen_notifikasi='$id_dosen' AND status_intern='berjalan'
       ORDER BY tgl_waktu_notifikasi DESC ":
           $result = mysqli_query($this->connection, $query);
278
           if (mvsali_num_rows(\$result) > 0) {
               $datas = array();
281
               $kalimat1 = "melakukan absensi pada";
282
               $kalimat2 = "mengkonfirmasi absensi";
283
               $kalimat3 = "mendaftar ke perusahaan";
               $kalimat4 = "mengkonfirmasi pendaftaran";
285
286
               while ($row = mysqli_fetch_array($result)) {
287
                    pesan = "";
288
                    if (preg_match ("~\b". $row['pesan_notifikasi']."\b~",
       $kalimat1)){
                        $pesan = ucwords($row['nama_mahasiswa'])." ".$row
290
       ['pesan_notifikasi'];
                    } elseif (preg_match ("~\b". $row['pesan_notifikasi']."\b
291
       ~", $kalimat2)){
                        $pesan = ucwords($row['nama_pembimbing'])." ".
292
       $row['pesan_notifikasi']." ".ucwords($row['nama_mahasiswa'])."
       pada":
                    }elseif(preg_match("~\b".$row['pesan_notifikasi']."\b
293
       ~", $kalimat3)){
                        $pesan = ucwords(($row['nama_mahasiswa']))." ".
294
       $row['pesan_notifikasi']." ".ucwords($row['
       nama_perusahaan_perusahaan'])." pada";
                    } elseif (preg_match ("~\b". $row['pesan_notifikasi']."\b
295
       ~", $kalimat4)){
                        $pesan = ucwords($row['nama_pembimbing'])." ".
296
       $row['pesan_notifikasi']." ".ucwords($row['nama_mahasiswa'])."
       pada";
                    }
                    $datas[] = array(
299
                    "id_intern" => $row['id_intern'],
300
                   "pesan" => $pesan." ". date_format(date_create($row['
301
       tgl_waktu_notifikasi']), 'd F Y \p\u\k\u\l G: i A'),
                    "tgl_waktu" => $row['tgl_waktu_notifikasi']
302
               );
303
304
```

```
305
306
               sison['status'] = 200;
307
               $json['message'] = 'Berhasil mengambil notifikasi';
308
               sison['data'] = sdatas;
311
               echo ison_encode($ison);
               mysqli_close ($this -> connection);
           } elseif (mysqli_num_rows($result) == 0) {
               sison['status'] = 300;
314
               $ison['message'] = 'Notifikasi tidak ada';
               echo json_encode($json);
               mysqli_close ($this -> connection);
318
           } else {
               sison['status'] = 400;
               $json['message'] = 'Gagal mengambil notifikasi';
               echo json_encode($json);
               mysqli_close ($this -> connection);
           }
324
       }
326
       public function ubah_username($id_dosen, $username){
           $query = "UPDATE user SET username='$username' WHERE id_user
       ='$id_dosen'";
           $result = mysqli_query($this->connection, $query);
330
           if ($this -> connection -> affected_rows > 0 && $result) {
               sison['status'] = 200;
               $json['message'] = 'Username berhasil diubah';
               echo json_encode($json);
               mysqli_close ($this -> connection);
336
           } else {
               sison['status'] = 400;
338
               $json['message'] = 'Username gagal diubah';
               echo json_encode($json);
340
               mysqli_close ($this -> connection);
341
           }
343
344
       public function ubah_nama($id_dosen, $nama){
345
           $query = "UPDATE dosen SET nama_dosen='$nama' WHERE id_dosen
       ='$id_dosen'";
347
           $result = mysqli_query($this->connection, $query);
348
349
           if ($this -> connection -> affected_rows > 0 && $result) {
               $json['message'] = 'Nama berhasil diubah';
352
               echo json_encode($json);
               mysqli_close ($this -> connection);
           } else {
               356
               $json['message'] = 'Nama berhasil diubah';
               echo json_encode($json);
358
```

```
mysgli_close ($this -> connection);
                          }
360
                 }
361
362
                 public function ubah_kontak($id_dosen, $kontak){
                           $query = "UPDATE dosen SET kontak_dosen='$kontak' WHERE
                 id_dosen='$id_dosen'";
365
                           $result = mysqli_query($this->connection, $query);
367
                           if ($this->connection->affected_rows > 0 && $result) {
                                     sistemath{ison['status'] = 200;
360
                                     $ison['message'] = 'Kontak berhasil diubah';
                                     echo json_encode($json);
                                     mysgli_close ($this -> connection);
                           } else {
                                     sistem = sistem size = sistem size = size 
                                     $json['message'] = 'Kontak gagal diubah';
                                     echo ison_encode($ison):
                                     mysqli_close ($this -> connection);
                          }
279
380
                 public function ubah_foto($id_dosen, $foto){
                           $query = "UPDATE dosen SET foto_dosen='$foto' WHERE id_dosen
382
                 ='$id_dosen'":
383
38/
                           $result = mysqli_query($this->connection, $query);
                           if ($this -> connection -> affected_rows > 0 && $result) {
386
                                     sistemath{ison['status'] = 200;
                                     $json['message'] = 'Foto berhasil diubah';
                                     echo ison_encode($ison);
389
                                     mysqli_close ($this -> connection);
                                     return true;
391
                          } else {
302
                                     sison['status'] = 400;
393
                                     $ison['message'] = 'Foto gagal diubah';
                                     echo json_encode($json);
                                     mysqli_close ($this -> connection);
206
                                     return false:
397
                          }
398
399
                 public function ubah_password($id_dosen, $password){
401
                           $query = "UPDATE user SET password='$password' WHERE id_user
402
                 ='$id_dosen'";
                           $result = mysqli_query($this->connection, $query);
404
405
                           if ($this -> connection -> affected_rows > 0 && $result) {
406
                                     407
                                     $ison['message'] = 'Password berhasil diubah';
                                     echo json_encode($json);
400
                                     mysqli_close ($this -> connection);
                           } else {
411
```

# **WEB**

### 5.1 Web

## 5.1.1 Dapur Hosting


Di tutorial kali ini kita akan menggunakan jasa web hosting. Web hosting adalah layanan penyimpanan file website, email, dan database yang terkoneksi ke internet dan dapat diakses dengan nama domain. Dapur Hosting menyediakan 2 pilihan lokasi web hosting murah, yaitu di Indonesia dan USA

Siapkan file yang akan di upload




Gambar 5.1 Upload.

### 1. Login ke dapurhosting



Gambar 5.2 Login.

2. masuk ke file manager dan upload disini



Gambar 5.3 Upload file.

```
$db['default'] = array(
         'dsn' => '',
'hostname' => 'localhost',
         'username' => 'himatifp actspot',
         'password' => 'actspot2019',
         'database' => 'himatifp_actspot',
'dbdriver' => 'mysqli',
'dbprefix' => '',
         'pconnect' => FALSE,
         'db debug' => (ENVIRONMENT !== 'production'),
         'cache_on' => FALSE,
         'char set' => 'utf8',
         'dbcollat' => 'utf8 general ci',
         'swap pre' => '',
         'encrypt' => FALSE,
         'compress' => FALSE,
         'stricton' => FALSE,
         'failover' => array(),
         'save queries' => TRUE
```


Gambar 5.4 database file.

4. setting config .php

```
$config['base_url'] = 'http://himatifpolpos.my.id/Maps/';
```

Gambar 5.5 config file.

5. Hasil



Gambar 5.6 Tampilan

Source code web

```
1 <?php
2 defined('BASEPATH') OR exit('No direct script access allowed')
;</pre>
```

```
4 /*
5
    Base Site URL
8
    URL to your CodeIgniter root. Typically this will be your
       base URL,
    WITH a trailing slash:
10
    http://example.com/
    WARNING: You MUST set this value!
14
    If it is not set, then CodeIgniter will try guess the
16
       protocol and path
    your installation, but due to security concerns the hostname
        will be set
    to $_SERVER['SERVER_ADDR'] if available, or localhost
18
       otherwise.
    The auto-detection mechanism exists only for convenience
    development and MUST NOT be used in production!
2.0
21
    If you need to allow multiple domains, remember that this
       file is still
    a PHP script and you can easily do that on your own.
24
25 */
$config['base_url'] = 'http://localhost/Maps/';
28
  /*
29
    Index File
30
31
32
    Typically this will be your index.php file, unless you've
       renamed it to
    something else. If you are using mod_rewrite to remove the
       page set this
    variable so that it is blank.
35
36
37
  $config['index_page'] = 'index.php';
30
40
41
    URI PROTOCOL
42
43
44
```

```
This item determines which server global should be used to
       retrieve the
    URI string. The default setting of 'REQUEST-URI' works for
       most servers.
    If your links do not seem to work, try one of the other
       delicious flavors:
48
    'REOUEST_URI'
                      Uses $_SERVER['REQUEST_URI']
49
                      Uses $_SERVER['OUERY_STRING']
50
     OUERY_STRING '
    'PATH_INFO'
                      Uses $_SERVER['PATH_INFO']
    WARNING: If you set this to 'PATH_INFO', URIs will always be
       URL-decoded!
54
  $config['uri_protocol'] = 'REQUEST_URI';
56
57
58
    URL suffix
59
60
61
    This option allows you to add a suffix to all URLs generated
62
       by CodeIgniter.
    For more information please see the user guide:
63
64
65
    https://codeigniter.com/user_guide/general/urls.html
  */
  $config['url_suffix'] = '';
68
69
    Default Language
    This determines which set of language files should be used.
      Make sure
    there is an available translation if you intend to use
       something other
    than english.
76
77
  */
78
  $config['language'] = 'english';
80
  /*
81
82
    Default Character Set
83
84
85
    This determines which character set is used by default in
      various methods
```

```
that require a character set to be provided.
87
88
     See http://php.net/htmlspecialchars for a list of supported
89
       charsets.
90
  */
91
  $config['charset'] = 'UTF-8';
93
    Enable/Disable System Hooks
96
97
98
     If you would like to use the 'hooks' feature you must enable
99
        it by
     setting this variable to TRUE (boolean). See the user guide
100
        for details.
101
  */
102
  $config['enable_hooks'] = FALSE;
103
104
105
106
     Class Extension Prefix
108
109
     This item allows you to set the filename/classname prefix
       when extending
     native libraries. For more information please see the user
       guide:
     https://codeigniter.com/user_guide/general/core_classes.html
     https://codeigniter.com/user_guide/general/
       creating_libraries.html
  */
116
  $config['subclass_prefix'] = 'MY_';
118
119
  /*
120
     Composer auto-loading
     Enabling this setting will tell CodeIgniter to look for a
124
       Composer
     package auto-loader script in application/vendor/autoload.
       php.
126
     $config['composer_autoload'] = TRUE;
128
```

```
Or if you have your vendor/ directory located somewhere else
       , you
     can opt to set a specific path as well:
130
     $config['composer_autoload'] = '/path/to/vendor/autoload.php
     For more information about Composer, please visit http://
134
       getcomposer.org/
     Note: This will NOT disable or override the CodeIgniter-
136
       specific
     autoloading (application/config/autoload.php)
138
  $config['composer_autoload'] = FALSE;
140
141
142
    Allowed URL Characters
143
144
145
     This lets you specify which characters are permitted within
       your URLs.
    When someone tries to submit a URL with disallowed
147
       characters they will
148
     get a warning message.
    As a security measure you are STRONGLY encouraged to
150
       restrict URLs to
     as few characters as possible. By default only these are
       allowed: a-z = 0-9^{-}\%.:_{-}
152
     Leave blank to allow all characters — but only if you are
       insane.
154
    The configured value is actually a regular expression
       character group
     and it will be executed as: ! preg_match('/^[<
156
       permitted_uri_chars >]+$/i
    DO NOT CHANGE THIS UNLESS YOU FULLY UNDERSTAND THE
       REPERCUSSIONS!!
159
  config['permitted_uri_chars'] = 'a-z 0-9^{\%}.:_\-';
161
163
  /*
164
    Enable Query Strings
165
167
```

```
By default CodeIgniter uses search-engine friendly segment
       based URLs:
     example.com/who/what/where/
169
170
     You can optionally enable standard query string based URLs:
     example.com?who=me&what=something&where=here
     Options are: TRUE or FALSE (boolean)
    The other items let you set the query string 'words' that
       wi11
     invoke your controllers and its functions:
178
     example.com/index.php?c=controller&m=function
     Please note that some of the helpers won't work as expected
       when
     this feature is enabled, since CodeIgniter is designed
181
       primarily to
     use segment based URLs.
182
183
  */
184
$$ $config['enable_query_strings'] = FALSE;
  $config['controller_trigger'] = 'c';
  $config['function_trigger'] = 'm';
  $config['directory_trigger'] = 'd';
189
190
101
    Allow $_GET array
192
193
194
    By default CodeIgniter enables access to the $_GET array.
195
       If for some
     reason you would like to disable it, set 'allow_get_array'
106
       to FALSE.
197
    WARNING: This feature is DEPRECATED and currently available
       only
              for backwards compatibility purposes!
199
200
201
   */
   $config['allow_get_array'] = TRUE;
203
204
205
     Error Logging Threshold
206
207
208
    You can enable error logging by setting a threshold over
       zero. The
     threshold determines what gets logged. Threshold options are
210
```

```
0 = Disables logging, Error logging TURNED OFF
     1 = Error Messages (including PHP errors)
     2 = Debug Messages
     3 = Informational Messages
     4 = A11 Messages
216
     You can also pass an array with threshold levels to show
218
       individual error types
       array(2) = Debug Messages, without Error Messages
220
     For a live site you'll usually only enable Errors (1) to be
       logged otherwise
     your log files will fill up very fast.
224
225
  */
  config['log_threshold'] = 0;
228
  / *
     Error Logging Directory Path
     Leave this BLANK unless you would like to set something
       other than the default
     application/logs/ directory. Use a full server path with
       trailing slash.
235
236
   */
  config['log_path'] = '';
  /*
239
240
    Log File Extension
242
243
     The default filename extension for log files. The default '
244
       php' allows for
     protecting the log files via basic scripting, when they are
       to be stored
     under a publicly accessible directory.
246
247
     Note: Leaving it blank will default to 'php'.
249
  */
250
   $config['log_file_extension'] = '';
252
253 /*
254
  | Log File Permissions
```

```
256
257
     The file system permissions to be applied on newly created
258
       log files.
259
    IMPORTANT: This MUST be an integer (no quotes) and you MUST
260
       use octal
                 integer notation (i.e. 0700, 0644, etc.)
261
262
   */
   $config['log_file_permissions'] = 0644;
263
264
265
   /*
266
    Date Format for Logs
267
268
269
     Each item that is logged has an associated date. You can use
        PHP date
     codes to set your own date formatting
   $config['log_date_format'] = 'Y-m-d H:i:s';
276
     Error Views Directory Path
278
280
     Leave this BLANK unless you would like to set something
281
       other than the default
     application/views/errors/ directory. Use a full server path
282
        with trailing slash.
283
   $config['error_views_path'] = '';
286
287
288
    Cache Directory Path
289
290
     Leave this BLANK unless you would like to set something
292
       other than the default
     application/cache/ directory. Use a full server path with
293
       trailing slash.
294
  */
295
  $config['cache_path'] = '';
297
```

```
298 /*
200
    Cache Include Query String
300
301
302
     Whether to take the URL query string into consideration when
303
        generating
     output cache files. Valid options are:
305
     FALSE
                = Disabled
306
307
    TRUE
                = Enabled, take all query parameters into account
                   Please be aware that this may result in
       numerous cache
                   files generated for the same page over and over
300
        again.
     array('q') = Enabled, but only take into account the
310
       specified list
                   of query parameters.
  */
   $config['cache_query_string'] = FALSE;
  /*
316
     Encryption Key
319
320
     If you use the Encryption class, you must set an encryption
     See the user guide for more info.
     https://codeigniter.com/user_guide/libraries/encryption.html
   $config['encryption_key'] = '';
328
330
     Session Variables
     'sess_driver'
334
     The storage driver to use: files, database, redis, memcached
336
     'sess_cookie_name'
338
339
     The session cookie name, must contain only [0-9a-z_-]
340
       characters
```

```
341
3/12
     'sess_expiration'
343
    The number of SECONDS you want the session to last.
     Setting to 0 (zero) means expire when the browser is closed.
     'sess_save_path'
3.17
348
    The location to save sessions to, driver dependent.
    For the 'files' driver, it's a path to a writable directory.
351
    WARNING: Only absolute paths are supported!
352
    For the 'database' driver, it's a table name.
    Please read up the manual for the format with other session
       drivers.
356
    IMPORTANT: You are REQUIRED to set a valid save path!
357
     'sess_match_ip'
260
    Whether to match the user's IP address when reading the
361
       session data.
    WARNING: If you're using the database driver, don't forget
363
       to update
              your session table's PRIMARY KEY when changing this
364
        setting.
     'sess_time_to_update'
366
367
    How many seconds between CI regenerating the session ID.
368
370
     'sess_regenerate_destroy'
    Whether to destroy session data associated with the old
       session ID
    when auto-regenerating the session ID. When set to FALSE,
       the data
     will be later deleted by the garbage collector.
    Other session cookie settings are shared with the rest of
       the application,
    except for 'cookie_prefix' and 'cookie_httponly', which are
       ignored here.
378
379 */
$\config['sess_driver'] = 'files';
$$\$\config['sess_cookie_name'] = 'ci_session';
$$\$\config['sess_expiration'] = 7200;
$\config['sess_save_path'] = NULL;
$$\$\config['sess_match_ip'] = FALSE;
$\config['sess_time_to_update'] = 300;
$$ $config['sess_regenerate_destroy'] = FALSE;
387
388 /*
```

```
389
     Cookie Related Variables
390
301
392
     'cookie_prefix'
                        = Set a cookie name prefix if you need to
303
       avoid collisions
     'cookie domain'
                        = Set to .your-domain.com for site-wide
       cookies
     'cookie_path'
395
                        = Typically will be a forward slash
                        = Cookie will only be set if a secure
     'cookie secure'
306
       HTTPS connection exists.
     'cookie_httponly' = Cookie will only be accessible via HTTP(
397
       S) (no javascript)
398
     Note: These settings (with the exception of 'cookie_prefix'
300
       and
            'cookie_httponly') will also affect sessions.
400
401
   */
402
   $config['cookie_prefix']
                               = ', ':
   $config['cookie_domain']
   $config['cookie_path']
                               = '/':
   $config['cookie_secure']
                             = FALSE;
   $config['cookie_httponly'] = FALSE;
407
408
400
   /*
410
     Standardize newlines
411
412
413
     Determines whether to standardize newline characters in
       input data,
     meaning to replace \r\n, \r, \n occurrences with the PHP_EOL
415
        value.
    WARNING: This feature is DEPRECATED and currently available
417
       only
               for backwards compatibility purposes!
418
   $config['standardize_newlines'] = FALSE;
421
422
423
424
     Global XSS Filtering
426
427
     Determines whether the XSS filter is always active when GET,
428
        POST or
    COOKIE data is encountered
```

```
WARNING: This feature is DEPRECATED and currently available
       only
              for backwards compatibility purposes!
432
433
   */
   $config['global_xss_filtering'] = FALSE;
436
437
438
     Cross Site Request Forgery
440
     Enables a CSRF cookie token to be set. When set to TRUE,
       token will be
     checked on a submitted form. If you are accepting user data,
442
        it is strongly
     recommended CSRF protection be enabled.
444
     'csrf_token_name' = The token name
     'csrf_cookie_name' = The cookie name
446
     'csrf_expire' = The number in seconds the token should
447
       expire.
     'csrf_regenerate' = Regenerate token on every submission
     'csrf_exclude_uris' = Array of URIs which ignore CSRF checks
449
450
   $config['csrf_protection'] = FALSE;
   $config['csrf_token_name'] = 'csrf_test_name';
   $config['csrf_cookie_name'] = 'csrf_cookie_name';
  config['csrf_expire'] = 7200;
   $config['csrf_regenerate'] = TRUE;
   $config['csrf_exclude_uris'] = array();
457
   /*
458
     Output Compression
461
462
     Enables Gzip output compression for faster page loads.
463
        enabled,
     the output class will test whether your server supports Gzip
     Even if it does, however, not all browsers support
465
       compression
     so enable only if you are reasonably sure your visitors can
       handle it.
467
     Only used if zlib.output_compression is turned off in your
468
       php.ini.
     Please do not use it together with httpd-level output
       compression.
```

```
VERY IMPORTANT: If you are getting a blank page when
       compression is enabled it
     means you are prematurely outputting something to your
472
       browser. It could
     even be a line of whitespace at the end of one of your
473
       scripts.
                  For
     compression to work, nothing can be sent before the output
474
       buffer is called
     by the output class. Do not 'echo' any values with
       compression enabled.
476
   */
477
   $config['compress_output'] = FALSE;
480
  / *
481
     Master Time Reference
482
483
191
     Options are 'local' or any PHP supported timezone. This
485
       preference tells
     the system whether to use your server's local time as the
486
       master 'now'
     reference, or convert it to the configured one timezone. See
487
        the 'date
     helper' page of the user guide for information regarding
       date handling.
480
490
491
   $config['time_reference'] = 'local';
493
494
     Rewrite PHP Short Tags
495
497
     If your PHP installation does not have short tag support
       enabled CI
     can rewrite the tags on-the-fly, enabling you to utilize
       that syntax
     in your view files. Options are TRUE or FALSE (boolean)
500
501
502
     Note: You need to have eval() enabled for this to work.
503
504
   $config['rewrite_short_tags'] = FALSE;
506
507
508
   Reverse Proxy IPs
```

```
510
511
     If your server is behind a reverse proxy, you must whitelist
512
        the proxy
     IP addresses from which CodeIgniter should trust headers
       such as
    HTTP_X_FORWARDED_FOR and HTTP_CLIENT_IP in order to properly
        identify
     the visitor's IP address.
516
    You can use both an array or a comma-separated list of proxy
517
        addresses.
     as well as specifying whole subnets. Here are a few examples
518
520
    Comma-separated: '10.0.1.200,192.168.5.0/24'
               array('10.0.1.200', '192.168.5.0/24')
    Array:
52.1
  */
523 $config['proxy_ips'] = '';
 1 <?php</pre>
 2 defined('BASEPATH') OR exit('No direct script access allowed')
 4 /*
 5
    DATABASE CONNECTIVITY SETTINGS
     This file will contain the settings needed to access your
       database.
     For complete instructions please consult the 'Database
       Connection'
     page of the User Guide.
    EXPLANATION OF VARIABLES
14
15
16
                  The full DSN string describe a connection to
     ['dsn']
       the database.
     ['hostname'] The hostname of your database server.
    ['username'] The username used to connect to the database
    ['password'] The password used to connect to the database
    ['database'] The name of the database you want to connect to
    ['dbdriver'] The database driver. e.g.: mysqli.
         Currently supported:
```

```
cubrid, ibase, mssql, mysql, mysqli, oci8,
24
           odbc, pdo, postgre, sqlite, sqlite3, sqlsrv
25
    ['dbprefix'] You can add an optional prefix, which will be
26
      added
           to the table name when using the
                                              Query Builder class
    ['pconnect'] TRUE/FALSE - Whether to use a persistent
      connection
    ['db_debug'] TRUE/FALSE - Whether database errors should be
29
      displayed.
    ['cache_on'] TRUE/FALSE - Enables / disables query caching
    ['cachedir'] The path to the folder where cache files should
       be stored
    ['char_set'] The character set used in communicating with
      the database
    ['dbcollat'] The character collation used in communicating
      with the database
           NOTE: For MySQL and MySQLi databases, this setting is
3.4
       only used
             as a backup if your server is running PHP < 5.2.3
35
      or MySQL < 5.0.7
           (and in table creation queries made with DB Forge).
36
             There is an incompatibility in PHP with
      mysql_real_escape_string() which
             can make your site vulnerable to SQL injection if
38
      you are using a
             multi-byte character set and are running versions
39
      lower than these.
             Sites using Latin-1 or UTF-8 database character set
40
       and collation are unaffected.
    ['swap_pre'] A default table prefix that should be swapped
41
      with the dbprefix
    ['encrypt'] Whether or not to use an encrypted connection.
42
43
        'mysql' (deprecated), 'sqlsrv' and 'pdo/sqlsrv' drivers
      accept TRUE/FALSE
        'mysqli' and 'pdo/mysql' drivers accept an array with
45
      the following options:
          'ssl_kev'
                       - Path to the private key file
          'ssl_cert'
                       - Path to the public key certificate file
48
          'ssl_ca'
                       - Path to the certificate authority file
49
          'ssl_capath' - Path to a directory containing trusted
50
      CA certificates in PEM format
          'ssl_cipher' - List of *allowed* ciphers to be used
      for the encryption, separated by colons (':')
          'ssl_verify' - TRUE/FALSE; Whether verify the server
      certificate or not
    ['compress'] Whether or not to use client compression (MySQL
       only)
    ['stricton'] TRUE/FALSE - forces 'Strict Mode' connections
                - good for ensuring strict SQL while developing
56
57
    ['ssl_options'] Used to set various SSL options that can be
      used when making SSL connections.
    ['failover'] array - A array with 0 or more data for
      connections if the main should fail.
```

```
['save_queries'] TRUE/FALSE - Whether to "save" all executed
        queries.
            NOTE: Disabling this will also effectively disable
60
       both
             $this ->db->last_query() and profiling of DB queries.
61
            When you run a query, with this setting set to TRUE
       (default),
             CodeIgniter will store the SQL statement for
      debugging purposes.
            However, this may cause high memory usage,
64
       especially if you run
            a lot of SQL queries ... disable this to avoid that
65
      problem.
66
    The $active_group variable lets you choose which connection
       group to
    make active.
                   By default there is only one group (the '
68
      default' group).
69
    The $query_builder variables lets you determine whether or
      not to load
    the query builder class.
72 db4free.net:3306
  */
$ $active_group = 'default';
  $query_builder = TRUE;
76
  $db['default'] = array(
    'dsn' => '',
    'hostname' => 'localhost'.
79
    'username' => 'root',
80
    'password' => ',',
    'database' => 'actspotv2',
82
    'dbdriver' => 'mysqli',
    'dbprefix' => ''
    'pconnect' => FALSE,
    'db_debug' => (ENVIRONMENT !== 'production'),
86
    'cache_on' => FALSE,
87
    'cachedir' => '',
    'char_set' => 'utf8',
90
    'dbcollat' => 'utf8_general_ci',
90
    'swap_pre' => '',
91
    'encrypt' => FALSE,
92
    'compress' => FALSE,
    'stricton' => FALSE,
    'failover' => array(),
96
    'save_queries' => TRUE
```

```
1 <?php
2 defined('BASEPATH') OR exit('No direct script access allowed')
;
3
4 class c_kelola_user extends CI_Controller {
5
6 function __construct(){</pre>
```

```
parent:: __construct();
       $this -> load -> model('m_data_user');
8
       $this -> load -> helper('url');
0
       if ($this -> session -> userdata ('status') != "login") {
         redirect(site_url("c_login"));
       }
    }
     public function index()
16
       $\data['user'] = $\this -> m_data_user -> \tampil_data() -> \result
18
       ();
19
       $this -> load -> view ('v_kelola_user', $data);
     // start kelola prodi
24
    public function getProdi()
26
       $this -> output -> set_content_type ('application/json');
28
       $employee = $this -> m_data_user -> getprodiJSON();
       echo json_encode ($employee);
30
    }
    public function saveprodi()
       $input = $this -> m_data_user -> saveprodi();
       if ($input) {
36
         echo json_encode(['success' => true]);
       }else {
38
30
         echo json_encode(['Msg'=>'Some Error occured!.']);
40
    }
42
     public function updateprodi($id)
43
       $input = $this -> m_data_user -> updateprodi($id);
45
       if ($input) {
46
         echo json_encode(['success' => true]);
47
48
       }else {
         echo json_encode(['Msg'=>'Some Error occured!.']);
50
    public function destroyprodi()
       $id = $_REQUEST['id_prodi'];
       $input = $this -> m_data_user -> destroyprodi($id);
       if ($input) {
56
         echo json_encode(array('success'=>true));
       }else {
58
         echo json_encode(array('errorMsg'=>'Some errors occured.
59
       <sup>'</sup>));
       }
60
```

```
//end kelola prodi
63
     // start kelola dosen
     public function getdosen()
67
68
       $this -> output -> set_content_type ('application/json');
       $employee = $this -> m_data_user -> getdosenJSON();
       echo json_encode ($employee);
     public function savedosen()
74
75
       $input = $this->m_data_user->savedosen();
76
       if ($input) {
         echo json_encode(['success' => true]);
78
       }else {
79
         echo json_encode(['Msg'=>'Some Error occured!.']);
80
82
83
     public function updatedosen ($id)
85
       $input = $this -> m_data_user -> updatedosen($id);
86
       if ($input) {
87
88
         echo json_encode(['success' => true]);
       }else {
         echo json_encode(['Msg'=>'Some Error occured!.']);
90
01
     public function destroydosen()
94
       $id = $_REQUEST['id_dosen'];
       $input = $this -> m_data_user -> destroydosen($id);
06
       if ($input) {
97
         echo ison_encode(array('success'=>true));
       }else {
         echo ison_encode (array ('errorMsg'=>'Some errors occured.
100
       <sup>'</sup>));
       }
     }
102
     //end kelola dosen
104
     // start kelola mahasiswa
106
     public function getmahasiswa()
108
109
       $this -> output -> set_content_type('application/json');
       $employee = $this -> m_data_user -> getmahasiswaJSON();
       echo json_encode($employee);
     public function savemahasiswa()
```

```
116
       $input = $this -> m_data_user -> savemahasiswa();
       if ($input) {
118
         echo json_encode(['success' => true]);
       }else {
120
         echo json_encode(['Msg'=>'Some Error occured!.']);
     }
124
     public function updatemahasiswa ($id)
126
       $input = $this -> m_data_user -> updatemahasiswa($id);
128
       if ($input) {
         echo json_encode(['success' => true]);
       }else {
130
         echo json_encode(['Msg'=>'Some Error occured!.']);
     public function destroymahasiswa()
134
       $id = $_REQUEST['id_mahasiswa'];
136
       $input = $this -> m_data_user -> destroy mahasis wa ($id);
       if ($input) {
138
         echo json_encode(array('success'=>true));
139
       }else {
140
         echo json_encode(array('errorMsg'=>'Some errors occured.
        <sup>'</sup>));
142
144
     //end kelola prodi
145
146
     // start kelola intern
147
148
     public function getintern()
149
150
       $this -> output -> set_content_type ('application/json');
       $employee = $this -> m_data_user -> getinternJSON();
       echo json_encode ($employee);
     public function saveintern()
156
       $input = $this -> m_data_user -> saveintern();
159
       if ($input) {
         echo json_encode(['success' => true]);
160
       }else {
         echo json_encode(['Msg'=>'Some Error occured!.']);
162
163
     }
164
     public function updateintern ($id)
166
167
       $input = $this -> m_data_user -> updateintern($id);
168
       if ($input) {
169
         echo json_encode(['success' => true]);
170
```

```
}else {
         echo ison_encode(['Msg'=>'Some Error occured!.']);
174
     public function destroyintern()
175
       $id = $_REQUEST['id_intern'];
       $input = $this -> m_data_user -> destroyintern($id);
178
       if ($input) {
         echo json_encode(array('success'=>true));
180
       }else {
         echo json_encode(array('errorMsg'=>'Some errors occured.
182
       '));
183
     }
185
     // start kelola absensi
186
187
     public function getabsensi()
188
189
       $this -> output -> set_content_type('application/json');
190
       $employee = $this -> m_data_user -> getabsensiJSON();
       echo json_encode ($employee);
193
     public function saveabsensi()
195
196
197
       $input = $this -> m_data_user -> saveabsensi();
       if ($input) {
         echo json_encode(['success' => true]);
199
       }else {
200
         echo json_encode(['Msg'=>'Some Error occured!.']);
202
204
     public function updateabsensi($id)
206
       $input = $this -> m_data_user -> updateabsensi($id);
207
       if ($input) {
         echo json_encode(['success' => true]);
209
       }else {
         echo json_encode(['Msg'=>'Some Error occured!.']);
       }
     public function destroyabsensi()
       $id = $_REQUEST['id_absensi'];
216
       $input = $this -> m_data_user -> destroyabsensi($id);
       if ($input) {
         echo json_encode(array('success'=>true));
       }else {
         echo json_encode(array('errorMsg'=>'Some errors occured.
       '));
224
```

```
//end kelola absensi
226
     // start kelola trigger
228
     public function gettrigger_radius()
       $this -> output -> set_content_type ('application/json');
230
       $employee = $this -> m_data_user -> gettrigger_radiusJSON();
       echo json_encode ($employee);
     // end kelola trigger
     // start kelola user
236
       public function getCustomers()
238
       $this -> output -> set_content_type ('application/json');
       $employee = $this -> m_data_user -> getCustomers();
240
       echo json_encode($employee);
241
242
     public function getCustomerJSON()
243
244
       $this -> output -> set_content_type ('application/json');
245
       $\data = \$\this -> \m_data_user -> \getCustomersJSON();
246
         echo ison_encode($data);
247
249
       public function saveCustomer()
250
       $input = $this -> m_data_user -> saveCustomer();
       if ($input) {
         echo ison_encode(['success' => true]);
254
       }else {
         echo json_encode(['Msg'=>'Some Error occured!.']);
256
258
       public function updateCustomer($id)
260
261
       $input = $this -> m_data_user -> updateCustomer($id);
262
       if ($input) {
         echo json_encode(['success' => true]);
264
       }else {
265
         echo json_encode(['Msg'=>'Some Error occured!.']);
266
267
     public function destroyCustomer()
269
       $id = intval($_REQUEST['id_user']);
       $input = $this -> m_data_user -> destroy Customer($id);
       if ($input) {
         echo json_encode(array('success'=>true));
       }else {
         echo json_encode(array('errorMsg'=>'Some errors occured.
276
       '));
279
```

280

```
281
  <?php
  class c_login extends CI_Controller{
     function __construct(){
       parent:: __construct();
       $this -> load -> model('m_login');
 8
 9
     }
     function index(){
       $this -> load -> view ('login');
     }
18
     function aksi_login(){
       $username = $this ->input ->post('username');
20
       $password = $this->input->post('password');
       $where = array(
         'username' => $username,
         'password' => $password
24
2.5
         );
       $cek = $this -> m_login -> cek_login ("user", $where) -> num_rows
26
       ();
       $cekstatus = $this -> m_login -> cek_login ("user", $where) ->
       row_array();
2.8
       if(scek > 0)
20
         if ($cekstatus['status_user'] == "aktif") {
30
            if($cekstatus['role_user'] == "admin"){
              $data_session = array(
                'nama' => $username,
                'id' => $cekstatus['id_user'],
34
                'statusakun' => $cekstatus['status_user'],
                'status' => "login"
36
                );
              $this -> session -> set_userdata ($data_session);
30
              redirect(site_url("dashboard"));
40
           } else if($cekstatus['role_user'] == "dosen"){
41
              data_session = array(
42
                'nama' => $username,
43
                'id' => $cekstatus['id_user'],
                'statusakun' => $cekstatus['status_user'],
45
                'status' => "login"
                );
              $this -> session -> set_userdata ($data_session);
48
49
              redirect(site_url("dashboard/viewdosen"));
50
51
```

```
else {
           echo 'akun anda tidak aktif';
54
      else if (scek == 0)
        echo "Akun tidak ada !";
      } else {
58
        echo "Username dan password salah!";
50
60
    }
    function logout(){
64
      $this -> session -> sess_destroy();
       redirect(site_url('c_login'));
67
```

#### src/web/controllers/cregister.php

```
defined ('BASEPATH') OR exit ('No direct script access allowed')
  class dashboard extends CI_Controller {
    function __construct(){
      parent:: __construct();
      $this -> load -> library ('pdf');
      $this -> load -> model('m_data_peta');
8
9
      $this -> load -> model('m_data_user');
      $this -> load -> helper('url');
       if ($this -> session -> userdata ('status') != "login") {
         redirect(site_url("c_login"));
14
    }
16
    public function index ()
18
      $data['data_prodi'] = $this->m_data_user->
20
       getprodidropdownn()->result();
      $data['totaldosen'] = $this->m_data_user->
       getjumlahdosenJSON();
      $\data['totaldoseninternal'] = $\this -> m_data_user ->
       getjumlahdoseninternalJSON();
      $data['gettahunangkatan'] = $this->m_data_user->
       gettahunangkatan()->result();
      $data['totalmahasiswa2015'] = $this->m_data_user->
2.4
       getjumlahmahasiswa2015();
      $data['totalmahasiswa2016'] = $this->m_data_user->
       getjumlahmahasiswa2016();
26
      $data['totalmahasiswa2017'] = $this->m_data_user->
       getjumlahmahasiswa2017();
      $data['totalmahasiswa'] = $this->m_data_user->
       getjumlahmahasiswaJSON();
      $data['totallokasiinternship'] = $this->m_data_user->
28
       getjumlahlokasiinternshipJSON();
```

```
$\data['totaluser'] = \$\this -> m_data_user -> getjumlahuserJSON
2.9
       $data['data_mahasiswa'] = $this->m_data_user->
30
       getdata_mahasiswa()->result();
       $data['data_dosen'] = $this->m_data_user->getdata_dosen()
       -> result():
       $data['data_user'] = $this->m_data_user->getdata_user()->
       result():
       $\data['data_intern'] = $\this -> m_data_user -> getintern()->
       result():
35
       $this -> load -> view ('index', $data);
36
     function perorang(){
       //$x['data']=$this->m_grafik->get_data_stok();
40
       $id = $this ->input ->post('npmmahasiswa');
41
       x['ian'] =  this ->m_data_user -> get_data_ian($id):
       x['feb'] = this \rightarrow m_data_user \rightarrow get_data_feb(sid);
       x['mar'] = this \rightarrow m_data_user \rightarrow get_data_mar(sid);
       x['apr'] = this \rightarrow m_data_user \rightarrow get_data_apr(tid);
45
       x['may'] = this \rightarrow m_data_user \rightarrow get_data_may(sid);
46
           'jun']=$this->m_data_user->get_data_june($id);
       x['iul'] = this \rightarrow m_data_user \rightarrow get_data_july (sid);
       x['aug'] = this \rightarrow m_data_user \rightarrow get_data_aug(sid);
49
       x['sep'] = this \rightarrow m_data_user \rightarrow get_data_sep(sid):
50
       x['oct'] = this \rightarrow m_data_user \rightarrow get_data_oct(sid);
       x['nov'] = this \rightarrow m_data_user \rightarrow get_data_nov(sid):
       x['dec'] = this \rightarrow m_data_user \rightarrow get_data_dec(sid);
       \frac{\sinh s}{\sinh s} = \frac{\sinh s}{\sinh s}
56
     function viewdosen(){
       $data['data_prodi'] = $this->m_data_user->
58
       getprodidropdownn()->result();
       $data['totaldosen'] = $this->m_data_user->
59
       getjumlahdosenJSON();
       $data['totaldoseninternal'] = $this->m_data_user->
       getjumlahdoseninternalJSON();
       $data['gettahunangkatan'] = $this->m_data_user->
       gettahunangkatan()->result();
       $\data['totalmahasiswa2015'] = $\this -> m_data_user ->
62
       getjumlahmahasiswa2015();
       $\data['totalmahasiswa2016'] = $\this -> m_data_user ->
       getjumlahmahasiswa2016();
       $data['totalmahasiswa2017'] = $this->m_data_user->
       getjumlahmahasiswa2017();
       $data['totalmahasiswa'] = $this->m_data_user->
       getjumlahmahasiswaJSON();
       $\data['totallokasiinternship'] = \$\this -> m_\data_\user->
       getjumlahlokasiinternshipJSON();
       $data['totaluser'] = $this->m_data_user->getjumlahuserJSON
       ();
       $data['data_mahasiswa'] = $this->m_data_user->
68
       getdata_mahasiswa()->result();
```

```
$data['data_dosen'] = $this->m_data_user->getdata_dosen()
69
       \rightarrowresult();
       $data['data_user'] = $this -> m_data_user -> getdata_user()->
70
       result();
       $data['data_intern'] = $this->m_data_user->getintern()->
       result():
       $this -> load -> view ('dosen', $data);
     }
     /// start kelola halaman dosen
76
     // start kelola profile dosen
78
79
80
     public function getprofiledosen()
22
83
       $this -> output -> set_content_type('application/json');
84
       $id_pengguna = $this -> session -> userdata("id");
85
       $employee = $this -> m_data_user -> getprofiledosenJSON(
86
       $id_pengguna);
       echo json_encode ($employee);
87
88
89
     public function updateprofiledosen ($id)
90
91
       $input = $this->m_data_user->updatprofiledosentabledosen(
02
       $id):
       $input2 = $this->m_data_user->updatprofiledosentableuser(
93
       $id);
       if ($input) {
94
         echo json_encode(['success' => true]);
       }else {
         echo json_encode(['Msg'=>'Some Error occured!.']);
     }
99
100
     //end kelola profile dosen
102
     // start view dosen mahasiswa
103
104
     public function getdosenmahasiswa()
       $this->output->set_content_type('application/json');
108
       $id_pengguna = $this -> session -> userdata("id");
109
       $employee = $this -> m_data_user -> getdosenmahasiswa (
       $id_pengguna);
       echo json_encode ($employee);
     }
     //end view dosen mahasiswa
114
     // start kelola dosen intern
```

```
public function getdosenintern()
118
110
       $this -> output -> set_content_type('application/json');
120
       $id_pengguna = $this -> session -> userdata("id");
       $employee = $this -> m_data_user -> getdoseninternJSON(
       $id_pengguna);
       echo ison_encode ($employee);
     }
124
     public function updatedosenintern ($id)
126
       $input = $this -> m_data_user -> updatedosenintern($id);
128
129
       if ($input) {
         echo json_encode(['success' => true]);
130
       }else {
         echo json_encode(['Msg'=>'Some Error occured!.']);
     }
134
     // end kelola dosen intern
136
     //end kelola halaman dosen
138
130
     // start kelola absensi halaman dosen
     public function getabsensimahasiswahalamandosenJSON()
142
143
       $this -> output -> set_content_type ('application/json');
       $id_pengguna = $this->session->userdata("id");
145
       $employee = $this -> m_data_user ->
146
       getabsensimahasiswahalamandosenJSON ($id_pengguna);
       echo json_encode ($employee);
148
149
     public function getmahasiswauntukdosenJSON()
150
       $this -> output -> set_content_type ('application/json');
       $id_pengguna = $this -> session -> userdata("id");
       $data = $this -> m_data_user -> getmahasis wauntuk dosen JSON (
       $id_pengguna);
         echo json_encode($data);
156
     //end kelola absensi halaman dosen
     public function buatpdfprodi() {
159
           pdf = new FPDF('1', 'mm', 'A5');
160
       // membuat halaman baru
       date_default_timezone_set('US/Eastern');
162
       $currentdate = date("m-d-Y");
164
           $pdf->AddPage();
           // setting jenis font yang akan digunakan
166
           $pdf->SetFont('Arial','B',16);
167
           // mencetak string
168
           $pdf->Cell(190,7,'Laporan Daftar Prodi',0,1,'C');
           $pdf->SetFont('Arial', 'B', 12);
170
```

```
$pdf->Cell(190,7,$currentdate,0,1,'C');
            // Memberikan space kebawah agar tidak terlalu rapat
            pdf \rightarrow Cell(10,7,'',0,1);
            $pdf->SetFont('Arial', 'B', 10);
174
            pdf \rightarrow Cell(20,6,'ID Prodi',1,0);
175
            $pdf->Cell(85,6,'Nama Prodi',1,1);
            $pdf->SetFont('Arial','',10);
            $mahasiswa = $this ->db->get('prodi')->result();
178
            foreach ($mahasiswa as $row){
                 pdf - Cell(20,6, row - id_prodi, 1, 0);
180
                 $pdf->Cell(85,6,$row->nama_prodi,1,1);
182
            $pdf->Output();
183
184
     public function buatpdfuser(){
186
            pdf = new FPDF('1', 'mm', 'A5');
187
       // membuat halaman baru
188
       date_default_timezone_set('US/Eastern');
189
       $currentdate = date("m-d-Y");
            $pdf->AddPage();
192
            // setting jenis font yang akan digunakan
            $pdf->SetFont('Arial', 'B', 16);
            // mencetak string
            $pdf->Cell(190,7,'Laporan Daftar user',0,1,'C');
196
            $pdf->SetFont('Arial', 'B', 12);
108
            $pdf->Cell(190,7,$currentdate,0,1,'C');
            // Memberikan space kebawah agar tidak terlalu rapat
            pdf \rightarrow Cell(10,7,'',0,1);
200
            $pdf->SetFont('Arial', 'B', 10);
201
            pdf \rightarrow Cell(20,6,'ID user',1,0);
       pdf \rightarrow Cell(25,6,'Username',1,0);
203
       pdf \rightarrow Cell(25,6, 'Password', 1,0);
204
       pdf \rightarrow Cell(25,6,'Status',1,0);
       $pdf->Cell(25,6,'Role',1,1);
206
            $pdf->SetFont('Arial','',10);
207
            $mahasiswa = $this ->db->get('user')->result();
208
            foreach ($mahasiswa as $row){
                 pdf \rightarrow Cell(20,6,srow \rightarrow id_user,1,0);
          pdf \rightarrow Cell(25,6,srow \rightarrow username,1,0);
          pdf \rightarrow Cell(25,6, row \rightarrow password, 1, 0);
          pdf \rightarrow Cell(25,6,srow \rightarrow status\_user,1,0);
          $pdf->Cell(25,6,$row->role_user,1,1);
214
            $pdf->Output();
216
218
219
     public function buatpdfdosen(){
            pdf = new FPDF('1', 'mm', 'A5');
220
       // membuat halaman baru
       date_default_timezone_set('US/Eastern');
       $currentdate = date("m-d-Y");
224
            $pdf->AddPage();
            // setting jenis font yang akan digunakan
226
```

```
$pdf->SetFont('Arial','B',16);
            // mencetak string
228
            $pdf->Cell(190,7,'Laporan Daftar dosen',0,1,'C');
229
            $pdf->SetFont('Arial', 'B', 12);
230
            $pdf->Cell(190,7,$currentdate,0,1,'C');
            // Memberikan space kebawah agar tidak terlalu rapat
            pdf \rightarrow Cell(10,7,'',0,1);
            $pdf->SetFont('Arial','B',10);
234
        pdf \rightarrow Cell(20,6,'ID Dosen',1,0);
        $pdf->Cell(70,6,'Nama Dosen',1,0);
236
        $pdf->Cell(15,6,'Prodi',1,0);
        #$pdf->Cell(70,6,'Foto',1,0);
238
        $pdf->Cell(25,6,'Status',1,1);
239
            $pdf->SetFont('Arial','',10);
240
            $mahasiswa = $this ->db->get('dosen')->result();
            foreach ($mahasiswa as $row){
242
          pdf \rightarrow Cell(20.6, row \rightarrow id_dosen.1.0);
          pdf \rightarrow Cell(70,6,srow \rightarrow nama_dosen,1,0);
244
          pdf \rightarrow Cell (15.6. row \rightarrow id_prodi_dosen.1.0):
245
          ##$pdf->Cell(70,6,$row->foto_dosen,1,0);
          pdf \rightarrow Cell(25,6, row \rightarrow status, 1, 1);
247
248
            $pdf->Output();
250
     public function buatpdfmahasiswa(){
            pdf = new FPDF('1', 'mm', 'A5');
254
        // membuat halaman baru
        date_default_timezone_set('US/Eastern');
        $currentdate = date("m-d-Y");
256
            $pdf->AddPage();
            // setting jenis font yang akan digunakan
2.59
            $pdf->SetFont('Arial', 'B', 16);
            // mencetak string
261
            $pdf->Cell(190,7,'Laporan Daftar mahasiswa',0,1,'C');
262
            $pdf->SetFont('Arial', 'B', 12);
263
            $pdf->Cell(190,7,$currentdate,0,1,'C');
264
            // Memberikan space kebawah agar tidak terlalu rapat
265
            pdf \rightarrow Cell(10,7,'',0,1);
266
            $pdf->SetFont('Arial', 'B', 10);
267
        pdf \rightarrow Cell(30,6,'ID mahasiswa',1,0);
268
        pdf \rightarrow Cell(40,6,'Nama',1,0);
269
        pdf \rightarrow Cell(15,6,'Kelas',1,0);
        $pdf->Cell(15,6,'Prodi',1,0);
        #$pdf->Cell(20,6,'Foto',1,0);
        $pdf->Cell (25,6, 'Angkatan', 1,1);
274
            $pdf->SetFont('Arial','',10);
276
            $mahasiswa = $this ->db->get('mahasiswa')->result();
            foreach ($mahasiswa as $row){
2.78
          pdf \rightarrow Cell(30,6,srow \rightarrow id_mahasiswa,1,0);
          pdf \rightarrow Cell(40,6,srow \rightarrow nama_mahasiswa,1,0);
280
          #$pdf->Cell(20,6,$row->foto_mahasiswa,1,0);
281
          pdf \rightarrow Cell (15,6, row \rightarrow kelas_mahasiswa, 1,0);
282
```

```
pdf \rightarrow Cell(15,6,srow \rightarrow id_prodi_mahasiswa,1,0);
283
          pdf \rightarrow Cell(25,6, row \rightarrow angkatan_mahasiswa, 1, 1);
284
285
            $pdf->Output();
     }
288
     public function buatpdfintern(){
289
            pdf = new FPDF('1', 'mm', 'A5');
290
       // membuat halaman baru
       date_default_timezone_set('US/Eastern');
       $currentdate = date("m-d-Y");
203
294
            $pdf->AddPage();
            // setting jenis font yang akan digunakan
            $pdf->SetFont('Arial','B',16);
            // mencetak string
208
            $pdf->Cell(190,7,'Laporan Daftar intern',0,1,'C');
            $pdf->SetFont('Arial', 'B', 12);
300
            $pdf->Cell(190,7,$currentdate,0,1,'C');
            // Memberikan space kebawah agar tidak terlalu rapat
302
            pdf \rightarrow Cell(10,7,'',0,1);
303
            $pdf->SetFont('Arial', 'B', 10);
       $pdf->Cell(20,6,'ID Intern',1,0);
305
       pdf \rightarrow Cell(25,6,'ID Koor Intern',1,0);
306
       $pdf->Cell(20,6,'Status',1,0);
307
       $pdf->Cell(40,6,'Tanggal Mulai',1,0);
308
300
       $pdf->Cell(40,6,'Tanggal Berakhir',1,1);
            $pdf->SetFont('Arial','',10);
            $mahasiswa = $this ->db->get('intern')->result();
            foreach ($mahasiswa as $row){
          $pdf->Cell(20,6,$row->id_intern,1,0);
          pdf \rightarrow Cell(25,6, row \rightarrow id_koor_intern, 1, 0);
314
          pdf \rightarrow Cell(20,6, row \rightarrow status\_intern, 1, 0);
          pdf \rightarrow Cell(40,6,srow \rightarrow tgl_mulai_intern,1,0);
316
          pdf \rightarrow Cell(40,6, row \rightarrow tgl_akhir_intern, 1, 1);
            $pdf->Output();
319
     public function getaddress ($lat,$lng)
324
       #hapus pagar pada lat dan lng kemudian ubah return jadi
       echo
       #$1at = "-6.873656";
326
       #$lng = "107.575550";
       $url = 'https://us1.locationiq.com/v1/reverse.php?key=1
328
        e2358be8ca540&lat='.$lat.'&lon='.$lng.'&format=json';
       $ison = @file_get_contents($url);
330
       $data=json_decode($json, true);
       $status = $data['display_name'];
        if (isset ($status))
       {
       return $status;
```

```
336
       else
       {
338
       return false:
330
3.42
     public function buatpdfabsensi(){
343
            pdf = new FPDF('1', 'mm', 'A3');
       // membuat halaman baru
345
       date_default_timezone_set('US/Eastern');
       $currentdate = date("m-d-Y");
3.17
348
            $pdf->AddPage();
349
            // setting jenis font yang akan digunakan
            $pdf->SetFont('Arial','B',16);
            // mencetak string
            $pdf->Cell(190,7,'Laporan Daftar absensi',0,1,'C');
            $pdf->SetFont('Arial', 'B', 12);
354
            $pdf->Cell(190,7,$currentdate,0,1,'C');
            // Memberikan space kebawah agar tidak terlalu rapat
356
            pdf \rightarrow Cell(10,7,'',0,1);
            $pdf->SetFont('Arial','B',10);
       $pdf->Cell(15,6,'Absensi',1,0);
       $pdf->Cell(15,6,'Intern',1,0);
360
       $pdf->Cell(20,6,'Mahasiswa',1,0);
361
       pdf \rightarrow Cell(20,6,'Dosen',1,0);
362
363
       pdf \rightarrow Cell(140,6,'Lokasi',1,0);
       #$pdf->Cell (45,6, 'Longitude', 1,0);
       $pdf->Cell(20,6,'Jarak',1,0);
365
       $pdf->Cell(25,6,'Tanggal',1,0);
366
       $pdf->Cell(20,6,'Kegiatan',1,0);
367
       pdf \rightarrow Cell(25,6,'IMEI',1,1);
368
       $pdf->SetFont('Arial','',10);
369
       this \rightarrow db \rightarrow distinct();
       $this ->db->select('a.id_absensi,a.id_intern_absensi,a.
        id_mahasiswa_absensi,a.id_dosen_absensi,
       a.latitude_absensi ,a.longitude_absensi ,a.tgl_waktu_absensi
        , a. imei_perangkat_absensi , a. kegiatan_absensi
        ,b.pergeseran_absensi ');
       $this -> db-> from ('absensi a');
374
       $this->db->join('detail_absensi b', 'b.
        id_mahasiswa_dt_absensi=a.id_mahasiswa_absensi', 'inner');
       $mahasiswa = $this ->db->get('absensi')->result();
378
            foreach ($mahasiswa as $row){
          pdf \rightarrow Cell (15, 6, row \rightarrow id_absensi, 1, 0);
380
          $pdf->Cell(15,6,$row->id_intern_absensi,1,0);
          $pdf->Cell (20,6,$row->id_mahasiswa_absensi,1,0);
382
          pdf \rightarrow Cell(20,6,srow \rightarrow id_dosen_absensi,1,0);
383
          $lat =\$row->latitude_absensi;
384
          $long = $row->longitude_absensi;
385
          pdf \rightarrow Cell(140,6, this \rightarrow getaddress(tlat, tlong), 1, 0);
386
          $pdf->Cell(20,6,$this->getstatusjarak($row->
387
        pergeseran_absensi),1,0);
```

```
$pdf->Cell (25,6,$row->tgl_waktu_absensi,1,0);
388
          $pdf->Cell(20,6,$row->kegiatan_absensi,1,0);
380
         $pdf->Cell(25,6,$row->imei_perangkat_absensi,1,1);
390
391
            $pdf->Output();
     }
393
304
     public function getstatusjarak ($pergeseran_absensi){
395
396
       if ($pergeseran_absensi > 20){
          return 'out spot';
       } else {
          return 'on the spot';
300
400
401
     function buatlaporangrafik ($id){
403
            x['data'] = this \rightarrow m_data_user \rightarrow get_data_stok(tid);
404
            $this -> load -> view ('chart_view', $x);
405
406
407
408
  <?php
   class M_data_peta extends CI_Model{
     function tampil_data(){
       return $this ->db->get('absensi');
 6
 7
  <?php
   class m_data_user extends CI_Model{
       function __construct()
     {
 6
       parent:: __construct();
            $this -> load -> database()
 8
 0
     }
       function tampil_data(){
       return $this -> db->get('user');
       }
       // get all data mahasiswa
16
       public function getdata_mahasiswa(){
18
            return $this -> db->get('mahasiswa');
20
       }
       // get data intern
       public function getintern(){
2.4
            $this ->db->where('status_intern','berjalan');
26
```

```
return $this -> db->get('intern');
28
       }
29
30
       // get all data dosen
       public function getdata_dosen(){
34
           return $this -> db->get('dosen');
       }
       public function getdata_user(){
38
39
           return $this -> db->get('user');
       }
40
41
42
       // get jumlah dosen eksternal
44
       public function getjumlahdosenJSON(){
           $this ->db->where ('status', 'eksternal');
48
           return $this -> db->get('dosen')->num_rows();
49
       }
       // get jumlah dosen internal
       public function getjumlahdoseninternalJSON(){
5.4
           $this ->db->where ('status', 'internal');
56
           return $this -> db->get('dosen')->num_rows();
       // get jumlah dosen
       public function gettahunangkatan(){
           $this -> db-> select ('angkatan_mahasiswa');
63
           this \rightarrow db \rightarrow distinct();
           $this->db->order_by("angkatan_mahasiswa", "asc");
66
           return $this -> db->get('mahasiswa');
       }
68
69
       // get jumlah mahasiswa 2015
70
       public function getjumlahmahasiswa2015(){
           $this ->db->where ('angkatan_mahasiswa', '2015');
74
           return $this -> db->get('mahasiswa')->num_rows();
76
       // get jumlah mahasiswa
78
       // get jumlah mahasiswa 2016
79
       public function getjumlahmahasiswa2016(){
80
           $this ->db->where ('angkatan_mahasiswa', '2016');
82
```

```
83
            return $this -> db->get('mahasiswa')->num_rows();
9.4
85
       // get jumlah mahasiswa
86
       // get jumlah mahasiswa 2017
       public function getjumlahmahasiswa2017(){
20
90
            $this ->db->where ('angkatan_mahasiswa', '2017');
            return $this -> db->get('mahasiswa')->num_rows();
0.4
       // get jumlah mahasiswa
95
96
       // get jumlah mahasiswa
       public function getjumlahmahasiswaJSON(){
00
            $query = $this -> db->get('mahasiswa');
100
            if ( query \rightarrow num_rows () > 0)
102
            return $query->num_rows();
            }
104
            else
106
            return 0;
108
109
       // get jumlah mahasiswa
110
       // get jumlah intern
       public function getjumlahlokasiinternshipJSON(){
            query = \frac{\sinh - db}{\gcd ('intern')};
            if (query \rightarrow num_rows() > 0)
            return $query->num_rows();
            else
120
            return 0;
       // get jumlah intern
       // get jumlah user
       public function getjumlahuserJSON(){
128
            $this ->db->where ('status_user', 'aktif');
            130
            if ( query -> num_rows () > 0)
            return $query->num_rows();
135
            else
136
            return 0;
138
```

```
// get jumlah user
140
141
       public function getCustomers()
142
143
       $page = isset($_POST['page']) ? intval($_POST['page']) :
144
       1;
           $rows = isset($_POST['rows']) ? intval($_POST['rows'])
145
        : 50:
           $sort = isset($_POST['sort']) ? strval($_POST['sort'])
        : 'user.id_user';
           $order = isset($_POST['order']) ? strval($_POST['order
147
       '1) : 'asc';
           $search = isset($_POST['search_customer']) ? strval(
148
       $_POST['search_customer']) : '';
           fiset = (page - 1) * page - 1
149
150
           $result = array();
           $result['total'] = $this->db->get('user')->num_rows();
           som = array();
154
           // select data from table product
           $query = "SELECT *
156
               from user
               where concat(id_user, username, password, status_user
158
       role_user) like '% search%' order by sort sorder limit
       $offset , $rows";
150
           $country = $this ->db->query ($query)->result_array ();
           $result = array_merge($result, ['rows' => $country]);
161
           return $result:
162
       }
164
       public function getCustomersJSON(){
166
           $query = $this -> db->get('absensi');
168
169
           // Return associative data array
           return $query->result_array();
       }
174
       // start prodi
176
       public function getprodiJSON(){
           $page = isset($_POST['page']) ? intval($_POST['page'])
180
        : 1:
           $rows = isset($_POST['rows']) ? intval($_POST['rows'])
        : 50;
           $sort = isset($_POST['sort']) ? strval($_POST['sort'])
182
        : 'prodi.id_prodi';
           $order = isset($_POST['order']) ? strval($_POST['order
183
       ']) : 'asc';
```

```
$search = isset($_POST['search_prodi']) ? strval(
184
       $_POST['search_prodi']) : '';
            fiset = (page -1)*frows;
185
186
            $result = array();
187
            $result['total'] = $this->db->get('prodi')->num_rows()
           som = array();
189
190
            // select data from table product
            $query = "SELECT *
                from prodi
103
                where concat(id_prodi,'', nama_prodi) like '%
194
       $search%' order by $sort $order limit $offset, $rows";
            $country = $this ->db->query ($query)->result_array();
196
            $result = array_merge($result, ['rows' => $country]);
            return $result;
198
199
       public function saveprodi()
200
            data = \Gamma
202
                'id_prodi' => $this -> input -> post('id_prodi'),
203
                'nama_prodi' => $this -> input -> post('nama_prodi'),
204
            1:
            $this ->db->insert('prodi', $data);
206
            return $this:
207
       }
208
       public function updateprodi($id)
       {
            data =
                'nama_prodi' => $this -> input -> post('nama_prodi'),
            1:
216
            $this ->db->where ('id_prodi', $id);
218
            this \rightarrow db \rightarrow set(sdata);
            return $this -> db-> update ('prodi');
220
       }
       public function destroyprodi($id_prodi)
            $this ->db->where ('id_prodi', $id_prodi);
            return $this ->db->delete ('prodi');
226
            // return $this ->db->delete ($this ->table, ['id' => $id
       ]);
       //end prodi
230
       // start dosen
       public function getdosenJSON(){
```

```
236
            $page = isset($_POST['page']) ? intval($_POST['page'])
         . 1:
            $rows = isset($_POST['rows']) ? intval($_POST['rows'])
238
         : 50:
            $sort = isset($_POST['sort']) ? strval($_POST['sort'])
         : 'dosen.id_dosen';
            $order = isset($_POST['order']) ? strval($_POST['order
240
        '1) : 'asc':
            $search = isset($_POST['search_dosen']) ? strval(
        $_POST['search_dosen']) : '';
            fiset = (page - 1) * rows;
242
243
            $result = arrav():
244
            \{\text{result}[', \text{total}'] = \{\text{this} \rightarrow \text{db} \rightarrow \text{get}(', \text{dosen}') \rightarrow \text{num\_rows}()\}
245
            som = array();
246
247
            // select data from table product
248
            $query = "SELECT *
249
                 from dosen
250
                 where concat(id_dosen, nama_dosen, id_prodi_dosen,
        foto_dosen, status) like '%$search%' order by $sort $order
         limit $offset, $rows";
252
            $country = $this ->db->query($query)->result_array();
            $result = array_merge($result, ['rows' => $country]);
254
            return $result;
        public function savedosen()
258
            data = \Gamma
                 'id_dosen' => $this -> input -> post('id_dosen'),
260
                 'nama_dosen' => $this -> input -> post('nama_dosen'),
261
                 'id_prodi_dosen' => $this -> input -> post('
262
        id_prodi_dosen'),
                 'foto_dosen' => $this -> input -> post('foto_dosen'),
263
                 'status' => $this -> input -> post('status'),
            $this ->db->insert ('dosen', $data);
266
            return $this:
267
        }
268
269
        public function updatedosen($id)
        {
            data = [
                 'nama_dosen' => $this -> input -> post('nama_dosen'),
274
                 'id_prodi_dosen' => $this -> input -> post('
        id_prodi_dosen'),
                 'foto_dosen' => $this -> input -> post('foto_dosen'),
276
                 'status' => $this -> input -> post('status'),
278
            ];
279
280
            \frac{1}{3} $\text{this} ->\db->\text{where} ('id_dosen', \$id);
281
```

```
this \rightarrow db \rightarrow set(sdata);
282
           return $this ->db->update('dosen');
283
       }
284
285
       public function destroydosen ($id_dosen)
           $this ->db->where ('id_dosen', $id_dosen);
288
           return $this ->db->delete ('dosen'):
289
           // return $this ->db->delete ($this ->table, ['id' => $id
290
       ]);
       }
291
202
       //end dosen
293
294
       // start mahasiswa
       public function getmahasiswaJSON(){
296
207
298
           $page = isset($_POST['page']) ? intval($_POST['page'])
        : 1;
           $rows = isset($_POST['rows']) ? intval($_POST['rows'])
200
        : 50:
           $sort = isset($_POST['sort']) ? strval($_POST['sort'])
301
        : 'mahasiswa.id_mahasiswa';
           $order = isset($_POST['order']) ? strval($_POST['order
302
       '1) : 'asc':
           $search = isset($_POST['search_mahasiswa']) ? strval(
303
       $_POST['search_mahasiswa']) : '';
           fiset = (page -1)*frows;
305
           $result = array();
306
           $result['total'] = $this->db->get('mahasiswa')->
307
       num_rows();
           row = array();
309
           // select data from table product
           $query = "SELECT *
                from mahasiswa
                where concat (id_mahasiswa, nama_mahasiswa,
       kelas_mahasiswa,id_prodi_mahasiswa,angkatan_mahasiswa,
       foto_mahasiswa) like '%$search%' order by $sort $order
       limit $offset, $rows";
314
           $country = $this ->db->query($query)->result_array();
           $result = array_merge($result, ['rows' => $country]);
316
           return $result;
       }
       public function savemahasiswa()
           data = [
                'id_mahasiswa' => $this -> input -> post('id_mahasiswa
       '),
                'nama_mahasiswa' => $this ->input ->post('
       nama_mahasiswa'),
                'kelas_mahasiswa' => $this ->input ->post('
       kelas_mahasiswa'),
```

```
'id_prodi_mahasiswa' => $this ->input ->post('
       id_prodi_mahasiswa'),
                'angkatan_mahasiswa' => $this ->input ->post('
        angkatan_mahasiswa').
                'foto_mahasiswa' => $this ->input ->post('
       foto_mahasiswa').
328
            1:
            $this ->db->insert ('mahasiswa', $data);
329
            return $this;
330
       }
       public function updatemahasiswa ($id)
334
            $data =
336
                'nama_mahasiswa' => $this ->input ->post('
       nama_mahasiswa'),
                'kelas_mahasiswa' => $this -> input -> post('
338
        kelas_mahasiswa').
                'id_prodi_mahasiswa' => $this ->input ->post('
339
        id_prodi_mahasiswa'),
                'angkatan_mahasiswa' => $this ->input ->post('
340
        angkatan_mahasiswa'),
                 'foto_mahasiswa' => $this ->input ->post('
        foto_mahasiswa'),
342
            1:
343
            $this ->db->where ('id_mahasiswa', $id);
345
            this \rightarrow db \rightarrow set (sdata);
346
            return $this ->db->update('mahasiswa');
3.17
       }
348
349
       public function destroymahasiswa ($id_mahasiswa)
350
            $this ->db->where ('id_mahasiswa', $id_mahasiswa);
            return $this -> db-> delete ('mahasiswa');
            // return $this ->db->delete ($this ->table, ['id' => $id
354
       ]);
       }
356
       //end mahasiswa
358
       // start intern
       public function getinternJSON(){
360
361
362
            $page = isset($_POST['page']) ? intval($_POST['page'])
363
         : 1:
            $rows = isset($_POST['rows']) ? intval($_POST['rows'])
364
         : 50:
            $sort = isset($_POST['sort']) ? strval($_POST['sort'])
365
         : 'intern.id_intern';
            $order = isset($_POST['order']) ? strval($_POST['order
366
        ']) : 'asc';
```

```
$search = isset($_POST['search_intern']) ? strval(
367
       $_POST['search_intern']) : '';
           fiset = (page -1)*frows;
368
360
           $result = array();
           $result['total'] = $this->db->get('intern')->num_rows
       ();
           som = arrav():
           // select data from table product
           $query = "SELECT *
                from intern
376
                where concat(id_intern,id_koor_intern,
       status_intern .tgl_mulai_intern .tgl_akhir_intern )
       $search%' order by $sort $order limit $offset, $rows";
378
           $country = $this->db->query($query)->result_array();
           $result = array_merge($result, ['rows' => $country]);
380
           return $result:
381
382
       public function saveintern()
202
       {
384
           $tanggal_mulai = $this -> input -> post('tgl_mulai_intern')
385
       );
           $tanggal_mulai = $this -> input -> post('tgl_akhir_intern')
386
       );
           $formattanggalmulai = date("YYYY-MM-DD hh:mm: ss",
387
       strtotime ($tanggal_mulai));
           $formattanggalakhir = date("YYYY-MM-DD hh:mm:ss",
       strtotime ($tanggal_mulai));
380
390
           data = [
391
                'id_intern' => $this -> input -> post('id_intern'),
392
                'id_koor_intern' => $this -> input -> post('
393
       id_koor_intern'),
                'status_intern' => $this ->input->post('
394
       status_intern'),
                'tgl_mulai_intern' => $formattanggalmulai,
                'tgl_akhir_intern' => $formattanggalakhir,
396
397
           $this ->db->insert('intern', $data);
398
           return $this;
399
       }
400
401
       public function updateintern ($id)
402
       {
403
           $tanggal_mulai = $this -> input -> post('tgl_mulai_intern')
       );
           $tanggal_mulai = $this -> input -> post('tgl_akhir_intern')
405
       ):
           $formattanggalmulai = date("YYYY-MM-DD hh:mm: ss",
406
       strtotime ($tanggal_mulai));
           $formattanggalakhir = date("YYYY-MM-DD hh:mm:ss",
407
       strtotime ($tanggal_mulai));
408
```

```
\$data = [
400
                'id_koor_intern' => $this -> input -> post('
       id_koor_intern').
                'status_intern' => $this ->input->post('
411
       status_intern').
                'tgl_mulai_intern' => $formattanggalmulai,
                'tgl_akhir_intern' => $formattanggalakhir,
413
           1:
414
           $this ->db->where ('id_intern', $id);
           this \rightarrow db \rightarrow set ( tata ) ;
417
           return $this ->db->update('intern');
418
419
       }
       public function destroyintern ($id_intern)
421
           $this ->db->where ('id_intern', $id_intern);
           return $this ->db->delete('intern');
424
           // return $this ->db->delete($this ->table .['id' => $id
       ]);
       }
       //end intern
128
       //start absensi
430
       public function getabsensiJSON(){
           $page = isset($_POST['page']) ? intval($_POST['page'])
434
        : 1;
           $rows = isset($_POST['rows']) ? intval($_POST['rows'])
        : 50:
           $sort = isset($_POST['sort']) ? strval($_POST['sort'])
436
        : 'absensi.id_absensi';
           $order = isset($_POST['order']) ? strval($_POST['order
437
       '1) : 'asc';
           $search = isset($_POST['search_absensi']) ? strval(
438
       $_POST['search_absensi']) : '';
           fiset = (page - 1) * rows;
           $result = array();
441
           $result['total'] = $this->db->get('absensi')->num_rows
442
       ();
           row = array();
444
           // select data from table product
445
           $query = "SELECT *
446
                from absensi
447
                where concat(id_absensi,id_intern_absensi,
448
       id_mahasiswa_absensi,id_dosen_absensi,latitude_absensi,
       longitude_absensi , tgl_waktu_absensi , imei_perangkat_absensi
       , foto_absensi) like '%$search%' order by $sort $order
       limit $offset, $rows";
440
           $country = $this ->db->query($query)->result_array();
450
           $result = array_merge($result, ['rows' => $country]);
451
```

```
return $result;
452
       }
453
454
155
       public function saveabsensi()
            \$data = [
458
                'id_absensi' => $this -> input -> post('id_absensi'),
460
                'id_intern_absensi' => $this -> input -> post('
461
       id_intern_absensi'),
                'id_mahasiswa_absensi' => $this->input->post('
462
       id_mahasiswa_absensi').
                'id_dosen_absensi' => $this->input->post('
463
       id_dosen_absensi').
                'latitude_absensi' => $this->input->post('
464
       latitude_absensi').
                'longitude_absensi' => $this -> input -> post('
465
       longitude_absensi').
                'tgl_waktu_absensi' => $this -> input -> post('
466
       tgl_waktu_absensi')
                'imei_perangkat_absensi' => $this -> input -> post('
467
       imei_perangkat_absensi'),
                'kegiatan_absensi' => $this -> input -> post('
       kegiatan_absensi'),
                'foto_absensi' => $this->input->post('foto_absensi
469
       <sup>'</sup>),
            1:
472
474
            return $this -> db->insert('absensi', $data);
       }
475
       public function updateabsensi($id)
            $data =
480
                'id_intern_absensi' => $this -> input -> post('
       id_intern_absensi').
                'id_mahasiswa_absensi' => $this->input->post('
482
       id_mahasiswa_absensi').
                'id_dosen_absensi' => $this -> input -> post('
       id_dosen_absensi').
                'latitude_absensi' => $this->input->post('
484
       latitude_absensi').
                'longitude_absensi' => $this -> input -> post('
185
       longitude_absensi'),
                'tgl_waktu_absensi' => $this -> input -> post('
486
       tgl_waktu_absensi')
                'imei_perangkat_absensi' => $this -> input -> post('
487
       imei_perangkat_absensi'),
                'kegiatan_absensi' => $this -> input -> post('
488
       kegiatan_absensi'),
                'foto_absensi' => $this->input->post('foto_absensi
480
       '),
```

```
490
            $this ->db->where ('id_absensi', $id);
401
            this \rightarrow db \rightarrow set(sdata);
492
            return $this -> db->update('absensi');
403
       }
       public function destroyabsensi ($id_absensi)
106
497
            $this ->db->where ('id_absensi', $id_absensi);
            return $this -> db-> delete ('absensi');
            // return $this ->db->delete ($this ->table, ['id' => $id
500
       ]);
501
502
       //end absensi
503
504
       // start trigger_radius
506
       public function gettrigger_radiusJSON(){
507
508
500
           $page = isset($_POST['page']) ? intval($_POST['page'])
        : 1:
           $rows = isset($_POST['rows']) ? intval($_POST['rows'])
        : 50;
            $sort = isset($_POST['sort']) ? strval($_POST['sort'])
        : 'trigger_radius.id_trigger';
            $order = isset($_POST['order']) ? strval($_POST['order
        '1) : 'asc':
            $search = isset($_POST['search_trigger_radius']) ?
       strval($_POST['search_trigger_radius']) : '';
            fiset = (page -1)*frows;
515
516
            $result = array();
            $result['total'] = $this->db->get('trigger_radius')->
       num_rows();
           som = arrav():
520
            // select data from table product
           $query = "SELECT *
                from trigger_radius
                where concat(id_trigger,'',id_intern,'','
524
       id_absensi', 'radius') like '%$search%' order by $sort
       $order limit $offset, $rows";
            $country = $this ->db->query($query)->result_array();
526
            $result = array_merge($result, ['rows' => $country]);
            return $result;
528
530
       //end trigger_radius
       public function saveCustomer()
534
           data = [
                'id_user' => $this -> input -> post('id_user'),
536
```

```
'username' => $this -> input -> post('username'),
                 'password' => $this -> input -> post('password'),
538
                 'status_user' => $this -> input -> post('status_user')
                 'role_user' => $this -> input -> post('role_user'),
542
            1:
543
            $this ->db->insert('user', $data);
            return $this;
        }
546
547
548
        public function updateCustomer($id)
549
            data = [
                 'username' => $this -> input -> post('username'),
                 'password' => $this -> input -> post('password'),
                 'status_user' => $this -> input -> post('status_user')
                 'role_user' => $this -> input -> post('role_user'),
554
            1;
556
            \frac{1}{3} $\text{this} \to \text{db} \to \text{where} ('id_user', \frac{1}{3}id);
            this \rightarrow db \rightarrow set ( tata ) ;
559
            return $this -> db->update('user');
        }
560
561
562
        public function destroyCustomer($id_user)
            $this ->db->where ('id_user', $id_user);
564
            return $this ->db->delete('user');
565
            // return $this ->db->delete ($this ->table, ['id' => $id
566
        ]);
        }
567
568
        // get data untuk dropdown
560
        function getprodidropdownn(){
        $query = $this -> db->query ('SELECT * FROM prodi');
            return $query;
        function get_data_stok($id){
            $query = $this ->db->query ("SELECT id_mahasiswa, COUNT(
576
        id_mahasiswa) AS kegiatan, datetime_absensi FROM absensi
       WHERE DATE_FORMAT(datetime_absensi, '%M') = '$id'");
            if ( query \rightarrow num_rows () > 0) 
                 foreach ($query->result() as $data){
                      hasil[] = data;
580
581
                 return $hasil:
582
            }
583
        }
584
585
        // start laporan per mahasiswa
586
587
```

```
function get_data_jan($id){
588
            $query = $this ->db->query ("SELECT id_mahasiswa_absensi
580
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
            WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'January'
       AND id_mahasiswa_absensi =\( \)id\( '):
501
            if ( query \rightarrow num_rows () > 0) 
592
                foreach ($query->result() as $data){
593
                     hasil[] = data;
                return $hasil;
506
            }
597
        function get_data_feb($id){
            $query = $this->db->query("SELECT id_mahasiswa_absensi
601
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
            WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'February'
602
        AND id_mahasiswa_absensi =\$id");
603
            if (\$query \rightarrow num\_rows() > 0)
604
                foreach ($query->result() as $data){
                     hasil[] = data;
606
                }
607
                return $hasil:
608
600
            }
        function get_data_mar($id){
612
            $query = $this -> db->query ("SELECT id_mahasiswa_absensi
613
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
            WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'March'
614
       AND id_mahasiswa_absensi =$id");
615
            if (\$query \rightarrow num\_rows() > 0)
616
                foreach ($query->result() as $data){
                     hasil[] = data;
618
                }
619
                return $hasil:
620
621
            }
       }
623
        function get_data_apr($id){
624
            $query = $this->db->query("SELECT id_mahasiswa_absensi
625
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
            WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'April'
626
       AND id_mahasiswa_absensi =\( \)id\( '):
62.7
            if (query \rightarrow num_rows() > 0)
                foreach ($query->result() as $data){
629
                     hasil[] = data;
631
```

```
return $hasil;
           }
       }
634
635
       function get_data_may($id){
            $query = $this ->db->query ("SELECT id_mahasiswa_absensi
         COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
           WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'May' AND
638
       id_mahasiswa_absensi =$id");
            if(query \rightarrow num_rows() > 0)
640
                foreach ($query->result() as $data){
641
                     hasil[] = data:
642
643
                return $hasil;
            }
       }
646
       function get_data_june($id){
            $query = $this ->db->query ("SELECT id_mahasiswa_absensi
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
           WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'June' AND
         id_mahasiswa_absensi =$id");
            if ( query \rightarrow num_rows() > 0) 
652
653
                foreach ($query -> result() as $data){
                     hasil[] = data;
                return $hasil;
656
            }
657
       }
658
       function get_data_july($id){
660
            $query = $this->db->query("SELECT id_mahasiswa_absensi
661
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
           WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'July ' AND
         id_mahasiswa_absensi =$id");
663
            if (query \rightarrow num_rows() > 0)
664
665
                foreach ($query -> result() as $data){
                     hasil[] = data;
667
                return $hasil;
668
            }
669
       }
       function get_data_aug($id){
672
            $query = $this ->db->query ("SELECT id_mahasiswa_absensi
673
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
           WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'August'
674
       AND id_mahasiswa_absensi =\$id");
675
```

```
if(\text{query}->\text{num}_{\text{rows}}() > 0)
                foreach ($query->result() as $data){
                     hasil[] = data;
678
670
                return $hasil:
            }
       }
682
683
       function get_data_sep($id){
            $query = $this ->db->query ("SELECT id_mahasiswa_absensi
685
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
            WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'September
686
        'AND id_mahasiswa_absensi =$id"):
            if ( query \rightarrow num_rows () > 0) 
                foreach ($query->result() as $data){
680
                     hasil[] = data;
690
691
                return $hasil;
            }
       }
695
       function get_data_oct($id){
            $query = $this->db->query("SELECT id_mahasiswa_absensi
         COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
            WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'October'
608
       AND id_mahasiswa_absensi =\$id");
            if(query \rightarrow num_rows() > 0)
700
                foreach ($query->result() as $data){
                     hasil[] = data;
702
                return $hasil;
704
            }
       }
706
707
       function get_data_nov($id){
            $query = $this -> db->query ("SELECT id_mahasiswa_absensi
709
         ,COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
            WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'November'
       AND id_mahasiswa_absensi =\( \)id");
            if ( query \rightarrow num_rows () > 0) 
                foreach ($query->result() as $data){
                     hasil[] = data;
714
                return $hasil:
716
            }
718
       function get_data_dec($id){
720
```

```
$query = $this -> db->query ("SELECT id_mahasiswa_absensi
         COUNT(DATE_FORMAT(tgl_waktu_absensi, '%M')) as kegiatan
       FROM absensi
           WHERE DATE_FORMAT(tgl_waktu_absensi, '%M') = 'December'
       AND id_mahasiswa_absensi =\( \)id\( ');
           if(\text{squery}-\text{>num}_{\text{rows}}() > 0)
                foreach ($query->result() as $data){
                    hasil[] = data;
726
               }
                return $hasil;
           }
       }
730
       //end laporan per mahasiswa
       // start kelola halaman dosen
       // start kelola profile dosen
736
       // start dosen
738
       public function getprofiledosenJSON($id_pengguna){
739
740
           $page = isset($_POST['page']) ? intval($_POST['page'])
742
        . 1:
           $rows = isset($_POST['rows']) ? intval($_POST['rows'])
743
        : 50;
           $sort = isset($_POST['sort']) ? strval($_POST['sort'])
        : 'a.id_dosen';
           $order = isset($_POST['order']) ? strval($_POST['order
       ']) : 'asc';
746
           fiset = (page -1)*frows;
748
           $result = array();
           $result['total'] = $this->db->get('dosen')->num_rows()
750
           row = array();
           // select data from table product
           $query = "SELECT a.id_dosen, a.nama_dosen, a.
       id_prodi_dosen, a. foto_dosen, b. username, b. password
               from dosen a
               INNER JOIN user b ON a.id_dosen = b.id_user
756
               WHERE a.id_dosen = $id_pengguna
               order by $sort $order limit $offset, $rows";
758
           $country = $this ->db->query($query)->result_array();
760
           $result = array_merge($result, ['rows' => $country]);
761
           return $result:
762
763
       public function updatprofiledosentabledosen($id)
764
765
           data = [
766
767
```

```
'nama_dosen' => $this -> input -> post('nama_dosen'),
768
                 'foto_dosen' => $this -> input -> post('foto_dosen'),
760
            1:
770
            \frac{1}{3} $\text{this} ->\db->\text{where} ('id_dosen', \$id);
            \frac{set}{set}
            return $this ->db->update('dosen');
       }
775
776
       public function updatprofiledosentableuser ($id)
            data =
780
                 'username' => $this -> input -> post('username'),
781
                 'password' => $this -> input -> post('password'),
            1:
783
784
            \frac{1}{3} this ->db->where ('id_user', $id);
785
            \frac{set}{set}
786
            return $this ->db->update('user');
787
       }
788
789
790
791
       //end dosen
793
794
       //end kelola profile dosen
705
       // start view dosen mahasiswa
797
       public function getdosenmahasiswa($id_pengguna){
708
799
800
            $page = isset($_POST['page']) ? intval($_POST['page'])
801
         : 1:
            $rows = isset($_POST['rows']) ? intval($_POST['rows'])
802
         : 50:
            $sort = isset($_POST['sort']) ? strval($_POST['sort'])
         : 'a.id_mahasiswa';
            $order = isset($_POST['order']) ? strval($_POST['order
80/4
        ']) : 'asc';
805
            fiset = (page -1)*frows;
806
807
            $result = array();
808
            $result['total'] = $this->db->get('dosen')->num_rows()
809
            som = array();
811
            // select data from table product
812
            $query = "SELECT DISTINCT
813
                          a.id_mahasiswa, a.nama_mahasiswa, a.
        kelas_mahasiswa ,a.id_prodi_mahasiswa ,a.angkatan_mahasiswa ,
       a.foto_mahasiswa
                         FROM mahasiswa a
```

```
INNER JOIN absensi b ON a.id mahasiswa = b
       .id_mahasiswa_absensi
                        WHERE b.id_dosen_absensi = $id_pengguna
817
                order by $sort $order limit $offset, $rows";
818
819
           $country = $this ->db->query ($query)->result_array ();
           $result = array_merge($result, ['rows' => $country]);
821
           return $result:
822
       //end view dosen mahasiswa
       // start kelola intern dosen
826
827
828
       // start dosen
       public function getdoseninternJSON($id_pengguna){
           $page = isset($_POST['page']) ? intval($_POST['page'])
        : 1:
           $rows = isset($_POST['rows']) ? intval($_POST['rows'])
832
        : 50:
           $sort = isset($_POST['sort']) ? strval($_POST['sort'])
        : 'intern.id_intern';
           $order = isset($_POST['order']) ? strval($_POST['order
834
       '1) : 'asc':
           $search = isset($_POST['search_intern']) ? strval(
       $_POST['search_intern']) : '';
           fiset = (page -1)*frows;
836
           $result = array();
           $result['total'] = $this->db->get('intern')->num_rows
839
       ();
           row = array();
840
841
842
           // select data from table product
           $query = "SELECT *
843
               from intern
                where concat(id_intern,id_koor_intern,
845
       status_intern ,tgl_mulai_intern ,tgl_akhir_intern ) like '%
       $search%'
               AND id_koor_intern = $id_pengguna
               order by $sort $order limit $offset, $rows";
847
           $country = $this ->db->query ($query)->result_array ();
849
           $result = array_merge($result, ['rows' => $country]);
           return $result:
       }
854
       public function updatedosenintern ($id)
855
       {
856
           data = [
857
                'id_koor_intern' => $this -> input -> post('
       id_koor_intern').
                'status_intern' => $this->input->post('
860
       status_intern'),
```

```
'tgl_mulai_intern' => $this -> input -> post('
861
       tgl_mulai_intern'),
                'tgl_akhir_intern' => $this->input->post('
862
       tgl_akhir_intern').
            1:
865
            $this ->db->where ('id_intern', $id):
866
            this \rightarrow db \rightarrow set(sdata);
867
            return $this ->db->update('intern');
       }
869
871
       // end kelola intern dosen
873
       //view absensi mahasiswa
       //start absensi
       public function getabsensimahasiswahalamandosenJSON(
       $id_pengguna){
           $page = isset($_POST['page']) ? intval($_POST['page'])
880
           $rows = isset($_POST['rows']) ? intval($_POST['rows'])
881
        : 50:
            $sort = isset($_POST['sort']) ? strval($_POST['sort'])
882
        : 'absensi.id_absensi';
            $order = isset($_POST['order']) ? strval($_POST['order
       '1) : 'asc';
            $search = isset($_POST['search_absensi']) ? strval(
884
       $_POST['search_absensi']) : '';
            fiset = (page - 1) * rows;
885
            $result = array();
887
            $result['total'] = $this->db->get('absensi')->num_rows
       ();
           som = array();
            // select data from table product
891
           $query = "SELECT *
892
                from absensi
893
                where concat(id_absensi,id_intern_absensi,
       id_mahasiswa_absensi,id_dosen_absensi,latitude_absensi,
       longitude_absensi ,tgl_waktu_absensi ,imei_perangkat_absensi
       , foto_absensi) like '%$search%'
               AND id_dosen_absensi = $id_pengguna
895
                order by $sort $order limit $offset, $rows";
896
            $country = $this->db->query($query)->result_array();
898
            $result = array_merge($result, ['rows' => $country]);
            return $result;
900
       }
901
902
       //end absensi mahasiswa
003
904
```

```
// start peta mahasiswa untuk masing masing dosen
905
006
       public function getmahasiswauntukdosenJSON($id_pengguna){
907
908
           $this ->db->where ('id_dosen_absensi', $id_pengguna);
           $query = $this ->db->get('absensi');
011
           // Return associative data array
912
           return $query->result_array();
913
       // start peta mahasiswa untuk masing masing dosen
915
       // end kelola halaman dosen
016
917
 1 <?php</pre>
   class M_login extends CI_Model{
     function cek_login($table,$where){
       return $this -> db->get_where ($table, $where);
  }
 1 <?php</pre>
 defined('BASEPATH') OR exit('No direct script access allowed')
   class m_register extends CI_Model {
 4
     function __construct(){
       parent:: __construct();
       $this -> load -> database();
 8
     public function getAllUsers(){
       return $query->result();
14
     public function insert ($user){
16
       $this->db->insert('user', $user);
       return $this;
18
       }
20
       public function inserttabelmahasiswa($user){
       $this ->db->insert ('mahasiswa', $user);
       return $this;
       }
24
       function create ($table, $data){
26
           $query = $this ->db->insert($table, $data);
2.8
           return $this:// return last insert id
       }
30
     public function getUser($id){
33
```

```
$\query = \$\this \rightarrow \dots \rightarrow \query \rightarrow \rightarrow \rightarrow \query \rightarrow \rightarrow \rightarrow \query \rightarrow \rightarrow \query \rightarrow \rightarrow \query \rightarrow \rightarrow \query \query \rightarrow \query \rightarrow \query \qquery \query \query \qquery \query \query \query \query \query \query \query \q\
```

```
<!DOCTYPE html>
2 <html>
  <head>
      <title > Grafik Stok Barang </title >
6
  </head>
  <body>
  <?php
           foreach($data as $data){
               $merk[] = $data->id_mahasiswa;
               $stok[] = (float) $data->kegiatan;
               echo "aa, $data->id_mahasiswa <br>";
               echo $data->kegiatan;
           }
      2>
      <canvas id="canvas" width="1000" height="280"></canvas>
18
      <!--Load chart js-->
10
      <script type="text/javascript" src="<?php echo base_url()</pre>
2.0
      .'assets/js/chart.min.js'?>"></script>
      <script>
               var lineChartData = {
                   labels : <?php echo json_encode($stok);?>,
24
                   datasets : [
26
                        {
                            fillColor: "rgba(60,141,188,0.9)",
28
                            strokeColor: "rgba(60,141,188,0.8)",
20
                            pointColor: "#3b8bba",
                            pointStrokeColor: "#fff"
                            pointHighlightFill: "#fff",
                            pointHighlightStroke: "rgba
       (152,235,239,1)",
34
                            data : <?php echo json_encode($merk)
      ;?>
                        }
36
                   1
38
               }
30
40
           var myLine = new Chart(document.getElementById("canvas
41
       ").getContext("2d")).Line(lineChartData);
```

```
<!DOCTYPE html>
2 <html>
3 <head>
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-</pre>
       scale=1">
    <title >Actspot505 </title >
6
    <link type="text/css" rel="stylesheet" href="<?php echo</pre>
       base_url(); ?>assets/css/bootstrap.css">
    <link href="<?php echo base_url(); ?>assets/css/bootstrap.
8
       min.css" rel="stylesheet">
    <script src="https://unpkg.com/leaflet@1.3.1/dist/leaflet.js</pre>
       " integrity="sha512 -/Nsx9X4HebayoByEBuyp3I7od5tA0UzAxs+
      i83KgC8PU0kgB4XiK4Lfe4y4cgBtaRJQEIFCW+oC506aPT2L1zw=="
       crossorigin=""></script>
      <link type="text/css" rel="stylesheet" href="<?php echo</pre>
       base_url(); ?>assets/css/leaflet.css" />
      <link type="text/css" rel="stylesheet" href="<?php echo</pre>
14
      base_url(); ?>assets/css/MarkerCluster.css" />
      <link type="text/css" rel="stylesheet" href="<?php echo</pre>
15
      base_url(); ?>assets/css/MarkerCluster.Default.css" />
      <link href="<?php echo base_url(); ?>assets/css/styles.css
16
      " rel="stylesheet">
18
    <style>
19
    #mapid{
20
      width: 100%;
      height: 400px;
24
    box-sizing: border-box;
26
  body {
    font-family: Arial, Helvetica, sans-serif;
30
31
33 /* Float four columns side by side */
34 . columna {
    float: left;
35
    width: 25%;
    margin-top:20px;
    padding: 0 10px;
38
39 }
40
41 /* Remove extra left and right margins, due to padding */
```

```
.rowa {margin: 0 -5px;}
43
 /* Clear floats after the columns */
  .rowa:after {
    content: "";
    display: table:
    clear: both;
48
  }
49
50
  /* Responsive columns */
  @media screen and (max-width: 600px) {
    .column {
      width: 100%:
54
      display: block;
      margin-bottom: 20px;
58
59
  /* Style the counter cards */
  .carda {
    box-shadow: 0 4px 8px 0 rgba(0, 0, 0, 0.2);
    padding: 16px;
63
    text-align: center;
64
    background-color: #f1f1f1;
66
  }
67
    </style>
68
60
  </head>
71
  <body>
    <nav class="navbar navbar-custom navbar-fixed-top" role="</pre>
       navigation">
      <div class="container-fluid">
        <div class="navbar-header">
74
           <button type="button" class="navbar-toggle collapsed"
       data-toggle="collapse" data-target="#sidebar-collapse"><
       span class="sr-only">Toggle navigation </span>
             <span class="icon-bar"></span>
76
             <span class="icon-bar"></span>
             <span class="icon-bar"></span></button>
78
          <a class="navbar-brand" href="#"><span>Lumino</span>
      Admin</a>
         </div>
80
      </div><!-- /. container-fluid -->
82
    </nav>
    <div id="sidebar-collapse" class="col-sm-3 col-lg-2 sidebar"</pre>
83
      <div class="profile-sidebar">
        <div class="profile-userpic">
          <img src="http://placehold.it/50/30a5ff/fff" class="</pre>
86
      img-responsive" alt="">
        </div>
87
        <div class="profile-usertitle">
88
           <div class="profile-usertitle-name"> <?php echo $this</pre>
89
      ->session ->userdata("nama"); ?></div>
```

```
<div class="profile-usertitle-status"><span class="</pre>
90
      indicator label-success"></span>Online</div>
       </div>
91
       <div class="clear"></div>
02
     </div>
93
     <div class="divider"></div>
     class="nav menu" style="position:relative; border:none
     : padding:unset:">
       <a href="<?php echo site_url(); ?>/
96
     dashboard">Dashboard </a> 
       <a href="<?php echo site_url('c_login/logout'); ?>"></a>
      Logout </a>
     98
    </div><!--/.sidebar--->
99
102
   <div class="col-sm-9 col-sm-offset-3 col-lg-10 col-lg-offset"</pre>
103
     -2 main">
   <div class="rowa">
104
   <div class="columna">
     <div class="carda">
106
     <h4>Jumlah Lokasi Internship </h4>
     109
       <thead>
       Total 
       </thead>
       \langle tr \rangle
116
        <?php echo $totallokasiinternship; ?>
       119
       </div>
    </div>
   <div class="columna">
     <div class="carda">
126
     <h4>Jumlah Mahasiswa</h4>
     <thead>
       130
       <?php
         foreach ($gettahunangkatan
                                 as $row) {
          echo "$row->
      angkatan_mahasiswa ";
         }
         ,,
136
       ?>
       138
       </thead>
139
```

```
140
        141
142
1/13
          <?php echo $totalmahasiswa2015; ?>
          <?php echo $totalmahasiswa2016; ?>
144
          <?php echo $totalmahasiswa2017; ?>
146
        </div>
150
    </div>
    </div>
154
      <div class="row">
        <div class="col-lg-12">
156
          <h1 class="page-header">Peta Lokasi Internship
      Mahasiswa </h1>
        </div>
158
      </div><!--/.row-->
159
      <div class="row">
160
        <div class="col-sm-12">
          <div id="map" style="width:100%; height:280px;">
163
          </div>
164
        </div>
165
166
      </div><!--/.row-->
      <!--
      <div class="row">
168
        <div class="col-lg-12">
169
          <h1 class="page-header">View Tabel Trigger radius </h1
        </div>
      </div>
      <div class="row">
        <div class="col-sm-12">
        <div class="panel panel-container">
        <div class="row">
178
            <div class="col-sm-12">
            <div id="container" class="easyui-layout" fit="true"</pre>
180
        style = "height: 300 px;" >
              <div region="center">
181
                <table id="dgtrigger_radius" toolbar="#
182
       toolbartrigger_radius" class="easyui-datagrid" fit="true"
       singleSelect="true" fitColumns="true" rowNumbers="false"
       pagination="true" url="<?= site_url('c_kelola_user/
       gettrigger_radius') ?>" pageSize="50" pageList="
      [25,50,75,100,125,150,200]" nowrap="false">
                  <thead>
183
                    \langle tr \rangle
184
                      ID
185
       trigger
```

```
ID
186
      Intern 
                    ID Track
187
      ID radius </
      th>
                   180
                 </thead>
190
               <div id="toolbartrigger_radius">
                 <input id="search_trigger_radius" class="</pre>
193
      easyui-searchbox" data-options="prompt: Please Input Value
      ', searcher: doSearchtrigger_radius,
                 inputEvents: $.extend({}, $.fn.searchbox.
194
      defaults.inputEvents, {
                   keyup: function(e){
                     var t = \$(e.data.target);
106
                     var opts = t.searchbox('options');
                    t.searchbox('setValue', $(this).val());
198
                     opts.searcher.call(t[0],t.searchbox('
      getValue '), t. searchbox ('getName'));
200
                 )" style="width:50%;"></input>
201
               </div>
202
203
             </div>
           </div>
204
           </div>
206
        </div>
207
      </div
208
      <u>---></u>
200
     <div class="row">
       <div class="col-lg-12">
         <h1 class="page-header">Print Absensi per mahasiswa </
      h1>
        </div>
      </div><!--/.row-->
     <div class="row">
       <div class="col-lg-12">
       <form action="<?php echo site_url(). '/dashboard/</pre>
      perorang'; ?>" method="post">
     219
        NPM : 
         input type="text" name="npmmahasiswa">
         button type="submit" value="Submit">Submit</
      button >
        226
    </form>
        </div>
228
      </div><!--/.row-->
229
     <!-- start kelola absensi-->
     <div class="row">
```

```
<div class="col-lg-12">
        <h1 class="page-header">Kelola absensi </h1>
       </div>
234
     </div><!--/.row-->
     <div class="row">
       <div class="col-sm-12">
238
      <div class="panel panel-container">
239
      <div class="row">
          <div class="col-sm-12">
          <div id="container" class="easyui-layout" fit="true"</pre>
242
      style = "height: 300px;">
243
           <div region="center">
             <table id="dgabsensi" toolbar="#toolbarabsensi"
244
     class="easyui-datagrid" fit="true" singleSelect="true"
     fitColumns="true" rowNumbers="false" pagination="true" url
     ="<?= site_url('dashboard/
     getabsensimahasiswahalamandosenJSON') ?>" pageSize="50"
     pageList="[25,50,75,100,125,150,200]" nowrap="false">
               <thead>
245
                 >
246
                  ID
247
     absensi 
                  ID Mahasiswa 
                  <th field="id_mahasiswa_absensi" width="
249
     100">ID Intern 
                  250
     ID Dosen 
                  Latitude absensi 
                  Longtitude absensi 
                  Date Time absensi 
                  <th field="imei_perangkat_absensi" width="
     100">Imei absensi 
                  Kegiatan absensi 
                  Photo
256
      absensi 
                 </thead>
258
             <div id="toolbarabsensi">
260
               <a href="<?php echo site_url(); ?>/dashboard/
261
     buatpdfabsensi" plain="true" class="easyui-linkbutton"
     iconCls="icon-print">Print </a>
               <input id="searchabsensi" class="easyui-</pre>
2.62
     searchbox" data-options="prompt: 'Please Input Value',
     searcher: doSearchabsensi.
               inputEvents: $.extend({}, $.fn.searchbox.
263
     defaults.inputEvents, {
                 keyup: function(e){
264
                  var t = \$(e.data.target);
265
                   var opts = t.searchbox('options');
266
```

```
t.searchbox('setValue', $(this).val());
267
                        opts.searcher.call(t[0],t.searchbox('
268
       getValue'), t. searchbox('getName'));
260
                    })" style="width:50%;"></input>
                  </div>
                </div>
               <div id="dlgabsensi" class="easyui-dialog" style="</pre>
       width: 780px; height: auto; padding: 10px; modal="true"
       closed="true" buttons="#dlgabsensiBtn">
                 <form id="fmabsensi" method="post">
                    <div class="col-sm-12 justify-content-sm-</pre>
276
       center">
278
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
280
                        <div class="form-group">
281
                          <label for="">ID absensi </label>
282
                          <input type="text" name="id_absensi"</pre>
202
       class="easyui-textbox" style="width: 100%;">
                         </div>
284
                      </div>
                      <div class="col-sm-6">
286
                        <div class="form-group">
287
                          <label for="">ID Intern </label>
288
                          <select class="" style="width: 100%;</pre>
280
       margin: Opx; padding-top: Opx; padding-bottom: Opx; height
       : 25px; line-height: 25px; name="id_intern_absensi">
290
                           <?php
291
                           foreach ($data_intern
                                                   as $row) {
292
                           echo "<option value="".$row->id_intern."
       '>".$row->id_intern." | ".$row->id_koor_intern."</option>"
294
                           echo"
295
                           ?>
297
                           </select>
298
                         </div>
299
                      </div>
300
                    </div>
301
302
                    <div class="row" style="width: 100%">
303
                      <div class="col-sm-6">
304
                        <div class="form-group">
305
                          <label for="">Id Mahasiswa</label>
306
                          <select class="" style="width: 100%;</pre>
307
       margin: 0px; padding-top: 0px; padding-bottom: 0px; height
       : 25px; line-height: 25px; name="id_mahasiswa_absensi">
308
                           <?php
309
                           foreach ($data_mahasiswa as $row) {
```

```
echo "<option value="." . $row->
       id_mahasiswa."'>".$row->id_mahasiswa." | ".$row->
       nama_mahasiswa."</option>";
                          echo"
                          ?>
                           </select>
316
                         </div>
                      </div>
                      <div class="col-sm-6">
319
                        <div class="form-group">
320
                          <label for="">ID Dosen</label>
                          <select class="" style="width: 100%;</pre>
       margin: Opx; padding-top: Opx; padding-bottom: Opx; height
       : 25px; line-height: 25px; name="id_dosen_absensi">
                          <?php
324
                           foreach ($data_dosen
                                                  as $row) {
                          echo "<option value='".$row->id_dosen."
326
       '>".$row->id_dosen." | ".$row->nama_dosen."</option>";
                          echo"
328
                          ?>
330
                           </select>
                         </div>
                      </div>
                    </div>
334
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
336
                        <div class="form-group">
                          <label for="">Latitude absensi </label>
338
                          <input type="text" name="</pre>
339
       latitude_absensi" class="easyui-textbox" style="width:
       100%;">
                         </div>
340
                      </div>
341
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">Longitude absensi </label>
344
                          <input type="text" name="</pre>
345
       longitude_absensi" class="easyui-textbox" style="width:
       100%;">
                         </div>
346
                      </div>
347
                    </div>
348
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
350
                        <div class="form-group">
                          <label for="">Tanggal dan waktu</label>
352
                          <input type="date" name="</pre>
       tgl_waktu_absensi" class="easyui-textbox" style="width:
       100%;">
                         </div>
354
                      </div>
```

```
<div class="col-sm-6">
356
                         <div class="form-group">
357
                           <label for="">Imei Perangkat </label>
358
                           <input type="text" name="</pre>
350
       imei_perangkat_absensi" class="easyui-textbox" style="
       width: 100%:">
                         </div>
360
                       </div>
361
                    </div>
362
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
364
                         <div class="form-group">
365
366
                           <label for="">Kegiatan absensi </label>
                           <input type="text" name="</pre>
367
       kegiatan_absensi" class="easyui-textbox" style="width:
       100%:">
                         </div>
368
                       </div>
369
                      <div class="col-sm-6">
370
                         <div class="form-group">
                           <label for="">Photo absensi </label>
                           <input type="text" name="foto_absensi"</pre>
       class="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
                    </div>
376
378
                    </div>
                  </form>
380
                </div>
381
                <div id="dlgabsensiBtn">
382
                  <a href="javascript:void(0)" id="btn_save" class
383
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       saveabsensi()" style="width:90px">Save</a>
                  <a href="javascript:void(0)" class="easyui-
384
       linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgabsensi').dialog('close'); $('#fmabsensi').form(clear)
                  " style = "width: 90 px" > Cancel </a>
                </div>
386
              </div>
387
388
389
              </div>
390
391
         </div>
392
       </div><!--/.row-->
393
       <!-- start kelola absensi-->
395
       <!-- start kelola intern->
396
       <div class="row">
397
         <div class="col-lg-12">
398
           <h1 class="page-header">Kelola Internship </h1>
399
         </div>
400
       </div><!--/.row-->
401
       <div class="row">
402
```

```
<div class="col-sm-12">
403
404
       <div class="panel panel-container">
405
       <div class="row">
406
           <div class="col-sm-12">
407
           <div id="container" class="easyui-layout" fit="true"</pre>
       style = "height: 300px;">
             <div region="center">
409
               <table id="dgdosenintern" toolbar="#
      toolbardosenintern" class="easyui-datagrid" fit="true"
      singleSelect="true" fitColumns="true" rowNumbers="false"
      pagination="true" url="<?= site_url('dashboard/
      getdosenintern') ?>" pageSize="50" pageList="
      [25,50,75,100,125,150,200]" nowrap="false">
                <thead>
411
                  412
                    ID intern
413
      Koordinator Internship 
                    Status Internship 
                    416
      Tanggal mulai 
                    417
      Tanggal berakhir 
                   </thead>
410
               <div id="toolbardosenintern">
421
                 <a href="javascript:void(0)" class="easyui-
423
      linkbutton" iconCls="icon-edit" plain="true" onClick="
      editdosenintern()">Edit </a>
424
                 <a href="<?php echo site_url(); ?>/dashboard/
      buatpdfintern" plain="true" class="easyui-linkbutton"
      iconCls="icon-print">Print </a>
                 <input id="searchdosenintern" class="easyui-</pre>
      searchbox" data-options="prompt: 'Please Input Value',
      searcher: doSearchdosenintern,
                 inputEvents: $.extend({}, $.fn.searchbox.
427
      defaults.inputEvents, {
                   keyup: function(e){
                     var t = $(e.data.target);
                     var opts = t.searchbox('options');
                    t.searchbox('setValue', $(this).val());
                     opts.searcher.call(t[0],t.searchbox('
432
      getValue '), t. searchbox ('getName'));
433
                 })" style="width:50%;"></input>
434
               </div>
             </div>
437
```

```
<div id="dlginterndosen" class="easyui-dialog"</pre>
438
       style="width: 780px; height: auto; padding: 10px;" modal="
       true" closed="true" buttons="#dlginterndosenBtn">
                  <form id="fminterndosen" method="post">
430
                    <div class="col-sm-12 justify-content-sm-</pre>
440
       center">
441
442
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
                        <div class="form-group">
445
                          <label for="">ID intern </label>
446
447
                          <input type="text" name="id_intern"</pre>
       class="easyui-textbox" style="width: 100%;">
                         </div>
448
                      </div>
                      <div class="col-sm-6">
                        <div class="form-group">
451
                          <label for="">ID Koordinator Internship
452
       </label>
                          <select class="" style="width: 100%;</pre>
452
       margin: 0px; padding-top: 0px; padding-bottom: 0px; height
       : 25px; line-height: 25px; name="id_koor_intern">
                          <?php
                           foreach ($data_dosen
                                                  as $row) {
456
                          echo "<option value='".$row->id_dosen."
457
       '>".$row->id_dosen." | ".$row->nama_dosen."</option>";
                          echo"
460
                          ?>
461
                           </select>
462
                         </div>
463
                      </div>
464
                    </div>
465
466
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
                        <div class="form-group">
460
                          <label for="">Status Internship </label>
                          <input type="text" name="status_intern"</pre>
471
       class="easyui-textbox" style="width: 100%;">
                         </div>
                      </div>
473
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">Tanggal Mulai</label>
                          <input type="datetime-local" data-date="</pre>
         data-date-format="YYYY MM DD" name="tanggal_mulai" class
       ="easyui-textbox" style="width: 100%;">
                        </div>
478
                      </div>
                    </div>
480
                    <div class="row" style="width: 100%">
481
                      <div class="col-sm-12">
482
```

```
<div class="form-group">
483
                          <label for="">Tanggal Berakhir </label>
181
                          <input type="datetime-local" data-date="</pre>
485
       " data-date-format="YYYY MM DD" name="tanggal_berakhir"
       class="easyui-textbox" style="width: 100%;">
                        </div>
                      </div>
187
                    </div>
488
489
                    </div>
491
                  </form>
402
493
               </div>
               <div id="dlginterndosenBtn">
494
                 <a href="javascript:void(0)" id="btn_save" class</a>
495
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       savedosenintern()" style="width:90px">Save</a>
                 <a href="javascript:void(0)" class="easyui-
496
       linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlginterndosen').dialog('close'); $('#fminterndosen').form
       (clear)
                    style = "width: 90 px" > Cancel </a>
497
                </div>
             </div>
500
             </div>
501
502
503
         </div>
504
       </div><!--/.row-->
505
       <!-- end kelola intern->
506
507
      <!-- start kelola dosenmahasiswa-->
508
      <div class="row">
509
         <div class="col-lg-12">
           <h1 class="page-header">View Mahasiswa </h1>
         </div>
       </div><!--/.row-->
      <div class="row">
         <div class="col-sm-12">
        <div class="panel panel-container">
        <div class="row">
518
             <div class="col-sm-12">
             <div id="container" class="easyui-layout" fit="true"</pre>
        style = "height: 300 px;" >
               <div region="center">
                 <table id="dgdosenmahasiswa" toolbar="#
       toolbardosenmahasiswa" class="easyui-datagrid" fit="true"
       singleSelect="true" fitColumns="true" rowNumbers="false"
       pagination="true" url="<?= site_url('dashboard/
       getdosenmahasiswa') ?>" pageSize="50" pageList="
       [25,50,75,100,125,150,200]" nowrap="false">
                    <thead>
```

```
ID</th
      >
                     Nama nMahasiswa 
                     Kelas 
                     <th field="id_prodi_mahasiswa" width="100"
528
      >Prodi 
                     <th field="angkatan_mahasiswa" width="100"
      >Angkatan 
                     530
      Photo mahasiswa 
                   </thead>
               <div id="toolbardosenmahasiswa">
                            <!--
536
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-add" plain="true" onClick="
      newdosenmahasiswa()">New</a>
                 <a href="javascript:void(0)" class="easyui-
538
      linkbutton" iconCls="icon-edit" plain="true" onClick="
      editdosenmahasiswa()">Edit </a>
                 <a href="javascript:void(0)" class="easyui-
530
      linkbutton" iconCls="icon-remove" plain="true" onClick="
      destroydosenmahasiswa () ">Destroy </a>
540
                 <a href="<?php echo site_url(); ?>/dashboard/
541
      buatpdfdosenmahasiswa" plain="true" class="easyui-
      linkbutton" iconCls="icon-print">Print </a>
                 <input id="searchdosenmahasiswa" class="</pre>
542
      easyui-searchbox" data-options="prompt: Please Input Value
      ', searcher: doSearchdosenmahasiswa,
                 inputEvents: $.extend({}, $.fn.searchbox.
543
      defaults.inputEvents, {
                   keyup: function(e){
544
                     var t = \$(e.data.target);
545
                     var opts = t.searchbox('options');
                     t.searchbox('setValue', $(this).val());
                     opts.searcher.call(t[0],t.searchbox('
548
      getValue '), t. searchbox ('getName'));
                 })" style="width:50%;"></input>
               </div>
             </div>
             <div id="dlgdosenmahasiswa" class="easyui-dialog"</pre>
554
      style="width: 780px; height: auto; padding: 10px;" modal="
      true" closed="true" buttons="#dlgdosenmahasiswaBtn">
               <form id="fmdosenmahasiswa" method="post">
                 <div class="col-sm-12 justify-content-sm-</pre>
556
      center">
558
                 <div class="row" style="width: 100%">
```

```
<div class="col-sm-6">
560
                        <div class="form-group">
561
                          <label for="">ID dosenmahasiswa</label>
562
                          <select class="" style="width: 100%;</pre>
563
       margin: 0px; padding-top: 0px; padding-bottom: 0px; height
       : 25px; line-height: 25px; name="id_dosenmahasiswa">
564
                           <?php
565
                           foreach ($data_user as $row) {
566
                           echo "<option value='".$row->id_user."'>
567
       ". $row->id_user."
                          ". $row->username."</option>";
568
                          echo"
569
                          ?>
                           </select>
                         </div>
                      </div>
                      <div class="col-sm-6">
                        <div class="form-group">
576
                          <label for="">Nama dosenMahasiswa </
       label>
                          <input type="text" name="</pre>
578
       nama_dosenmahasiswa" class="easyui-textbox" style="width:
       100%;">
                         </div>
                       </div>
580
                    </div>
581
                    <div class="row" style="width: 100%">
583
                      <div class="col-sm-6">
584
                        <div class="form-group">
585
                          <label for="">Kelas dosenmahasiswa
586
       label>
                          <input type="text" name="</pre>
587
       kelas_dosenmahasiswa" class="easyui-textbox" style="width:
        100%:">
                         </div>
                      </div>
                      <div class="col-sm-6">
590
                        <div class="form-group">
                          <label for="">Prodi </label>
592
593
                          <select class="" style="width: 100%;</pre>
594
       margin: 0px; padding-top: 0px; padding-bottom: 0px; height
       : 25px; line-height: 25px; name="id_prodi_dosenmahasiswa"
                           <?php
596
                           foreach ($data_prodi
                                                   as $row) {
597
                           echo "<option value='".$row->id_prodi."
       '>".$row->nama_prodi."</option>";
                           }
                           echo"
600
601
                           ?>
602
```

```
</select>
603
                         </div>
604
                       </div>
605
606
                    </div>
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
600
                        <div class="form-group">
610
                           <label for="">Tahun Angkatan</label>
611
                           <input type="text" name="</pre>
612
       angkatan_dosenmahasiswa" class="easyui-textbox" style="
       width: 100%;">
613
                         </div>
                       </div>
                      <div class="col-sm-6">
                        <div class="form-group">
616
                           <label for="">foto dosenmahasiswa </label
617
       >
                           <input type="text" name="</pre>
618
       foto_dosenmahasiswa" class="easyui-textbox" style="width:
       100%:">
                         </div>
619
                       </div>
620
                    </div>
623
                    </div>
624
625
                  </form>
                </div>
                <div id="dlgdosenmahasiswaBtn">
                  <a href="javascript:void(0)" id="btn_save" class
628
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       savedosenmahasiswa()" style="width:90px">Save</a>
                  <a href="javascript:void(0)" class="easyui-
629
       linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgdosenmahasiswa').dialog('close'); $('#fmdosenmahasiswa
        ').form(clear)
                    style="width:90px">Cancel</a>
                </div>
              </div>
633
              </div>
634
635
         </div>
637
       </div><!--/.row-->
638
       <!-- start kelola dosenmahasiswa-->
       <!-- start kelola dosen-->
       <div class="row">
642
         <div class="col-lg-12">
643
           <h1 class="page-header">Kelola Profil </h1>
644
         </div>
645
       </div><!--/.row-->
646
       <div class="row">
647
         <div class="col-sm-12">
648
```

```
<div class="panel panel-container">
649
        <div class="row">
           <div class="col-sm-12">
651
           <div id="container" class="easyui-layout" fit="true"</pre>
       style = "height: 300 px;" >
             <div region="center">
               <table id="dgprofiledosen" toolbar="#
      toolbardosen" class="easyui-datagrid" fit="true"
      singleSelect="true" fitColumns="true" rowNumbers="false"
      pagination="true" url="<?= site_url('dashboard/
      getprofiledosen') ?>" pageSize="50" pageList="
      [25,50,75,100,125,150,200]" nowrap="false">
655
                 <thead>
                   >
656
                     ID Dosen</
      th>
                     Nama
      Dosen 
                     Prodi 
                     Photo
660
      Dosen 
                     Username
661
      <th field="password"
662
      width="100">Password 
                   663
                 </thead>
664
               <div id="toolbardosen">
                 <a href="javascript:void(0)" class="easyui-
667
      linkbutton" iconCls="icon-edit" plain="true" onClick="
      editprofiledosen()">Edit </a>
               </div>
             </div>
669
             <div id="dlgprofiledosen" class="easyui-dialog"</pre>
671
      style="width: 780px; height: auto; padding: 10px;" modal="
      true" closed="true" buttons="#dlgprofiledosenbtn">
               <form id="fmprofiledosen" method="post">
                 <div class="col-sm-12 justify-content-sm-</pre>
673
      center">
674
                 <div class="row" style="width: 100%">
                   <div class="col-sm-6">
677
                     <div class="form-group">
678
                      <label for="">ID Dosen </label><br/>br>
                      <input type="text" name="id_dosen" class</pre>
680
      ="easyui-textbox" style="width: 100%;" readonly>
                     </div>
                   </div>
682
                   <div class="col-sm-6">
683
                     <div class="form-group">
684
                      <label for="">Nama Dosen</label>
685
```

```
<input type="text" name="nama_dosen"</pre>
686
       class="easyui-textbox" style="width: 100%;">
                         </div>
687
                       </div>
688
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">Prodi </label>br>
601
                          <select class="" style="width: 100%;</pre>
692
       margin: 0px; padding-top: 0px; padding-bottom: 0px; height
       : 25px; line-height: 25px; name="id_prodi_dosen" readonly
603
694
                           <?php
                           foreach ($data_prodi
                                                   as $row) {
695
                           echo "<option value='".$row->id_prodi."
       '>".$row->nama_prodi."</option>";
                           }
607
                          echo"
                           ?>
700
                           </select>
                         </div>
702
                       </div>
703
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">Photo Dosen</label>
706
                          <input type="text" name="foto_dosen"</pre>
       class="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
700
                    </div>
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">username </label>
716
                          <input type="text" name="username" class</pre>
       ="easyui-textbox" style="width: 100%;">
                         </div>
718
                       </div>
                                          <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">password </label>
                          <input type="text" name="password" class</pre>
       ="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
                    </div>
728
729
730
                    </div>
                  </form>
                </div>
               <div id="dlgprofiledosenbtn">
```

```
<a href="javascript:void(0)" id="btn_save" class</pre>
734
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       saveaprofiledosen()" style="width:90px">Save</a>
                  <a href="javascript:void(0)" class="easyui-
       linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgprofiledosen').dialog('close'); $('#fmprofiledosen').
       form (clear)
                    style = "width: 90 px" > Cancel </a>
736
                </div>
             </div>
739
              </div>
740
741
         </div>
742
       </div><!--/.row-->
743
744
745
       <!--end kelola dosen-->
746
     </div><!--/.row-->
748
   </div> <!--/.main-->
749
750
  </body>
754
  <script src="<?php echo base_url(); ?>assets/js/jquery -1.11.1.
       min. is "></script>
       <script src="<?php echo base_url(); ?>assets/js/bootstrap.
       \min.js"></script>
758
       <script type="text/javascript" src="<?php echo base_url();</pre>
759
        ?>assets/js/leaflet.js"></script>
760
       <script type="text/javascript" src="<?php echo base_url();</pre>
761
        ?>assets/js/leaflet.markercluster.js"></script>
762
       <link rel="stylesheet" type="text/css" href="<?php echo</pre>
       base_url('assets/css/icon.css') ?>">
764
       <script src="<?php echo base_url(); ?>assets/js/jquery.min
765
       . is "></script>
       <script type="text/javascript" src="<?php echo base_url('</pre>
       assets/js/jquery.easyui.min.js') ?>"></script>
       <script type="text/javascript" src="<?php echo base_url('</pre>
767
       assets/js/script.js') ?>"></script>
       <link rel="stylesheet" type="text/css" href="<?php echo</pre>
       base_url('assets/css/easyui.css') ?>">
       <script type="text/javascript">
769
         var map, newUser, users, mapquest, firstLoad;
         firstLoad = true;
         // users = new L. FeatureGroup();
```

```
users = new L. MarkerClusterGroup ({ spiderfyOnMaxZoom:
       true, showCoverageOnHover: false, zoomToBoundsOnClick:
       true });
         newUser = new L. LayerGroup();
776
         mapquest = new L. TileLayer ("https://api.tiles.mapbox.com
780
       \sqrt{v4/\{id\}/\{z\}/\{x\}/\{y\}}, png?access_token={accessToken}", {
           maxZoom: 18,
           id: 'mapbox.streets'
782
           subdomains: ["otile1", "otile2", "otile3", "otile4"],
783
784
           attribution: 'Map data © <a href="http://
       openstreetmap.org">OpenStreetMap </a> contributors, <a href
       ="http://creativecommons.org/licenses/by-sa/2.0/">CC-BY-SA
       </a>, Imagery
                         <a href="http://mapbox.com">Mapbox</a>',
           accessToken: 'pk.
785
       eyJ1IjoiY2hhbmRyYWtwIiwiYSI6ImNrMzJpOWJoMDBhdDczZG1tZXk3MmppeGEifQ
       . wWJUgnRB1DsKnmYOdsJVxO'
         });
         map = new L.Map('map', {
788
           center: new L. LatLng(-6.914744, 107.609810),
789
           zoom: 10,
           layers: [mapquest, users, newUser]
         });
792
793
704
         // GeoLocation Control
         //map.locate({setView: true, maxZoom: 3});
796
         $(document).ready(function() {
           $.ajaxSetup({cache: false});
799
           ('#map').css('height', ($(window).height() - 300));
           getUsers();
801
         });
802
803
         $(window).resize(function () {
804
           ('#map').css('height', (((window).height() - 300));
         }).resize();
806
807
808
809
         function getUsers() {
           $.getJSON("<?php echo site_url(); ?>/dashboard/
       getmahasiswauntukdosenJSON", function (data) {
              for (var i = 0; i < data.length; i++) {
812
                var location = new L.LatLng(data[i].
       latitude_absensi , data[i].longitude_absensi);
                var name = data[i].id_mahasiswa_absensi;
814
                var website = data[i].foto_absensi;
815
         var host = window.base_url = <?php echo json_encode(
816
       base_url()); ?>;
819
```

```
var marker = new L. Marker(location, { title: name
       });
                marker.bindPopup("<div style='text-align: center;
821
       margin-left: auto; margin-right: auto;'><img style='width
       :100px; height:100px; 'src="+ host + website+">"+ name +"
       </div>", {maxWidth: '400'});
               users.addLayer(marker);
822
824
           }).complete(function() {
              if (firstLoad == true) {
               map.fitBounds(users.getBounds());
                firstLoad = false:
827
              };
828
           });
         }
832
833
       </script>
836 </html>
```

```
<!DOCTYPE html>
2 <html>
3 <head>
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-</pre>
       scale=1">
    <title >Actspot505 </title >
    <link type="text/css" rel="stylesheet" href="<?php echo</pre>
       base_url(); ?>assets/css/bootstrap.css">
    <link href="<?php echo base_url(); ?>assets/css/bootstrap.
8
      min.css" rel="stylesheet">
Ω
    <script src="https://unpkg.com/leaflet@1.3.1/dist/leaflet.js</pre>
       "integrity="sha512 -/Nsx9X4HebavoBvEBuyp3I7od5tA0UzAxs+
      j83KgC8PU0kgB4XiK4Lfe4y4cgBtaRJQEIFCW+oC506aPT2L1zw=="
      crossorigin=""></script>
      <link type="text/css" rel="stylesheet" href="<?php echo</pre>
      base_url(); ?>assets/css/leaflet.css" />
      <link type="text/css" rel="stylesheet" href="<?php echo</pre>
14
      base_url(); ?>assets/css/MarkerCluster.css" />
      <link type="text/css" rel="stylesheet" href="<?php echo</pre>
      base_url(); ?>assets/css/MarkerCluster.Default.css" />
      <link href="<?php echo base_url(); ?>assets/css/styles.css
16
      " rel="stylesheet">
19
    <style>
    #mapid{
      width: 100%;
      height: 400px;
24
```

```
box-sizing: border-box;
27
28
29 body {
    font-family: Arial, Helvetica, sans-serif;
31
32
  /* Float four columns side by side */
  .columna {
    float: left;
    width: 25%;
36
    margin-top:20px;
    padding: 0 10px;
38
39
  }
40
41 /* Remove extra left and right margins, due to padding */
42 .rowa {margin: 0 -5px;}
43
 /* Clear floats after the columns */
  .rowa:after {
45
    content: "";
    display: table;
47
    clear: both;
40
50
 /* Responsive columns */
51
  @media screen and (max-width: 600px) {
    .column {
      width: 100%;
54
      display: block;
      margin-bottom: 20px;
56
57
58
59
  /* Style the counter cards */
  .carda {
61
    box-shadow: 0.4px.8px.0.rgba(0, 0, 0, 0.2);
62
    padding: 16px;
    text-align: center;
    background-color: #f1f1f1;
65
66
67
    </style>
68
69
70 </head>
71
  <body>
    <nav class="navbar navbar-custom navbar-fixed-top" role="</pre>
       navigation">
      <div class="container-fluid">
        <div class="navbar-header">
74
           <button type="button" class="navbar-toggle collapsed"
       data-toggle="collapse" data-target="#sidebar-collapse"><
       span class="sr-only">Toggle navigation </span>
             <span class="icon-bar"></span>
76
             <span class="icon-bar"></span>
```

```
<span class="icon-bar"></span></button>
78
         <a class="navbar-brand" href="#"><span>Lumino</span>
70
      Admin</a>
        </div>
80
      </div><!-- /. container-fluid -->
81
    </nav>
    <div id="sidebar-collapse" class="col-sm-3 col-lg-2 sidebar"</pre>
83
     >
     <div class="profile-sidebar">
       <div class="profile-userpic">
85
         <img src="http://placehold.it/50/30a5ff/fff" class="</pre>
      img-responsive" alt="">
       </div>
87
       <div class="profile-usertitle">
88
         <div class="profile-usertitle-name"> <?php echo $this</pre>
      ->session->userdata("nama"); ?></div>
         <div class="profile-usertitle-status"><span class="</pre>
QΩ
      indicator label-success"></span>Online</div>
        </div>
       <div class="clear"></div>
      </div>
     <div class="divider"></div>
94
     class="nav menu" style="position:relative; border:none
05
      ; padding:unset;">
       <a href="<?php echo site_url(); ?>/
      dashboard">Dashboard </a>
       <a href="<?php echo site_url('c_login/logout'); ?>">
97
       Logout </a> 
      </div><!--/.sidebar--->
00
100
    <div class="col-sm-9 col-sm-offset-3 col-lg-10 col-lg-offset</pre>
      -2 main">
    <div class="rowa">
    <div class="columna">
     <div class="carda">
106
     <h4>Jumlah Pembimbing </h4>
     108
       <thead>
109
       Eksternal 
         Internal 
        </thead>
       116
         <?php echo $totaldosen; ?>
         <?php echo $totaldoseninternal; ?>
118
        120
        </div>
    </div>
124
```

```
<div class="columna">
126
    <div class="carda">
    <h4>Jumlah Mahasiswa</h4>
128
    129
      <thead>
130
      <?php
        foreach ($gettahunangkatan
                            as $row) {
         echo "$row->
134
     angkatan_mahasiswa ";
136
        ,,
138
      ?>
      139
      </thead>
140
      141
      142
143
       <?php echo $totalmahasiswa2015; ?>
144
       <?php echo $totalmahasiswa2016; ?>
145
       <?php echo $totalmahasiswa2017; ?>
146
      148
      149
     150
     </div>
   </div>
   <div class="columna">
154
    <div class="carda">
    <h4>Jumlah Lokasi Internship </h4>
156
157
    158
      <thead>
150
      160
       Total
161
      </thead>
163
      >
165
       <?php echo $totallokasiinternship; ?>
166
      167
168
      169
170
     </div>
   </div>
174
   <div class="columna">
    <div class="carda">
175
176
    <h4>Jumlah pengguna aktif </h4>
    <thead>
178
179
```

```
Total 
180
        181
        </thead>
182
       183
       \langle tr \rangle
         <?php echo $totaluser; ?>
186
        187
188
        190
      </div>
    </div>
192
    </div>
      <div class="row">
        <div class="col-lg-12">
         <h1 class="page-header">Peta Lokasi Internship
      Mahasiswa </h1>
        </div>
196
      </div><!--/.row-->
      <div class="row">
        <div class="col-sm-12">
199
         <div id="map" style="width:100%; height:280px;">
200
201
          </div>
202
        </div>
203
      </div><!--/.row-->
204
206
      <div class="row">
        <div class="col-lg-12">
207
         <h1 class="page-header">View Tabel Trigger radius </h1
208
        </div>
      </div>
      <div class="row">
       <div class="col-sm-12">
       <div class="panel panel-container">
       <div class="row">
           <div class="col-sm-12">
           <div id="container" class="easyui-layout" fit="true"</pre>
2.18
       style = "height: 300px;">
             <div region="center">
219
               <table id="dgtrigger_radius" toolbar="#
      toolbartrigger_radius" class="easyui-datagrid" fit="true"
      singleSelect="true" fitColumns="true" rowNumbers="false"
      pagination="true" url="<?= site_url('c_kelola_user/
      gettrigger_radius') ?>" pageSize="50" pageList="
      [25,50,75,100,125,150,200]" nowrap="false">
                 <thead>
                   ID
      trigger 
                     ID
      Intern
```

**WEB** 

```
ID Track
      ID radius </
226
      th >
                    </thead>
               <div id="toolbartrigger_radius">
230
                        id="search_trigger_radius" class="
      easyui-searchbox" data-options="prompt: Please Input Value
      ', searcher: doSearchtrigger_radius,
                  inputEvents: $.extend({}, $.fn.searchbox.
      defaults.inputEvents, {
                    keyup: function(e){
                      var t = \$(e.data.target);
234
                      var opts = t.searchbox('options');
                     t.searchbox('setValue', $(this).val());
236
                      opts.searcher.call(t[0],t.searchbox('
      getValue').t.searchbox('getName')):
238
                  })" style="width:50%;"></input>
220
                </div>
240
              </div>
241
            </div>
243
            </div>
244
        </div>
245
      </div
246
      <del>---</del>>
248
      <div class="row">
249
       <div class="col-lg-12">
250
         <h1 class="page-header">Print Absensi per mahasiswa </
      h1>
        </div>
      </div><!--/.row-->
      <div class="row">
254
       <div class="col-lg-12">
        <form action="<?php echo site_url(). '/dashboard/</pre>
      perorang'; ?>" method="post">
      258
          NPM : 
         input type="text" name="npmmahasiswa">
260
          button type="submit" value="Submit">Submit</
261
      button >
        2.62
263
      264
    </form>
265
        </div>
266
      </div><!--/.row-->
267
      <!-- start kelola absensi-->
268
      <div class="row">
269
       <div class="col-lg-12">
         <h1 class="page-header">Kelola absensi </h1>
```

```
</div>
     </div><!--/.row-->
     <div class="row">
      <div class="col-sm-12">
275
      <div class="panel panel-container">
      <div class="row">
278
         <div class="col-sm-12">
279
          <div id="container" class="easyui-layout" fit="true"</pre>
280
      style = "height: 300px;">
           <div region="center">
281
             <table id="dgabsensi" toolbar="#toolbarabsensi"
282
     class="easyui-datagrid" fit="true" singleSelect="true"
     fitColumns="true" rowNumbers="false" pagination="true" url
     ="<?= site_url('c_kelola_user/getabsensi') ?>" pageSize="
     50" pageList="[25,50,75,100,125,150,200]" nowrap="false">
              <thead>
283
                284
                  ID
285
     absensi 
                  286
     ID Mahasiswa 
                  <th field="id_mahasiswa_absensi" width="
287
     100">ID Intern 
                  ID Dosen 
                  289
     Latitude absensi 
                  Longtitude absensi 
                  291
     Date Time absensi 
                  292
     100">Imei absensi 
                  293
     Kegiatan absensi 
                  Photo
294
      absensi 
                </thead>
296
             <div id="toolbarabsensi">
298
              <a href="javascript:void(0)" class="easyui-
299
     linkbutton" iconCls="icon-add" plain="true" onClick="
     newabsensi()">New</a>
              <a href="javascript:void(0)" class="easyui-
300
     linkbutton" iconCls="icon-edit" plain="true" onClick="
     editabsensi()">Edit </a>
              <a href="javascript:void(0)" class="easyui-
301
     linkbutton" iconCls="icon-remove" plain="true" onClick="
     destroyabsensi () ">Destroy </a>
              <a href="<?php echo site_url(); ?>/dashboard/
302
     buatpdfabsensi" plain="true" class="easyui-linkbutton"
     iconCls="icon-print">Print </a>
```

```
<input id="searchabsensi" class="easyui-</pre>
303
       searchbox" data-options="prompt: 'Please Input Value',
       searcher: doSearchabsensi,
                    inputEvents: $.extend({}, $.fn.searchbox.
304
       defaults.inputEvents, {
                      keyup: function(e){
                        var t = \$(e.data.target);
306
                        var opts = t.searchbox('options');
307
                        t.searchbox('setValue', $(this).val());
308
                        opts.searcher.call(t[0],t.searchbox('
309
       getValue '), t. searchbox('getName'));
                    })" style="width:50%:"></input>
                  </div>
               </div>
               <div id="dlgabsensi" class="easyui-dialog" style="</pre>
       width: 780px; height: auto; padding: 10px; modal="true"
       closed="true" buttons="#dlgabsensiBtn">
                 <form id="fmabsensi" method="post">
316
                    <div class="col-sm-12 justify-content-sm-</pre>
       center">
318
                   <div class="row" style="width: 100%">
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">ID absensi </label>
                          <input type="text" name="id_absensi"</pre>
       class="easyui-textbox" style="width: 100%;">
                        </div>
                      </div>
326
                      <div class="col-sm-6">
                        <div class="form-group">
328
                          <label for="">ID Intern </label>
329
                          <select class="" style="width: 100%;</pre>
       margin: 0px; padding-top: 0px; padding-bottom: 0px; height
       : 25px; line-height: 25px; name="id_intern_absensi">
                          <?php
                          foreach ($data_intern as $row) {
                          echo "<option value='".$row->id_intern."
334
       '>".$row->id_intern." | ".$row->id_koor_intern."</option>"
                          }
                          echo"
336
                          ?>
                          </select>
339
                        </div>
340
                      </div>
341
                    </div>
342
343
                    <div class="row" style="width: 100%">
344
                      <div class="col-sm-6">
345
                        <div class="form-group">
346
```

```
<label for="">Id Mahasiswa</label>
3.17
                          <select class="" style="width: 100%;</pre>
3/18
       margin: Opx; padding-top: Opx; padding-bottom: Opx; height
       : 25px; line-height: 25px;" name="id_mahasiswa_absensi">
349
                          <?php
                           foreach ($data_mahasiswa as $row) {
                          echo "<option value="".$row->
       id_mahasiswa."'>".$row->id_mahasiswa." | ".$row->
       nama_mahasiswa."</option>";
                          echo"
354
                          ?>
356
                           </select>
                         </div>
358
                      </div>
350
                      <div class="col-sm-6">
360
                        <div class="form-group">
361
                          <label for="">ID Dosen</label>
362
                          <select class="" style="width: 100%;</pre>
262
       margin: Opx; padding-top: Opx; padding-bottom: Opx; height
       : 25px; line-height: 25px; name="id_dosen_absensi">
                          <?php
365
                           foreach ($data_dosen
                                                  as $row) {
366
                          echo "<option value='".$row->id_dosen."
367
       '>".$row->id_dosen." | ".$row->nama_dosen."</option>";
                          echo"
360
                          ?>
                           </select>
                         </div>
                      </div>
                    </div>
                    <div class="row" style="width: 100%">
376
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">Latitude absensi </label>
                          <input type="text" name="</pre>
380
       latitude_absensi" class="easyui-textbox" style="width:
       100%;">
                         </div>
                      </div>
382
                      <div class="col-sm-6">
383
                        <div class="form-group">
384
                          <label for="">Longitude absensi </label>
385
                          <input type="text" name="</pre>
386
       longitude_absensi" class="easyui-textbox" style="width:
       100%:">
                        </div>
387
                      </div>
388
                    </div>
389
                    <div class="row" style="width: 100%">
390
                      <div class="col-sm-6">
391
```

```
<div class="form-group">
392
                           <label for="">Tanggal dan waktu</label>
303
                           <input type="date" name="</pre>
394
       tgl_waktu_absensi" class="easyui-textbox" style="width:
       100%:">
                         </div>
                       </div>
306
                      <div class="col-sm-6">
397
                        <div class="form-group">
398
                           <label for="">Imei Perangkat </label>
                           <input type="text" name="</pre>
400
       imei_perangkat_absensi" class="easyui-textbox" style="
       width: 100%:">
                         </div>
401
                       </div>
402
                    </div>
402
                    <div class="row" style="width: 100%">
404
                      <div class="col-sm-6">
405
                        <div class="form-group">
406
                           <label for="">Kegiatan absensi </label>
407
                           <input type="text" name="</pre>
400
       kegiatan_absensi" class="easyui-textbox" style="width:
       100%:">
                         </div>
                       </div>
                      <div class="col-sm-6">
411
                        <div class="form-group">
412
                           <label for="">Photo absensi </label>
413
                           <input type="text" name="foto_absensi"</pre>
414
       class="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
416
                    </div>
417
                    </div>
                  </form>
421
                </div>
422
                <div id="dlgabsensiBtn">
423
                  <a href="javascript:void(0)" id="btn_save" class</a>
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       saveabsensi()" style="width:90px">Save</a>
                  <a href="javascript:void(0)" class="easyui-
425
       linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgabsensi').dialog('close'); $('#fmabsensi').form(clear)
                    style = "width: 90 px" > Cancel </a>
                </div>
              </div>
              </div>
430
431
432
433
         </div>
       </div><!--/.row-->
434
       <!-- start kelola absensi-->
436
```

```
<!-- start kelola intern->
437
     <div class="row">
438
       <div class="col-lg-12">
         <h1 class="page-header">Kelola Intern </h1>
440
        </div>
441
      </div><!--/.row-->
     <div class="row">
443
       <div class="col-sm-12">
       <div class="panel panel-container">
       <div class="row">
           <div class="col-sm-12">
448
           <div id="container" class="easyui-layout" fit="true"</pre>
449
       stvle = "height: 300 px:" >
             <div region="center">
               <table id="dgintern" toolbar="#toolbarintern"
451
      class="easyui-datagrid" fit="true" singleSelect="true"
      fitColumns="true" rowNumbers="false" pagination="true" url
      ="<?= site_url('c_kelola_user/getintern') ?>" pageSize="50
        pageList="[25,50,75,100,125,150,200]" nowrap="false">
                <thead>
452
                   >
                    ID intern
      Koordinator Internship 
                    456
      Status Internship 
                    Tanggal mulai 
                    458
      Tanggal berakhir 
                   </thead>
               461
               <div id="toolbarintern">
462
                 <a href="javascript:void(0)" class="easyui-
463
      linkbutton" iconCls="icon-add" plain="true" onClick="
      newintern()">New</a>
                 <a href="javascript:void(0)" class="easyui-
464
      linkbutton" iconCls="icon-edit" plain="true" onClick="
      editintern()">Edit </a>
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-remove" plain="true" onClick="
      destroyintern()">Destroy</a>
                 <a href="<?php echo site_url(); ?>/dashboard/
466
      buatpdfintern" plain="true" class="easyui-linkbutton"
      iconCls="icon-print">Print </a>
                 <input id="searchintern" class="easyui-</pre>
467
      searchbox" data-options="prompt: 'Please Input Value',
      searcher: do Searchintern.
                 inputEvents: $.extend({}, $.fn.searchbox.
468
      defaults.inputEvents, {
                   keyup: function(e){
460
                     var t = \$(e.data.target);
                     var opts = t.searchbox('options');
471
```

```
t.searchbox('setValue', $(this).val());
472
                         opts.searcher.call(t[0],t.searchbox('
473
       getValue '), t. searchbox('getName'));
                    })" style="width:50%:"></input>
                  </div>
                </div>
477
478
               <div id="dlgintern" class="easyui-dialog" style="</pre>
       width: 780px; height: auto; padding: 10px; modal="true"
       closed="true" buttons="#dlginternBtn">
                  <form id="fmintern" method="post">
480
481
                    <div class="col-sm-12 justify-content-sm-</pre>
       center">
482
483
                    <div class="row" style="width: 100%">
484
                      <div class="col-sm-6">
485
                        <div class="form-group">
486
                          <label for="">ID intern </label>
487
                          <input type="text" name="id_intern"</pre>
100
       class="easyui-textbox" style="width: 100%;">
                         </div>
480
                       </div>
                      <div class="col-sm-6">
401
                        <div class="form-group">
492
                          <label for="">ID Koordinator Internship
493
       </label>
                          <select class="" style="width: 100%;</pre>
494
       margin: Opx; padding-top: Opx; padding-bottom: Opx; height
       : 25px; line-height: 25px; name="id_koor_intern">
495
                           <?php
496
                           foreach ($data_dosen
                                                   as $row) {
497
                           echo "<option value='".$row->id_dosen."
498
       '>".$row->id_dosen." | ".$row->nama_dosen."</option>";
499
                           echo"
500
                           ?>
502
                           </select>
503
                         </div>
504
                       </div>
505
                    </div>
506
507
                    <div class="row" style="width: 100%">
508
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">Status Internship </label>
                          <input type="text" name="status_intern"</pre>
       class="easyui-textbox" style="width: 100%;">
                         </div>
                      </div>
514
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">Tanggal Mulai</label>
```

```
<input type="datetime-local" data-date="</pre>
518
         data-date-format="YYYY MM DD" name="tanggal_mulai" class
       ="easyui-textbox" style="width: 100%;">
                        </div>
                      </div>
520
                    </div>
                   <div class="row" style="width: 100%">
                      <div class="col-sm-12">
                        <div class="form-group">
                          <label for="">Tanggal Berakhir </label>
                          <input type="datetime-local" data-date="</pre>
526
         data-date-format="YYYY MM DD" name="tanggal_berakhir"
       class="easyui-textbox" style="width: 100%;">
                        </div>
                      </div>
528
                    </div>
                    </div>
                 </form>
               </div>
               <div id="dlginternBtn">
                 <a href="javascript:void(0)" id="btn_save" class
536
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       saveintern()" style="width:90px">Save</a>
                 <a href="javascript:void(0)" class="easyui-
       linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgintern').dialog('close'); $('#fmintern').form(clear)
                 " style = "width: 90 px" > Cancel </a>
               </div>
             </div>
540
541
             </div>
542
543
544
         </div>
       </div><!--/.row-->
546
       <!-- end kelola intern->
547
      <!-- start kelola mahasiswa-->
      <div class="row">
         <div class="col-lg-12">
           <h1 class="page-header">Kelola Mahasiswa </h1>
         </div>
       </div><!--/.row-->
554
       <div class="row">
         <div class="col-sm-12">
556
        <div class="panel panel-container">
        <div class="row">
             <div class="col-sm-12">
560
             <div id="container" class="easyui-layout" fit="true"</pre>
561
        style = "height: 300 px;" >
               <div region="center">
562
                 <table id="dgmahasiswa" toolbar="#
563
       toolbarmahasiswa" class="easyui-datagrid" fit="true"
```

```
singleSelect="true" fitColumns="true" rowNumbers="false"
      pagination="true" url="<?= site_url('c_kelola_user/
      getmahasiswa') ?>" pageSize="50" pageList="
      [25,50,75,100,125,150,200]" nowrap="false">
                 <thead>
564
                   565
                     ID</th
566
      >
                     Nama Mahasiswa 
                     Kelas 
                     <th field="id_prodi_mahasiswa" width="100"
569
      >Prodi 
                     <th field="angkatan_mahasiswa" width="100"
      >Angkatan 
                     Photo mahasiswa 
                   </thead>
               <div id="toolbarmahasiswa">
576
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-add" plain="true" onClick="
      newmahasiswa()">New</a>
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-edit" plain="true" onClick="
      editmahasiswa () ">Edit </a>
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-remove" plain="true" onClick="
      destroymahasiswa () ">Destroy </a>
                 <a href="<?php echo site_url(); ?>/dashboard/
580
      buatpdfmahasiswa" plain="true" class="easyui-linkbutton"
      iconCls="icon-print">Print </a>
                 <input id="searchmahasiswa" class="easyui-</pre>
581
      searchbox" data-options="prompt: 'Please Input Value',
      searcher: doSearchmahasiswa,
                 inputEvents: $.extend({}, $.fn.searchbox.
      defaults.inputEvents, {
                   keyup: function(e){
583
                     var t = \$(e.data.target);
584
                     var opts = t.searchbox('options');
585
                     t.searchbox('setValue', $(this).val());
586
                     opts.searcher.call(t[0],t.searchbox('
587
      getValue'), t. searchbox ('getName'));
588
                 })" style="width:50%;"></input>
               </div>
590
             </div>
591
             <div id="dlgmahasiswa" class="easyui-dialog" style</pre>
593
      ="width: 780px; height: auto; padding: 10px;" modal="true"
       closed="true" buttons="#dlgmahasiswaBtn">
               <form id="fmmahasiswa" method="post">
594
```

```
<div class="col-sm-12 justify-content-sm-</pre>
505
       center">
596
507
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
                        <div class="form-group">
600
                           <label for="">ID mahasiswa</label>
601
                           <select class="" style="width: 100%;</pre>
602
       margin: Opx; padding-top: Opx; padding-bottom: Opx; height
       : 25px; line-height: 25px; name="id_mahasiswa">
603
604
                           <?php
                           foreach ($data_user as $row) {
605
                           echo "<option value='".$row->id_user."'>
       ". $row->id_user."
                           ". $row->username."</option>";
607
                           echo"
608
                           ?>
                           </select>
611
                         </div>
612
                       </div>
613
                      <div class="col-sm-6">
                        <div class="form-group">
                           <label for="">Nama Mahasiswa </label>
616
                           <input type="text" name="nama_mahasiswa"</pre>
617
        class="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
                    </div>
620
621
                    <div class="row" style="width: 100%">
622
                      <div class="col-sm-6">
                        <div class="form-group">
624
                           <label for="">Kelas mahasiswa</label>
                           <input type="text" name="kelas_mahasiswa</pre>
626
         class="easyui-textbox" style="width: 100%;">
                         </div>
                      </div>
628
                      <div class="col-sm-6">
                        <div class="form-group">
630
                          <label for="">Prodi </label>
631
                           <select class="" style="width: 100%;</pre>
633
       margin: 0px; padding-top: 0px; padding-bottom: 0px; height
       : 25px; line-height: 25px;" name="id_prodi_mahasiswa">
634
                           <?php
                           foreach ($data_prodi
                                                   as $row) {
636
                           echo "<option value='".$row->id_prodi."
       '>".$row->nama_prodi."</option>";
                           }
                           echo"
630
                           ?>
641
```

```
</select>
642
                         </div>
643
                       </div>
644
645
                    </div>
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
648
                         <div class="form-group">
649
                           <label for="">Tahun Angkatan</label>
                           <input type="text" name="</pre>
651
        angkatan_mahasiswa" class="easyui-textbox" style="width:
        100%:">
652
                         </div>
                       </div>
                      <div class="col-sm-6">
654
                         <div class="form-group">
655
                           <label for="">foto mahasiswa</label>
                           <input type="text" name="foto_mahasiswa"</pre>
657
         class="easyui-textbox" style="width: 100%;">
                         </div>
658
                       </div>
660
                     </div>
661
                    </div>
663
                  </form>
664
                </div>
665
                <div id="dlgmahasiswaBtn">
666
                  <a href="javascript:void(0)" id="btn_save" class
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       savemahasiswa()" style="width:90px">Save</a>
                  <a href="javascript:void(0)" class="easyui-
668
        linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgmahasiswa').dialog('close'); $('#fmmahasiswa').form(
        clear)
                  " style = "width : 90 px" > Cancel </a>
                </div>
670
              </div>
671
              </div>
674
675
         </div>
676
       </div><!--/.row-->
       <!-- start kelola mahasiswa-->
678
       <!-- start kelola dosen-->
680
       <div class="row">
681
         <div class="col-lg-12">
682
           <h1 class="page-header">Kelola Dosen </h1>
683
         </div>
684
       </div><!--/.row-->
685
       <div class="row">
686
         <div class="col-sm-12">
687
         <div class="panel panel-container">
688
         <div class="row">
689
```

```
<div class="col-sm-12">
690
           <div id="container" class="easyui-layout" fit="true"</pre>
601
       style = "height: 300 px;" >
             <div region="center">
602
               <table id="dgdosen" toolbar="#toolbardosen"
693
      class="easyui-datagrid" fit="true" singleSelect="true"
      fitColumns="true" rowNumbers="false" pagination="true" url
      ="<?= site_url('c_kelola_user/getdosen') ?>" pageSize="50"
       pageList="[25,50,75,100,125,150,200]" nowrap="false">
                 <thead>
                   ID Dosen</
606
      th>
                     Nama
697
      Dosen 
                     ID
      Prodi 
                     Photo
600
      Dosen 
                     Status
700
      Dosen 
                   </thead>
702
               703
               <div id="toolbardosen">
704
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-add" plain="true" onClick="
      newdosen()">New</a>
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-edit" plain="true" onClick="
      editdosen()">Edit </a>
                 <a href="javascript:void(0)" class="easyui-
707
      linkbutton" iconCls="icon-remove" plain="true" onClick="
      destroydosen()">Destroy </a>
                 <a href="<?php echo site_url(); ?>/dashboard/
708
      buatpdfdosen" plain="true" class="easyui-linkbutton"
      iconCls="icon-print">Print </a>
                 <input id="searchdosen" class="easyui-</pre>
      searchbox" data-options="prompt: 'Please Input Value',
      searcher: doSearchdosen.
                 inputEvents: $.extend({}, $.fn.searchbox.
      defaults.inputEvents, {
                   keyup: function(e){
                     var t = \$(e.data.target);
                     var opts = t.searchbox('options');
                     t.searchbox('setValue', $(this).val());
                     opts.searcher.call(t[0],t.searchbox(
      getValue '), t. searchbox ('getName'));
                 })" style="width:50%;"></input>
               </div>
             </div>
719
             <div id="dlgdosen" class="easyui-dialog" style="</pre>
      width: 780px; height: auto; padding: 10px;" modal="true"
      closed="true" buttons="#dlgdosenBtn">
```

```
<form id="fmdosen" method="post">
                    <div class="col-sm-12 justify-content-sm-</pre>
       center">
724
725
                    <div class="row" style="width: 100%">
                      <div class="col-sm-6">
                        <div class="form-group">
728
                          <label for="">ID Dosen </label><br/>br>
729
                          <select class="" style="width: 100%;</pre>
730
       margin: Opx; padding-top: Opx; padding-bottom: Opx; height
       : 25px; line-height: 25px; name="id_dosen">
                           <?php
                           foreach ($data_user as $row) {
                           echo "<option value="...$row->id_user."">
       ".$row->id_user." | ".$row->username."</option>";
                           echo"
736
                          ?>
738
                           </select>
739
740
                         </div>
                      </div>
742
                      <div class="col-sm-6">
743
                        <div class="form-group">
744
                          <label for="">Nama Dosen</label>
                          <input type="text" name="nama_dosen"</pre>
       class="easyui-textbox" style="width: 100%;">
                         </div>
747
                      </div>
748
                      <div class="col-sm-6">
749
                        <div class="form-group">
750
                          <label for="">ID Prodi </label><br/>br>
                          <select class="" style="width: 100%;</pre>
       margin: 0px; padding-top: 0px; padding-bottom: 0px; height
       : 25px; line-height: 25px; name="id_prodi_dosen">
                           <?php
754
                           foreach ($data_prodi
                                                   as $row) {
                           echo "<option value='".$row->id_prodi."
756
       '>".$row->nama_prodi."</option>";
                           }
                           echo"
758
                          ?>
760
                           </select>
761
                         </div>
762
                      </div>
763
                      <div class="col-sm-6">
                        <div class="form-group">
765
                          <label for="">Photo Dosen</label>
766
                          <input type="text" name="foto_dosen"</pre>
767
       class="easyui-textbox" style="width: 100%;">
                         </div>
768
```

```
</div>
769
                    </div>
                    <div class="row" style="width: 100%">
                      <div class="col-sm-12">
774
                         <div class="form-group">
                           <label for="">Status Dosen</label>
776
                           <select class="" style="width: 100%;</pre>
       margin: Opx; padding-top: Opx; padding-bottom: Opx; height
        : 25px; line-height: 25px; name="status">
                           <option value="eksternal">Eksternal 
778
        option>
                           <option value="internal">Internal 
        option>
                           </select>
780
781
                         </div>
782
                       </div>
783
784
                    </div>
785
786
787
                     </div>
788
                  </form>
789
                </div>
790
                <div id="dlgdosenBtn">
791
                  <a href="javascript:void(0)" id="btn_save" class</a>
702
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       savedosen()" style="width:90px">Save</a>
                  <a href="javascript:void(0)" class="easyui-
703
        linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgdosen ') . dialog('close'); $('#fmdosen') . form(clear)
                  " style = "width: 90 px" > Cancel </a>
                </div>
              </div>
706
797
              </div>
798
         </div>
800
       </div><!--/.row-->
801
802
803
       <!--end kelola dosen-->
804
     <!--start kelola user-->
805
       <div class="row">
806
         <div class="col-lg-12">
807
           <h1 class="page-header">Kelola User </h1>
808
809
         </div>
       </div><!--/.row-->
810
       <div class="row">
811
         <div class="col-sm-12">
812
         <div class="panel panel-container">
         <div class="row">
814
             <div class="col-sm-12">
```

```
<div id="container" class="easyui-layout" fit="true"</pre>
       style = "height: 300px;">
             <div region="center">
817
               <table id="dgCustomers" toolbar="#
      toolbarCustomer" class="easyui-datagrid" fit="true"
      singleSelect="true" fitColumns="true" rowNumbers="false"
      pagination="true" url="<?= site_url('c_kelola_user/
      getcustomers') ?>" pageSize="50" pageList="
      [25,50,75,100,125,150,200]" nowrap="false">
                 <thead>
                   ID User</th
821
      >
                     Username
822
      Password
      Status
824
      Status </
825
      th>
                   826
                 </thead>
827
               <div id="toolbarCustomer">
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-add" plain="true" onClick="
      newCustomer()">New</a>
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-edit" plain="true" onClick="
      editCustomer()">Edit </a>
                 <a href="javascript:void(0)" class="easyui-
832
      linkbutton" iconCls="icon-remove" plain="true" onClick="
      destroyCustomer()">Destroy </a>
                 <a href="<?php echo site_url(); ?>/dashboard/
      buatpdfuser" plain="true" class="easyui-linkbutton"
      iconCls="icon-print">Print </a>
                 <input id="searchCustomer" class="easyui-</pre>
      searchbox" data-options="prompt: 'Please Input Value',
      searcher: doSearchCustomer,
                 inputEvents: $.extend({}, $.fn.searchbox.
      defaults.inputEvents, {
                   keyup: function(e){
836
                     var t = \$(e.data.target);
                     var opts = t.searchbox('options');
838
                     t.searchbox('setValue', $(this).val());
                     opts.searcher.call(t[0],t.searchbox(
840
      getValue '), t. searchbox ('getName'));
                  })" style="width:50%;"></input>
842
               </div>
843
              </div>
844
845
             <div id="dlgCustomer" class="easyui-dialog" style=</pre>
846
      "width: 780px; height: auto; padding: 10px;" modal="true"
      closed="true" buttons="#dlgCustomerBtn">
```

```
<form id="fmCustomer" method="post">
847
                     <div class="col-sm-12 justify-content-sm-</pre>
8/18
        center">
                    <div class="row" style="width: 100%">
                       <div class="col-sm-6">
852
                         <div class="form-group">
853
                           <label for="">ID</label>
                           <input type="text" name="id_user" class=</pre>
       "easyui-textbox" style="width: 100%;">
                         </div>
856
                       </div>
857
                       <div class="col-sm-6">
                         <div class="form-group">
                           <label for="">Username </label>
860
                           <input type="text" name="username" class</pre>
861
       ="easyui-textbox" style="width: 100%;">
                         </div>
862
                       </div>
863
                     </div>
964
865
                     <div class="row" style="width: 100%">
866
                       <div class="col-sm-6">
                         <div class="form-group">
868
                           <label for="">Password</label>
869
                           <input type="text" name="password" class</pre>
       ="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
872
                       <div class="col-sm-6">
873
                         <div class="form-group">
874
                           <label for="">status </label>
875
                           <input type="text" name="status_user"</pre>
        class="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
878
                     </div>
880
                     <div class="row" style="width: 100%">
881
                       <div class="col-sm-12">
882
                         <div class="form-group">
883
                           <label for="">Role User</label>
884
                           <input type="text" name="role_user"</pre>
885
        class="easyui-textbox" style="width: 100%;">
                         </div>
886
                       </div>
887
                     </div>
220
890
                     </div>
891
                   </form>
892
                </div>
893
                <div id="dlgCustomerBtn">
894
```

```
<a href="javascript:void(0)" id="btn_save" class</a>
895
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       saveCustomer()" style="width:90px">Save</a>
                 <a href="javascript:void(0)" class="easyui-
806
       linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgCustomer').dialog('close'); $('#fmCustomer').form(clear
                 " style =" width: 90 px">Cancel </a>
897
898
               </div>
             </div>
             </div>
001
902
         </div><!--/.row-->
903
       </div>
904
005
         </div>
006
       </div><!--/.row-->
907
908
      <!--end kelola user-->
909
910
911
      <!--Start kelola prodi -->
912
      <div class="row">
913
        <div class="col-lg-12">
914
          <h1 class="page-header">Kelola Prodi </h1>
915
         </div>
916
       </div><!--/.row-->
017
      <div class="row">
918
        <div class="col-sm-12">
010
        <div id="container" class="easyui-layout" fit="true"</pre>
020
       style = "height: 200 px; width: 100\%;">
              <div region="center">
921
                 <table id="dgprodi" toolbar="#toolbarkelolaprodi
922
         class="easyui-datagrid" fit="true" singleSelect="true"
       fitColumns="true" rowNumbers="false" pagination="true" url
       ="<?= site_url('c_kelola_user/getProdi') ?>" pageSize="50"
        pageList="[25,50,75,100,125,150,200]" nowrap="false">
                  <thead>
                     924
                       ID Prodi</
925
       th>
                       Nama
926
       Prodi 
                     927
                   </thead>
                 929
                 <div id="toolbarkelolaprodi">
                   <a href="javascript:void(0)" class="easyui-
931
       linkbutton" iconCls="icon-add" plain="true" onClick="
       newprodi()">New</a>
                  <a href="javascript:void(0)" class="easyui-
932
       linkbutton" iconCls="icon-edit" plain="true" onClick="
       editprodi()">Edit </a>
```

```
<a href="javascript:void(0)" class="easyui-
033
       linkbutton" iconCls="icon-remove" plain="true" onClick="
       destroyprodi () ">Destroy </a>
                    <a href="<?php echo site_url(); ?>/dashboard/
       buatpdfprodi" plain="true" class="easyui-linkbutton"
       iconCls="icon-print">Print </a>
                    <input id="searchprodi" class="easyui-</pre>
035
       searchbox" data-options="prompt: 'Please Input Value',
       searcher: doSearchprodi,
                    inputEvents: $.extend({}, $.fn.searchbox.
       defaults.inputEvents, {
                      keyup: function(e){
037
938
                         var t = \$(e.data.target);
                         var opts = t.searchbox('options');
                         t.searchbox('setValue', $(this).val());
940
                         opts.searcher.call(t[0],t.searchbox(
941
       getValue '), t. searchbox ('getName'));
0.12
                     )" style="width:50%:"></input>
                  </div>
0.4.4
                </div>
0.45
946
                <div id="dlgprodi" class="easyui-dialog" style="</pre>
0.17
       width: 780px; height: auto; padding: 10px; modal="true"
       closed="true" buttons="#dlgprodiBtn">
                  <form id="fmprodi" method="post">
948
                    <div class="col-sm-12 justify-content-sm-</pre>
949
       center">
951
                    <div class="row" style="width: 100%">
052
                      <div class="col-sm-6">
953
                        <div class="form-group">
954
                           <label for="">ID Prodi </label>
955
                           <input type="text" name="id_prodi" class</pre>
956
       ="easyui-textbox" style="width: 100%;">
                         </div>
957
                       </div>
                      <div class="col-sm-6">
                        <div class="form-group">
060
                           <label for="">Nama Prodi </label>
961
                           <input type="text" name="nama_prodi"</pre>
962
       class="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
964
                    </div>
965
966
967
068
                    </div>
969
                  </form>
970
                </div>
971
972
                <div id="dlgprodiBtn">
                  <a href="javascript:void(0)" id="btn_save" class
073
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       saveprodi()" style="width:90px">Save</a>
```

```
<a href="javascript:void(0)" class="easyui-
074
        linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
        dlgprodi').dialog('close'); $('#fmprodi').form(clear)
                   " style = "width: 90 px" > Cancel </a>
075
                 </div>
              </div>
          </div>
078
        </div><!--/.row-->
979
980
981
982
     </div><!--/.row-->
083
   </div> <!--/.main-->
984
985
987
   </body>
088
989
990
   <script src="<?php echo base_url(); ?>assets/js/jquery-1.11.1.
        min. is "></script>
       <script src="<?php echo base_url(); ?>assets/js/bootstrap.
992
        \min. js"></script>
       <script type="text/javascript" src="<?php echo base_url();</pre>
994
         ?>assets/js/leaflet.js"></script>
995
       <script type="text/javascript" src="<?php echo base_url();</pre>
006
         ?>assets/js/leaflet.markercluster.js"></script>
007
       <link rel="stylesheet" type="text/css" href="<?php echo</pre>
008
        base_url('assets/css/icon.css') ?>">
999
       <script src="<?php echo base_url(); ?>assets/js/jquery.min
1000
        . is "></script>
       <script type="text/javascript" src="<?php echo base_url('</pre>
1001
        assets/js/jquery.easyui.min.js') ?>"></script>
       <script type="text/javascript" src="<?php echo base_url('</pre>
1002
        assets/js/script.js') ?>"></script>
       <link rel="stylesheet" type="text/css" href="<?php echo</pre>
1003
        base_url('assets/css/easyui.css') ?>">
       <script type="text/javascript">
1004
          var map, newUser, users, mapquest, firstLoad;
1005
1006
          firstLoad = true:
1007
          //users = new L. FeatureGroup();
1009
          users = new L. MarkerClusterGroup ({ spiderfyOnMaxZoom:
        true, showCoverageOnHover: false, zoomToBoundsOnClick:
        true });
          newUser = new L. LayerGroup();
1011
1012
1013
1014
          mapquest = new L. TileLayer ("https://api.tiles.mapbox.com
        \sqrt{v4/\{id\}/\{z\}/\{x\}/\{y\}}.png?access_token={accessToken}", {
```

```
maxZoom: 18,
            id: 'mapbox.streets'
1017
           subdomains: ["otile1", "otile2", "otile3", "otile4"],
1018
            attribution: 'Map data © <a href="http://
1010
        openstreetmap.org">OpenStreetMap</a> contributors, <a href
       ="http://creativecommons.org/licenses/by-sa/2.0/">CC-BY-SA
       </a>, Imagery
                         <a href="http://mapbox.com">Mapbox</a>'.
            accessToken: 'pk.
       eyJ1IjoiY2hhbmRyYWtwIiwiYSI6ImNrMzJpOWJoMDBhdDczZG1tZXk3MmppeGEifO
        . wWJUgnRB1DsKnmYQdsJVxQ'
         });
1021
1022
1023
         map = new L.Map('map', {
            center: new L. LatLng(-6.914744, 107.609810),
           zoom: 10,
1025
            layers: [mapquest, users, newUser]
         });
1028
         // GeoLocation Control
         //map.locate({setView: true, maxZoom: 3});
1032
         $(document).ready(function() {
           $.ajaxSetup({cache: false});
           ('#map').css('height', ($(window).height() - 300));
            getUsers();
1036
         });
1037
1038
         $(window).resize(function () {
           ('#map').css('height', (((window).height() - 300));
         }).resize();
1041
1042
1043
1044
         function getUsers() {
1045
           $.getJSON("<?php echo site_url(); ?>/c_kelola_user/
       getCustomerJSON", function (data) {
              for (var i = 0; i < data.length; i++) {
1047
                var location = new L.LatLng(data[i].
        latitude_absensi, data[i].longitude_absensi);
                var name = data[i].id_mahasiswa_absensi;
                var website = data[i].foto_absensi;
         var host = window.base_url = <?php echo json_encode(
1051
        base_url()); ?>;
1052
                var marker = new L. Marker(location, { title: name
        });
                marker.bindPopup("<div style='text-align: center;
       margin-left: auto; margin-right: auto;'><img style='width
       :100px; height:100px; src="+ host + website+">"+ name +"
        </div>", {maxWidth: '400'});
                users.addLayer(marker);
            }).complete(function() {
```

```
if (firstLoad == true) {
1060
                   map. fitBounds (users.getBounds());
1061
                    firstLoad = false:
1062
1063
              });
           }
1065
1066
1067
1068
1070
         </script>
    </html>
1071
```

```
<!DOCTYPE html>
2 <html>
3 <head>
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-</pre>
       scale=1">
    <title >Lumino - Login </title >
6
    <link href="<?php echo base_url(); ?>assets/css/bootstrap.
      min.css" rel="stylesheet">
    <link href="<?php echo base_url(); ?>assets/css/datepicker3.
       css" rel="stylesheet">
    <link href="<?php echo base_url(); ?>assets/css/styles.css"
0
       rel="stylesheet">
    <!--[if 1t IE 9]>
    <script src="is/html5shiv.js"></script>
    <script src="js/respond.min.js"></script>
    <![endif]-->
  </head>
  <body>
    <div class="row">
      <div class="col-xs-10 col-xs-offset-1 col-sm-8 col-sm-</pre>
       offset -2 col-md-4 col-md-offset -4">
        <div class="login-panel panel panel-default">
18
          <div class="panel-heading">Log in </div>
          <div class="panel-body">
20
          <form action="<?php echo site_url('c_login/aksi_login</pre>
       '); ?>" method="post">
                 <div class="form-group">
                   <input class="form-control" placeholder="</pre>
      username" name="username" type="text" autofocus="">
                 </div>
                 <div class="form-group">
                   <input class="form-control" placeholder="</pre>
26
       password" name="password" type="password" value="">
                 </div>
                 <input type="submit" value="Login" class="btn</pre>
28
      btn-primary">
2.9
                 <a href="<?php echo site_url(); ?>/c_register">
       Register </a>
30
             </form>
           </div>
        </div>
```

</div><!-- /.col-->

```
</div><!--- /.row --->
36
38 < script src="<?php echo base_url(); ?>assets/js/jquery -1.11.1.
       \min.js"></script>
    <script src="<?php echo base_url(); ?>assets/js/bootstrap.
30
       min. is "></script>
40 </body>
41 </html>
  <!DOCTYPE html>
2 <html>
  <head>
    <title > Grafik Aktivitas Mahasiswa </title >
    <?php
6
           foreach ($jan as $data) {
               $jumlahjanuary[] = $data->kegiatan;
0
           foreach ($feb as $data) {
               $jumlahfebruary[] = $data->kegiatan;
           foreach ($mar as $data) {
               $jumlahmarch[] = $data->kegiatan;
1.4
           foreach ($apr as $data) {
               $jumlahapril[] = $data->kegiatan;
           foreach ($may as $data) {
               $jumlahmay[] = $data->kegiatan;
           foreach($jun as $data){
               $jumlahjune[] = $data->kegiatan;
24
           foreach($jul as $data){
               $jumlahjuly[] = $data->kegiatan;
26
           foreach (\sug as \state) \{
               $jumlahaugust[] = $data->kegiatan;
29
30
           foreach ($sep as $data) {
               $jumlahseptember[] = $data->kegiatan;
           foreach ($oct as $data) {
34
               $jumlahoctober[] = $data->kegiatan;
35
36
           foreach ($nov as $data) {
               $jumlahnovember[] = $data->kegiatan;
38
39
40
           foreach ($dec as $data) {
               $jumlahdecember[] = $data->kegiatan;
41
42
      ?>
43
44 </head>
45 <body>
```

```
46
    <canvas id="canvas" width="1000" height="280"></canvas>
47
48
40
    <!--Load chart is-->
    <script type="text/javascript" src="<?php echo base_url().'</pre>
50
       assets/js/Chart.min.js'?>"></script>
51
    <script>
               var lineChartData = {
                   labels: ["January", "February", "March", "April"
       , "May", "June", "July", "August", "September", "October", "
      November", "December"],
                   datasets : [
56
                        {
                            fillColor: "rgba(60,141,188,0.9)",
                            strokeColor: "rgba(60,141,188,0.8)",
50
                            pointColor: "#3b8bba".
60
                            pointStrokeColor: "#fff"
61
                            pointHighlightFill: "#fff",
                            pointHighlightStroke: "rgba
       (152,235,239,1)",
                            data : [<?php echo ison_encode(
64
       $jumlahjanuary);?>,<?php echo json_encode($jumlahfebruary)</pre>
      ;?>,<?php echo json_encode($jumlahmarch);?>,<?php echo
      json_encode($jumlahapril);?>,<?php echo json_encode(
       $jumlahmay);?>,<?php echo json_encode($jumlahjune);?>,<?</pre>
      php echo ison_encode($jumlahjuly);?>,<?php echo
       ison_encode($jumlahaugust);?>,<?php echo ison_encode(</pre>
       $jumlahseptember);?>,<?php echo json_encode($jumlahoctober</pre>
       );?>,<?php echo json_encode($jumlahnovember);?>,<?php echo
       json_encode($jumlahdecember);?>1
                        }
                   1
               }
70
           var myLine = new Chart(document.getElementById("canvas
       ").getContext("2d")).Line(lineChartData);
      </script>
 </body>
  </html>
```

```
<link rel="stylesheet" type="text/css" href="<?php echo</pre>
      base_url('assets/css/easyui.css') ?>">
      <link rel="stylesheet" type="text/css" href="<?php echo</pre>
10
      base_url('assets/css/icon.css') ?>">
    <script src="<?php echo base_url(); ?>assets/js/jquery.min.
      is"></script>
    <script type="text/javascript" src="<?php echo base_url('</pre>
      assets/js/jquery.easyui.min.js') ?>"></script>
      <script type="text/javascript" src="<?php echo base_url('</pre>
      assets/js/script.js') ?>"></script>
16
20
    <link rel="stylesheet" href="https://openlayers.org/en/v4</pre>
      .6.5/css/ol.css" type="text/css">
      <script src="https://cdn.jsdelivr.net/gh/openlayers/</pre>
      openlayers.github.io@master/en/v6.1.1/build/ol.js"></
      script>
    <!--Custom Font-->
24
    <link href="https://fonts.googleapis.com/css?family=</pre>
      Montserrat:300,300i,400,400i,500,500i,600,600i,700,700i"
      rel="stylesheet">
    <!--[if 1t IE 9]>
26
    <script src="is/html5shiv.js"></script>
    <script src="js/respond.min.js"></script>
28
    <![endif]-->
29
30
 </head>
31
 <body>
    <nav class="navbar navbar-custom navbar-fixed-top" role="</pre>
      navigation">
      <div class="container-fluid">
34
        <div class="navbar-header">
35
          <button type="button" class="navbar-toggle collapsed"
      data-toggle="collapse" data-target="#sidebar-collapse"><
      span class="sr-only">Toggle navigation </span>
            <span class="icon-bar"></span>
            <span class="icon-bar"></span>
38
            <span class="icon-bar"></span></button>
          <a class="navbar-brand" href="#"><span>Lumino</span>
40
      Admin</a>
          <!--
          42
            <a class="dropdown-toggle count</pre>
      -info" data-toggle="dropdown" href="#">
              <span class="label label-danger">15</span>
            </a>
              class="dropdown-menu dropdown-messages">
                <1i>>
47
                  <div class="dropdown-messages-box"><a href="</pre>
48
      profile.html" class="pull-left">
```

```
<img alt="image" class="img-circle" src="</pre>
49
       http://placehold.it/40/30a5ff/fff">
                     </a>
50
                     <div class="message-body"><small class="pull</pre>
      -right">3 mins ago </small>
                       <a href="#"><strong>John Doe</strong>
      commented on <strong>your photo</strong>.</a>
                     <br /><small class="text-muted">1:24 pm -
      25/03/2015 < / small > < / div >
                   </div>
                 class="divider">
56
                 < 1i >
                   <div class="dropdown-messages-box"><a href="</pre>
       profile.html" class="pull-left">
                     <img alt="image" class="img-circle" src="</pre>
50
       http://placehold.it/40/30a5ff/fff">
                     </a>
60
                     <div class="message-body"><small class="pull</pre>
61
      -right">1 hour ago </small>
                       <a href="#">New message from <strong>Jane
62
      Doe < / strong > . < /a >
                     <br /><small class="text-muted">12:27 pm -
63
      25/03/2015 < / \text{small} > < / \text{div} >
                   </div>
                 class="divider">
66
                 <1i>
                   <div class="all-button"><a href="#">
                     <strong>All Messages</strong>
60
                   </a></div>
70
                 <a class="dropdown-toggle count</pre>
74
      -info" data-toggle="dropdown" href="#">
               <span class="label label-info">5</span>
             </a>
76
               < a href="#">
78
                   <div><em class="fa fa-envelope"></em> 1 New
      Message
80
                     <span class="pull-right text-muted small">3
       mins ago </span></div>
                 </a>
81
                 class="divider">
82
                 <a href="#"></a>
                   <div>em class="fa fa-heart"></em> 12 New
      Likes
                     <span class="pull-right text-muted small">4
85
      mins ago </span></div>
                 </a>
86
                 class="divider">
87
                 <1i><a href="#">
88
                   \langle \text{div} \rangle = \text{class} = \text{fa fa-user} > \langle \text{em} \rangle = 5 \text{ New}
89
       Followers
```

```
<span class="pull-right text-muted small">4
90
      mins ago </span></div>
                </a>
91
              _>
        </div>
96
      </div><!-- /. container-fluid -->
    </nav>
    <div id="sidebar-collapse" class="col-sm-3 col-lg-2 sidebar"</pre>
100
      <div class="profile-sidebar">
        <div class="profile-userpic">
          <img src="http://placehold.it/50/30a5ff/fff" class="</pre>
      img-responsive" alt="">
        </div>
        <div class="profile-usertitle">
104
          <div class="profile-usertitle-name"> <?php echo $this</pre>
      ->session ->userdata("nama"); ?></div>
          <div class="profile-usertitle-status"><span class="</pre>
106
      indicator label-success"></span>Online</div>
        </div>
        <div class="clear"></div>
      </div>
      <div class="divider"></div>
      <form role="search">
        <div class="form-group">
          <input type="text" class="form-control" placeholder="</pre>
      Search">
        </div>
      </form>
      116
      border-style:none; padding:inherit;">
        <a href="<?php echo site_url(); ?>/
      dashboard">Dashboard </a> 
        class="parent active"><a data-toggle="collapse" href</li>
118
      ="\#sub-item-1">
          Kelola <span data-toggle="collapse" href="#sub-item-1"
       class="icon pull-right"></span>
          </a>
          <a class="active" href="<?php echo site_url();</pre>
      ?>/c_kelola_user">
               User
            </a>
             < a class = "" href = "#" >
               Track
            </a></1i>
            \langle 1i \rangle \langle a class = "" href = "#" \rangle
128
               Dosen
129
            </a>
130
          <a href="<?php echo site_url('c_login/logout'); ?>">
       Logout </a>
```

```
134
    </div><!--/.sidebar--->
136
    <div class="col-sm-9 col-sm-offset-3 col-lg-10 col-lg-offset</pre>
      -2 main">
      <div class="row">

    class="breadcrumb">

130
          \langle 1i \rangle \langle a \text{ href} = "#" \rangle
140
            <em class="fa fa-home"></em>
141
          </a>
          class="active">Kelola User
143
        </01>
144
      </div><!--/.row-->
145
146
      <div class="row">
147
        <div class="col-lg-12">
148
          <h1 class="page-header">Kelola User </h1>
140
        </div>
150
      </div><!--/.row-->
      <div class="panel panel-container">
        <div class="row">
154
            <div class="col-sm-12">
            <div id="container" class="easyui-layout" fit="true"</pre>
       style = "height: 300 px;" >
              <div region="center">
                <table id="dgCustomers" toolbar="#
158
      toolbarCustomer" class="easyui-datagrid" fit="true"
      singleSelect="true" fitColumns="true" rowNumbers="false"
      pagination="true" url="<?= site_url('c_kelola_user/
      getcustomers') ?>" pageSize="50" pageList="
      [25,50,75,100,125,150,200]" nowrap="false">
                 <thead>
159
160
                   ID User</th
161
      >
                     Username
162
      Password
      Status
164
                    165
                  </thead>
166
                <div id="toolbarCustomer">
168
                 <a href="javascript:void(0)" class="easyui-
169
      linkbutton" iconCls="icon-add" plain="true" onClick="
      newCustomer()">New</a>
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-edit" plain="true" onClick="
      editCustomer()">Edit</a>
                 <a href="javascript:void(0)" class="easyui-
      linkbutton" iconCls="icon-remove" plain="true" onClick="
      destroyCustomer()">Destroy </a>
```

```
<input id="searchCustomer" class="easyui-</pre>
       searchbox" data-options="prompt: 'Please Input Value',
       searcher: doSearchCustomer,
                    inputEvents: $.extend({}, $.fn.searchbox.
       defaults.inputEvents, {
                      keyup: function(e){
                         var t = \$(e.data.target);
                         var opts = t.searchbox('options'):
176
                         t.searchbox('setValue', $(this).val());
                         opts.searcher.call(t[0],t.searchbox('
178
       getValue '), t. searchbox ('getName'));
170
                    })" style="width:50%:"></input>
180
                  </div>
181
                </div>
182
183
               <div id="dlgCustomer" class="easyui-dialog" style=</pre>
184
       "width: 780px; height: auto; padding: 10px;" modal="true"
       closed="true" buttons="#dlgCustomerBtn">
                  <form id="fmCustomer" method="post">
185
                    <div class="col-sm-12 justify-content-sm-</pre>
186
       center">
187
                    <div class="row" style="width: 100%">
189
                      <div class="col-sm-6">
190
                        <div class="form-group">
                          <label for="">ID</label>
102
                          <input type="text" name="id_user" class=</pre>
       "easyui-textbox" style="width: 100%;">
                         </div>
104
                       </div>
                      <div class="col-sm-6">
196
                        <div class="form-group">
197
                          <label for="">Username </label>
198
                          <input type="text" name="username" class</pre>
100
       ="easyui-textbox" style="width: 100%;">
                         </div>
200
                       </div>
                    </div>
202
                    <div class="row" style="width: 100%">
204
                      <div class="col-sm-6">
205
                        <div class="form-group">
206
                          <label for="">Password</label>
207
                          <input type="text" name="password" class</pre>
208
       ="easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
                      <div class="col-sm-6">
                        <div class="form-group">
                          <label for="">status </label>
                          <input type="text" name="status" class="</pre>
214
       easyui-textbox" style="width: 100%;">
                         </div>
                       </div>
216
```

```
</div>
218
                   </div>
219
                 </form>
220
               </div>
               <div id="dlgCustomerBtn">
                 <a href="javascript:void(0)" id="btn_save" class</a>
       ="easyui-linkbutton" iconCls="icon-ok-a" onclick="
       saveCustomer()" style="width:90px">Save</a>
                 <a href="javascript:void(0)" class="easyui-
224
       linkbutton" iconCls="icon-del-a" onclick="javascript:$('#
       dlgCustomer').dialog('close'); $('#fmEmployee').form(clear
                 " style = "width: 90 px" > Cancel </a>
               </div>
226
             </div>
             </div>
230
         </div><!--/.row-->
       </div>
234
        <div class="col-sm-12">
          Lumino Theme by <a href="https://</pre>
236
      www.medialoot.com">Medialoot</a>
         </div>
       </div><!--/.row-->
238
     </div> <!--/.main-->>
240
241
242
243
244
  </body>
245
246
247
    <script src="<?php echo base_url(); ?>assets/js/bootstrap.
       \min. js"></script>
    <script src="<?php echo base_url(); ?>assets/js/chart.min.js
249
       "></script>
    <script src="<?php echo base_url(); ?>assets/js/chart-data.
250
       is"></script>
    <script src="<?php echo base_url(); ?>assets/js/easypiechart
       . is "></script>
    <script src="<?php echo base_url(); ?>assets/js/easypiechart
252
       -data.js"></script>
    <script src="<?php echo base_url(); ?>assets/js/bootstrap-
       datepicker.js"></script>
    <script src="<?php echo base_url(); ?>assets/js/custom.js"
254
       ></script>
  </html>
```

```
<meta charset='utf-8'>
4
                                      <meta name='viewport' content=
5
       'width=device-width, initial-scale=1'>
                                      <title > Snippet - BBBootstrap </
6
       title >
                                      <link href='https://maxcdn.</pre>
       bootstrapedn.com/bootstrap/4.3.1/css/bootstrap.min.css'
       rel='stylesheet'>
                                      <link href='https://cdnjs.</pre>
8
       cloudflare.com/ajax/libs/font-awesome/4.0.3/css/font-
       awesome.css' rel='stylesheet'>
                                      \langle style \rangle *  {
0
       margin: 0;
       padding: 0
  html {
1.4
       height: 100%
16
  #grad1 {
18
       background-color: : #9C27B0;
19
       background-image: linear-gradient(120deg, #FF4081, #81D4FA
2.0
  #msform {
       text-align: center;
       position: relative;
       margin-top: 20px
26
28
  #msform fieldset .form-card {
29
       background: white;
30
       border: 0 none;
31
       border-radius: 0px;
       box-shadow: 0 \ 2px \ 2px \ 2px \ rgba(0, 0, 0, 0.2);
       padding: 20px 40px 30px 40px;
34
       box-sizing: border-box;
       width: 94%:
36
       margin: 0 3% 20px 3%;
       position: relative
38
30
40
  #msform fieldset {
41
       background: white;
42
       border: 0 none;
       border-radius: 0.5 rem;
       box-sizing: border-box;
       width: 100%;
46
       margin: 0;
47
       padding-bottom: 20px;
48
       position: relative
50
51
52 #msform fieldset:not(:first-of-type) {
```

```
display: none
  }
54
  #msform fieldset .form-card {
56
       text-align: left;
       color: #9E9E9E
50
60
  #msform input,
  #msform textarea {
       padding: Opx 8px 4px 8px;
       border: none;
64
       border-bottom: 1px solid #ccc;
       border-radius: 0px;
66
       margin-bottom: 25px;
       margin-top: 2px;
68
       width: 100%;
60
       box-sizing: border-box;
70
       font-family: montserrat;
       color: #2C3E50;
       font-size: 16px;
       letter-spacing: 1px
74
75
76
  #msform input: focus,
  #msform textarea: focus {
78
       -moz-box-shadow: none !important;
79
80
       -webkit-box-shadow: none !important;
       box-shadow: none !important;
       border: none;
82
       font-weight: bold;
23
       border-bottom: 2px solid skyblue;
       outline-width: 0
86
87
  #msform .action-button {
22
       width: 100px;
89
       background: skyblue;
90
       font-weight: bold;
       color: white;
92
       border: 0 none;
       border-radius: 0px;
94
95
       cursor: pointer;
       padding: 10px 5px;
       margin: 10px 5px
98
99
  #msform . action - button: hover,
  #msform .action-button:focus {
       box-shadow: 0 0 0 2px white, 0 0 0 3px skyblue
  }
104
  #msform .action-button-previous {
       width: 100px;
106
       background: #616161;
       font-weight: bold;
108
```

```
color: white;
109
       border: 0 none;
       border-radius: 0px;
       cursor: pointer;
       padding: 10px 5px;
       margin: 10px 5px
115
116
   #msform . action -button - previous: hover,
   #msform .action-button-previous:focus {
       box-shadow: 0 0 0 2px white, 0 0 0 3px #616161
119
120
   select.list-dt {
       border: none;
       outline: 0;
       border-bottom: 1px solid #ccc;
125
       padding: 2px 5px 3px 5px;
126
       margin: 2px
128
   select.list-dt:focus {
130
       border-bottom: 2px solid skyblue
   .card {
134
       z-index: 0;
136
       border: none;
       border-radius: 0.5 rem;
138
       position: relative
139
140
   .fs-title {
142
       font-size: 25px;
       color: #2C3E50;
143
       margin-bottom: 10px;
       font-weight: bold;
       text-align: left
146
147
148
   #progressbar {
149
150
       margin-bottom: 30px;
151
       overflow: hidden;
       color: lightgrey
154
   #progressbar .active {
       color: #000000
156
157
158
   #progressbar li {
        list-style-type: none;
160
       font-size: 12px;
161
       width: 25%;
162
        float: left;
163
       position: relative
164
```

```
165
166
   #progressbar #account:before {
167
       font-family: FontAwesome;
168
       content: "\f023"
170
   #progressbar #personal:before {
       font-family: FontAwesome;
       content: "\f007"
175
176
   #progressbar #payment:before {
       font-family: FontAwesome;
178
       content: "\f09d"
180
181
   #progressbar #confirm:before {
182
       font-family: FontAwesome;
183
       content: "\f00c"
185
186
   #progressbar li:before {
187
       width: 50px;
188
       height: 50px;
189
       line-height: 45px;
190
       display: block;
192
       font-size: 18px;
       color: #ffffff;
194
       background: lightgray;
       border-radius: 50%;
       margin: 0 auto 10px auto;
196
       padding: 2px
197
198
199
    progressbar li:after {
200
       content:
201
       width: 100%;
202
       height: 2px;
203
       background: lightgray;
204
       position: absolute;
        left: 0:
206
       top: 25px;
207
       z-index: -1
208
209
   #progressbar li.active:before,
   #progressbar li.active:after {
       background: skyblue
215
   .radio-group {
216
        position: relative;
       margin-bottom: 25px
218
219
220
```

```
.radio {
       display: inline-block;
       width: 204:
       height: 104;
       border-radius: 0;
225
       background: lightblue;
       box-shadow: 0 \ 2px \ 2px \ 2px \ rgba(0, 0, 0, 0.2);
       box-sizing: border-box;
228
       cursor: pointer;
       margin: 8px 2px
   .radio:hover {
       box-shadow: 2px 2px 2px 2px rgba(0, 0, 0, 0.3)
234
236
   .radio.selected {
       box-shadow: 1px 1px 2px 2px rgba(0, 0, 0, 0.1)
238
239
240
   . fit -image {
241
       width: 100%;
242
       object-fit: cover
243
   </style>
                                      <script type='text/javascript'</pre>
245
        src='https://cdnjs.cloudflare.com/ajax/libs/jquery/3.2.1/
       jquery.min.js'></script>
246
                                      <script type='text/javascript'</pre>
        src='https://maxcdn.bootstrapcdn.com/bootstrap/4.3.1/js/
       bootstrap.min.js'></script>
                                      <script type='text/javascript'</pre>
247
       >$ (document).ready(function(){
248
   var current_fs, next_fs, previous_fs; // fieldsets
   var opacity;
  $(".next").click(function(){
   current_fs = $(this).parent();
   next_fs = $(this).parent().next();
256
257
   //Add Class Active
   $("#progressbar li").eq($("fieldset").index(next_fs)).addClass
       ("active");
259
260 //show the next fieldset
   next_fs.show();
  // hide the current fieldset with style
   current_fs.animate({opacity: 0}, {
  step: function(now) {
  // for making fielset appear animation
   opacity = 1 - now;
266
267
   current_fs.css({
268
   'display': 'none',
  'position': 'relative'
```

```
271 });
272 next_fs.css({'opacity': opacity});
273 },
274 duration: 600
275 }):
  }):
  $(".previous").click(function(){
278
   current_fs = $(this).parent();
   previous_fs = $(this).parent().prev();
281
282
283
  //Remove class active
  $("#progressbar li").eq($("fieldset").index(current_fs)).
       removeClass("active");
   //show the previous fieldset
286
   previous_fs.show();
287
  // hide the current fieldset with style
290 current_fs.animate({opacity: 0}, {
  step: function (now) {
292 // for making fielset appear animation
   opacity = 1 - now;
294
  current_fs.css({
295
   'display': 'none'
  'position': 'relative'
297
   previous_fs.css({'opacity': opacity});
300 },
301
  duration: 600
  });
303
   });
304
305 $('.radio-group .radio').click(function(){
$(this).parent().find('.radio').removeClass('selected');
  $(this).addClass('selected');
  });
309
310 $(". submit").click(function(){
  return false:
311
312
  })
   }); </script>
                                </head>
                                <body>
316
                                <!-- MultiStep Form -->
  <div class="container-fluid" id="grad1">
       <div class="row justify-content-center mt-0">
           <div class="col-11 col-sm-9 col-md-7 col-lg-6 text-
       center p-0 mt-3 mb-2">
               <div class="card px-0 pt-4 pb-0 mt-3 mb-3">
                   <h2><strong>Sign Up Your User Account</strong
       ></h2>
                   Fill all form field to go to next step
```

```
<div class="row">
324
                       <div class="col-md-12 mx-0">
                           <form id="msform" method="POST" action
326
       ="<?php echo site_url('c_register/register'); ?>">
                               <!-- progressbar -->
                               class="active" id="account
       "><strong>Account</strong>
                                    id="personal"><strong>
330
       Personal </strong>
                                    id="payment"><strong>
331
       Payment </strong >
                                    id="confirm"><strong>
       Finish </strong >

<!-- fieldsets -->
                               <fieldset>
                                    <div class="form-card">
                                    <?php
336
                                        if (validation_errors()){
                                            ?>
338
                                            <div class="alert
220
       alert-info text-center">
                                                 <?php echo
340
       validation_errors(); ?>
                                            </div>
341
                                            <?php
342
                                        }
343
344
                                        if ($this -> session ->
       flashdata('message')){
346
                                            <div class="alert
347
       alert-info text-center">
                                                 <?php echo $this ->
       session -> flashdata ('message'); ?>
                                            </div>
                                            <?php
350
                                        }
                                    ?>
                                        <h2 class="fs-title">
       Informasi Akun</h2>
                                        <input type="number" name=</pre>
354
       "npm" placeholder="NPM anda" />
                                        <input type="text" name="</pre>
       nama" placeholder="nama" />
                                        <input type="text" name="</pre>
356
       kelas" placeholder="Kelas" />
                                    </div> <input type="button"
358
       name="next" class="next action-button" value="Next Step"
       />
                                </fieldset>
359
                               <fieldset>
360
                                    <div class="form-card">
361
                                        <h2 class="fs-title">
362
       Registrasi </h2>
```

```
363
                                          <input type="text" name="</pre>
364
       prodi" placeholder="Prodi" />
                                          <input type="text" name="</pre>
365
       angkatan" placeholder="Angkatan" />
                                          <input type="text" name="</pre>
       foto" placeholder="Foto" />
367
                                      </div> <input type="button"
368
       name="previous" class="previous action-button-previous"
       value="Previous" /> <input type="button" name="next" class
       ="next action-button" value="Next Step" />
369
                                 </fieldset>
                                 <fieldset>
                                     <div class="form-card">
                                          <h2 class="fs-title">
       Registrasi </h2>
                                          <div class="row">
                                          <input type="text" name="</pre>
       username" placeholder="Username" />
                                          <input type="text" name="</pre>
376
       password" placeholder="password" />
                                          <input type="email" name="</pre>
       email" placeholder="email" />
378
                                          </div>
380
                                      </div> <input type="button"
       name="previous" class="previous action-button-previous"
       value="Previous" /> <input type="button" name="
       make_payment" class="next action-button" value="Confirm"
       />
                                 </fieldset>
382
                                 <fieldset>
383
                                      <div class="form-card">
384
                                          <h2 class="fs-title text-
385
       center">Success !</h2> <br>br>
                                          <div class="row justify-</pre>
       content-center">
                                              <div class="col-3"> <
387
       img src="https://img.icons8.com/color/96/000000/ok-v2.png
       " class="fit-image"> </div>
                                          </div><br><br><>
                                          <div class="row justify-</pre>
389
       content-center">
                                              <div class="col-7 text</pre>
390
       -center">
                                                   <h5>Sudah Yakin?
       Submit formnya </h5>
                                                   <input type="
392
       submit" class="btn btn-primary">
                                               </div>
393
                                          </div>
394
                                      </div>
395
                                 </fieldset>
396
```

## **202** WEB

```
</form>
397
                         </div>
398
                     </div>
399
                </div>
400
           </div>
401
       </div>
402
   </div>
403
                                   </body>
404
                               </html>
405
```