

# OOPS Interface Abstract Class



OOPS - Interface, Abstract class

now we go level by level growth like a game on this java topic, provide coding example with its explanation, realworld usecase example, neccary hinds, points to remember, usual mistakes, etc.

start lvl1

Got it Divakar.

We'll make this like a **game-style growth path** on **OOPS – Interface vs Abstract class**.

We'll start from **Level 1 (basics)**, and in each level, we'll move deeper step by step.

## OOPS Growth Path – Level 1: Basics of Interface & Abstract Class

### Concepts

#### Interface

- A contract/blueprint: says *what* should be done, not *how*.
- Only **method declarations** (till Java 7), from Java 8 onwards supports:
  - Default methods (with body)
  - Static methods
- Cannot have constructors.
- Supports **multiple inheritance** (a class can implement many interfaces).

**Think:** A *remote control* interface: different TVs implement it differently.

#### Abstract Class

- A class that **cannot be instantiated directly**.
- Can have:
  - Abstract methods (only declaration)
  - Concrete methods (with implementation)
- Can have constructors, fields, and access modifiers.
- Used when classes share **common code** but also need customization.

👉 **Think:** A *Vehicle* abstract class: some properties common to all vehicles (wheels, engine), but "drive()" is different.

## 2 Code Example

### Interface Example

```
java

interface RemoteControl {
    void turnOn();
    void turnOff();
}

class TV implements RemoteControl {
    public void turnOn() {
        System.out.println("TV is ON");
    }
    public void turnOff() {
        System.out.println("TV is OFF");
    }
}

public class Main {
    public static void main(String[] args) {
        RemoteControl rc = new TV(); // Polymorphism
        rc.turnOn();
        rc.turnOff();
    }
}
```

### ✓ Output:

```
vbnet

TV is ON
TV is OFF
```

### Abstract Class Example

```
java

abstract class Vehicle {
    abstract void drive(); // abstract method
    void fuel() {           // concrete method
        System.out.println("Vehicle needs fuel.");
    }
}

class Car extends Vehicle {
    void drive() {
        System.out.println("Car is driving...");
    }
}

public class Main {
    public static void main(String[] args) {
        Vehicle v = new Car(); // Polymorphism
        v.fuel();
        v.drive();
    }
}
```

```
}  
}
```

## ✓ Output:

```
csharp  
  
Vehicle needs fuel.  
Car is driving...
```

## 3 Real-World Use Cases

- **Interface:**
  - Payment gateways → **Payable** interface (CreditCard, UPI, PayPal implement differently).
  - JDBC in Java → **Connection**, **ResultSet**, etc. are interfaces.
- **Abstract Class:**
  - GUI frameworks → **AbstractButton** in Swing.
  - Game development → **Character** base class (health, attack) but each character attacks differently.

## 4 Hints & Points to Remember

- Interface = 100% abstraction (before Java 8), Abstract class = 0–100% abstraction.
- Use **interface** when you just need a contract.
- Use **abstract class** when you have shared code + contract.
- A class **can extend only one abstract class** but **can implement multiple interfaces**.

## 5 Usual Mistakes

✗ Trying to create an object of an abstract class/interface:

```
java  
  
RemoteControl rc = new RemoteControl(); // ERROR
```

- ✗ Forgetting to implement **all interface methods** in a class.
- ✗ Using abstract class when interface is enough → leads to unnecessary inheritance restrictions.

🎯 **Level 1 Goal Achieved:** You now know the **difference between interface & abstract class**, with **basic code + real examples**.

👉 Do you want me to unlock **Level 2 (deeper concepts: multiple inheritance, default methods, constructors in abstract classes, etc.)**?



next

Perfect 🚀 Divakar!

Let's **unlock Level 2** of our OOPS game on **Interface & Abstract Class**.

## 🎮 Level 2 – Advanced Usage (Multiple Inheritance, Default/Static Methods, Constructors in Abstract Classes)

### 1 Multiple Inheritance in Interfaces

In Java, a **class cannot extend multiple classes**, but it **can implement multiple interfaces**.

👉 This solves the **diamond problem** in Java because interfaces only provide method **signatures**, not implementations (except default methods).

#### Example:

```
java

interface Camera {
    void takePhoto();
}

interface MusicPlayer {
    void playMusic();
}

class Smartphone implements Camera, MusicPlayer {
    public void takePhoto() {
        System.out.println("Taking a photo with smartphone...");
    }
    public void playMusic() {
        System.out.println("Playing music on smartphone...");
    }
}

public class Main {
    public static void main(String[] args) {
        Smartphone phone = new Smartphone();
        phone.takePhoto();
        phone.playMusic();
    }
}
```

#### ✓ Output:

```
csharp

Taking a photo with smartphone...
Playing music on smartphone...
```

### Real World Example:

A **Smartphone** can act as a **Camera** and a **Music Player** → multiple roles with interfaces.

## 2 Default & Static Methods in Interfaces (Java 8+)

- **Default methods:** allow method implementation inside interface (no breaking changes for existing code).
- **Static methods:** can be called on the interface directly.

### Example:

```
java

interface Vehicle {
    void drive();

    default void honk() {
        System.out.println("Honking... Beep Beep!");
    }

    static void serviceInfo() {
        System.out.println("Service available at authorized centers.");
    }
}

class Car implements Vehicle {
    public void drive() {
        System.out.println("Car is driving...");
    }
}

public class Main {
    public static void main(String[] args) {
        Car c = new Car();
        c.drive();
        c.honk(); // default method

        Vehicle.serviceInfo(); // static method
    }
}
```

### ✓ Output:

```
mathematica

Car is driving...
Honking... Beep Beep!
Service available at authorized centers.
```

**Hint:** Default methods solve the problem of updating interfaces without forcing all implementing classes to change.

## 3 Constructors in Abstract Classes

- Abstract classes **can have constructors**.
- They are called when a **concrete subclass is created**.

- Useful for initializing common fields.

## Example:

```
java

abstract class Animal {
    String name;
    Animal(String name) {
        this.name = name;
        System.out.println("Animal constructor called for: " + name);
    }
    abstract void sound();
}

class Dog extends Animal {
    Dog(String name) {
        super(name);
    }
    void sound() {
        System.out.println(name + " says Woof!");
    }
}

public class Main {
    public static void main(String[] args) {
        Dog d = new Dog("Buddy");
        d.sound();
    }
}
```

## ✓ Output:

```
kotlin

Animal constructor called for: Buddy
Buddy says Woof!
```

## Real World Example:

Every `Employee` in a company must have a name (set in constructor), but `calculateSalary()` is abstract since it differs for `FullTimeEmployee` and `Intern`.

## 4 Key Points & Hints

- **Interfaces:** support **multiple inheritance** (class can implement many interfaces).
- **Abstract classes:** support **single inheritance**, but allow shared **fields + constructors**.
- Default methods in interfaces help evolve APIs smoothly (e.g., Java's `List.sort()` method was added later without breaking old code).
- Use **abstract class** when there's **common code/state**, use **interface** when you just need **behavior contracts**.

## 5 Usual Mistakes at This Level

- ✗ Forgetting `super()` call in subclass when abstract class has constructor.
- ✗ Overusing default methods in interfaces → makes them behave like abstract classes (bad design).
- ✗ Assuming interfaces can have instance variables (they **cannot**, only **public static final** constants).

### 🎯 Level 2 Goal Achieved:

You now know **multiple inheritance with interfaces, default & static methods, and constructors in abstract classes** with real-world examples.

👉 Shall we unlock **Level 3 (deeper design decisions: when to choose interface vs abstract class, mixing both, real system design examples, interview pitfalls)?**



next

Awesome ⚡ Divakar, let's power up to **Level 3** of our OOPS growth path!  
Now we go from **syntax & features** → **design decisions & real-world scenarios**.

## 🎮 Level 3 – Interface vs Abstract Class: Design Choices & Real-World Applications

### 1 When to Use Interface vs Abstract Class

#### ✅ Use an Interface when:

- You just need a **contract** (behavior guarantee).
- Multiple unrelated classes need the same behavior.
- No common state/fields are required.

👉 Example:

- **Comparable** interface → Both **Integer** and **String** can implement comparison.
- Payment systems → **Payable** interface for **UPI**, **CreditCard**, **PayPal**.

#### ✅ Use an Abstract Class when:

- You need **shared state (fields)** or **base logic**.
- You want a **template** where subclasses override parts.
- You want constructors for initialization.

👉 Example:

- **Vehicle** abstract class → All vehicles have **fuel**, but **drive()** differs.

- `GameCharacter` → All have `health`, but attack styles differ.

## 2 Mixing Both (Hybrid Approach)

Sometimes you combine both **abstract class + interface** for flexible design.

### Example:

```
java

interface PaymentGateway {
    void processPayment(double amount);
}

abstract class BankPayment implements PaymentGateway {
    String bankName;
    BankPayment(String bankName) {
        this.bankName = bankName;
    }
    void connectToBankServer() {
        System.out.println("Connecting to " + bankName + " server...");
    }
}

class HDFCPayment extends BankPayment {
    HDFCPayment() {
        super("HDFC Bank");
    }
    public void processPayment(double amount) {
        connectToBankServer();
        System.out.println("Processing payment of ₹" + amount + " via HDFC.");
    }
}

public class Main {
    public static void main(String[] args) {
        PaymentGateway payment = new HDFCPayment();
        payment.processPayment(2500);
    }
}
```

### ✓ Output:

```
css

Connecting to HDFC Bank server...
Processing payment of ₹2500 via HDFC.
```

### Explanation:

- `PaymentGateway` → contract (all payments must implement `processPayment`).
- `BankPayment` → common logic (connection).
- `HDFCPayment` → specialization.

👉 **Real world:** Most frameworks (Spring, Hibernate) use this hybrid approach.

## 3 Real-World Examples from Java



- **Interface:** `Runnable` → implemented by threads, doesn't care about class hierarchy.
- **Abstract Class:** `HttpServletRequest` → provides default implementations for some methods (`doGet`, `doPost`), but forces you to override necessary ones.

## 4 Interview-Level Hints

- **Q:** Can abstract class implement an interface?  
 ✓ Yes, but it doesn't need to provide implementation for all methods → subclass must do it.
- **Q:** Can interface extend another interface?  
 ✓ Yes (multiple inheritance of interfaces).
- **Q:** Can abstract class have final methods?  
 ✓ Yes, final methods cannot be overridden by subclasses.
- **Q:** Why can't interfaces have constructors?  
 ✓ Because they don't hold state → no object creation.

## 5 Common Mistakes at This Level

- ✗ Treating interfaces as “just abstract classes with no code” (they are not).
- ✗ Overusing abstract classes → leads to rigid inheritance hierarchies.
- ✗ Designing interfaces with too many methods → violates **Interface Segregation Principle** (SOLID).

## 6 Points to Remember

- Interface = **capability** → “what an object can do”.
- Abstract class = **base class** → “what an object is”.
- Prefer **interfaces** in APIs for flexibility, use **abstract classes** internally for code reuse.
- In modern Java, **interfaces with default methods** sometimes overlap abstract classes, but don't overuse defaults.

### 🎯 Level 3 Goal Achieved:

You can now **decide when to use interface vs abstract class**, understand **hybrid usage**, and avoid common design mistakes.

👉 Do you want to unlock **Level 4 (expert-level: design patterns using interface & abstract class – e.g., Strategy, Template Method, Factory, plus pitfalls asked in interviews)**?



next

Alright ⚡ Divakar, welcome to **Level 4 – Expert Design & Patterns**.

Here, we go beyond syntax and design choices into **real-world patterns** using **Interface & Abstract Class**, which are **common in interviews**.

## 🎮 Level 4 – Design Patterns & Expert Usage of Interface & Abstract Class

### 1 Strategy Pattern – Interface Based

**Goal:** Define a family of algorithms, encapsulate each, and make them interchangeable.

- **Interface** defines behavior.
- Concrete classes implement different strategies.
- Context class uses interface reference.

**Example:**

```
java

interface PaymentStrategy {
    void pay(double amount);
}

class CreditCardPayment implements PaymentStrategy {
    public void pay(double amount) {
        System.out.println("Paid ₹" + amount + " using Credit Card.");
    }
}

class PayPalPayment implements PaymentStrategy {
    public void pay(double amount) {
        System.out.println("Paid ₹" + amount + " using PayPal.");
    }
}

class ShoppingCart {
    private PaymentStrategy paymentStrategy;

    ShoppingCart(PaymentStrategy paymentStrategy) {
        this.paymentStrategy = paymentStrategy;
    }

    void checkout(double amount) {
        paymentStrategy.pay(amount);
    }
}

public class Main {
    public static void main(String[] args) {
        ShoppingCart cart1 = new ShoppingCart(new CreditCardPayment());
        cart1.checkout(5000);

        ShoppingCart cart2 = new ShoppingCart(new PayPalPayment());
        cart2.checkout(3000);
    }
}
```

✓ Output:

```
cpp
```

```
Paid ₹5000 using Credit Card.
Paid ₹3000 using PayPal.
```

### Interview Tip:

- Always mention **flexibility**: you can switch payment strategies **without modifying ShoppingCart**.
- **Interface = strategy contract**.

## 2 Template Method Pattern – Abstract Class Based

**Goal:** Define skeleton of an algorithm in an abstract class, let subclasses fill specific steps.

### Example:

```
java

abstract class Game {
    final void play() { // template method
        start();
        playTurn();
        end();
    }

    abstract void start();
    abstract void playTurn();
    abstract void end();
}

class Chess extends Game {
    void start() { System.out.println("Chess started."); }
    void playTurn() { System.out.println("Playing chess turn."); }
    void end() { System.out.println("Chess ended."); }
}

class Football extends Game {
    void start() { System.out.println("Football started."); }
    void playTurn() { System.out.println("Playing football turn."); }
    void end() { System.out.println("Football ended."); }
}

public class Main {
    public static void main(String[] args) {
        Game chess = new Chess();
        chess.play();

        Game football = new Football();
        football.play();
    }
}
```

### ✓ Output:

```
arduino
```

```
Chess started.
Playing chess turn.
Chess ended.
Football started.
```

Playing football turn.  
Football ended.

#### Interview Tip:

- **Abstract class** = skeleton
- **Subclasses** = customizable steps

## 3 Factory Pattern – Interface + Abstract Class Combination

- **Interface:** type of product.
- **Abstract Class or Concrete Classes:** implement product behavior.
- **Factory:** decides which product to create.

#### Example:

```
java

interface Vehicle {
    void drive();
}

class Car implements Vehicle {
    public void drive() { System.out.println("Car is driving."); }
}

class Bike implements Vehicle {
    public void drive() { System.out.println("Bike is driving."); }
}

class VehicleFactory {
    static Vehicle createVehicle(String type) {
        if(type.equalsIgnoreCase("Car")) return new Car();
        else if(type.equalsIgnoreCase("Bike")) return new Bike();
        else throw new IllegalArgumentException("Unknown vehicle");
    }
}

public class Main {
    public static void main(String[] args) {
        Vehicle v1 = VehicleFactory.createVehicle("Car");
        v1.drive();

        Vehicle v2 = VehicleFactory.createVehicle("Bike");
        v2.drive();
    }
}
```

#### ✓ Output:

```
csharp

Car is driving.
Bike is driving.
```

#### Interview Tip:

- Shows **interface for abstraction, factory for object creation, decouples client from concrete implementation.**

## 4 Common Expert-Level Hints

- **Interface vs Abstract Class in patterns:**
  - Interface → used for **Strategy, Observer, Decorator** (behavior abstraction)
  - Abstract Class → used for **Template Method, partially implemented class hierarchies**
- **Polymorphism is key:** always code to interface, not implementation.
- **Default methods in interfaces** are handy for evolving APIs, e.g., Java Collections `sort()`.
- **Avoid multiple abstract classes** → Java doesn't allow multiple inheritance of classes.

## 5 Pitfalls in Interviews

- ✗ Overloading abstract methods instead of overriding → breaks template pattern.
- ✗ Using interface when you need shared state → abstract class is better.
- ✗ Ignoring **SOLID principles**:

- Interface Segregation → small, focused interfaces.
- Liskov Substitution → subclass should honor base class contract.

### 🎯 Level 4 Goal Achieved:

- You can **design real-world systems** using **interface & abstract class**.
- You can **recognize patterns** in interviews.
- You know the **best practices + pitfalls** at an expert level.

If you want, I can create **Level 5 – Ultimate Master Level**:

- **Polymorphism tricks, multiple default method conflicts, advanced interview scenarios, deep comparison table, live examples in frameworks like Spring/Hibernate.**

Do you want to go to **Level 5**?



next

Awesome ⚡ Divakar, now we're entering **Level 5 – Ultimate Mastery** of Interface & Abstract Class in Java.

Here, we focus on **advanced nuances, tricky interview scenarios, conflicts, and framework-level real-world applications.**



# Level 5 – Ultimate Mastery: Interface & Abstract Class

## 1 Polymorphism Tricks & Casting

- **Interface reference** → **concrete class object** (common in APIs)
- **Abstract class reference** → **concrete subclass object**

### Example:

```
java

interface Animal {
    void sound();
}

abstract class Mammal implements Animal {
    abstract void sleep();
}

class Dog extends Mammal {
    public void sound() { System.out.println("Woof Woof!"); }
    void sleep() { System.out.println("Dog sleeps..."); }
}

public class Main {
    public static void main(String[] args) {
        Animal a = new Dog();    // Interface reference
        a.sound();                // allowed
        // a.sleep();            // ❌ Not allowed, Animal doesn't have sleep()

        Mammal m = new Dog();    // Abstract class reference
        m.sound();                // allowed
        m.sleep();                // allowed
    }
}
```

**Hint:** Reference type controls what methods are **visible at compile time**, actual object decides **runtime behavior**.

## 2 Default Method Conflicts in Interfaces

- Java allows **multiple interfaces with default methods**, but conflicts must be resolved in the implementing class.

### Example:

```
java

interface A {
    default void hello() { System.out.println("Hello from A"); }
}

interface B {
    default void hello() { System.out.println("Hello from B"); }
}

class C implements A, B {
    public void hello() {
    }
}
```

```

        A.super.hello(); // resolve conflict
        B.super.hello();
        System.out.println("Hello from C");
    }
}

public class Main {
    public static void main(String[] args) {
        C obj = new C();
        obj.hello();
    }
}

```

✓ Output:

```

css

Hello from A
Hello from B
Hello from C

```

### Interview Tip:

- Always know how to **resolve default method conflicts**.
- This is a common tricky question.

## 3 Interface + Abstract Class in Frameworks

- **Spring Framework:**
  - `ApplicationContext` is an interface → multiple implementations (`AnnotationConfigApplicationContext`, `ClassPathXmlApplicationContext`)
  - `AbstractApplicationContext` is an abstract class → provides **shared logic** (refresh, shutdown hooks)
- **Hibernate:**
  - `Interceptor` → interface
  - `EmptyInterceptor` → abstract class with empty implementations (you override only needed methods)

### Takeaway:

- Interface → contract
- Abstract class → default/common implementation

## 4 Live Example: Solving a Real Problem

**Problem:** You want a payment system with optional features (like discount, cashback) and multiple banks.

```
java

interface Payment {
    void pay(double amount);
}

abstract class BankPayment implements Payment {
    String bankName;
    BankPayment(String bankName) { this.bankName = bankName; }

    void connect() { System.out.println("Connecting to " + bankName); }
}

class HDFCPayment extends BankPayment {
    HDFCPayment() { super("HDFC"); }
    public void pay(double amount) {
        connect();
        System.out.println("Paying ₹" + amount + " via HDFC");
    }
}

class ICICIPayment extends BankPayment {
    ICICIPayment() { super("ICICI"); }
    public void pay(double amount) {
        connect();
        System.out.println("Paying ₹" + amount + " via ICICI");
    }
}

public class Main {
    public static void main(String[] args) {
        Payment p1 = new HDFCPayment();
        p1.pay(5000);

        Payment p2 = new ICICIPayment();
        p2.pay(3000);
    }
}
```

#### ✓ Output:

```
css

Connecting to HDFC
Paying ₹5000 via HDFC
Connecting to ICICI
Paying ₹3000 via ICICI
```

#### Master-Level Design Tip:

- Interface → flexible contract
- Abstract → reduces code duplication
- Reference type → promotes **polymorphism**

## 5 Advanced Interview Tricks

| Question  | Key Points / Answer                              |
|---|--|
| Can interface have private methods?               | Yes, Java 9+, for code reuse in default methods. |
| Can abstract class implement interface partially? | Yes, subclass must implement remaining methods.  |
| Multiple inheritance of abstract class?           | ✗ Not allowed. Only interfaces.                  |



| Question  | Key Points / Answer                                   |
|---|---|
| Diamond problem with interfaces?                      | Resolved via default method override.                 |
| When to prefer abstract over interface in frameworks? | When <b>shared state or common logic</b> is required. |

## 6 Ultimate Tips & Mistakes to Avoid

- Avoid **interface pollution** → keep them focused.
- Avoid **overusing default methods** → don't turn interfaces into abstract classes.
- Always code to **interface/abstract class** in APIs → improves flexibility.
- Use **abstract class** for template patterns or shared logic.
- Remember **reference type ≠ object type** → affects accessible methods.

### Level 5 Goal Achieved:

- You now master **interface vs abstract class at syntax, design, pattern, and framework levels**.
- You can handle **default method conflicts, polymorphism tricks, and real-world scenarios**.
- You're ready for **any interview questions** on this topic, including tricky and framework-related questions.

If you want, I can also create a **bonus "Interface vs Abstract Class Quick Reference Cheat Sheet"**

- With **all rules, do's & don'ts, and examples in one place** for interviews.

Do you want me to make that cheat sheet?