Experiment 2: Finding Largest and Smallest Values

(a) Find Largest Number from an Array

Aim

To find the largest number from an array using 8085 microprocessor.

Apparatus Required

- 8085 Simulator

- PC

Algorithm

1. Start the program.

2. Initialize a memory pointer (using HL register pair) to point to the starting address of the array.

3. Load the count of numbers in the array into a register (say, register B).

4. Increment the memory pointer to point to the first data element.

5. Load the first element into the Accumulator (A) – this is the initial largest number.

6. Decrement the count by 1 since the first number is already considered.

7. Repeat the following steps until the count becomes 0:

    - Increment the memory pointer to move to the next element.

    - Compare the current memory element with the value in Accumulator.

    - If the current element is greater than the Accumulator content:

        - Move the current element into the Accumulator (update the largest).

    - Decrement the count.

8. After all elements are checked, the Accumulator will contain the largest number.

9. Store the content of the Accumulator (i.e., the largest number) in memory at the required address.

10. End the program.

Program

```
; Program to find the greatest number using I/O Ports

IN 01H      ; Read first number
MOV D, A    ; Assume first number is greatest

IN 02H      ; Read second number
CMP D
JC NEXT2    ; If A < D, skip update
MOV D, A    ; Else update greatest
NEXT2:

IN 03H      ; Read third number
CMP D
JC NEXT3
MOV D, A
NEXT3:

IN 04H      ; Read fourth number
CMP D
JC NEXT4
MOV D, A
NEXT4:

IN 05H      ; Read fifth number
CMP D
JC DONE
MOV D, A

DONE: MOV A, D
OUT 06H     ; Output greatest number at port 06H
HLT
```

Input Ports (numbers are read from these ports):

- 01H → First number

- 02H → Second number

- 03H → Third number

- 04H → Fourth number

- 05H → Fifth number

Output Port:

- 06H → Greatest number

Result

Thus, the program to find the **largest number in an array** was executed successfully.

Find Smallest Number from an Array

Aim

To find the smallest number from an array using 8085 microprocessor.

Apparatus Required

- 8085 Simulator

- PC

Algorithm

1. Start the program.

2. Initialize the HL register pair to point to the starting address of the array.

3. Load the count of elements from memory into a register (e.g., register B).

4. Increment HL to point to the first data element.

5. Load the first data into the Accumulator (A) – assume this is the smallest number initially.

6. Decrement the count (B) by 1 because the first number is already loaded.

7. Repeat the following steps until the count becomes 0:

   - Increment HL to point to the next data element.

   - Compare the content of memory (M) with the Accumulator (A).

   - If **M < A**, move M to Accumulator (update the smallest number).

   - Decrement the count (B).

8. After the loop ends, the Accumulator holds the smallest number.

9. Store the content of the Accumulator in a desired memory location (e.g., 4300H).

10. End the program.

Program

; Program to find the smallest number using I/O Ports

```
IN 01H      ; Read first number
MOV D, A    ; Assume first number is smallest
```

```
IN 02H        ; Read second number
CMP D
JNC NEXT2     ; If A >= D, skip update
MOV D, A      ; Else update smallest
NEXT2:

IN 03H        ; Read third number
CMP D
JNC NEXT3
MOV D, A
NEXT3:

IN 04H        ; Read fourth number
CMP D
JNC NEXT4
MOV D, A
NEXT4:

IN 05H        ; Read fifth number
CMP D
JNC DONE
MOV D, A

DONE: MOV A, D
OUT 07H       ; Output smallest number at port 07H
HLT
```

Input Ports (numbers are read from these ports):

- 01H → First number

- 02H → Second number

- 03H → Third number

- 04H → Fourth number

- 05H → Fifth number

Output Port:

- 06H → Smallest number

Result

Thus, the program to find the **smallest number in an array** was executed successfully.