

SOL L-8.
29/07/2026

Date: 29/07/2026

SOL Practice Set (Group By, Having & left join)

Q1

⇒ SELECT rider_type, Count(*) AS total_rides,
Sum(fare) AS total_fare FROM rides
GROUP BY rider_type HAVING Count(*) > 7
ORDER BY total_fare DESC;

Q2

⇒ SELECT station_id,
Count(*) AS ride_count,
ROUND(AVG(duration_min), 2) AS avg_duration
FROM rides
GROUP BY station_id
HAVING AVG(duration_min) > 30
ORDER BY avg_duration DESC;

Q3

⇒ SELECT
MONTH(ride_date) AS ride_month,
COUNT(*) AS total_rides,
ROUND(SUM(distance_km), 1) AS total_distance
FROM rides
GROUP BY MONTH(ride_date)
HAVING SUM(distance_km) > 30
ORDER BY ride_month;

Q4

7) SELECT
rider_type,
MAX(duration_min) AS longest_ride,
MIN(duration_min) AS shortest_ride,
ROUND(AVG(duration_min), 2) AS avg_ride
FROM rides
GROUP BY rider_type
HAVING MAX(duration_min) >= 50
ORDER BY longest_ride DESC;

Q5

7) SELECT
Station-id, rider_type, COUNT(*) AS ride_count,
ROUND(SUM(distance_km), 1) AS total_distance
FROM rides
GROUP BY Station-id, rider_type
HAVING SUM(distance_km) > 10
ORDER BY Station-id ASC;

Q6

⇒ SELECT

```
station_id,  
COUNT(ST DISTINCT rides_type) AS rides_type_count,  
COUNT(*) AS total_rides,  
ROUND(AVG(fare), 2) AS Avg_fare  
FROM rides  
GROUP BY station_id  
HAVING COUNT(DISTINCT rides_type) = 3  
ORDER BY station_id ASC;
```

Q7

⇒ ~~SELECT~~

SELECT

```
station_id, station_name, zone, ride_id, rides_type,  
fare FROM station LEFT JOIN rides ON station  
id = station_id AND MONTH(ride_date) = 6  
AND YEAR(ride_date) = 2024  
ORDER BY station_id, ride_id;
```


Q9

Types of SQL languages are :-

① DDL (Data Definition Language)

- It is used to create and modify database objects.

Commands: • CREATE, ALTER, DROP, TRUNCATE
RENAME.

② DML (Data Manipulation Language)

- It is used to insert, update & delete records.

Commands:

• INSERT, UPDATE, DELETE

③ DQL (Data Query Language)

- It is used to retrieve data.

Command:

• SELECT.

④ DCL (Data Control Language)

- used to control user permissions.

Commands:

• GRANT

• REVOKE

⑤ TCl (Transactiion Control Language)

Commands:-

COMMIT, ROLL BACK, SAVEPOINT

Q10

JOIN is used to combine rows from two or more tables based on related columns.

Types of JOIN

- 1.) INNER JOIN :- Returns only matching records from both tables.
- 2.) LEFT JOIN :- Returns all records from the left table and matching records from the right table.
- 3.) RIGHT JOIN :- Returns all records from ~~both~~ the right table and matching records from left table.
- 4.) CROSS JOIN :- Returns every possible combinations rows from both tables.
- 5.) FULL OUTER JOIN :- show all records from both tables.