

Machine Safety Guide

Approved worker rules and site regulations from the SentinelLoop knowledge base. These instructions support factory safety practice. They do not replace trained emergency responders or a competent person's isolation and repair work.

Immediate worker actions

1. Never bypass, remove, or reach around a machine guard while equipment is running.
2. Keep emergency-stop controls clear and easy to reach.
3. Stop the machine before clearing a jam, adjusting a part, or retrieving material.
4. Stay clear of rotating, cutting, or pinch-point equipment.
5. Warn nearby workers if a guard is missing or a machine is behaving abnormally.
6. Report the machine hazard immediately through the site safety process.
7. Do not restart equipment until trained personnel confirm it is safe.

Site regulations

1. Machine guarding must remain in place during operation; missing guards are a stop-work condition.
2. Only trained and authorized operators may start, set, or service production machinery.
3. Isolation and lock-out are required before maintenance, cleaning inside the machine, or tool changes.
4. Emergency stops, interlocks, and light curtains must not be bypassed or taped over.
5. Abnormal noise, vibration, smoke, or unexpected movement requires an immediate stop and report.
6. Floor markings and exclusion zones around CNC, presses, and conveyors must be respected.
7. Loose clothing, jewellery, and unsecured hair are not permitted near rotating equipment.
8. Compressed air must not be used to clean clothing or to blow chips toward people.
9. Contractors working on machinery must follow the same isolation rules as site staff.
10. After any incident or near miss, the machine stays locked out until released by a supervisor.

Worker duties

1. Inspect guards, e-stops, and workholding before starting a cycle.
2. Keep hands, tools, and rags away from the point of operation.
3. Use push sticks, holders, or approved fixtures instead of reaching into the machine.
4. Tell the next shift if a machine was stopped for a safety reason.
5. Stand clear of automatic start-up and robotic motion paths.

Prohibited actions

1. Do not reach into a machine to grab a part while it can still move.

2. Do not operate machinery you have not been trained and signed off to use.
3. Do not silence interlocks, jumper safety circuits, or remove covers for convenience.
4. Do not restart after a jam until the cause is controlled and the guard is refitted.

Always follow instructions from trained safety or emergency personnel.