Radiative processes in astrophysics notes

Jacopo Tissino, Giorgio Mentasti

2020-03-15

Contents

1		Fundamentals of radiative transfer			
	1.1	Basic	properties of the EM spectrum	2	
		1.1.1	The radiative flux	2	
	1.2	Radia	tive energy density	3	
		1.2.1	Isotropic radiation field	4	
		1.2.2	Specific intensity along a ray	5	
	1.3		tive transfer		
		1.3.1	Emission	6	
		1.3.2	Absorption	7	
			The radiative transfer equation		

Introduction

The professor, Roberto Turolla, will follow the pdf of the book by Rybicki and Lightman [RL79] on his screen. It is available for free.

Radiative processes are fundamental for several processes: for example, in the Crab nebula the main process is Synchrotron radiation, in the Coma cluster we have Bremsstrahlung, in Cygnus-X1 we have Compton scattering.

Even in the era of multimessenger astrophysics, most of the information still comes from electromagnetic radiation. The required background is classical EM, special relativity and the basics of atomic structure.

The exam is an oral one. The lectures will be recorded and put on the Moodle until the emergency ends, every Wednesday and Thursday. The duration of recorded lectures is actually shorter than the duration of the lectures we would have in the classroom.

Chapter 1

Fundamentals of radiative transfer

1.1 Basic properties of the EM spectrum

Electromagnetic radiation can be decomposed into a spectrum; the frequency ν and wavelength λ are connected by $c = \lambda \nu$, where c is the speed of light.

Sometimes we give the energy of the photons, which can be found using Planck's constant h: E = hv.

Thursday 2020-3-12, compiled 2020-03-15

We conventionally divide the spectrum into bands: γ -rays, X-rays, ultraviolet light, visible light, infrared radiation, radio band.

1.1.1 The radiative flux

Let us consider an area element dA, through which radiation passes for a time dt: the energy will be proportional to both dA and dt, so we say that it is equal to F dA dt. Of course we need to account for orientation: if the surface is not perpendicular to the source the energy is less.

Let us consider a pointlike source, and draw two spherical surfaces of radii r_1 and r_2 along which we compute the flux: if there is no energy loss we must have

$$F(r_1)A_1 dt = F(r_2)A_2 dt (1.1)$$

$$F(r_1)4\pi r_1^2 = F(r_2)4\pi r_2^2 \tag{1.2}$$

$$F(r_1) = F(r_2) \frac{r_2^2}{r_1^2}.$$
 (1.3)

The flux of energy is a measure of all the energy which passes through the surface; however we can get a more detailed description. We cannot consider photons at a specific frequency: the set has measure 0. We look at a "pencil" of radiation: all the radiation coming from a solid angle $d\Omega$ over an area dA and carried by photons of frequencies between ν and $\nu + d\nu$.

So, we define the *specific intensity of brightness* I_{ν} by

$$dE \stackrel{\text{def}}{=} I_{\nu} dA dt d\Omega d\nu . \tag{1.4}$$

This will depend on position (where we put the detector area) and on direction (where we look).

We usually neglect the time-dependence. The units of this quantity are those of energy per unit time, area, frequency, solid angle.

How do we account for the direction? The differential flux for radiation coming with an angle θ to the normal is

$$dF_{\nu} = I_{\nu} \cos(\theta) d\Omega , \qquad (1.5)$$

so the total net flux is

$$F_{\nu} = \int I_{\nu} \cos(\theta) \, d\Omega \ . \tag{1.6}$$

This is about energy, but we can define the momentum flux per unit time per unit area (which is the pressure) we can do the same, but we get an additional factor of $\cos \theta$ since \vec{p} is a vector, and we are interested in its component along the normal of the surface. So, the global formula for this pressure is

$$P_{\nu} = \frac{1}{c} \int I_{\nu} \cos^2 \theta \, d\Omega . \qquad (1.7)$$

These are moments: in general, a moment is something in the form

$$n$$
-th moment = $\int I_{\nu} \cos^{n} \theta \, d\Omega$. (1.8)

These are frequency dependent; the corresponding *grey* (that is, frequency-integrated) quantities are in the form

$$F = \int F_{\nu} \, \mathrm{d}\nu \ . \tag{1.9}$$

Saturday 2020-3-14, compiled 2020-03-15

1.2 Radiative energy density

We define the energy density per unit solid angle, $u_{\nu}(\Omega)$ by: $dE = u_{\nu}(\Omega) dV d\Omega d\nu$. This is the differential amount of energy in the volume dV, carried by radiation coming from the solid angle $d\Omega$ which has energies between ν and $\nu + d\nu$.

We consider a cylinder for our volume, its axis being aligned with the direction the radiation is coming from. Its volume can be expressed as dV = dA c dt, where dt is the time taken by light to cross the height of the cylinder.

We can also express the differential energy using the definition of the specific intensity: then, we will have the following two equations:

$$dE = u_{\nu}(\Omega)c \, dA \, dt \, d\Omega \, d\nu \tag{1.10}$$

$$= I_{\nu} \, \mathrm{d}A \, \mathrm{d}t \, \mathrm{d}\Omega \, \mathrm{d}\nu \, , \tag{1.11}$$

therefore $u_{\nu} = I_{\nu}/c$. Also, if we want to get the total energy density we just need to integrate over the volume of the whole sphere:

$$u_{\nu} = \frac{1}{c} \int I_{\nu}(\Omega) d\Omega \stackrel{\text{def}}{=} \frac{4\pi}{c} J_{\nu}, \qquad (1.12)$$

where J_{ν} is the mean intensity: $J_{\nu} = \langle I_{\nu} \rangle_{\Omega}$.

We can also integrate over frequencies to get the total energy density:

$$u = \int u_{\nu} \, \mathrm{d}\nu = \frac{4\pi}{c} \int J_{\nu} \, \mathrm{d}\nu \ . \tag{1.13}$$

1.2.1 Isotropic radiation field

An isotropic radiation field is one for which the specific intensity does not depend on angles. Let us start from the definitions of u_{ν} and P_{ν} :

$$u_{\nu} = \int \frac{I_{\nu}}{c} \, \mathrm{d}\Omega = \frac{4\pi J_{\nu}}{c} \tag{1.14}$$

$$P_{\nu} = \int \frac{I_{\nu}}{c} \cos^2 \theta \, d\Omega = \int \frac{I_{\nu}}{c} \cos^2 \theta \sin \theta \, d\theta \, d\varphi \,, \qquad (1.15)$$

and let us use the assumption that I_{ν} does not depend on Ω : so we can bring it out of the integrals, to find

$$u_{\nu} = 4\pi \frac{I_{\nu}}{c} \tag{1.16}$$

$$P_{\nu} = -2\pi \frac{I_{\nu}}{c} \int \cos^2 \theta \, \mathrm{d} \cos \theta = 2\pi \frac{I_{\nu}}{c} \int_{-1}^{1} x^2 \, \mathrm{d} x$$
 (1.17) The differential is negative, but we swap the integration bounds. (1.18)

which gives us the result we sought:

$$P_{\nu} = \frac{u_{\nu}}{3} \,. \tag{1.19}$$

1.2.2 Specific intensity along a ray

We wish to see how the specific intensity I_{ν} changes along a beam of light rays. Let us consider two positions 1, 2 along the beam, separated by a distance R. Then, by definition we will have, for i = 1, 2:

$$dE_i = I_{\nu,i} dA_i dt_i d\Omega_i d\nu_i . (1.20)$$

First of all we make the assumption of the gravitational field being weak: therefore $dt_1 = dt_2$ and $dv_1 = dv_2$. Now, we ask these two expressions to describe the same beam: the same photons will pass through dA_1 and dA_2 . Therefore, by conservation of energy, $dE_1 = dE_2$.

This means that

$$I_{\nu,1} dA_1 d\Omega_1 = I_{\nu,2} dA_2 d\Omega_2 . {(1.21)}$$

We can treat the photons' motion as time-reversal symmetric: so, whether they pass through dA_1 or dA_2 first is irrelevant. So, since the linear scale of the differential are element is negligible compared to R we can consider all the photons which come through dA_2 to be coming from the apparent size of dA_1 from position 2. Therefore, the differential solid angle will look like

$$d\Omega_2 = \frac{dA_1}{R^2}, \tag{1.22}$$

and we can apply the same reasoning reversing the photons' motion to find the same, alternate relation with $(1 \leftrightarrow 2)$. We can use this to write

$$I_{\nu,1}\frac{\mathrm{d}A_1}{\mathrm{d}\Omega_2} = I_{\nu,2}\frac{\mathrm{d}A_2}{\mathrm{d}\Omega_1} \tag{1.23}$$

$$I_{\nu,1}R^2 = I_{\nu,2}R^2 \tag{1.24}$$

$$I_{\nu,1} = I_{\nu,2} \,. \tag{1.25}$$

This means that, under our assumptions, the specific intensity is conserved:

$$\frac{\mathrm{d}I_{\nu}}{\mathrm{d}s} = 0\,,\tag{1.26}$$

where *s* is a parameter describing the light ray's trajectory. This is useful since, if the variation of the specific intensity is zero in a vacuum, then its variation in the presence of matter will only be due to transfer phenomena, and the sign of the variation will describe whether energy is being added or removed.

1.3 Radiative transfer

In general, as radiation passes through matter, its specific intensity changes. This is due to emission and absorption, but also to scattering, which preserves the total number of photons: even in the low-energy limit it can change the angular distribution of the radiation, and in general it also changes the energy of the photon.

1.3.1 Emission

Emission is a process through which photons are created. We can define the grey emission coefficient j and the monochromatic emission coefficient j_{ν} as:

$$dE = j dV d\Omega dt (1.27)$$

$$dE = j_{\nu} dV d\Omega dt d\nu , \qquad (1.28)$$

they quantify the energy added to the radiation field per unit volume, solid angle (in order to account for the direction of emission) and unit time. For the monochromatic coefficient, we restrict ourselves to radiation emitted in the range from ν to $\nu + d\nu$.

In the case of an isotropic emission we can integrate over the solid angle to find

$$P_{\nu} = 4\pi j_{\nu} \,, \tag{1.29}$$

the radiated power per unit volume and frequency.

Another useful concept is the emissivity ϵ_{ν} : it is the energy added to the radiation field per unit time, frequency and mass in the direction described by $d\Omega$. We express the infinitesimal mass as dm, so that

$$dE = \epsilon_{\nu} \rho \, dV \, dt \, d\nu \, \frac{d\Omega}{4\pi} \,, \tag{1.30}$$

so that the emissivity and the emission coefficient are connected by

$$j_{\nu} = \frac{\epsilon_{\nu} \rho}{4\pi} \,. \tag{1.31}$$

We wish to describe the variation in specific intensity due to this emission. We consider a beam of cross section dA going through a length ds, so that the volume it occupies is dV = dA ds.

Now, if we compare the definitions of j_{ν} and I_{ν} we find that they differ by a factor dV / dA = ds, the length of the beam cylinder we defined.

The difference between the specific intensities at the start and end of the cylinder would be zero without emission, now instead their difference can be calculated from the energy added; as we said most of the differentials simplify and we get that the variation of specific intensity is

$$dI_{\nu} = j_{\nu} ds . \qquad (1.32)$$

1.3.2 Absorption

Absorption is described by a coefficient $\alpha_{\nu} > 0$, which is dimensionally an inverse length. The absorption law which defined the coefficient gives the decrease in radiative intensity for radiation of intensity I_{ν} crossing an absorbing medium of length ds:

$$dI_{\nu} = -\alpha_{\nu}I_{\nu} ds . \qquad (1.33)$$

Why should the variation in intensity be proportional to the intensity itself? We give a simple argument: let us assume that absorption is due to randomly absorbers with number density n and (frequency dependent) cross section σ_{ν} .

Let us consider our usual cylinder with cross sectional area dA and length ds: the number of absorber in it will be d $N = n \, dA \, ds$. The total effective cross section area presented for absorption will be $\sigma_{\nu} \, dN$. The energy contained in photons in this cross sectional area will be lost: the energy lost $- \, dI_{\nu}$ can be calculated as

$$- dI_{\nu} dA dt d\Omega d\nu = I_{\nu}(\sigma_{\nu} n dA ds) dt d\Omega d\nu$$
 (1.34)

$$-dI_{\nu} = -n\sigma_{\nu}I_{\nu} ds , \qquad (1.35)$$

which is the relation written above, with $n\sigma_{\nu} = \alpha_{\nu}$. The number density is proportional to the mass density: $n\overline{m} = \rho$ where \overline{m} is the average mass of a particle. Therefore, we can express α_{ν} as

$$\alpha_{\nu} = \rho \kappa_{\nu} = n \overline{m} \frac{\sigma_{\nu}}{\overline{m}}, \qquad (1.36)$$

so we can see that κ_{ν} is a cross sectional area per unit mass. It is called the *mass absorption coefficient* or the *opacity*.

Conditions for validity This holds as long as the inter-absorber distances $d \sim n^{-1/3}$ are large compared to the linear scale of the cross section $\sigma_{\nu}^{1/2}$: we ask

$$\sigma_{\nu}^{1/2} \ll n^{-1/3}$$
, (1.37)

and also we must assume that the absorbers are independent and randomly distributed (at least locally). These assumptions are usually met in astrophysical systems.

1.3.3 The radiative transfer equation

We can account for both absorption and emission in a combined equation for the derivative with respect to the beam length travelled s of the specific intensity I_{ν} :

$$\frac{\mathrm{d}I_{\nu}}{\mathrm{d}s} = -\alpha_{\nu}I_{\nu} + j_{\nu}\,,\tag{1.38}$$

and we can see that in the absence of emission and absorption it is unchanged as we have shown before. If j_{ν} and α_{ν} are known we can integrate this differential equation to find the specific intensity.

This will *not* be the case when we will include scattering: the scattering term will not just depend on I_{ν} but in its integral, making this an integro-differential equation.

Bibliography

[RL79] G. B. Rybicki and A. P. Lightman. *Radiative Processes in Astrophysics*. John Wiley and Sons, 1979. ISBN: 978-0-471-82759-7. URL: http://www.bartol.udel.edu/~owocki/phys633/RadProc-RybLightman.pdf.