



Hyperspectral Imaging for Ink Mismatch Detection

Zohaib Khan, Faisal Shafait and Ajmal Mian
School of Computer Science and Software Engineering
The University of Western Australia


Overview

Ink mismatch detection provides important clues to forensic document examiners [1]

- identifying whether a particular handwritten note is written with a specific ink
- showing that some part (e.g. signature) is written with a different ink as compared to the rest of the note [2].

Hyperspectral images capture fine spectral detail


- non-destructive and efficient capture
- automated, accurate identification



Ink Mismatch Detection

Inks are distinguishable in visible and near infrared range

- CCD camera with tunable filter captures hyperspectral images
- spectral responses vary in different portions of the EM spectrum
- non-uniform illumination modulates true spectral reflectances



Ink Segmentation and Clustering Algorithm

- segment ink pixels using Sauvola's algorithm [3]
- normalize spectral responses to unit magnitude
- k-means clustering of ink spectral responses ($k=2$)

$$\arg \min_{\mathcal{C}} \sum_{i=1}^k \sum_{\hat{x}_j \in \mathcal{C}_i} \|\hat{x}_j - \mu_i\|^2$$

- forward feature (band) selection. leave-1-ink-out cross validation

Database

- Handwritten note: 'A quick brown fox jumps over the lazy dog'
- 5 blue and 5 black inks by 7 subjects
- 33 band hyperspectral image in 400-720nm range (10nm steps)
- 3 channel RGB scan for comparison

UWA Writing Ink Hyperspectral Image Database:
<http://www.csse.uwa.edu.au/~ajmal/databases.html>

This research was supported by ARC Grant DP110102399

Experiments


Evaluation Setup

- mix 2 different ink images in equal proportions
- 5 inks, taken 2 at a time, results in 10 different mixed ink images

$$\text{Accuracy} = \frac{\text{True Positives}}{\text{True Positives} + \text{False Positives} + \text{False Negatives}}$$

Segmentation Results

- RGB versus HSI segmentation comparison
- Sub-visual range comparative analysis
- Segmentation with and without feature selection



Example: Discriminating Black Inks

- mix black ink 4 and black ink 5

Original Image	
Ground Truth	
Result (RGB)	
Result (HSI-All)	
Result (HSI-FS)	

Conclusion

Hyperspectral imaging is of critical value in supporting ink examination.

- 1st database collected and made publicly available
- overcome hardware limitations in future

References

- [1] G. Edelman, E. Gaston, T. van Leeuwen, P. Cullen, and M. Alders, "Hyperspectral imaging for non-contact analysis of forensic traces," *Forensic Science International*, vol. 223, pp. 28–39, 2012
- [2] E. B. Brauns and R. B. Dyer, "Fourier transform hyperspectral visible imaging and the nondestructive analysis of potentially fraudulent documents," *Applied spectroscopy*, vol. 60, no. 8, pp. 833–840, 2006.
- [3] F. Shafait, D. Keysers, and T. M. Breuel, "Efficient implementation of local adaptive thresholding techniques using integral images," *Document Recog. and Retrieval XV*, pp. 681510–681510–6, 2008