

GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Tuesday, 8 October 2024, 9:24 AM
Duration	76 days 8 hours

Question 1

Correct

Marked out of 3.00

☐ Flag question

Objective

This is a simple challenge to help you practice printing to stdout.

We're starting out by printing the most famous computing phrase of all time! In the editor below, use either printf or cout to print the string **Hello, World!** to stdout.

Input Format

You do not need to read any input in this challenge.

Output Format

Print **Hello, World!** to stdout.

Sample Output

Hello, World!

Answer: (penalty regime: 0 %)

	Expected	Got	
	Hello, World!	Hello, World!	

Passed all tests!

Question 2

Correct

Objective

REC-CIS

☐ Flag
question

To take a single character **ch** as input, you can use `scanf("%c", &ch);` and `printf("%c", ch)` writes a character specified by the argument `ch` to `stdout`:

```
char ch;  
scanf("%c", &ch);  
printf("%c", ch);
```

This piece of code prints the character **ch**.

Task

You have to print the character, **ch**.

Input Format

Take a character, **ch** as input.

Output Format

Print the character, **ch**.

Answer: (penalty regime: 0 %)

	Input	Expected	Got	
	C	C	C	

Passed all tests!

Question **3**
Correct
Marked out of
7.00
☐ Flag
question

Objective

The fundamental data types in C are `int`, `float` and `char`. Today, we're discussing `int` and `float` data types.

The `printf()` function prints the given statement to the console. The syntax is `printf("format string", argument_list);`. In the function, if we are using an integer, character, string or float as arguments, the format string we have to write `%d` (integer), `%c` (character), `%s` (string), `%f` (float) respectively.

in variable *number*.

To input two integers separated by a space on a single line, the command is `scanf("%d %d", &n, &m)` where *n* and *m* are the two integers.

Task

Your task is to take two numbers of `int data type`, two numbers of float data type as input and output

1. Declare **4** variables: two of type int and two of type float.
2. Read **2** lines of input from stdin (according to the sequence given in the 'Input Format' section) initialize your **4** variables.
3. Use the **+** and **-** operator to perform the following operations:
 - o Print the sum and difference of two int variable on a new line.
 - o Print the sum and difference of two float variable rounded to one decimal place on a new line.

Input Format

The first line contains two integers.

The second line contains two floating point numbers.

Constraints

- $1 \leq \text{integer variables} \leq 10^4$
- $1 \leq \text{float variables} \leq 10^4$

Output Format

Print the sum and difference of both integers separated by a space on the first line, and the sum and of both float (scaled to **1** decimal place) separated by a space on the second line.

Sample Input

```
10 4
4.0 2.0
```

Sample Output

```
14 6
6.0 2.0
```

Explanation

When we sum the integers **10** and **4**, we get the integer **14**. When we subtract the second number **4** from the first number **10**, we get **6** as their difference.

When we sum the floating-point numbers **4.0** and **2.0**, we get **6.0**. When we subtract the second number **2.0** from the first number **4.0**, we get **2.0** as their difference.

Answer: (penalty regime: 0 %)

REC-CIS

	Input	Expected	Got	
	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	
	20 8 8.0 4.0	28 12 12.0 4.0	28 12 12.0 4.0	

Passed all tests!

Save the state of the flags