

Firewall Scan Report				
Generated: 2026-06-02T03:04:13.527856Z · 4094 records				
class	vulnerability_description	attack_vector	mitigation	references
Information disclosure — non-443 exposure	TCP/1 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/2 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/3 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/4 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/5 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/6 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/7 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/8 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/9 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/10 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/11 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/12 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/13 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/14 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/15 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/16 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/17 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/18 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/19 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/20 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — credentials & data exfiltration	File Transfer Protocol transmits usernames	Passive sniffing of the network captures	Disable or replace with SFTP (port 22 in	CWE-319; CVE-2019-11461
Information disclosure — interactive shell	Secure Shell allows interactive remote access	Username enumeration, credential spraying	Restrict to bastion hosts behind a VPN;	CWE-307; CIS-4.1.1
Information disclosure — remote shell	Telnet provides interactive shell access	Network sniffing, MITM, banner-grabbing	Decommission entirely; replace with SSH;	CWE-319; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/24 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — relay	Simple Mail Transfer Protocol open to the internet	Open-relay abuse, sender-spoofing, VRFY/EXPN	Require authentication and TLS; block 25	CWE-693; RFC-5321
Information disclosure — non-443 exposure	TCP/26 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/27 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/28 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/29 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/30 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/31 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/32 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/33 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/34 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461
Information disclosure — non-443 exposure	TCP/35 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	CWE-1188; CVE-2019-11461

[illegible]

[illegible]

[illegible]

[illegible]

Security Vulnerability Catalog: Network Services				
class	vulnerability_description	attack_vector	mitigation	references
Port — non-443 exposure	TCP/493 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/494 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/495 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/496 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/497 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/498 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/499 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/500 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/501 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/502 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/503 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/504 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/505 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/506 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/507 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/508 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/509 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/510 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/511 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Key remote shell	rexec authenticates with cleartext crede	Credential capture; legacy buffer-overfl	Remove rexec/rlogin/rsh; replace with SS	CVE-1999-065
Basic remote login	.rhosts trust files allow passwordless l	IP spoofing into the trust list; clearte	Decommission; replace with SSH key auth.	CVE-1999-065
Logging & legacy shell	UDP/TCP 514 carries unauthenticated sysl	Log spoofing/forgery; cleartext credenti	Use TLS-protected syslog (RFC 5425) or H	RFC 5425; CW
Port — non-443 exposure	TCP/515 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/516 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/517 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/518 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/519 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/520 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/521 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/522 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/523 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/524 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/525 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/526 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/527 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/528 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/529 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI
Port — non-443 exposure	TCP/530 (well-known system port) is react	Adversaries fingerprint the listening se	Close the port at the host firewall and	CWE-1188; CI

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]