

Firewall Scan Report				
Generated: 2026-05-26T13:47:16.470876Z · 4095 records				
severity_class	vulnerability_description	attack_vector	mitigation	references
Information disclosure — non-443 exposure	TCP/1 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/2 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/3 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/4 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/5 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/6 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/7 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/8 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/9 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/10 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/11 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/12 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/13 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/14 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/15 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/16 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/17 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/18 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/19 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/20 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Credential theft & data exfiltration	File Transfer Protocol transmits usernames	Passive sniffing of the network captures	Disable or replace with SFTP (port 22 in	[CWE-319],
Interactive shell	Secure Shell allows interactive remote access	Username enumeration, credential spraying	Restrict to bastion hosts behind a VPN;	[CWE-307],
Interactive shell	Telnet provides interactive shell access	Network sniffing, MITM, banner-grabbing	Decommission entirely; replace with SSH;	[CWE-319],
Information disclosure — non-443 exposure	TCP/24 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Abuse	Simple Mail Transfer Protocol open to the	Open-relay abuse, sender-spoofing, VRFY/	Require authentication and TLS; block 25	[CWE-693],
Information disclosure — non-443 exposure	TCP/26 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/27 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/28 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/29 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/30 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/31 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/32 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/33 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/34 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]
Information disclosure — non-443 exposure	TCP/35 (well-known system port) is reachable	Adversaries fingerprint the listening service	Close the port at the host firewall and	[CWE-1188]

[illegible]

cy_class	vulnerability_description	attack_vector	mitigation	references
ion — non-443 exposure	TCP/112 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/113 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/114 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/115 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/116 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/117 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/118 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/119 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/120 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/121 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/122 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/123 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/124 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/125 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/126 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/127 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/128 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/129 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/130 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/131 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/132 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/133 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/134 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
PC endpoint mapper	Microsoft RPC exposed externally enables	Enumeration of named pipes; chained expl	Block 135/137-139/445 at the perimeter;	[CVE-2017-0
ion — non-443 exposure	TCP/136 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/138 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
s session	Pre-SMB2 session service typically assoc	Null-session enumeration, downgrade to S	Disable SMBv1; block 139/445 externally;	[CVE-2017-0
ion — non-443 exposure	TCP/140 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/141 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/142 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ail retrieval	IMAP without TLS exposes credentials and	Credential capture, mailbox content thef	Use IMAPS (993) only; enforce TLS 1.2+;	[CWE-319]
ion — non-443 exposure	TCP/144 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/145 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/146 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/147 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/148 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/149 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]
ion — non-443 exposure	TCP/150 (well-known system port) is reac	Adversaries fingerprint the listening se	Close the port at the host firewall and	[CWE-1188]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]