Ex. No: 3

CREATE SEQUENCE student_seq START WITH 1 INCREMENT BY 1;

Output:

Sequence created.

CREATE TABLE students (student_id INT PRIMARY KEY, student_name VARCHAR(100), student_email VARCHAR(100));

Output:

Table created.

INSERT INTO students (student_id, student_name, student_email) VALUES (student_seq.NEXTVAL, 'Alice Johnson', 'alice@example.com');
INSERT INTO students (student_id, student_name, student_email) VALUES (student_seq.NEXTVAL, 'Bob Smith', 'bob@example.com');
INSERT INTO students (student_id, student_name, student_email) VALUES (student_seq.NEXTVAL, 'Charlie Brown', 'charlie@example.com');

Output:

3 rows created.

CREATE VIEW student_view AS SELECT student_id, student_name, student_email FROM students;

Output:

View created.

INSERT INTO students (student_id, student_name, student_email) VALUES (student_seq.NEXTVAL, 'Diana Prince', 'diana@example.com');

Output:

1 row created.

UPDATE students SET student_email = 'new_bob@example.com' WHERE student_name = 'Bob Smith';

Output:

1 row updated.

DELETE FROM students WHERE student_name = 'Charlie Brown';

Output:

1 row deleted.

CREATE INDEX idx_student_email ON students (student_email);

Output:

Index created.

SELECT * FROM student_view;

Output:

student_id	student_name	student_email
1	Alice Johnson	alice@example.com
2	Bob Smith	new_bob@example.com
4	Diana Prince	diana@example.com