Ex. No: 5

Procedure:

```
SET SERVEROUTPUT ON;
CREATE OR REPLACE PROCEDURE Sum_Proc(a IN number, b IN number) IS
 c number;
BEGIN
 c := a + b;
   dbms_output.put_line('Sum of two nos = ' || c);
END Sum_Proc;
/
```

Output:

Procedure created.

```
DECLARE
 x number;
 y number;
BEGIN
 x := &x;
 y := &y;
 Sum_Proc(x, y);
END;
/
```

Output:

Enter value for x: 10
Enter value for y: 20
Sum of two nos = 30
PL/SQL procedure successfully completed.

Function:

```
SET SERVEROUTPUT ON;
CREATE OR REPLACE FUNCTION Sum_Func(a IN number, b IN number)
RETURN number IS
 c number;
BEGIN
 c := a + b;
   RETURN c;
END Sum_Func;
```

Output:

Function created.

```
DECLARE
 no1 number;
 no2 number;
 result number;
BEGIN
 no1 := &no1;
 no2 := &no2;
 result := Sum_Func(no1, no2);
   dbms_output.put_line('Sum of two nos = ' || result);
END;
/
```

Output:

Enter value for no1: 5
Enter value for no2: 5
Sum of two nos = 10
PL/SQL procedure successfully completed.