

Question **1**

Correct

Marked out of
1.00 [Flag question](#)

You are a bank account hacker. Initially you have 1 rupee in your account, and you want exactly **N** rupees in your account. You wrote two hacks, first hack can multiply the amount of money you own by 10, while the second can multiply it by 20. These hacks can be used any number of time. Can you achieve the desired amount **N** using these hacks.

Constraints:

$$1 \leq T \leq 100$$

$$1 \leq N \leq 10^{12}$$

Input

- The test case contains a single integer N.

Output

For each test case, print a single line containing the string "1" if you can make exactly N rupees or "0" otherwise.

SAMPLE INPUT

1

SAMPLE OUTPUT

1

SAMPLE INPUT

2

SAMPLE OUTPUT

0

Answer: (penalty regime: 0 %)

Reset answer

```
1  /*
2   * Complete the 'myFunc' function below.
3   *
4   * The function is expected to return an
5   * The function accepts INTEGER n as para
6   */
7
8  int myFunc(int n)
9  {
10     while (n>1) {
11         if(n%20==0){
12             n/=20;
13         }else if(n%10==0){
14             n/=10;
15         }else{
16             return 0;
17         }
18     }
19     return n==1?1:0;
20 }
21
22 void start(){
23     int T,N;
24     scanf("%d",&T);
25     while(T--){
26         scanf("%d", &N);
27         printf("%d",myFunc(N));
28     }
29 }
30
```

| | Test | Expected | Got | |
|---|---------------------------|----------|-----|---|
| ✓ | printf("%d", myFunc(1)) | 1 | 1 | ✓ |
| ✓ | printf("%d", myFunc(2)) | 0 | 0 | ✓ |
| ✓ | printf("%d", myFunc(10)) | 1 | 1 | ✓ |
| ✓ | printf("%d", myFunc(25)) | 0 | 0 | ✓ |
| ✓ | printf("%d", myFunc(200)) | 1 | 1 | ✓ |

Passed all tests! ✓

Question 2
Correct
Marked out of 100
Flag question

Find the number of ways that a given integer, **X**, can be expressed as the sum of the **Nth** powers of unique, natural numbers.

Question **2**

Correct

Marked out of
1.00

Flag question

Find the number of ways that a given integer, ***X***, can be expressed as the sum of the ***Nth*** powers of unique, natural numbers.

For example, if ***X* = 13** and ***N* = 2**, we have to find all combinations of unique squares adding up to **13**. The only solution is $2^2 + 3^2$.

Function Description

Complete the powerSum function in the editor below. It should return an integer that represents the number of possible combinations.

powerSum has the following parameter(s):

X: the integer to sum to

N: the integer power to raise numbers to

Input Format

The first line contains an integer ***X***.

The second line contains an integer ***N***.

Constraints

$$1 \leq X \leq 1000$$

$$2 \leq N \leq 10$$

Output Format

Output a single integer, the number of possible combinations calculated.

Sample Input 0

10

2

Sample Output 0

Sample Output 0

1

Explanation 0

If $X = 10$ and $N = 2$, we need to find the number of ways that 10 can be represented as the sum of squares of unique numbers.

$$10 = 1^2 + 3^2$$

This is the only way in which 10 can be expressed as the sum of unique squares.

Sample Input 1

100

2

Sample Output 1

3

Explanation 1

$$100 = (10^2) = (6^2 + 8^2) = (1^2 + 3^2 + 4^2 + 5^2 + 7^2)$$

Sample Input 2

100

3

Sample Output 2

1

Explanation 2

100 can be expressed as the sum of the cubes of **1, 2, 3, 4**.

(1 + 8 + 27 + 64 = 100). There is no other way to express **100** as the sum of cubes.

Answer: (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'powerSum' function below
3  *
4  * The function is expected to return an
5  * The function accepts following paramet
6  * 1. INTEGER x
7  * 2. INTEGER n
8  */
9
10 int powerSum(int x, int m, int n)
11 {
12     if(x==0)
13     {
14         return 1;
15     }
16     if(x<0)
17     {
18         return 0;
19     }
20     int count =0;
21     for(int i=m;;i++)
22     {
23         int power=1;
24         for(int j=0;j<n;j++)
25         {
26             power*=i;
27         }
28         if(power>x)
29         {
30             break;
31         }
32         count+=powerSum(x-power,i+1,n);
33     }
34     return count;
35 }
36
```


| est | Expected | Got | |
|----------------------------------|----------|-----|---|
| printf("%d", powerSum(10, 1, 2)) | 1 | 1 | ✓ |

Passed all tests! ✓

Finish review

**Completed** Monday, 13 January 2025, 8:40 PM**Duration** 10 mins 38 secsQuestion **1**

Correct

 [Flag question](#)

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

`arr=[1,2,3,4,6]`

- the sum of the first three elements, $1+2+3=6$. The value of the last element is 6.
- Using zero based indexing, `arr[3]=4` is the pivot between the two subarrays.
- The index of the pivot is 3.

Function Description

Complete the function `balancedSum` in the editor below.

`balancedSum` has the following parameter(s):

`int arr[n]`: an array of integers

Returns:

`int`: an integer representing the index of the pivot

Constraints

- $3 \leq n \leq 10^5$
- $1 \leq arr[i] \leq 2 \times 10^4$, where $0 \leq i < n$
- It is guaranteed that a solution always exists.

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer `n`, the size of the array `arr`.

Each of the next `n` lines contains an integer `arr[i]`, where $0 \leq i$

The first line contains an integer n , the size of the array `arr`.

Each of the next n lines contains an integer, `arr[i]`, where $0 \leq i < n$.

Sample Case 0

Sample Input 0

STDIN Function Parameters

4 \rightarrow `arr[]` size $n = 4$

1 \rightarrow `arr = [1, 2, 3, 3]`

2

3

3

Sample Output 0

2

Explanation 0

- The sum of the first two elements, $1+2=3$. The value of the last element is 3.
- Using zero based indexing, `arr[2]=3` is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1

Sample Input 1

STDIN Function Parameters

3 \rightarrow `arr[]` size $n = 3$

1 \rightarrow `arr = [1, 2, 1]`


2

1

Sample Output 1

1

Explanation 1



Explanation 1

- The first and last elements are equal to 1.
- Using zero based indexing, arr[1]=2 is the pivot between the two subarrays.
- The index of the pivot is 1.

Answer: (penalty regime: 0 %)

Reset answer

```

1  /*
2   * Complete the 'balancedSum' function be
3   *
4   * The function is expected to return an
5   * The function accepts INTEGER_ARRAY arr
6   */
7
8  int balancedSum(int arr_count, int* arr)
9  {
10     int totalsum=0;
11     for(int i=0;i<arr_count;i++){
12         totalsum+=arr[i];
13     }
14     int leftsum=0;
15     for(int i=0;i<arr_count;i++){
16         int rightsum=totalsum-leftsum-arr
17         if(leftsum==rightsum){
18             return i;
19         }
20         leftsum+=arr[i];
21     }
22     return 1;
23 }
24

```

| | Test | Expected |
|---|---|----------|
| ✓ | int arr[] = {1,2,3,3}; printf("%d", balancedSum(4, arr)) | 2 |

Passed all tests! ✓

Question **2**

Correct

Flag question

Calculate the sum of an array of integers.

Example

Passed all tests!

Question **2**

Correct

[Flag question](#)

Calculate the sum of an array of integers.

Example

numbers = [3, 13, 4, 11, 9]

The sum is $3 + 13 + 4 + 11 + 9 = 40$.

Function Description

Complete the function arraySum in the editor below.

arraySum has the following parameter(s):

int numbers[n]: an array of integers

Returns

int: integer sum of the numbers array

Constraints

 $1 \leq n \leq 10^4$ $1 \leq \text{numbers}[i] \leq 10^4$

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n , the size of the array numbers.

Each of the next n lines contains an integer $\text{numbers}[i]$ where $0 \leq i < n$.

Sample Case 0

Sample Input 0

STDIN Function

5 \rightarrow numbers[] size $n = 5$

| STDIN | Function |
|-------|----------|
|-------|----------|

| | |
|-------|-------|
| ----- | ----- |
|-------|-------|

| | |
|---|------------------------|
| 5 | → numbers[] size n = 5 |
|---|------------------------|

| | |
|---|-----------------------------|
| 1 | → numbers = [1, 2, 3, 4, 5] |
|---|-----------------------------|

| | |
|---|--|
| 2 | |
|---|--|

| | |
|---|--|
| 3 | |
|---|--|

| | |
|---|--|
| 4 | |
|---|--|

| | |
|---|--|
| 5 | |
|---|--|

Sample Output 0

15

Explanation 0

1 + 2 + 3 + 4 + 5 = 15.

Sample Case 1

Sample Input 1

| STDIN | Function |
|-------|----------|
|-------|----------|

| | |
|-------|-------|
| ----- | ----- |
|-------|-------|

| | |
|---|------------------------|
| 2 | → numbers[] size n = 2 |
|---|------------------------|

| | |
|----|----------------------|
| 12 | → numbers = [12, 12] |
|----|----------------------|

| | |
|----|--|
| 12 | |
|----|--|

Sample Output 1

24

Explanation 1

12 + 12 = 24.

Answer: (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'arraySum' function below
3  *
4  * The function is expected to return an
5  * The function accepts INTEGER_ARRAY num
6  */
7
8  int arraySum(int numbers count, int *numb
```



```
12 → numbers = [12, 12]
12
```

Sample Output 1

24

Explanation 1

12 + 12 = 24.

Answer: (penalty regime: 0 %)

Reset answer

```
1
2 Complete the 'arraySum' function below.
3
4 The function is expected to return an INT
5 The function accepts INTEGER_ARRAY number
6
7
8 int arraySum(int numbers_count, int *numbers
9
10 int sum=0;
11 for(int i=0;i<numbers_count;i++){
12     sum=sum+numbers[i];
13 }
14 return sum;
15
16
```

| | Test | Expected | Go |
|---|--|----------|----|
| ✓ | int arr[] = {1,2,3,4,5}; printf("%d", arraySum(5, arr)) | 15 | 15 |

Passed all tests! ✓

Question **3**
Correct
[Flag question](#)

Given an array of n integers, rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example n = 5 arr = [1, 3, 3, 2, 4] If the list is rearranged as arr' = [1, 2, 3, 3, 4], the absolute differences are |1 - 2| = 1, |2 - 3| = 1, |3 - 3| = 0, |3 - 4| = 1. The sum of those differences is 1 + 1 + 0 + 1 = 3. Function Description

Question **3**

Correct

Flag question

Given an array of n integers, rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example $n = 5$ $arr = [1, 3, 3, 2, 4]$ If the list is rearranged as $arr' = [1, 2, 3, 3, 4]$, the absolute differences are $|1 - 2| = 1$, $|2 - 3| = 1$, $|3 - 3| = 0$, $|3 - 4| = 1$. The sum of those differences is $1 + 1 + 0 + 1 = 3$. Function Description Complete the function `minDiff` in the editor below. `minDiff` has the following parameter: `arr`: an integer array Returns: `int`: the sum of the absolute differences of adjacent elements Constraints $2 \leq n \leq 105$ $0 \leq arr[i] \leq 109$, where $0 \leq i < n$ Input Format For Custom Testing The first line of input contains an integer, n , the size of `arr`. Each of the following n lines contains an integer that describes `arr[i]` (where $0 \leq i < n$). Sample Case 0 Sample Input For Custom Testing STDIN Function ----- 5 \rightarrow `arr[]` size $n = 5$ 5 \rightarrow `arr[] = [5, 1, 3, 7, 3]` 1 3 7 3 Sample Output 6 Explanation $n = 5$ $arr = [5, 1, 3, 7, 3]$ If `arr` is rearranged as $arr' = [1, 3, 3, 5, 7]$, the differences are minimized. The final answer is $|1 - 3| + |3 - 3| + |3 - 5| + |5 - 7| = 6$. Sample Case 1 Sample Input For Custom Testing STDIN Function ----- 2 \rightarrow `arr[]` size $n = 2$ 3 \rightarrow `arr[] = [3, 2]` 2 Sample Output 1 Explanation $n = 2$ $arr = [3, 2]$ There is no need to rearrange because there are only two elements. The final answer is $|3 - 2| = 1$.

Answer: (penalty regime: 0 %)

Reset answer

```

1  /*
2   * Complete the 'minDiff' function below.
3   *
4   * The function is expected to return an
5   * The function accepts INTEGER_ARRAY arr
6   */
7  #include <stdlib.h>
8  int compare(const void *a, const void *b){
9      return (*(int *)a - *(int *)b);
10 }
11 int minDiff(int arr_count, int* arr)
12 {
13     qsort(arr, arr_count, sizeof(int), compare);
14     int totaldiff = 0;
15     for(int i=1; i<arr_count; i++){
16         totaldiff += abs(arr[i] - arr[i-1]);
17     }
18     return totaldiff;
19 }
20

```

| | Test | Expected | Got |
|---|---|----------|-----|
| ✓ | <code>int arr[] = {5, 1, 3, 7, 3};</code> | 6 | 6 |

$|1 - 2| = 1, |2 - 3| = 1, |3 - 3| = 0, |3 - 4| = 1$. The sum of those differences is $1 + 1 + 0 + 1 = 3$. Function Description

Complete the function `minDiff` in the editor below. `minDiff` has the following parameter:

- `arr`: an integer array

Returns:

- `int`: the sum of the absolute differences of adjacent elements

Constraints

- $2 \leq n \leq 105$
- $0 \leq \text{arr}[i] \leq 109$, where $0 \leq i < n$

Input Format

For Custom Testing The first line of input contains an integer, n , the size of `arr`. Each of the following n lines contains an integer that describes `arr[i]` (where $0 \leq i < n$).

Sample Case 0

Sample Input For Custom Testing

```
STDIN
Function ----- 5 → arr[] size n = 5
5 → arr[] = [5, 1, 3, 7, 3]
1 3 7 3
Sample Output 6
Explanation n = 5 arr = [5, 1, 3, 7, 3]
If arr is rearranged as arr' = [1, 3, 3, 5, 7], the differences are minimized. The final answer is  $|1 - 3| + |3 - 3| + |3 - 5| + |5 - 7| = 6$ .


Sample Case 1



Sample Input For Custom Testing



```
STDIN
Function ----- 2 → arr[] size n = 2
3 → arr[] = [3, 2]
2
Sample Output 1
Explanation n = 2 arr = [3, 2]
There is no need to rearrange because there are only two elements. The final answer is $|3 - 2| = 1$.

```


```

Answer: (penalty regime: 0 %)

Reset answer

```

1  /*
2   * Complete the 'minDiff' function below.
3   *
4   * The function is expected to return an
5   * The function accepts INTEGER_ARRAY arr
6   */
7  #include <stdlib.h>
8  int compare(const void *a, const void *b){
9      return (*(int *)a - *(int *)b);
10 }
11 int minDiff(int arr_count, int* arr)
12 {
13     qsort(arr, arr_count, sizeof(int), compare);
14     int totaldiff = 0;
15     for(int i=1; i<arr_count; i++){
16         totaldiff += abs(arr[i] - arr[i-1]);
17     }
18     return totaldiff;
19 }
20

```

| Test | Expected | Got | |
|---|----------|-----|---|
| <pre>int arr[] = {5, 1, 3, 7, 3}; printf("%d", minDiff(5, arr))</pre> | 6 | 6 | ✓ |

Passed all tests! ✓

Finish review