

SIZE SET INSPECTION REPORT

STYLE NO# -

DIVISION -

Date: -

DESCRIPTION: -

COLOUR: -

ACCESSORIES CHECKLIST

ACCESSORIES	MIS	ALT	ACT	PLA	ACCESSORIES	MIS	ALT	ACT	PLA	ACCESSORIES	MIS	ALT	ACT	PLA	ACCESSORIES	MIS	ALT	ACT	PLA
MAIN LABEL		✓			POLYBAG					BUTTON		✓			PRINT				
BOOK FOLD					POLY BAG STICKER					HOOK EYE/BAR					LAYOUT				
FCTY CODE					LOT STICKER					LACE					EMB THREAD COLOR				
HANG TAG					PRE PACK STICKER					BUCKLE					PLACEMENT				
HANGER					CARTON MARKINGS					SNAP					BEADS/SEQUINS				
WASHCARE					PLACEMENT UPC/P.PACK					THREAD			✓		BEADS/SEQUINS LAYOUT				
INTERLINING			✓		FOLDING					LINING					AFTER TREATMENT				
					SPARE BUTTON POSITION					ZIPPER					PH				

* **BUTTON:** Add shanking; gaping observed
* **THREAD:** Vardhman Core Eco thread / Vardhman Eco thread
* **MAIN LABEL:** Labels need to be printed
* **INTERLINING:** Compatibility report code EG9231DR

PATTERN CHECK LIST

Grain Line: -
Notches: -
Graded Nest: OK
Corrections Implemnted: -
YY/ Mini Marker: OK

Planned Size Set Submission Date: -
Actual Submission Date: -
PCD: -
Cut Quantity: -
Size Set Inspection Result: -

SHRINKAGE SHELL: L = 2.4%, 2.8%, 2.4% W = 0.8%, 0.8%, 0.8%
3 samples tested; all under 3%, acceptable

DETAILED COMMENTS

- (1) Colour tone differs between samples; quality not as per FOB
- (2) Placket has been made flat; fit sample carries crinkle effect
- (3) Elastic width differs slightly
- (4) Button has no shanking and garment is gaping
- (5) Labels need to be printed

OVERALL: Begin our production. Start doing the cutting.

I AGREE WITH THE ABOVE COMMENTS AND WILL INCORPORATE ALL ABOVE COMMENTS

VENDOR'S SIGNATURE

MEASUREMENT (SPEC ATTACHED)

Result: -
Graded Nest: OK
Corrections To Be Done: Add shanking to the buttons; Labels need to be printed
Bring Back To Specs: -

Cutting Check: -
Seam Allowance: -
Corrections Implemented: -

LINING: -

ACTION TO BE TAKEN BY VENDOR

- Confirm and use correct approved fabric quality
- Maintain the approved crinkle effect on placket
- Keep elastic width consistent
- Add shanking to the buttons
- Print the required labels

MEASUREMENT DETAIL (ATTACHED SPEC SHEET)

Extracted from recording · Source: Recording_20(2)(1) · 117 rows · 11 need review (shown in red)

Size M (32)

No	Point of measure	Measured	Dev	Note	Conf
8	Front length from HPS to center front hem	22			1.00
9	Waist position from HPS	13 1/2	+1/8		1.00
10	Shoulder seam	1 3/8	+1/8		1.00
11	Shoulder seam forward at neck	5/8	+1/8		1.00
12	Shoulder seam forward at armhole	5/8			0.88
13	Across shoulder seam to seam	12 3/4	-1/8		1.00
14	Across front at 5 inches below HPS	11 1/4	-1/4	Position was initially spoken as 5/8, then clarified as 5 inches	0.90
15	Armhole	9			1.00
16	Across back at 5 inches below	13 1/4			1.00
17	Chest one inch below armhole	38	-1/2		1.00
18	Waist	35			1.00
19	Bottom opening straight	39	-1/4		1.00
20	Front shirt tail	2 3/4	+1/4		0.95
21	Back shirt tail	1 3/4			0.95
22	Sleeve length	6 3/4			1.00
23	Sleeve opening relaxed	12			1.00
24	Sleeve opening extended	17 1/2			1.00
25	Neck width seam to seam	7 1/4			1.00
26	Front neck drop	3 7/8			0.95
27	Back neck drop	1/2	-1/8		1.00
28	Collar length at neckband seam	15 3/8	-1/8		1.00
29	Collar length at outer edge	16 1/8			1.00
30	Neckband height at center back	3/4			1.00
31	Collar height	2 1/4			1.00
32	Collar point	2 1/4			1.00
33	Button position from below neck seam	8 1/4			1.00
34	Button position from bottom edge	2			1.00
35	Center front placket width	3/4			1.00
36	Side seam tie position from underarm	4 1/2			1.00
37	Side seam tie length	24 3/4			1.00
38	Side seam tie width	1/4			1.00
39	Hem height / bottom fold	1/4			1.00

Size L (29)

No	Point of measure	Measured	Dev	Note	Conf
40	Front length	22 5/8			1.00
41	Waist position from HPS	14 1/8			1.00
42	Shoulder	13 1/2	-1/8	Spoken only as shoulder	0.82
43	Across front	12	+1/8	Field name was unclear immediately after shoulder	0.66
44	Neck width	7 1/2			1.00
45	Front neck drop	4	-1/8		1.00
46	First button position	8 1/4			1.00
47	Chest one inch below armhole	41		Measured with shirring spread	0.95
48	Waist	38			1.00
49	Bottom	42	-1/2		1.00
50	Armhole	9 5/8			1.00
51	Sleeve length	7 1/8			1.00
52	Sleeve opening relaxed	13 1/4	+1/2		1.00
53	Sleeve opening extended	18 3/4		Initially called as 19, then reconfirmed as 18 3/4; gauze may be opening up	0.82
54	Collar length at neckband seam	16	-1/4		1.00
55	Collar length at outer edge	16 3/4			1.00
56	Neckband height	3/4			1.00
57	Collar height	2 1/4			0.85
58	Collar point	2 1/4			0.90
59	Across back	14	+1/4	Position was first called 5 1/2 inches, then corrected to 5 inches	0.88
60	Back neck drop	1/2			1.00
61	Button position from bottom	2			1.00
62	Center front placket width	3/4			1.00
63	Front shirt tail	2 3/4		Speaker briefly expressed uncertainty before confirming	0.76
64	Back shirt tail	1 3/4			0.95
65	Side seam tie position from underarm	4 1/8		Spoken ambiguously as four by eight	0.55
66	Side seam tie length	25 1/2	-1		1.00
67	Side seam tie width	1/4			1.00
68	Bottom fold	1/4			1.00

Size XXS (29)

No	Point of measure	Measured	Dev	Note	Conf
69	Front length	21 1/8	-1/8	Spoken as twenty one eight	0.93
70	Waist position / bodice	12 3/8		Speaker called it bodice slope	0.78
71	Shoulder seam	1 3/8		Spoken as slope	0.82
72	Shoulder seam forward	5/8			0.87
73	Across shoulder	11 1/4			1.00
74	Across front at 5 inches	9 3/4	+1/4		1.00
75	Across back at 5 inches	11 3/4			1.00
76	Chest one inch below armhole	32			1.00
77	Waist	29	+1/2		1.00
78	Bottom	33	-1/4		1.00
79	Sleeve length	6			1.00
80	Armhole	7 7/8	+1/8		1.00
81	Sleeve opening relaxed	9 3/4			1.00
82	Sleeve opening extended	15 1/4			1.00
83	Neck width	6 1/2	-1/8		1.00
84	Front neck drop	3 1/2	+1/8		1.00
85	Back neck drop	1/2			1.00
86	Collar length at neckband seam	13 1/2			1.00
87	Collar length at outer edge	14 1/4			1.00
88	Neckband height	3/4			1.00
89	Collar height	2 1/4		Initially introduced as back neck, then clarified as collar height	0.85
90	Collar point	2 1/4			1.00
91	Center front placket width	3/4			1.00
92	Front shirt tail	2 3/4			0.92
93	Back shirt tail	1 3/4			0.92
95	Side seam tie placement	4 3/8	+1/8		1.00
96	Side seam tie length	23 1/4	-1	Several conflicting calls, including 21 3/4; final value reconfirmed as 23 1/4. Deviation less certain	0.64
97	Side seam tie width	1/4			1.00
98	Bottom fold	1/4			1.00

Construction

No	Item	Value	Note	Conf
1	Front and back grading		Armhole aligned; waist grading uniform; shoulder slope and neck constant; bottom okay	0.90
2	Collar and patch		Okay	0.95
3	Colour tone		Colour tone differs between samples	1.00
4	Placket appearance		Placket made flat; fit sample shows crinkle effect	1.00
5	Elastic width		Slight difference in width; elastic tighter	0.90
6	General appearance and construction		Generally same; construction okay	0.95
7	Front number of buttons	5		1.00
94	Button shanking		No shanking; gaping observed. Add shanking to buttons	1.00

Bill of materials

No	Item	Value	Note	Conf
99	Shell fabric		Monica seersucker, RMP solid; 91% cotton and 9% other fibre stated	0.72
100	Button		Fox shell buttons; 69K mentioned	0.78
101	Thread		Vardhman Core Eco thread / Vardhman Eco thread	0.95
102	Main label and side label		Eco thread; labels need to be printed	0.85
103	Interlining		EG9231DR confirmed from compatibility report; 9231ER was also called before correction	0.83
104	Elastic	1/4	White colour	0.92

Shrinkage

No	Item	Value	Note	Conf
105	Sample 1 length shrinkage	2.4%		1.00
106	Sample 1 width shrinkage	0.8%		1.00
107	Sample 2 length shrinkage	2.8%		1.00
108	Sample 2 width shrinkage	0.8%		1.00
109	Sample 3 length shrinkage	2.4%		1.00
110	Sample 3 width shrinkage	0.8%		1.00
111	Shrinkage control	3%	All three tested samples are under 3%; acceptable	1.00

Mini marker

No	Item	Value	Note	Conf
112	Marker direction		Two-way marker; each garment is one-way	0.95
113	YY	0.76		1.00

Comments and vendor actions

No	Item	Value	Note	Conf
114	Fabric quality		Colour tone differs and quality called correct although not as per FOB	0.95
115	Placket crinkle		Maintain approved crinkle effect; do not make placket flat	1.00
116	Button shanking		Add shanking to prevent gaping	1.00
117	Production instruction		Begin production and start cutting	1.00