

STYLE: 7147 7147 V NECK FITTED TOP

HOLIDAY-B 2026 | STATUS: FNL

GRADE MEASUREMENTS - SIZE SET INSPECTION RESULT

Company: AMERICAN EAGLE OUTFITTERS  
Division / Dept: 02 / 035  
Season: HOLIDAY-B 2026  
Style Desc: 7147 V NECK FITTED TOP

Size Range: XXS, XS, S, M, L, XL, XXL  
Base Size: M  
Sizes Measured: XS, S, M, L, XL  
Measurement Result: FAIL CONDITIONALLY (14 out of tolerance of 112 checked)

| POM   | Description                                       | Tol- | Tol+ | XXS *          | XS                   | S                    | M                    | L                    | XL                   | XXL *          |
|-------|---------------------------------------------------|------|------|----------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------|
| 1.01A | REFERENCE ON BODY - FRONT LENGTH                  | 0    | 0    | -              | -                    | -                    | 22<br>spec           | -                    | -                    | -              |
| 1.01A | FRONT LENGTH FROM HPS                             | -3/8 | +3/8 | 19 1/8<br>spec | 19 3/4<br>ok<br>100% | 20 3/8<br>ok<br>55%  | 21<br>ok<br>100%     | 21 5/8<br>ok<br>100% | 22 3/8<br>ok<br>100% | 23 1/8<br>spec |
| 2.02A | SHOULDER SLOPE FROM HPS                           | -1/4 | +1/4 | 1/2<br>spec    | 1/2<br>ok<br>100%    | 1/2<br>ok<br>100%    | 1/2<br>ok<br>100%    | 1/2<br>ok<br>100%    | 1/2<br>ok<br>100%    | 1/2<br>spec    |
| 2.01A | SHOULDER SEAM FORWARD                             | -1/8 | +1/8 | 3/4<br>spec    | 3/4<br>ok<br>100%    | 3/4<br>ok<br>100%    | 3/4<br>ok<br>100%    | 3/4<br>ok<br>100%    | 3/4<br>ok<br>100%    | 3/4<br>spec    |
| 1.20A | ACROSS SHOULDER SEAM TO SEAM                      | -1/4 | +1/4 | 12<br>spec     | 12 1/2<br>ok<br>100% | 13<br>ok<br>100%     | 13 1/2<br>ok<br>100% | 14 1/4<br>ok<br>100% | 15<br>ok<br>100%     | 15 3/4<br>spec |
| 1.22A | ACROSS FRONT POSITION FROM HPS                    | 0    | 0    | 5<br>spec      | 5<br>ok<br>100%      | 5<br>ok<br>100%      | 5<br>ok<br>100%      | 5<br>ok<br>100%      | 5<br>ok<br>100%      | 5<br>spec      |
| 1.23A | ACROSS FRONT SEAM TO SEAM                         | -1/4 | +1/4 | 10 3/4<br>spec | 11 1/4<br>ok<br>100% | 11 3/4<br>ok<br>100% | 12 1/4<br>ok<br>100% | 13<br>ok<br>100%     | 13 3/4<br>ok<br>100% | 14 1/2<br>spec |
| 1.24A | ACROSS BACK POSITION FROM HPS                     | 0    | 0    | 5<br>spec      | 5<br>ok<br>100%      | 5<br>ok<br>100%      | 5<br>ok<br>100%      | 5<br>ok<br>100%      | 5<br>ok<br>100%      | 5<br>spec      |
| 1.25A | ACROSS BACK SEAM TO SEAM                          | -1/4 | +1/4 | 11 5/8<br>spec | 12 1/8<br>ok<br>100% | 12 5/8<br>ok<br>100% | 13 1/8<br>ok<br>100% | 13 7/8<br>ok<br>100% | 14 5/8<br>ok<br>100% | 15 3/8<br>spec |
| 1.28E | CHEST 1" BELOW ARMHOLE (SIDESEAM ON TOP SIDESEAM) | -3/4 | +3/4 | 33 1/2<br>spec | 35 1/2<br>ok<br>100% | 37 1/2<br>ok<br>100% | 39 1/2<br>ok<br>100% | 42 1/2<br>ok<br>100% | 45 1/2<br>ok<br>100% | 49 1/2<br>spec |
| 1.29F | EMPIRE SEAM POSITION FROM HPS                     | -1/4 | +1/4 | 12 5/8<br>spec | 13<br>ok<br>100%     | 13 3/8<br>ok<br>80%  | 13 3/4<br>ok<br>100% | 14 3/8<br>ok<br>100% | 15 1/8<br>ok<br>100% | 15 7/8<br>spec |
| 1.31A | EMPIRE WAIST                                      | -3/4 | +3/4 | 30 1/2<br>spec | 32 1/2<br>ok<br>100% | 34 1/2<br>ok<br>100% | 36 1/2<br>ok<br>100% | 39 1/2<br>ok<br>100% | 42 1/2<br>ok<br>100% | 46 1/2<br>spec |
| 4.22A | BOTTOM SWEEP                                      | -3/4 | +3/4 | 38 1/2<br>spec | 40 1/2<br>ok<br>55%  | 42 1/2<br>ok<br>100% | 44 1/2<br>ok<br>100% | 47 1/2<br>ok<br>100% | 50 1/2<br>ok<br>55%  | 54 1/2<br>spec |
| 4.27A | BOTTOM HEM HEIGHT                                 | -1/8 | +1/8 | 3/16<br>spec   | 3/16<br>ok<br>100%   | 3/16<br>ok<br>100%   | 3/16<br>ok<br>100%   | 3/16<br>ok<br>100%   | 3/16<br>ok<br>100%   | 3/16<br>spec   |

| POM      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Tol- | Tol+ | XXS *          | XS                       | S                        | M                        | L                        | XL                       | XXL *          |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|----------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|----------------|
| 1.08C    | CF BODICE LENGTH TO EMPIRE                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | -1/8 | +1/8 | 1 3/8<br>spec  | 1 1/2<br>ok<br>100%      | 1 5/8<br>ok<br>100%      | 1 3/4<br>ok<br>100%      | 2 1/8<br>ok<br>100%      | 2 5/8<br>ok<br>100%      | 3 1/8<br>spec  |
| 1.09C    | BODICE LENGTH AT SIDE SEAM                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | -1/8 | +1/8 | 4 3/8<br>spec  | 4 1/2<br>ok<br>100%      | 4 5/8<br>ok<br>100%      | 4 3/4<br>ok<br>100%      | 5 1/8<br>ok<br>100%      | 5 5/8<br>ok<br>100%      | 6 1/8<br>spec  |
| 7.02B GR | WR'S LEFT SIDE SEAM INVISIBLE ZIPPER LENGTH                                                                                                                                                                                                                                                                                                                                                                                                                                                           | -1/4 | +1/4 | 4<br>spec      | 4 1/2<br>ok<br>100%      | 5<br>ok<br>100%          | 5 1/2<br>ok<br>100%      | 6<br>ok<br>100%          | 6 1/2<br>ok<br>100%      | 7 1/4<br>spec  |
| 3.02B    | SLEEVE LENGTH FROM ARMHOLE SHORT INCL LACE                                                                                                                                                                                                                                                                                                                                                                                                                                                            | -1/4 | +1/4 | 3 7/8<br>spec  | 4 1/8<br>ok<br>55%       | 4 3/8<br>ok<br>100%      | 4 5/8<br>ok<br>100%      | 5<br>ok<br>100%          | 5 3/8<br>ok<br>100%      | 5 7/8<br>spec  |
| 3.06B    | ARMHOLE STRAIGHT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | -1/4 | +1/4 | 7 5/8<br>spec  | 8<br>ok<br>100%          | 8 3/8<br>ok<br>100%      | 8 3/4<br>ok<br>100%      | 9 3/8<br>ok<br>100%      | 10<br>ok<br>100%         | 10 3/4<br>spec |
| 3.19B    | SLEEVE OPENING (S/S)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -1/4 | +1/4 | 10 1/4<br>spec | 11<br>ok<br>100%         | 11 3/4<br>ok<br>100%     | 12 1/2<br>ok<br>100%     | 13 3/4<br>ok<br>100%     | 15<br>ok<br>100%         | 16 1/2<br>spec |
| 8.08A    | SLEEVE CAP SHIRRING SPREAD - EVENLY BETWEEN OUTSEAM                                                                                                                                                                                                                                                                                                                                                                                                                                                   | -1/8 | +1/8 | 2 7/8<br>spec  | 2 7/8<br>ok<br>100%      | 2 7/8<br>ok<br>100%      | 2 7/8<br>ok<br>100%      | 2 7/8<br>ok<br>100%      | 2 7/8<br>ok<br>100%      | 2 7/8<br>spec  |
| 2.05B    | NECK WIDTH EDGE TO EDGE -1/2 1/2 7 1/4 7 3/4 8 1/4 8 3/4 9 1/2 10 1/4 11 STATUS: FNL STYLE: 7147 7147 V NECK FITTED TOP HOLIDAY-B 2026 Company: AMERICAN EAGLE OUTFITTERS Division / Dept: 02 / 035 Season: HOLIDAY-B 2026 Style Desc: 7147 V NECK FITTED TOP Fit / Other: GRADE MEASUREMENTS - APPROVED FOR PRODUCTION - TRIBURG CONSULTANTS PVT LTD. Tolerance Model : WW TOP L20 Size Range : ALPHA WW POM Descr : GRADE SPECIFICATIONS Base Size : M Block : Grading Method/UM : Incremental / IN | 0    | 0    | -              | -                        | -                        | -                        | -                        | -                        | -              |
| 2.03A    | FRONT NECK DROP FROM HPS TO EDGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | -1/4 | +1/4 | 9 7/8<br>spec  | 10<br>spec               | 10 1/8<br>spec           | 10 1/4<br>spec           | 9 1/2<br>-7/8<br>80%     | 10 1/4<br>-1/4<br>100%   | 10 5/8<br>spec |
| 2.04A    | BACK NECK DROP FROM HPS TO EDGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | -1/8 | +1/8 | 1/2<br>spec    | 7 3/4<br>+7 1/4<br>100%  | 8 1/4<br>+7 3/4<br>100%  | 8 3/4<br>+8 1/4<br>100%  | 1/2<br>ok<br>100%        | 1/2<br>ok<br>100%        | 1/2<br>spec    |
| 8.05A    | BACK FISH DART LENGTH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | -1/4 | +1/4 | 6 1/2<br>spec  | 1/2<br>-6<br>100%        | 1/2<br>-6<br>100%        | 1/2<br>-6<br>100%        | 10 3/8<br>+3 7/8<br>100% | 10 1/2<br>+4<br>100%     | 6 1/2<br>spec  |
| 7.06B    | NG TIE LENGTH EXPOSED                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | -3/8 | +3/8 | 25 3/4<br>spec | 6 1/2<br>-19 1/4<br>100% | 6 1/2<br>-19 1/4<br>100% | 6 1/2<br>-19 1/4<br>100% | 6 1/2<br>-19 1/4<br>100% | 6 1/2<br>-19 1/4<br>100% | 25 3/4<br>spec |
| 8.08A    | BUST SHIRRING SPREAD - AT EMPIRE                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | -1/4 | +1/4 | 2 3/4<br>spec  | 2 3/4<br>ok<br>100%      | 2 3/4<br>ok<br>75%       | 2 3/4<br>ok<br>100%      | 2 3/4<br>ok<br>100%      | 2 3/4<br>ok<br>100%      | 2 3/4<br>spec  |

Each cell shows the measured value, its deviation, and how confidently it was transcribed. **Orange** = outside tolerance. **Blue** = heard with under 90% confidence, so confirm against the recording. **Grey** = the style set's own specification, shown for a size marked \* that this inspection did not measure. Those are not readings.

#### OUT OF TOLERANCE

2.04A BACK NECK DROP FROM HPS TO EDGE — size XS: measured 7 3/4 against 1/2, +7 1/4

8.05A BACK FISH DART LENGTH — size XS: measured 1/2 against 6 1/2, -6

7.06B NG TIE LENGTH EXPOSED — size XS: measured 6 1/2 against 25 3/4, -19 1/4

2.04A BACK NECK DROP FROM HPS TO EDGE — size S: measured 8 1/4 against 1/2, +7 3/4

8.05A BACK FISH DART LENGTH — size S: measured  $1\frac{1}{2}$  against  $6\frac{1}{2}$ , -6  
7.06B NG TIE LENGTH EXPOSED — size S: measured  $6\frac{1}{2}$  against  $25\frac{3}{4}$ , -19  $\frac{1}{4}$   
2.04A BACK NECK DROP FROM HPS TO EDGE — size M: measured  $8\frac{3}{4}$  against  $1\frac{1}{2}$ , +8  $\frac{1}{4}$   
8.05A BACK FISH DART LENGTH — size M: measured  $1\frac{1}{2}$  against  $6\frac{1}{2}$ , -6  
7.06B NG TIE LENGTH EXPOSED — size M: measured  $6\frac{1}{2}$  against  $25\frac{3}{4}$ , -19  $\frac{1}{4}$   
2.03A FRONT NECK DROP FROM HPS TO EDGE — size L: measured  $9\frac{1}{2}$  against  $10\frac{3}{8}$ , -7/8  
8.05A BACK FISH DART LENGTH — size L: measured  $10\frac{3}{8}$  against  $6\frac{1}{2}$ , +3  $\frac{7}{8}$   
7.06B NG TIE LENGTH EXPOSED — size L: measured  $6\frac{1}{2}$  against  $25\frac{3}{4}$ , -19  $\frac{1}{4}$   
8.05A BACK FISH DART LENGTH — size XL: measured  $10\frac{1}{2}$  against  $6\frac{1}{2}$ , +4  
7.06B NG TIE LENGTH EXPOSED — size XL: measured  $6\frac{1}{2}$  against  $25\frac{3}{4}$ , -19  $\frac{1}{4}$

18 spoken measurements could not be matched to a point of measure and are listed in the CSV.

Generated from SIZE SET 7147 and checked against style\_7147.pdf. Every value must be confirmed before this report is sent to a vendor.