

SIZE SET INSPECTION REPORT

STYLE NO# 2356

DIVISION -

Date: -

DESCRIPTION: oversized flannel shirt piping

COLOUR: -

ACCESSORIES CHECKLIST

ACCESSORIES	MIS	ALT	ACT	PLA	ACCESSORIES	MIS	ALT	ACT	PLA	ACCESSORIES	MIS	ALT	ACT	PLA	ACCESSORIES	MIS	ALT	ACT	PLA
MAIN LABEL			✓		POLYBAG			✓		BUTTON			✓		PRINT				
BOOK FOLD					POLY BAG STICKER					HOOK EYE/BAR					LAYOUT				
FCTY CODE					LOT STICKER					LACE					EMB THREAD COLOR				
HANG TAG					PRE PACK STICKER					BUCKLE					PLACEMENT				
HANGER					CARTON MARKINGS					SNAP					BEADS/SEQUINS				
WASHCARE			✓		PLACEMENT UPC/P.PACK					THREAD			✓		BEADS/SEQUINS LAYOUT				
INTERLINING					FOLDING			✓		LINING					AFTER TREATMENT				
					SPARE BUTTON POSITION					ZIPPER					PH				

* WASHCARE: placement OK

* SPARE BUTTON POSITION: not required

PATTERN CHECK LIST

Grain Line: OK
Notches: OK
Graded Nest: OK
Corrections Implemnted: YES
YY/ Mini Marker: YES

Planned Size Set Submission Date: 11. 8

Actual Submission Date: 24

PCD: 25

Cut Quantity: 7 piece

Size Set Inspection Result: Pass with comment

SHRINKAGE SHELL: L = 1.5% W = +3%

All four colors

MEASUREMENT (SPEC ATTACHED)

Result: PASS
Graded Nest: OK
Corrections To Be Done: Match overlock construction with approved PP sample; correct pocket shape; loosen pocket cord; correct collar point and tie-space shape; eliminate skip stitches; correct stripe alignment and uneven topstitching; improve hand feel
Bring Back To Specs: All measurements out of tolerance

Cutting Check: OK
Seam Allowance: OK
Corrections Implemented: OK

LINING: -

DETAILED COMMENTS

(1) Approved PP sample has 6-thread overlock; updated tech pack has 5-thread overlock

(2) Pocket shape found poor

(3) Cord found tight at pocket

(4) Poor collar point shape

(5) Poor tie-space shape and overlapping

(6) Locker loop measurement found minus

(7) Skip stitch visible at cuff, placket slit and collar

(8) Body stripe found wavy while pocket attached

(9) Topstitch found uneven and placket bumping/wavy

(10) Hand feel observed slightly harsh

(11) Placket found uneven at back yoke, placket and collar

ACTION TO BE TAKEN BY VENDOR

Match side seam and armhole overlock with approved PP sample

Correct pocket shape to spec

Loosen pocket cord

Correct collar point shape

Correct tie-space shape and overlap

Bring locker loop measurement to spec

Eliminate skip stitches

Keep body stripe straight during pocket attachment

Make topstitch even and correct placket waviness

Improve hand feel

Correct alignment at back yoke, placket and collar

I AGREE WITH THE ABOVE COMMENTS AND WILL INCORPORATE ALL ABOVE COMMENTS

VENDOR'S SIGNATURE

SENT VIA MAIL

STATUS: FNL

STYLE: 2365

2365 OVERSIZED FLANNEL SHIRT W PIPING

HOLIDAY-B 2026



Company: AMERICAN EAGLE OUTFITTERS
Division / Dept: 07 / 066
Season: HOLIDAY-B 2026
Style Desc: 2365 OVERSIZED FLANNEL SHIRT W PIPING
Fit / Other:



GRADE MEASUREMENTS - APPROVED FOR PRODUCTION - TRIBURG CONSULTANTS PVT LTD.

Tolerance Model :	WW TOP L20 Size Range : ALPHA WW	Size Range :	XXS, XS, S, M, L, XL, XXL
POM Descr :	XXS-XXL- TRIBURG Base Size : S	Base Size :	S
Block :		Grading Method/UM :	Incremental / IN
Modified By :	BIASIE Modified Date/Time : 2026-06-11 12:07:03	Status :	FNL
Sizes Measured :	S	Measurement Result :	FAIL CONDITIONALLY (1 of 38 out of tolerance)

POM	Description	Tol-	Tol+	XXS *	XS *	S	M *	L *	XL *	XXL *
0.00Z	SISTER 2365	0	0	-	-	-	-	-	-	-
0.00Z	SISTER 2365,2377,2390	0	0	-	-	-	-	-	-	-
0.00B	DISCLAIMER (Wvn): Measure Gmts in Circumference	0	0	-	-	-	-	-	-	-
1.01A	REF ON BODY - FRONT LENGTH FROM HPS	-3/8	+3/8	-	-	27 1/4 spec	-	-	-	-
1.01A	REF ON BODY - BACK LENGTH FROM HPS	-3/8	+3/8	-	-	28 spec	-	-	-	-
1.01A	FRONT LENGTH FROM HPS	-1/2	+1/2	26 spec	26 5/8 spec	27 1/4 +1/8 100%	27 7/8 spec	28 1/2 spec	29 1/4 spec	30 spec
1.01B	BACK LENGTH FROM HPS	-1/2	+1/2	26 1/4 spec	26 7/8 spec	27 1/2 +1/8 100%	28 1/8 spec	28 3/4 spec	29 1/2 spec	30 1/4 spec
2.02A	SHOULDER SLOPE FROM HPS	-1/4	+1/4	1 7/8 spec	1 7/8 spec	1 7/8 +1/8 100%	1 7/8 spec	1 7/8 spec	1 7/8 spec	1 7/8 spec
2.01A	SHOULDER SEAM FORWARD @ NECK	-1/8	+1/8	1/2 spec	1/2 spec	1/2 ok 100%	1/2 spec	1/2 spec	1/2 spec	1/2 spec
2.01B	SHOULDER SEAM FORWARD AT ARMHOLE	-1/8	+1/8	3/4 spec	3/4 spec	3/4 ok 100%	3/4 spec	3/4 spec	3/4 spec	3/4 spec
1.20A	ACROSS SHOULDER SEAM TO SEAM	-3/8	+3/8	17 3/4 spec	18 1/4 spec	18 3/4 +1/4 100%	19 1/4 spec	20 spec	20 3/4 spec	21 3/4 spec
1.22A	ACROSS FRONT POSITION	0	0	5 spec	5 spec	5 ok 95%	5 spec	5 spec	5 spec	5 spec
1.23A	ACROSS FRONT SEAM TO SEAM	-3/8	+3/8	16 1/4 spec	16 3/4 spec	17 1/4 +1/4 100%	17 3/4 spec	18 1/2 spec	19 1/4 spec	20 1/4 spec

POM	Description	Tol-	Tol+	XXS *	XS *	S	M *	L *	XL *	XXL *
1.25A	ACROSS BACK AT YOKE SEAM	-3/8	+3/8	17 spec	17 1/2 spec	18 +1/4 100%	18 1/2 spec	19 1/4 spec	20 spec	21 spec
1.28A	CHEST 1" BELOW ARMHOLE-PLEAT EXTENDED	-3/4	+3/4	45 spec	47 spec	49 +1/2 100%	51 spec	54 spec	57 spec	61 spec
4.21A	BOTTOM OPENING STRAIGHT-ABOVE SHIRT TAIL	-3/4	+3/4	45 spec	47 spec	49 ok 55%	51 spec	54 spec	57 spec	61 spec
4.20A	FRONT SHIRT TAIL HEIGHT	-1/8	+1/8	4 3/4 spec	4 3/4 spec	4 3/4 +1/8 100%	4 3/4 spec	4 3/4 spec	4 3/4 spec	4 3/4 spec
4.20A	BACK SHIRT TAIL HEIGHT	-1/8	+1/8	4 spec	4 spec	4 +1/8 100%	4 spec	4 spec	4 spec	4 spec
3.22B	BOTTOM HEM HEIGHT - SELF TURN	-1/8	+1/8	1/4 spec	1/4 spec	1/4 ok 100%	1/4 spec	1/4 spec	1/4 spec	1/4 spec
3.01A	SLEEVE LENGTH FROM CB LONG	-3/8	+3/8	32 1/2 spec	33 spec	33 1/2 -1/4 100%	34 spec	34 3/4 spec	35 1/2 spec	36 1/2 spec
3.05A	SLEEVE CAP HEIGHT	-1/4	+1/4	5 3/4 spec	6 spec	6 1/4 +1/4 100%	6 1/2 spec	6 7/8 spec	7 1/4 spec	7 3/4 spec
3.06B	ARMHOLE STRAIGHT	-3/8	+3/8	8 7/8 spec	9 1/4 spec	9 5/8 ok 100%	10 spec	10 5/8 spec	11 1/4 spec	12 spec
3.13A	MUSCLE 1" FROM UNDERARM	-1/4	+1/4	15 1/4 spec	16 spec	16 3/4 ok 100%	17 1/2 spec	18 3/4 spec	20 spec	21 1/2 spec
3.14B	ELBOW POSITION FROM CUFF EDGE	0	0	10 spec	10 spec	10 ok 90%	10 spec	10 spec	10 spec	10 spec
3.15A	ELBOW	-1/4	+1/4	13 1/4 spec	13 7/8 spec	14 1/2 ok 85%	15 1/8 spec	16 spec	16 7/8 spec	18 1/8 spec
3.19A	SLEEVE OPENING (L/S) @ EDGE	-1/4	+1/4	8 1/2 spec	9 spec	9 1/2 ok 80%	10 spec	10 1/2 spec	11 spec	11 1/2 spec
3.22A	SLEEVE CUFF HEIGHT	-1/8	+1/8	2 1/2 spec	2 1/2 spec	2 1/2 ok 100%	2 1/2 spec	2 1/2 spec	2 1/2 spec	2 1/2 spec
3.24A	SLEEVE PLACKET OPENING LENGTH	-1/8	+1/8	4 1/2 spec	4 1/2 spec	4 1/2 -1/8 100%	4 1/2 spec	4 1/2 spec	4 1/2 spec	4 1/2 spec
3.24C	SLEEVE PLACKET WIDTH	-1/8	+1/8	3/4 spec	3/4 spec	3/4 ok 85%	3/4 spec	3/4 spec	3/4 spec	3/4 spec
2.03A	FRONT NECK DROP FROM HPS TO SEAM	-1/8	+1/8	3 3/4 spec	3 7/8 spec	4 +1 90%	4 1/8 spec	4 1/4 spec	4 3/8 spec	4 1/2 spec

POM	Description	Tol-	Tol+	XXS *	XS *	S	M *	L *	XL *	XXL *
2.04A	BACK NECK DROP FROM HPS TO SEAM	-1/8	+1/8	3/4 spec	3/4 spec	3/4 ok 75%	3/4 spec	3/4 spec	3/4 spec	3/4 spec
2.05C	BACK NECK WIDTH SEAM TO SEAM	-1/4	+1/4	5 3/4 spec	6 spec	6 1/4 +1/8 65%	6 1/2 spec	6 3/4 spec	7 spec	7 1/4 spec
2.09A	NECKBAND HEIGHT AT CB	-1/8	+1/8	1 1/8 spec	1 1/8 spec	1 1/8 ok 95%	1 1/8 spec	1 1/8 spec	1 1/8 spec	1 1/8 spec
2.11A	COLLAR POINT	-1/8	+1/8	2 1/4 spec	2 1/4 spec	2 1/4 -1/8 75%	2 1/4 spec	2 1/4 spec	2 1/4 spec	2 1/4 spec
2.08C	COLLAR LENGTH AT OUTER EDGE	-1/4	+1/4	15 3/4 spec	16 3/8 spec	17 -1/4 100%	17 5/8 spec	18 1/4 spec	18 7/8 spec	19 1/2 spec
9.01B	LOCKER LOOP WIDTH	-1/8	+1/8	3/8 spec	3/8 spec	3/8 -1/8 100%	3/8 spec	3/8 spec	3/8 spec	3/8 spec
9.01C	LOCKER LOOP SPREAD	-1/8	+1/8	2 spec	2 spec	2 ok 90%	2 spec	2 spec	2 spec	2 spec
2.10A	COLLAR HEIGHT AT CB	-1/8	+1/8	2 spec	2 spec	2 ok 100%	2 spec	2 spec	2 spec	2 spec
2.18A	CENTER FRONT PLACKET WIDTH	0	0	1 spec	1 spec	1 ok 95%	1 spec	1 spec	1 spec	1 spec
*	BUTTON POSITION FRM NK SM TO 1ST BTN	-1/8	+1/8	3 spec	3 1/8 spec	3 1/4 ok 95%	3 3/8 spec	3 1/2 spec	3 5/8 spec	3 3/4 spec
7.04B	BUTTON POSITION FROM BOTTOM EDGE	-1/8	+1/8	4 1/4 spec	4 1/4 spec	4 1/4 ok 100%	4 1/4 spec	4 1/4 spec	4 1/4 spec	4 1/4 spec
1.11B GR	CB YOKE DEPTH @ CB NECK	-1/8	+1/8	4 spec	4 1/4 spec	4 1/2 spec	4 3/4 spec	5 spec	5 1/4 spec	5 1/2 spec
2.20B	CB YOKE BOX PLEAT WIDTH	-1/8	+1/8	1 1/2 spec	1 1/2 spec	1 1/2 ok 95%	1 1/2 spec	1 1/2 spec	1 1/2 spec	1 1/2 spec
6.01A GR	CHEST POCKET LENGTH AT CENTER	-1/8	+1/8	5 1/4 spec	5 1/4 spec	5 1/2 ok 95%	5 1/2 spec	5 3/4 spec	5 3/4 spec	6 spec
6.02A GR	CHEST POCKET WIDTH AT TOP	-1/8	+1/8	4 3/4 spec	4 3/4 spec	5 spec	5 spec	5 1/4 spec	5 1/4 spec	5 1/2 spec
6.16A	POCKET HEM HEIGHT	-1/8	+1/8	3/4 spec	3/4 spec	3/4 spec	3/4 spec	3/4 spec	3/4 spec	3/4 spec
6.50A GR	CHEST POCKET POSITION FROM HPS	-1/8	+1/8	8 3/4 spec	9 spec	9 1/4 ok 70%	9 1/2 spec	9 3/4 spec	10 spec	10 1/4 spec
6.50C GR	CHEST POCKET POSITION FROM CF	-1/8	+1/8	1 1/2 spec	1 5/8 spec	1 3/4 ok 90%	1 7/8 spec	2 1/8 spec	2 3/8 spec	2 5/8 spec

Each cell shows this style set's specified measurement, the deviation the inspector called against it, and how confidently that was transcribed. **ok** means the inspector said okay; every stated deviation is shown, whether or not it falls inside the tolerance band. **An orange outline = outside tolerance.** **Blue figures = heard with under 100% confidence, so confirm against the recording.** The two are independent: an outlined cell with blue figures is out of tolerance and wants checking. Grey = a size marked * that this inspection did not measure, so the specification is shown alone. Those carry no reading.

OUT OF TOLERANCE
2.03A FRONT NECK DROP FROM HPS TO SEAM — size S: measured 5 against 4, +1

Generated from rec 2365(5) and checked against style_2365.pdf. Every value must be confirmed before this report is sent to a vendor.

APPROVED FOR PRODUCTION

MEASUREMENT DETAIL (ATTACHED SPEC SHEET)

Style 2356 · oversized flannel shirt piping · Pass with comment · Source: rec 2365(5) · 56 rows · 7 need review (shown in red)

Construction

No	Item	Value	Note	Conf
6	Side seam and armhole overlock	Approved PP sample 6-thread; updated tech pack 5-thread	construction mismatch	0.95

Shrinkage

No	Item	Value	Note	Conf
4	Pattern shrinkage length	1.5%	all four colors	1.00
5	Pattern shrinkage width	+3%	all four colors	1.00

Mini marker

No	Item	Value	Note	Conf
1	YY shell	1.45 meter		1.00
2	Locker loop	0.003 meter		1.00
3	Pocket trim	0.01 meter		1.00

Comments and vendor actions

No	Item	Value	Note	Conf
47	Pocket shape	poor	Correct to spec	1.00
48	Cord at pocket	tight	Loosen cord	1.00
49	Collar point shape	poor	Correct shape	1.00
50	Tie-space shape	poor and overlapping	Correct shape and overlap	0.85
51	Locker loop measurement	minus	Bring back to spec	1.00
52	Skip stitch	visible	Cuff, placket slit and collar	1.00
53	Body stripe	wavy	Observed while pocket attached	1.00
54	Topstitch and placket	uneven and wavy	Placket bumping	1.00
55	Hand feel	slightly harsh	Improve hand feel	1.00
56	Alignment at back yoke, placket and collar	uneven	Spoken as placket found uneven	0.75