

STATUS: FNL

STYLE: 2365

2365 OVERSIZED FLANNEL SHIRT W PIPING

HOLIDAY-B 2026



**Company:** AMERICAN EAGLE OUTFITTERS  
**Division / Dept:** 07 / 066  
**Season:** HOLIDAY-B 2026  
**Style Desc:** 2365 OVERSIZED FLANNEL SHIRT W PIPING  
**Fit / Other:**



## GRADE MEASUREMENTS - APPROVED FOR PRODUCTION - TRIBURG CONSULTANTS PVT LTD.

|                          |                                                 |                             |                                               |
|--------------------------|-------------------------------------------------|-----------------------------|-----------------------------------------------|
| <b>Tolerance Model :</b> | WW TOP L20 Size Range : ALPHA WW                | <b>Size Range :</b>         | XXS, XS, S, M, L, XL, XXL                     |
| <b>POM Descr :</b>       | XXS-XXL- TRIBURG Base Size : S                  | <b>Base Size :</b>          | S                                             |
| <b>Block :</b>           |                                                 | <b>Grading Method/UM :</b>  | Incremental / IN                              |
| <b>Modified By :</b>     | BIASIE Modified Date/Time : 2026-06-11 12:07:03 | <b>Status :</b>             | FNL                                           |
| <b>Sizes Measured :</b>  | S                                               | <b>Measurement Result :</b> | FAIL CONDITIONALLY (1 of 38 out of tolerance) |

| POM   | Description                                     | Tol- | Tol+ | XXS *          | XS *           | S                      | M *            | L *            | XL *           | XXL *          |
|-------|-------------------------------------------------|------|------|----------------|----------------|------------------------|----------------|----------------|----------------|----------------|
| 0.00Z | SISTER 2365                                     | 0    | 0    | -              | -              | -                      | -              | -              | -              | -              |
| 0.00Z | SISTER 2365,2377,2390                           | 0    | 0    | -              | -              | -                      | -              | -              | -              | -              |
| 0.00B | DISCLAIMER (Wvn): Measure Gmts in Circumference | 0    | 0    | -              | -              | -                      | -              | -              | -              | -              |
| 1.01A | REF ON BODY - FRONT LENGTH FROM HPS             | -3/8 | +3/8 | -              | -              | 27 1/4<br>spec         | -              | -              | -              | -              |
| 1.01A | REF ON BODY - BACK LENGTH FROM HPS              | -3/8 | +3/8 | -              | -              | 28<br>spec             | -              | -              | -              | -              |
| 1.01A | FRONT LENGTH FROM HPS                           | -1/2 | +1/2 | 26<br>spec     | 26 5/8<br>spec | 27 1/4<br>+1/8<br>100% | 27 7/8<br>spec | 28 1/2<br>spec | 29 1/4<br>spec | 30<br>spec     |
| 1.01B | BACK LENGTH FROM HPS                            | -1/2 | +1/2 | 26 1/4<br>spec | 26 7/8<br>spec | 27 1/2<br>+1/8<br>100% | 28 1/8<br>spec | 28 3/4<br>spec | 29 1/2<br>spec | 30 1/4<br>spec |
| 2.02A | SHOULDER SLOPE FROM HPS                         | -1/4 | +1/4 | 1 7/8<br>spec  | 1 7/8<br>spec  | 1 7/8<br>+1/8<br>100%  | 1 7/8<br>spec  | 1 7/8<br>spec  | 1 7/8<br>spec  | 1 7/8<br>spec  |
| 2.01A | SHOULDER SEAM FORWARD @ NECK                    | -1/8 | +1/8 | 1/2<br>spec    | 1/2<br>spec    | 1/2<br>ok<br>100%      | 1/2<br>spec    | 1/2<br>spec    | 1/2<br>spec    | 1/2<br>spec    |
| 2.01B | SHOULDER SEAM FORWARD AT ARMHOLE                | -1/8 | +1/8 | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>ok<br>100%      | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec    |
| 1.20A | ACROSS SHOULDER SEAM TO SEAM                    | -3/8 | +3/8 | 17 3/4<br>spec | 18 1/4<br>spec | 18 3/4<br>+1/4<br>100% | 19 1/4<br>spec | 20<br>spec     | 20 3/4<br>spec | 21 3/4<br>spec |
| 1.22A | ACROSS FRONT POSITION                           | 0    | 0    | 5<br>spec      | 5<br>spec      | 5<br>ok<br>95%         | 5<br>spec      | 5<br>spec      | 5<br>spec      | 5<br>spec      |
| 1.23A | ACROSS FRONT SEAM TO SEAM                       | -3/8 | +3/8 | 16 1/4<br>spec | 16 3/4<br>spec | 17 1/4<br>+1/4<br>100% | 17 3/4<br>spec | 18 1/2<br>spec | 19 1/4<br>spec | 20 1/4<br>spec |

| POM   | Description                              | Tol- | Tol+ | XXS *          | XS *           | S                      | M *            | L *            | XL *           | XXL *          |
|-------|------------------------------------------|------|------|----------------|----------------|------------------------|----------------|----------------|----------------|----------------|
| 1.25A | ACROSS BACK AT YOKE SEAM                 | -3/8 | +3/8 | 17<br>spec     | 17 1/2<br>spec | 18<br>+1/4<br>100%     | 18 1/2<br>spec | 19 1/4<br>spec | 20<br>spec     | 21<br>spec     |
| 1.28A | CHEST 1" BELOW ARMHOLE-PLEAT EXTENDED    | -3/4 | +3/4 | 45<br>spec     | 47<br>spec     | 49<br>+1/2<br>100%     | 51<br>spec     | 54<br>spec     | 57<br>spec     | 61<br>spec     |
| 4.21A | BOTTOM OPENING STRAIGHT-ABOVE SHIRT TAIL | -3/4 | +3/4 | 45<br>spec     | 47<br>spec     | 49<br>ok<br>55%        | 51<br>spec     | 54<br>spec     | 57<br>spec     | 61<br>spec     |
| 4.20A | FRONT SHIRT TAIL HEIGHT                  | -1/8 | +1/8 | 4 3/4<br>spec  | 4 3/4<br>spec  | 4 3/4<br>+1/8<br>100%  | 4 3/4<br>spec  | 4 3/4<br>spec  | 4 3/4<br>spec  | 4 3/4<br>spec  |
| 4.20A | BACK SHIRT TAIL HEIGHT                   | -1/8 | +1/8 | 4<br>spec      | 4<br>spec      | 4<br>+1/8<br>100%      | 4<br>spec      | 4<br>spec      | 4<br>spec      | 4<br>spec      |
| 3.22B | BOTTOM HEM HEIGHT - SELF TURN            | -1/8 | +1/8 | 1/4<br>spec    | 1/4<br>spec    | 1/4<br>ok<br>100%      | 1/4<br>spec    | 1/4<br>spec    | 1/4<br>spec    | 1/4<br>spec    |
| 3.01A | SLEEVE LENGTH FROM CB LONG               | -3/8 | +3/8 | 32 1/2<br>spec | 33<br>spec     | 33 1/2<br>-1/4<br>100% | 34<br>spec     | 34 3/4<br>spec | 35 1/2<br>spec | 36 1/2<br>spec |
| 3.05A | SLEEVE CAP HEIGHT                        | -1/4 | +1/4 | 5 3/4<br>spec  | 6<br>spec      | 6 1/4<br>+1/4<br>100%  | 6 1/2<br>spec  | 6 7/8<br>spec  | 7 1/4<br>spec  | 7 3/4<br>spec  |
| 3.06B | ARMHOLE STRAIGHT                         | -3/8 | +3/8 | 8 7/8<br>spec  | 9 1/4<br>spec  | 9 5/8<br>ok<br>100%    | 10<br>spec     | 10 5/8<br>spec | 11 1/4<br>spec | 12<br>spec     |
| 3.13A | MUSCLE 1" FROM UNDERARM                  | -1/4 | +1/4 | 15 1/4<br>spec | 16<br>spec     | 16 3/4<br>ok<br>100%   | 17 1/2<br>spec | 18 3/4<br>spec | 20<br>spec     | 21 1/2<br>spec |
| 3.14B | ELBOW POSITION FROM CUFF EDGE            | 0    | 0    | 10<br>spec     | 10<br>spec     | 10<br>ok<br>90%        | 10<br>spec     | 10<br>spec     | 10<br>spec     | 10<br>spec     |
| 3.15A | ELBOW                                    | -1/4 | +1/4 | 13 1/4<br>spec | 13 7/8<br>spec | 14 1/2<br>ok<br>85%    | 15 1/8<br>spec | 16<br>spec     | 16 7/8<br>spec | 18 1/8<br>spec |
| 3.19A | SLEEVE OPENING (L/S) @ EDGE              | -1/4 | +1/4 | 8 1/2<br>spec  | 9<br>spec      | 9 1/2<br>ok<br>80%     | 10<br>spec     | 10 1/2<br>spec | 11<br>spec     | 11 1/2<br>spec |
| 3.22A | SLEEVE CUFF HEIGHT                       | -1/8 | +1/8 | 2 1/2<br>spec  | 2 1/2<br>spec  | 2 1/2<br>ok<br>100%    | 2 1/2<br>spec  | 2 1/2<br>spec  | 2 1/2<br>spec  | 2 1/2<br>spec  |
| 3.24A | SLEEVE PLACKET OPENING LENGTH            | -1/8 | +1/8 | 4 1/2<br>spec  | 4 1/2<br>spec  | 4 1/2<br>-1/8<br>100%  | 4 1/2<br>spec  | 4 1/2<br>spec  | 4 1/2<br>spec  | 4 1/2<br>spec  |
| 3.24C | SLEEVE PLACKET WIDTH                     | -1/8 | +1/8 | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>ok<br>85%       | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec    |
| 2.03A | FRONT NECK DROP FROM HPS TO SEAM         | -1/8 | +1/8 | 3 3/4<br>spec  | 3 7/8<br>spec  | 4<br>+1<br>90%         | 4 1/8<br>spec  | 4 1/4<br>spec  | 4 3/8<br>spec  | 4 1/2<br>spec  |

| POM      | Description                          | Tol- | Tol+ | XXS *          | XS *           | S                    | M *            | L *            | XL *           | XXL *          |
|----------|--------------------------------------|------|------|----------------|----------------|----------------------|----------------|----------------|----------------|----------------|
| 2.04A    | BACK NECK DROP FROM HPS TO SEAM      | -1/8 | +1/8 | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>ok<br>75%     | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec    |
| 2.05C    | BACK NECK WIDTH SEAM TO SEAM         | -1/4 | +1/4 | 5 3/4<br>spec  | 6<br>spec      | 6 1/4<br>+1/8<br>65% | 6 1/2<br>spec  | 6 3/4<br>spec  | 7<br>spec      | 7 1/4<br>spec  |
| 2.09A    | NECKBAND HEIGHT AT CB                | -1/8 | +1/8 | 1 1/8<br>spec  | 1 1/8<br>spec  | 1 1/8<br>ok<br>95%   | 1 1/8<br>spec  | 1 1/8<br>spec  | 1 1/8<br>spec  | 1 1/8<br>spec  |
| 2.11A    | COLLAR POINT                         | -1/8 | +1/8 | 2 1/4<br>spec  | 2 1/4<br>spec  | 2 1/4<br>-1/8<br>75% | 2 1/4<br>spec  | 2 1/4<br>spec  | 2 1/4<br>spec  | 2 1/4<br>spec  |
| 2.08C    | COLLAR LENGTH AT OUTER EDGE          | -1/4 | +1/4 | 15 3/4<br>spec | 16 3/8<br>spec | 17<br>-1/4<br>100%   | 17 5/8<br>spec | 18 1/4<br>spec | 18 7/8<br>spec | 19 1/2<br>spec |
| 9.01B    | LOCKER LOOP WIDTH                    | -1/8 | +1/8 | 3/8<br>spec    | 3/8<br>spec    | 3/8<br>-1/8<br>100%  | 3/8<br>spec    | 3/8<br>spec    | 3/8<br>spec    | 3/8<br>spec    |
| 9.01C    | LOCKER LOOP SPREAD                   | -1/8 | +1/8 | 2<br>spec      | 2<br>spec      | 2<br>ok<br>90%       | 2<br>spec      | 2<br>spec      | 2<br>spec      | 2<br>spec      |
| 2.10A    | COLLAR HEIGHT AT CB                  | -1/8 | +1/8 | 2<br>spec      | 2<br>spec      | 2<br>ok<br>100%      | 2<br>spec      | 2<br>spec      | 2<br>spec      | 2<br>spec      |
| 2.18A    | CENTER FRONT PLACKET WIDTH           | 0    | 0    | 1<br>spec      | 1<br>spec      | 1<br>ok<br>95%       | 1<br>spec      | 1<br>spec      | 1<br>spec      | 1<br>spec      |
| *        | BUTTON POSITION FRM NK SM TO 1ST BTN | -1/8 | +1/8 | 3<br>spec      | 3 1/8<br>spec  | 3 1/4<br>ok<br>95%   | 3 3/8<br>spec  | 3 1/2<br>spec  | 3 5/8<br>spec  | 3 3/4<br>spec  |
| 7.04B    | BUTTON POSITION FROM BOTTOM EDGE     | -1/8 | +1/8 | 4 1/4<br>spec  | 4 1/4<br>spec  | 4 1/4<br>ok<br>100%  | 4 1/4<br>spec  | 4 1/4<br>spec  | 4 1/4<br>spec  | 4 1/4<br>spec  |
| 1.11B GR | CB YOKE DEPTH @ CB NECK              | -1/8 | +1/8 | 4<br>spec      | 4 1/4<br>spec  | 4 1/2<br>spec        | 4 3/4<br>spec  | 5<br>spec      | 5 1/4<br>spec  | 5 1/2<br>spec  |
| 2.20B    | CB YOKE BOX PLEAT WIDTH              | -1/8 | +1/8 | 1 1/2<br>spec  | 1 1/2<br>spec  | 1 1/2<br>ok<br>95%   | 1 1/2<br>spec  | 1 1/2<br>spec  | 1 1/2<br>spec  | 1 1/2<br>spec  |
| 6.01A GR | CHEST POCKET LENGTH AT CENTER        | -1/8 | +1/8 | 5 1/4<br>spec  | 5 1/4<br>spec  | 5 1/2<br>ok<br>95%   | 5 1/2<br>spec  | 5 3/4<br>spec  | 5 3/4<br>spec  | 6<br>spec      |
| 6.02A GR | CHEST POCKET WIDTH AT TOP            | -1/8 | +1/8 | 4 3/4<br>spec  | 4 3/4<br>spec  | 5<br>spec            | 5<br>spec      | 5 1/4<br>spec  | 5 1/4<br>spec  | 5 1/2<br>spec  |
| 6.16A    | POCKET HEM HEIGHT                    | -1/8 | +1/8 | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec          | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec    | 3/4<br>spec    |
| 6.50A GR | CHEST POCKET POSITION FROM HPS       | -1/8 | +1/8 | 8 3/4<br>spec  | 9<br>spec      | 9 1/4<br>ok<br>70%   | 9 1/2<br>spec  | 9 3/4<br>spec  | 10<br>spec     | 10 1/4<br>spec |
| 6.50C GR | CHEST POCKET POSITION FROM CF        | -1/8 | +1/8 | 1 1/2<br>spec  | 1 5/8<br>spec  | 1 3/4<br>ok<br>90%   | 1 7/8<br>spec  | 2 1/8<br>spec  | 2 3/8<br>spec  | 2 5/8<br>spec  |

Each cell shows this style set's specified measurement, the deviation the inspector called against it, and how confidently that was transcribed. **ok** means the inspector said okay; every stated deviation is shown, whether or not it falls inside the tolerance band. **An orange outline = outside tolerance.** **Blue figures = heard with under 100% confidence, so confirm against the recording.** The two are independent: an outlined cell with blue figures is out of tolerance and wants checking. Grey = a size marked \* that this inspection did not measure, so the specification is shown alone. Those carry no reading.

OUT OF TOLERANCE

2.03A FRONT NECK DROP FROM HPS TO SEAM — size S: measured 5 against 4, +1

Generated from rec 2365(6) and checked against style\_2365.pdf. Every value must be confirmed before this report is sent to a vendor.

APPROVED FOR PRODUCTION