# Techniques for Testing-Training Dataset Separation

Project Report

Submitted in partial fulfillment of the requirement for the award of the degree of

**BACHELOR OF TECHNOLOGY**


Submitted by:

**Divyanshi Gupta**

Roll No: 25SCS1003001141

Under the supervision of: **Mr. Ramavath Ganesh**

Department of Computer Science and Engineering IILM University

# Abstract

This project focuses on the importance of splitting a dataset into training and testing parts when developing an AI model. The training part helps the model learn patterns, while the testing part evaluates how well the model performs on data it has never seen before. This separation is necessary to measure real accuracy, avoid overfitting, and ensure that the model can generalize to real-world situations. The project also discusses how different splitting methods, such as random splits, cross-validation, and bootstrap techniques, affect model performance, speed, and reliability. Overall, the study highlights that careful dataset splitting is a key step in building trustworthy and effective AI models.

**Keyword:** Dataset splitting, Training set, Testing set, Overfitting, Accuracy, Validation, Cross-validation, Bootstrap method, Learning processes, Generalization, Resampling methods.

# Contents

**Abstract**

**1 Introduction**
- 1.1 Overview
- 1.2 Objectives
- 1.3 Problem Statement

**2 Literature Review**

**3 Methodology**
- 3.1 Architecture Overview
- 3.2 Algorithms
  - 3.2.1 Train/Test Split
  - 3.2.2 Tenfold Cross-Validation
  - 3.2.3 Leave one out (LOO) Cross-Validation
  - 3.2.4 Repeated Random train/Test Split
  - 3.2.5 Bootstrap Resampling

**4 Implementation**
- 4.1 Environment Setup
- 4.2 Train/Test Implementation
- 4.3 Tenfold Cross-Validation Implementation
- 4.4 Bootstrap Resampling Implementation
- 4.5 Key Points

**5 Result and Discussion**
- 5.1 Performance Comparison
- 5.2 Discussion

**6 Conclusion and Future Scope**
- 6.1 Conclusion
- 6.2 Future Scope

# List of Tables

5.1 Performance Summary

# Chapter 1

# Introduction

## 1.1 Overview

This project focuses on understanding and comparing different methods for splitting a dataset into training and testing parts, which is a crucial step in building machine-learning models. The studies examines how various resampling techniques—such as train/test split, tenfold cross-validation, leave-one-out, and the bootstrap method—affect a model's accuracy, error rate, and computation time. By testing these methods on different classification algorithms, the project aims to identify which approach provides the most reliable results with the least computational effort. Overall, the project helps in selecting the best data-splitting strategy to build accurate and efficient AI models.

## 1.2 Objectives

• **To understand the importance of splitting data** into training and testing sets for building accurate machine-learning models.

• **To compare different resampling methods**, including train/test split, tenfold cross-validation, leave-one-out, and the bootstrap method.

- **To analyze how each method affects** model performance in terms of **accuracy**, **error rate**, and **computation time**.

- **To identify the most efficient splitting method** that provides high accuracy while reducing computational time.

- **To study the behavior of various classification algorithms** (Logistic Regression, Decision Tree, K-Nearest Neighbour) under different splitting techniques.

- **To recommend the best data-splitting strategy** for large datasets and real-world machine learning applications.

# 1.2 Problem Statement

In machine learning, models are often trained and tested on the same or improperly split datasets, which leads to **overfitting** and inaccurate performance evaluation. Traditional data-splitting methods like simple train-test splits may not always provide a reliable estimate of how well a model will perform on unseen data. Additionally, commonly used resampling techniques such as **cross-validation** can be time-consuming when dealing with large datasets.

To address these challenges, this project examines the need for effective and efficient dataset splitting methods. It specifically explores how different resampling techniques—such as **tenfold cross-validation**, **leave-one-out**, and the **bootstrap method**—influence the model's accuracy, error rate, and computational time. The problem focuses on identifying which method provides the most reliable performance evaluation while also reducing computation time for classification models.

# Chapter 2

# Literature Review

Splitting a dataset into training and testing parts is crucial for building reliable and accurate machine learning models. Different methods have been proposed and studied over time:

- **Train/Test Split:** The simplest approach, where the dataset is divided into two sets. It is easy to implement but may produce inconsistent results, especially with small datasets.
- **Cross-Validation:** Techniques like tenfold cross-validation provide more reliable accuracy estimates by rotating the testing sets. However, they can be computationally expensive for large datasets.
- **Leave-One-Out (LOO) Validation:** Offers nearly unbiased accuracy estimates by testing each observation individually, but it is extremely slow for big datasets.
- **Bootstrap Method:** Creates multiple samples by resampling with replacement. Research shows it provides stable and reliable accuracy while reducing computation time and overfitting, making it suitable for large datasets.

Overall, the literature highlights that the choice of data-splitting method significantly affects **accuracy, error rate, and computation time**. Among these methods, the **bootstrap technique** stands out as an efficient and reliable alternative for evaluating machine learning models, especially on large datasets.

# Chapter 3

# Methodology

## 3.1 Architecture Overview

The system architecture follows a **Data-Model Feedback Loop**. The dataset is split into **training and testing sets**, and models are trained and evaluated using various **resampling methods**.

**Process:**

1. The dataset is preprocessed and divided into **training and testing sets**.
2. A **classification model** (Logistic Regression, Decision Tree, or K-Nearest Neighbors) is trained on the training set.
3. Resampling methods (Tenfold Cross-Validation, Leave-One-Out, Repeated Random Split, Bootstrap) are applied for model evaluation.
4. The model predicts on the **testing set**, and performance metrics are recorded.
5. **Accuracy, error rate, and computation time** are analyzed to determine the best resampling method.

## 3.2 Algorithms

### 3.2.1 Train/Test Split

- Divides dataset into separate **training** and **testing** sets.
- Ensures evaluation on **unseen data**.
- Simple and fast but sensitive to the split ratio.

### 3.2.2 Tenfold Cross-Validation

- Dataset is divided into **10 folds**.
- Uses 9 folds for training and 1 for testing, repeated **10 times**.
- Provides **stable accuracy** and reduces the risk of overfitting.

### 3.2.3 Leave-One-Out (LOO) Cross-Validation

- Each observation is tested individually while the rest are used for training.
- Very **accurate**, but computationally intensive for large datasets.

### 3.2.4 Repeated Random Train/Test Split

- Dataset is randomly split into training and testing sets multiple times.
- Accuracy is averaged across repetitions.
- Balances **speed and reliability**.

### 3.2.5 Bootstrap Resampling

- Creates **multiple resampled datasets** from the training set using **replacement**.
- Evaluates the model on the testing set for each resample.
- Produces **stable accuracy** and **reduces computation time**, especially for large datasets.

# Chapter 4

# Implementation

## 4.1 Environment Setup

The system simulates a **Data-Model Evaluation Environment** where datasets are split, models are trained, and performance is evaluated. The dataset is divided into **training and testing sets**, and various **resampling methods** are applied to ensure reliable evaluation.

- **Dataset:** Standard datasets like Adult, Monica, or Food
- **Training Set:** Used to **train the model**
- **Testing Set:** Used to **evaluate model performance on unseen data**
- **Evaluation Methods:**
    1. Train/Test Split
    2. Tenfold Cross-Validation
    3. Leave-One-Out (LOO) Cross-Validation
    4. Repeated Random Train/Test Split
    5. Bootstrap Resampling
- **Metrics:** Accuracy, Error Rate, Computation Time

Splitting datasets is essential in **machine learning** to prevent

overfitting. The model learns patterns from the training set and is evaluated on the testing set to measure **generalization performance**. Resampling methods improve reliability of evaluation and provide insights into **model stability** across different data samples

## 4.2 Train/Test Split Implementation

Train/Test split is the simplest method for **model validation**. While fast, it is sensitive to the way the data is divided, which can lead to **biased accuracy estimates** if the split is unlucky.

## 4.3 Tenfold Cross-Validation Implementation

Tenfold Cross-Validation divides the dataset into **10 folds** and rotates the test set across them. This reduces **variance** in performance estimates and provides a **more stable evaluation** than a single train/test split.

## 4.4 Bootstrap Resampling Implementation

Bootstrap resampling repeatedly draws samples **with replacement** from the training data and evaluates the model on the testing set. This method **reduces computation time** while providing **stable accuracy estimates**, making it suitable for **large datasets**.

## 4.5 Key Points

- Classification models are evaluated using **multiple resampling methods**.
- **Bootstrap method** provides **stable accuracy** and **reduced computation time**.
- Performance metrics recorded: **Accuracy, Error Rate and Computation Time**.
- Methods are applicable to **large datasets** and various **classification models**.

# Chapter 5

# Results and Discussion

## 5.1 Performance Comparison

### Logistic Regression

• **Bootstrap:** Fastest, stable accuracy.
• **Tenfold CV:** Slightly slower, similar accuracy.
• **LOO:** Very slow, no accuracy benefit.
• **Random Split:** Fast but small accuracy changes.

#### Decision Tree

• **Bootstrap:** Fastest and stable.
• **Cross-Validation:** Accurate but slower.
• **LOO:** Too slow.
• **Random Split:** Fast but fluctuates.

### KNN

• **Bootstrap:** Fast but lower accuracy.
• **Tenfold CV:** Best accuracy and most suitable.
• **LOO:** Slow and unnecessary.
• **Random Split:** Fast but less accurate.

## Table 5.1: Performance Summary

| Metric | Bootstrap | Tenfold CV | LOO | Random Split |
|---|---|---|---|---|
| Speed | Fastest | Moderate | Slowest | Fast |
| Accuracy | High (LR, DT) | High | High | Moderate |
| KNN Accuracy | Low | Highest | Moderate | Low |
| Stability | High | High | Moderate | Low |

## 5.2 Discussion

Bootstrap is the **fastest** method and works best for **Logistic Regression** and **Decision Tree**, giving good accuracy with less time.
For **KNN**, tenfold cross-validation performs better because bootstrap reduces its accuracy.
Overall, bootstrap is great for speed, while cross-validation is better for accuracy in KNN.

# Chapter 6

# Conclusion and Future Scope

## 6.1 Conclusion

The experiments show that splitting the dataset into training and testing parts is a **crucial step** for building accurate and reliable AI models. Among the resampling methods, the **bootstrap procedure** is the fastest and most efficient for Logistic Regression and Decision Tree classifiers, providing stable accuracy even when the training set size is reduced. For K-Nearest Neighbour, **tenfold cross-validation** gives better accuracy, while bootstrap is faster but less precise. Overall, proper dataset splitting ensures fair evaluation, reduces overfitting, and improves the generalization of the model.

## 6.2 Future Scope

The study can be extended in several ways:

- Applying **other resampling methods** or hybrid approaches to further improve accuracy and speed.
- Using **larger and more complex datasets**, including image or text data, to test model scalability.
- Investigating the impact of **feature selection, normalization, and preprocessing** on the performance of bootstrap and cross-validation.
- Implementing these methods in **real-world applications**, such as medical diagnosis, spam detection, or financial prediction, to validate their effectiveness.
- Exploring **other machine learning models** like Support Vector Machines or Neural Networks with bootstrap and cross-validation for comparison.

# Bibliography


1. James, G., Witten, D., Hastie, T., & Tibshirani, R. (2013). *An*
2. *Introduction to Statistical Learning: with Applications in R*. Springer.
3. Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., & Duchesnay, E. (2011). Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research, 12*, 2825–2830.
4. Vrigazova, O., & Ivanov, S. (2019). Tenfold Bootstrap Procedure for Classification Problems. *Journal of Computational Statistics, 34*(2), 215–230.
5. Pampel, F. (2000). *Logistic Regression: A Primer*. SAGE Publications.