EXPERIMENT 3:
DML Commands using INSERT, SELECT

```
mysql> insert into student values('divya',101,'cse');
Query OK, 1 row affected (0.02 sec)

mysql> insert into student values('keerthi',102,'cse aiml');
Query OK, 1 row affected (0.01 sec)

mysql> insert into student values('varshini',103,'cse IT');
Query OK, 1 row affected (0.01 sec)

mysql> insert into student values('pridiksha',104,'cse aids');
Query OK, 1 row affected (0.02 sec)

mysql> insert into student values('tharani',105,'cse');
Query OK, 1 row affected (0.01 sec)

mysql> select * from student;
+-------------+---------+-----------+
| studname    | studid  | course    |
+-------------+---------+-----------+
| divya       |     101 | cse       |
| keerthi     |     102 | cse aiml  |
| varshini    |     103 | cse IT    |
| pridiksha   |     104 | cse aids  |
| tharani     |     105 | cse       |
+-------------+---------+-----------+
5 rows in set (0.00 sec)
```

INSERT COMMAND

```
mysql> select * from student;
+-----------+---------+-----------+
| studname  | studid | course    |
+-----------+---------+-----------+
| divya     |    101 | cse       |
| keerthi   |    102 | cse aiml  |
| varshini  |    103 | cse IT    |
| pridiksha |    104 | cse aids  |
| tharani   |    105 | cse       |
+-----------+---------+-----------+
5 rows in set (0.00 sec)

mysql> select studname from student where course='cse';
+-----------+
| studname  |
+-----------+
| divya     |
| tharani   |
+-----------+
2 rows in set (0.00 sec)
```

SELECT COMMAND