

EX.NO:5 ADT QUEUE USING EXCEPTION HANDLING

PROGRAM:

```
import java.io.*;
interface MyQueue
{
    void enqueue();
    void dequeue();
    void display();
}
class CircularQueue implements MyQueue
{
    final int SIZE = 5;
    int queue[] = new int[SIZE];
    int front = -1;
    int rear = -1;
    public void enqueue()
    {
        try
        {
            BufferedReader br = new BufferedReader(new InputStreamReader(System.in));
            if((front == 0 && rear == SIZE - 1) || (front == rear + 1))
            {
                System.out.println("Queue Overflow");
                return;
            }
            System.out.print("Enter the element: ");
            int item = Integer.parseInt(br.readLine());
            if(front == -1)
            {
                front = 0;
                rear = 0;
            }
            else if(rear == SIZE - 1)
            {
                rear = 0;
            }
            else
            {
                rear++;
            }
            queue[rear] = item;
        }
        catch(Exception e)
```

```

{
System.out.println(e);
}
}
public void dequeue()
{
if(front == -1)
{

System.out.println("Queue Underflow");
return;
}
System.out.println("Deleted Element: " + queue[front]);
if(front == rear)
{
front = -1;
rear = -1;
}
else if(front == SIZE - 1)
{
front = 0;
}
else
{
front++;
}
}
public void display()
{
if(front == -1)
{
System.out.println("Queue is Empty");
return;
}
System.out.println("Queue Elements:");

if(front <= rear)
{
for(int i = front; i <= rear; i++)
{
System.out.print(queue[i] + " ");
}
}
else

```

```

    {
        for(int i = front; i < SIZE; i++)
        {
            System.out.print(queue[i] + " ");

        }
        for(int i = 0; i <= rear; i++)
        {
            System.out.print(queue[i] + " ");
        }
    }

System.out.println();
}
}

public class Main
{
    public static void main(String args[]) throws Exception
    {
        BufferedReader br = new BufferedReader(new InputStreamReader(System.in));
        CircularQueue q = new CircularQueue();
        int ch;
        do
        {
            System.out.println("\n*** CIRCULAR QUEUE ***");
            System.out.println("1. Enqueue");
            System.out.println("2. Dequeue");
            System.out.println("3. Display");
            System.out.println("4. Exit");
            System.out.print("Enter your choice: ");
            ch = Integer.parseInt(br.readLine());
            switch(ch)
            {
                case 1:
                    q.enqueue();
                    break;
                case 2:
                    q.dequeue();
                    break;
                case 3:
                    q.display();
                    break;
                case 4:

```

```
System.out.println("Program Ended");
break;
default:
System.out.println("Invalid Choice");
}
} while(ch != 4);
}
}
Out put for this
```

*** CIRCULAR QUEUE ***

1. Enqueue
2. Dequeue
3. Display
4. Exit

Enter your choice: 1
Enter the element: 10

Enter your choice: 1
Enter the element: 20

Enter your choice: 3
Queue Elements:
10 20

Enter your choice: 2
Deleted Element: 10

Enter your choice: 4
Program Ended