





ATLASTM

TECHNOLOGIES PVT. LTD.
CIN No.U72200GJ2009PTC056104

Cell : +91 09099 314000
+91 09099 414000

WORKING VIEW



Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com

🌐: www.atlastechnologiesindia.com

MFG. OF ROAD & CIVIL CONSTRUCTION MACHINERY

Subject to Mehsana Jurisdiction



DETAIL FORM FOR PORTABLE CONCRETE BATCHING PLANT WITH PAN MIXER

BELOW REFERENCE IS 20 M³ PER HOUR

Item 1	four (2/4) bin feeder with individual bin , conveyors, weighing/mixing section & control cabin
Item 2	40 tons cement silo with accessories (Optional)
Item 3	cement feeding system for cement silo(Optional)
Item 4	Plant control system
Item 5	Wiring
Item 6	Supervisory installation and commissioning

TECHNICAL SPECIFICATION

PLANT CAPACITY

For Reference: 20 m³ based on a mixer capacity of 500/350 litres. Of vibrated concrete per batch 0.35 m³ and at (60) second weigh/mix cycle.

Assuming the following conditions: -

- 1) 100% Plant utilisation
- 2) Material density (2400) Kg/m³

1 INDIVIDUAL 4 BIN FEEDERS, CHARGING (WEIGH) CONVEYOR, DISCHARGE CONVEYOR

1.1 AGGREGATE HOPPERS

Feeders	-	Four (4) individual Bin
Capacity	-	3 m ³ /each bin
Loading width	-	2.75 meter
Loading height	-	3 meter
Material	-	4 mm thick mild steel plate
Vibrator	-	One (1)
Discharge gates	-	Four (4) pneumatically controlled discharge gates, One gates per hopper



1.2 CHARGING (WEIGH) CONVEYOR

Weigh conveyor	-	Mounted under weigh hoppers
Length	-	Metres
Belt	-	6 Mtr. X 500 mm wide 4 ply with vulcanised joint
Idlers	-	Troughed bolted to steel section support frame
Drive	-	5 HP gear motor unit direct on head shaft
Belt tensioning	-	Tension bolts fitted to tail drum slide bearings
Belt scraper	-	Fitted under head drum
Weigh hopper	-	Manufactured from 5 mm mild steel plate
Weighing capacity		0.5 m ³ total from all hoppers, mounted on load cells
Load cells	-	1000 kg. "S" type - 4 no.
Transfer load capacity		90 Kg. cm ²

1.3 CEMENT WEIGH HOPPERS

Capacity	-	One 250 Kg. load cell mounted
Load cells	-	225 kg. Shear beam type - 3 no.
Plate thickness	-	3 & 5 mm steel plate
Discharge doors	-	200 mm pneumatically operated butterfly valves with On-Off limit switch
Vibrator	-	0.18 HP vibrating motor
Total inlets	-	Two for optional customer supply flyesh silo / feed screw

1.4 WATER WEIGH HOPPER

Capacity	-	200 litre load cell mounted
Load cells	-	200 kg. "S" type - 2 no.
Plate thickness	-	3 mm mild steel plate
Discharge valve	-	75 mm pneumatically operated butterfly valve with On-Off switch

1.5 ADDITIVE WEIGH HOPPER

Capacity	-	10 liter load cell mounted
Load cells	-	50 kg. "S" type - 1 no.
Material	-	5 mm thick and transparent acrylic dispenser.
Discharge valve	-	Spherical valve operated via actuator

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com

🌐: www.atlastechnologiesindia.com



1.6 **ATLAS MAKE PAN MIXER 500/350 Litter**

Pan Mixer cap.500/350 liter. No.of 6 arms are jointed with spiders for mixing material. Niherd tips. Driven by electric motors, the twin stage planetary gear boxes, rated at 94% efficiency, are connected to The spider, which virtually eliminates the transmission of any possible force from the mixing spider to The reducer output spiders. Mixing tank is completely protected with special 12mm replaceable Anti-wear liners

1.7 **PNEUMATICS**

Compressor	-	2 HP to give 12 Kg. pressure with 10.04 CFM of piston displacement.
Pneumatics	-	Cylinder, Solenoid valves, nylon pipe work and fittings

1.8 **UNDER FRAME**

Under frame	-	Fabricated rolled steel section chassis
Support jacks	-	6 nos. Fixed supports under chassis.
Loading height	-	3.8 meter clearance under mixer outlet chute

1.9 **1.5 TON CEMENT HOPPER**

Cement feeding hopper capacity 30 bags (1.5 T) with 168 MM X 10000 MM screw conveyor. There are two support lag for screw conveyor mounting.

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com
🌐: www.atlastechnologiesindia.com



2

40 T CEMENT SILO (OPTIONAL)

- 2.1 40 Ton Capacity Silo for Cement** With fabricated 4 Column, Cross Bracings, Railing at Top, Climbing Ladder, Seamless Pipe (Dia: 100 mm Seamless pipe for feeding material in silo), Aeration System at Bottom of cone & with other necessary filaments.

2.2 SILO ACCESSORIES (1 set)

Double Flange Butterfly Valve with Cast Iron Disc Dia. 300 mm and Manual Lever for above Butterfly valve	- One unit
Special Dust Collector for Silo Venting	- One unit
Level Indicator 115/230 V/AC Paddle type Rotating	- Two units
Pressure Safety Relief Valve M.O.C. – M– M.S.	- One unit
Vibrating Bin aerator - (1 set inclusive of below items)	
1" Two way valve with coil	- 1 No.
1" Filter regulator with gauge	- 1 No.
Bracket for FRL	- 1 No.
Manifold 1/2" female x 2 outlet.	- 1 No.
Reducer 1" male X 1/2" female.	- 1 No.
1" Nipple-- 3 Nos	
Straight connector 1/2" x 12mm OD	- 4 No.
Equal tee 12mm OD	- 2 No.
PU tube 12mm OD	- 10 Meter
Male elbow 3/8" X 12mm OD	- 4 No.

Transfer screws - 168 mm diameter with 6 metres length cement screw conveyor

3 **SILO FEEDING SYSTEM (OPTIONAL)**

3.1 Cement feeding compressor for bulk feeding

SPECIFICATION	
CAPACITY (FAD)	400(800 M3 / Hr)
PRESSURE	1.0 Kg. / Cm2.
MACHINE SPEED	1450 RPM
POWER AT SHAFT	37.5 K.W.
RECOMM. MOTOR	50 H.P. / 1450 RPM.
TYPE OF DRIVE	V – BELT
TYPE OF COOLING	AIR COOLED

P

LANT CONTROL SYSTEM

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com

🌐: www.atlastechnologiesindia.com



4 CONTROLS

- 4.2 **CONTROL DESK** - Containing key switches for manual/auto control, manual Start/stop buttons and PLC weigh/mix control system
- 4.3 **WEIGH/MIX** - Weighing and mixing control system comprising of:
Operator interface terminal with Sunlight Visible Colour TFT (5.7 INCH) Touch Screen Display (HMI – SIEMENSE OR DELTA) Super Bright LED display ensures maximum readability with a clear keyboard design and eight multifunction soft keys. Automatic control of the batching process via English interface with unlimited recipe storage. Printer supplied for production logging of essential data from each batch. Production data stored on non-volatile Compact Flash, accessible by USB cable. Network port to allow remote viewing and control of the batching process on customers PC.
- OPTIONAL**
SCADA type control system with Wi-Fi internet attachment facility and also facility to operate plant by mobile / tablet.

5 WIRING

Feeder and mixing unit section of mobile concrete plant is prewired with junction box. And from panel to genset is on customer's scope

GUARDS

Safety guards are provided over all V belt drives, chain drives and gears.

STEELWORK

All welds to be cleaned as necessary, steelwork to be wire brushed and generally cleaned of all mill scale etc before painting.

PAINTING

All external surfaces are chipped and painted with one-coat primer with double coated PU paint.

VOLTAGE

400 Volt, 3 phase, 50 Hz



Mobile Concrete Plant Connected Power

Item	Quantity	HP	Qty.	Power (HP)
1	Pan Mixer	20	1	20
2	Weigh conveyor	5	1	5
3	Agg. hopper vibrator	0.18	1	0.18
4	Cement weigh hopper vibrator	0.18	1	0.18
5	Air compressor	2	1	2
6	Water pump	2	1	2
7	Additive motor	1	1	1
8	Screw conveyor 168 mm x 6 meters	7.5	1	7.5
			TOTAL	37 HP

Sr. No.	DESCRIPTION	MAKE
1	All other gear boxes	Brevini/Ingico/ Bonfiglioliin
2	Screw conveyor	WAM / IVA BULK
3	Motors	Kirloskar / Crompton / Hindustan
4	Conveyor belt	MRF OR COMPERABLE
5	V belt	Fenner
6	Compressor	Anest Iwata OR Indo Air
7	Pneumatics	SMC
8	Load cell	ASI OR KELLY OR SENSOTRONIC
9	Pedestal bearing	TR
10	Vibrating motors	ISI Standard
11	Silo accessories	WAM OR IVA BULK
12	Water Pump	Kirloskar or kebee

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com

🌐: www.atlastechnologiesindia.com



Note: We recommend you to buy gen set of 62 kva. For the plant
Main cable size: 25 sq. mm x 3 ½ core armoured copper – Length depending on the
Generator distance.

Exclusions

Civil works, foundations etc
Mains power supply or generator (for usage of 62 KVA , 3 phases for grid and equivalent generator for power consumption on site)
Mains incoming cable or distribution board
Water supply and incoming pipe work
Aggregate storage hopper grids
Site labour and carnage
Any item not specified

Warranty

The equipment is covered by guarantee under proper use, for faulty material or workman ship for a period of 12 months from the date of dispatch.

Consumable, electric components, rubber components and general wear and tear components are not covered under guarantee.

Purchaser shall inform supplier in writing, of any defect in equipment noticed during guarantee period. On receipt of purchaser's letter, supplier shall at his option, replace or repair free of cost the defective part supplied by him. In case repair is required to be done at works, purchaser shall send such defective part to the works after receiving supplier's confirmation.

We are in no event be liable for any damages whatsoever (including special, incidental consequential, direct or indirect damages, for personal injury, loss of business profits, or any other pecuniary loss) arising out of the use of or inability to use the equipment.

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com
🌐: www.atlastechnologiesindia.com