




ATLASTM

TECHNOLOGIES PVT. LTD.
CIN No.U72200GJ2009PTC056104

Cell : +91 09099 314000
+91 09099 414000

PORTABLE CONCRETE BATCHING PLANT CAP. 10 TO 25 M3/ HR.



Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com

🌐: www.atlastechnologiesindia.com

MFG. OF ROAD & CIVIL CONSTRUCTION MACHINERY

Subject to Mehsana Jurisdiction



DETAIL FORM FOR PORTABLE CONCRETE BATCHING PLANT WITH REVERSIBLE MIXER

BELOW REFERENCE IS 20 M³ PER HOUR

Item 1	four (2/4) bin feeder with individual bin , conveyors, weighing/mixing section & control cabin
Item 2	40 tons cement silo with accessories (Optional)
Item 3	cement feeding system for cement silo(Optional)
Item 4	Plant control system
Item 5	Wiring
Item 6	Supervisory installation and commissioning

TECHNICAL SPECIFICATION

PLANT CAPACITY

For Reference: 20 m³ based on a mixer capacity of 1050/800 litres. Of vibrated concrete per batch 0.5 m³ and at (90) second weigh/mix cycle.

Assuming the following conditions: -

- 1) 100% Plant utilisation
- 2) Material density (2400) Kg/m³

1 INDIVIDUAL 4 BIN FEEDERS CHARGING (WEIGH) CONVEYOR

1.1 AGGREGATE HOPPERS

Feeders	-	Four (4) individual Bin
Capacity	-	4.5 m ³ /each bin
Loading width	-	2.75 meter
Loading height	-	4 meter
Material	-	5 mm thick mild steel plate
Vibrator	-	One (1)
Discharge gates	-	Four (4) pneumatically controlled discharge gates, One gates per hopper



1.2 CHARGING (WEIGH) CONVEYOR

Weigh conveyor	-	Mounted under weigh hoppers
Length	-	4.2 Metres
Belt	-	600 mm wide 4 ply with vulcanised joint
Idlers	-	Troughed bolted to steel section support frame
Drive	-	7.5 HP gear motor unit direct on head shaft
Belt tensioning	-	Tension bolts fitted to tail drum slide bearings
Belt scraper	-	Fitted under head drum
Weigh hopper	-	Manufactured from 3 mm mild steel plate
Weighing capacity		0.7 m ³ total from all hoppers, mounted on load cells
Load cells	-	1000 kg. "S" type - 4 no.
Transfer load capacity		90 Kg. cm ²

1.3 CEMENT WEIGH HOPPERS

Capacity	-	One 450 Kg. load cell mounted
Load cells	-	350 kg. "S" type - 2 no.
Plate thickness	-	3 & 5 mm steel plate
Discharge doors	-	200 mm pneumatically operated butterfly valves with On-Off limit switch
Vibrator	-	0.18 HP vibrating motor
Total inlets	-	Two for optional customer supply flyesh silo / feed screw

1.4 WATER WEIGH HOPPER

Capacity	-	250 litre load cell mounted
Load cells	-	200 kg. "S" type - 2 no.
Plate thickness	-	3 mm mild steel plate
Discharge valve	-	75 mm pneumatically operated butterfly valve with On-Off switch

1.5 ADDITIVE WEIGH HOPPER

Capacity	-	10 liter load cell mounted
Load cells	-	50 kg. "S" type - 1 no.
Material	-	5 mm thick and transparent acrylic dispenser.
Discharge valve	-	Spherical valve operated via actuator



1.6 REVERSIBBLE MIXER (1050/800) – ATLAS MAKE

Mixing drum supplied with Atlas make ready mix concrete plant is carved out extreme precision Keeping in mind that it is subjected to most torture. The flights of the mixing drum are designed to throw out even the smallest particle out of the mixing drum. The drum movement in forward (Clockwise) direction dose the mixing while the drum movement in backward (anti-clockwise) direction aids i discharge of the material. The mixing drum drive motor here is connected to chain wheel drive & V belt pulley. This drives the mixing drum. This helps in minimizing vibrations and is also low on maintenance.

1.7 PNEUMATICS

Compressor	-	3 HP to give 12 Kg. pressure with 10.04 CFM of piston displacement.
Pneumatics	-	Cylinder, Solenoid valves, nylon pipe work and fittings

1.8 UNDER FRAME

Under frame	-	Fabricated rolled steel section chassis
Support jacks	-	8 nos. Fixed supports under chassis.
Loading height	-	1.7 meter clearance under mixer outlet chute

1.9 1.5 TON CEMENT HOPPER

Cement feeding hopper capacity 30 bags (1.5 T) with 219MM X 6000 MM screw conveyor. There are two support lag for screw conveyor mounting.



2

40 T CEMENT SILO (OPTIONAL)

- 2.1 40 Ton Capacity Silo for Cement** With fabricated 4 Column, Cross Bracings, Railing at Top, Climbing Ladder, Seamless Pipe (Dia: 100 mm Seamless pipe for feeding material in silo), Aeration System at Bottom of cone & with other necessary filaments.

2.2 SILO ACCESSORIES (1 set)

Double Flange Butterfly Valve with Cast Iron Disc Dia. 300 mm and Manual Lever for above Butterfly valve	- One unit
Special Dust Collector for Silo Venting	- One unit
Level Indicator 115/230 V/AC Paddle type Rotating	- Two units
Pressure Safety Relief Valve M.O.C. – M– M.S.	- One unit
Vibrating Bin aerator - (1 set inclusive of below items)	
1" Two way valve with coil	- 1 No.
1" Filter regulator with gauge	- 1 No.
Bracket for FRL	- 1 No.
Manifold 1/2" female x 2 outlet.	- 1 No.
Reducer 1" male X 1/2" female.	- 1 No.
1" Nipple-- 3 Nos	
Straight connector 1/2" x 12mm OD	- 4 No.
Equal tee 12mm OD	- 2 No.
PU tube 12mm OD	- 10 Meter
Male elbow 3/8" X 12mm OD	- 4 No.

Transfer screws - 219 mm diameter with 6 metres length cement screw conveyor

3 SILO FEEDING SYSTEM (OPTIONAL)

3.1 Cement feeding compressor for bulk feeding

PLAN
T
CONT

SPECIFICATION	
CAPACITY (FAD)	400(800 M3 / Hr)
PRESSURE	1.0 Kg. / Cm2.
MACHINE SPEED	1450 RPM
POWER AT SHAFT	33.5 K.W.
RECOMM. MOTOR	40 H.P. / 1450 RPM.
TYPE OF DRIVE	V – BELT
TYPE OF COOLING	AIR COOLED

ROL SYSTEM

4

CONTROLS

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com
🌐: www.atlastechnologiesindia.com



- 4.2 CONTROL DESK** - Containing key switches for manual/auto control, manual Start/stop buttons and PLC weigh/mix control system
- 4.3 WEIGH/MIX** - Weighing and mixing control system comprising of:
Operator interface terminal with Sunlight Visible Colour TFT (5.7 INCH) Touch Screen Display (HMI - B&R OR DELTA) Super Bright 850 cd/M3 Display ensures maximum readability with a clear keyboard design and eight multifunction soft keys. Automatic control of the batching process via English interface with unlimited recipe storage. Printer supplied for production logging of essential data from each batch. Production data stored on non-volatile Compact Flash, accessible by USB cable. Network port to allow remote viewing and control of the batching process on customers PC.
- OPTIONAL**
SCADA type control system with Wi-Fi internet attachment facility and also facility to operate plant by mobile / tablet.

5 WIRING

Feeder and mixing unit section of mobile concrete plant is prewired with junction box. And from panel to genset is on customer's scope

GUARDS

Safety guards are provided over all V belt drives, chain drives and gears.

STEELWORK

All welds to be cleaned as necessary, steelwork to be wire brushed and generally cleaned of all mill scale etc before painting.

PAINTING

All external surfaces are chipped and painted with one-coat primer With double coated PU paint.

VOLTAGE

400 Volt, 3 phase, 50 Hz

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com
🌐: www.atlastechnologiesindia.com



Portable Concrete Plant Connected Power

Item	Quantity	HP	Qty.	Power (HP)
1	Reversible Mixer	15	1	15
2	Charging/Weigh conveyor	5	1	5
3	Agg. hopper vibrator	0.25	1	0.25
4	Cement weigh hopper vibrator	0.25	1	0.25
5	Air compressor	2	1	2
6	Water pump	2	1	2
7	Additive motor	1	1	1
8	Screw conveyor 219 mm x 6 meters	6	1	6
			TOTAL	32 HP

Sr. No.	DESCRIPTION	MAKE
1	All other gear boxes	Ingico
2	Screw conveyor	WAM / IVA BULK
3	Motors	Hindustan/ Kirloskar / Crompton
4	Conveyor belt	MRF OR COMPERABLE
5	V belt	Fenner
6	Compressor	Anest Iwata OR Indo Air
7	Pneumatics	SMC
8	Load cell	SENSORTRONICS OR ASI OR KELLY
9	Pedestal bearing	TR
10	Vibrating motors	ISI Standard
11	Silo accessories	IVA BULK OR WAM
12	Water Pump	Kirloskar or kebee

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com
🌐: www.atlastechnologiesindia.com



**Note: We recommend you to buy gen set of 62 kva. For the plant
Main cable size: 25 sq. mm x 3 ½ core armoured copper – Length depending on the
Generator distance.**

Exclusions

Civil works, foundations etc
Mains power supply or generator (for usage of 62 KVA , 3 phases for grid and equivalent generator for power consumption on site)
Mains incoming cable or distribution board
Water supply and incoming pipe work
Aggregate storage hopper grids
Site labour and carnage
Any item not specified

Warranty

The equipment is covered by guarantee under proper use, for faulty material or workman ship for a period of 12 months from the date of dispatch.

Consumable, electric components, rubber components and general wear and tear components are not covered under guarantee.

Purchaser shall inform supplier in writing, of any defect in equipment noticed during guarantee period. On receipt of purchaser's letter, supplier shall at his option, replace or repair free of cost the defective part supplied by him. In case repair is required to be done at works, purchaser shall send such defective part to the works after receiving supplier's confirmation.

We are in no event be liable for any damages whatsoever (including special, incidental consequential, direct or indirect damages, for personal injury, loss of business profits, or any other pecuniary loss) arising out of the use of or inability to use the equipment.

Reg. Off.: Block no.97,
Mehsana-Ahmedabad Highway,
B/h.Bhupendra House,
At & Po. Ditasan-382710,
Dist. Mehsana.[Gujarat] INDIA.

✉: contact@atlastechnologiesindia.com

🌐: www.atlastechnologiesindia.com