
DiWaCS Documentation

Release 0.9.3.1

Nick Eriksson

August 27, 2013

CONTENTS

1	Automated Code Documentation	3
1.1	Add file module	3
1.2	Send file module	3
1.3	Controller package	4
1.4	Dialogs module	9
1.5	DiWaCS module	12
1.6	DiWaVars module	15
1.7	Filesystem module	17
1.8	Graphical Design module	18
1.9	Macro module	20
1.10	Modelsbase module	23
1.11	Models module	24
1.12	Setup module	28
1.13	Models state	29
1.14	SWNP module	31
1.15	Testing module	34
1.16	Threads package	35
1.17	Utils module	40
2	Bugs	41
3	Features	43
4	License	45
4.1	1. Definitions	45
4.2	2. Scope of the rights granted by the Licence	46
4.3	3. Communication of the Source Code	46
4.4	4. Limitations on copyright	46
4.5	5. Obligations of the Licensee	46
4.6	6. Chain of Authorship	47
4.7	7. Disclaimer of Warranty	47
4.8	8. Disclaimer of Liability	47
4.9	9. Additional agreements	48
4.10	10. Acceptance of the Licence	48
4.11	11. Information to the public	48
4.12	12. Termination of the Licence	48
4.13	13. Miscellaneous	48
4.14	14. Jurisdiction	49
4.15	15. Applicable Law	49
4.16	Appendix	49

5	User Interface	51
6	Indices and tables	53
	Python Module Index	55
	Index	57

DiWaCS is an application developed for [DiWa smart space](#) and should be used **only** inside **Diwaamo**. DiWaCS connects to address **239.128.128.1:5555** using [Pragmatic General Multicast \(PGM\)](#). DiWaCS is built on [Python](#) and [WxPython](#) is used for UI programming. Currently, only supported platform is **Windows 7**.

Required python modules for DiWaCS:

- [Configobj](#)
- [lxml](#)
- [PIL](#)
- [PyAudio](#)
- [Python Pubsub](#)
- [SQLAlchemy](#)
- [Watchdog](#)
- [WMI](#)
- [WxPython](#)
- [ZeroMQ](#) with [openpgm](#) support

Contents:

AUTOMATED CODE DOCUMENTATION

Documentation generated on 2013-08-26 at 11:39.

1.1 Add file module

Created on 5.6.2012

platform Windows

synopsis Used to add a file in the current project.

warning Requires ZeroMQ.

author neriksso

`add_file.main()`

Main function of the sub program.

Sub program is meant to be bound to windows explorer context menu. Context menu allows the user to quickly add files to project without interacting with DiWaCS directly.

Transmits the `add_file` command to DiWaCS via interprocess socket.

Parameters `filepath` (*String*) – Path of the file to be added.

Returns windows success code (0 on success).

Return type Integer

1.2 Send file module

Created on 5.6.2012

author neriksso

requires Requires ZeroMQ

synopsis Used to send a file to another node.

`send_file_to.main()`

Main function of the sub program.

Sub program is meant to be bound to windows explorer context menu. Context menu allows the user to quickly send files without interacting with DiWaCS directly.

Transmits the `send_to` command to DiWaCS via interprocess connection.

Parameters

- **node_id** (*Integer*) – ID of the node to send the file to.
- **filepath** (*String*) – Path of the file to be sent.

Returns windows success code (0 on success).

Return type Integer

1.3 Controller package

Used to control the database.

1.3.1 controller.activity module

Created on 28.6.2013

author neriksso

`controller.activity.add_or_update_activity(project_id, pgm_group, session_id=0, activity_id=0)`

Add activity to database or update it if it exists already.

Parameters

- **project_id** (*Integer*) – ID of the project Activity is associated with.
- **pgm_group** (*Integer*) – The PGM Group number.
- **session_id** (*Integer*) – ID of the session Activity is associated with.
- **activity_id** (*Integer*) – ID of the activity.

Returns Activity ID of the added activity.

Return type Integer

`controller.activity.get_active_activity(pgm_group)`

Get the latest active activity.

Parameters **pgm_group** (*Integer*) – The PGM Group number.

Returns Latest active activity.

Return type `models.Activity`

`controller.activity.unset_activity(pgm_group)`

Unsets activity for PGM Group.

Parameters **pgm_group** (*Integer*) – The PGM Group number.

1.3.2 controller.common module

Created on 28.6.2013

author neriksso

`controller.common.delete_record(record_model, id_number)`

Delete a record from database

Parameters

- **record_model** (`sqlalchemy.ext.declarative.declarative_base()`) – The model for which to delete a record.
- **id_number** (*Integer*) – Record id.

Returns Success.

Return type Boolean

`controller.common.get_or_create(model, *filters, **initializers)`

Fetches or creates a instance.

Parameters **model** (`sqlalchemy.ext.declarative.declarative_base()`) – The model of which an instance is wanted.

Filters are given after model and represent the query conditions for get.

Initializers are given after filters and are keyword arguments used for initializing a new object.

Returns An object of the desired model.

Throws `sqlalchemy.exc.SQLAlchemyException`

`controller.common.set_node_name(name)`

Set the stored node name for own swnp node as global.

Warning This should be removed in the future as globals are bad.

`controller.common.set_node_screens(screens)`

Set the stored node screens settings for own swnp node as global.

Warning This should be removed in the future as globals are bad.

`controller.common.test_connection()`

Test the connection to database.

Returns Does the software have access to the database at this time.

Return type Boolean

1.3.3 controller.computer module

Created on 28.6.2013

author neriksso

`controller.computer.add_computer(name, pc_ip, wos_id)`

Add a new computer to the database.

Parameters

- **name** (*String*) – Name of the computer.
- **pc_ip** (*String*) – IP address of the computer.
- **wos_id** (*Integer*) – Node ID of the computer (usually the last part of IP).

Returns The added computer

Return type `models.Computer`

`controller.computer.add_computer_to_session(session, name, pc_ip, wos_id)`

Adds a computer to a session.

Parameters

- **session** (`models.Session`) – A current session.

- **name** (*String*) – A name of the computer.
- **pc_ip** (*Integer*) – Computers IP address.
- **wos_id** (*Integer*) – Wos id of the computer.

Note This is not currently used so consider removing it.

`controller.computer.get_active_computers (timeout, *filters)`

Get all the active computers from database.

Parameters **timeout** (*Integer*) – The number of seconds an “active” computer may have been idle while still being considered active. Default is 10 seconds.

Returns A list of active computers.

Return type List of `models.Computer`

`controller.computer.get_active_responsive_nodes (pgm_group)`

Return the `wos_id` fields of all active responsive nodes.

Parameters **pgm_group** (*Integer*) – The responsive group we want.

Returns A list of node IDs that are both active and responsive.

Return type A list of `Integer`

`controller.computer.last_active_computer ()`

Is the current node last active computer.

Return type `Boolean`

`controller.computer.refresh_computer (computer)`

Refresh the computer in database.

Parameters **computer** (`models.Computer`) – The computer to refresh.

`controller.computer.refresh_computer_by_wos_id (wos_id, new_name=None, new_screens=None, new_responsive=None)`

Refresh the computer by node id and give it optionally new configurations.

Parameters

- **wos_id** (*Integer*) – The ID of the node to refresh.
- **new_name** (*String*) – Optional new name for the node.
- **new_screens** (*Integer*) – Optional new screens configuration for the node.
- **new_responsive** (*Integer*) – Optional new responsive setting for the node.

1.3.4 controller.handlers module

Created on 28.6.2013

author neriksso

class `controller.handlers.PROJECT_EVENT_HANDLER (project_id, handler_type='project')`

Handler for FileSystem events on project folder. It uses watchdog library internally.

Parameters **project_id** (*Integer*) – Project id from database.

1.3.5 controller.project module

Created on 28.6.2013

author neriksso

`controller.project.add_file_to_project (file_path, project_id)`

Add a file to project. Copies it to the folder and adds a record to database.

Parameters

- **file_path** (*String*) – A file_path.
- **project_id** – Project id from database.

Returns New file_path.

Return type String

`controller.project.add_project (data)`

Adds a project to database and returns a project instance

Parameters **data** (*A dictionary*) – Project information

Return type an instance of `models.Project`

`controller.project.check_password (project_id, password)`

Check that the password is correct for accessing a given project.

Note This returns true also if the project does not have password specified as the project is public in that case. The password provided is ignored in this case.

Parameters

- **project_id** (*Integer*) – ID of the project.
- **password** (*String*) – Password to check.

Returns Is the password authorized to access the project.

Type Boolean

`controller.project.create_file_action (path, action_id, session_id, project_id)`

Logs a file action to the database.

Parameters

- **path** (*String*) – Filepath.
- **action_id** (*Integer*) – File action id.
- **session_id** (*Integer*) – Current session id.
- **project_id** (*Integer*) – Project id from database.

`controller.project.edit_project (project_id, row)`

Update the project info.

Parameters

- **project_id** (*Integer*) – Database id number of the project.
- **row** (*A dictionary*) – The new project information.

`controller.project.get_active_project (pgm_group)`

Get the active project.

Parameters **pgm_group** (*Integer*) – The PGM Group number.

Returns Active project ID.

Return type Integer

`controller.project.get_project_id_by_activity(activity_id)`

Get the project ID that this `activity_id` is a part of.

Parameters `activity_id` (*Integer*) – ID of the `activity_id`.

Returns The project ID.

Return type Integer

`controller.project.get_projects_by_company(company_id)`

Fetches projects by a company.

Parameters `company_id` (*Integer*) – A company id from database.

`controller.project.init_sync_project_directory(project_id)`

Initial sync of project dir and database.

Parameters `project_id` (*Integer*) – Project id from database.

`controller.project.is_project_file(filename, project_id)`

Checks, if a file belongs to a project. Checks both project folder and database.

Parameters

- **filename** (*String*) – a filepath.
- **project_id** (*Integer*) – Project id from database.

Return type Boolean

1.3.6 controller.session module

Created on 28.6.2013

author neriksso

`controller.session.add_event(session_id, title, description)`

Adds an event to the database. Returns the ID field of the added event.

Parameters

- **session** (`models.Session`) – The current session.
- **description** (*String*) – Description of the event.

Returns The event ID.

Return type Integer

`controller.session.end_session(session_id)`

Ends a session, sets its endtime to database. Ends file scanner.

Parameters `session` (`models.Session`) – Current session.

`controller.session.get_active_session(pgm_group)`

Get the active session.

Parameters `pgm_group` (*Integer*) – The PGM Group number.

Returns The active session ID.

Return type Integer

```
controller.session.get_latest_event_id()
```

Get the latest event id.

Returns The ID of latest event.

Return type Integer

```
controller.session.get_session_id_by_activity(activity_id)
```

Get the session ID that this activity_id is a part of.

Parameters activity_id (*Integer*) – ID of the activity_id.

Returns The project ID.

Return type Integer

```
controller.session.start_new_session(project_id, old_session_id=None)
```

Creates a session to the database and return a session object.

Parameters

- **project_id** (*Integer*) – Project id from database.
- **old_session_id** (*Integer*) – A session id of a session which will be continued.

1.4 Dialogs module

Created on 4.6.2013

platform Windows Vista, Windows 7, Windows 8

synopsis Define the pop-up dialogs for the application.

note Requires WxPython.

author neriksso

```
class dialogs.AddProjectDialog(parent, title, project_id=None)
```

A dialog for adding a new project

Parameters

- **parent** (*wx.Frame*) – Parent frame.
- **title** (*String*) – A title for the dialog.

OnAdd (*event*)

Handles the addition of a project to database, when “Add” button is pressed.

Parameters event (*Event*) – GUI Event.

OnClose (*event*)

Handles “Close” button presses.

Parameters event (*Event*) – GUI Event.

OnText (*event*)

Event handler for text changed.

```
class dialogs.ChooseDiwaProfileDialog(parent, profiles)
```

Allows user to select a DiWa profile from a list of profiles. Profiles are loaded from the filesystem.

Parameters

- **parent** (*Object*) – The parent object.

- **profiles** (*List*) – List of profiles

Exit (*event*)

Event handler for Exit button press.

Parameters **event** (`wx.Event`) – GUI event.

static ListDatabaseProfiles ()

Returns the list of available profiles.

Returns A list of profiles.

Return type List of Strings

OnComboBox (*event*)

Event handler for updating the state of OK button, depending if there's anything selected in the combo-box.

Parameters **event** (`wx.Event`) – GUI event.

SelectDiwaProfile (*event*)

Load settings from a profile, event handler.

Parameters **event** (`wx.Event`) – GUI event.

exception `dialogs.CloseError` (*args, **kws)

Class describing an error while closing application.

class `dialogs.ConnectionErrorDialog` (*parent*)

Create a connection error dialog that informs the user about reconnection attempts made by the software.

GetResult ()

Try to reconnect and return the outcome.

class `dialogs.DeleteProjectDialog` (*parent, title, project_id*)

A dialog for deleting project.

OnCancel (*event*)

Event handler for pressing Cancel button.

OnOk (*event*)

Event handler for pressing OK button.

class `dialogs.ErrorDialog` (*parent, message*)

Error dialog.

class `dialogs.PreferencesDialog` (*parent, config_object*)

Creates and displays a preferences dialog that allows the user to change some settings.

Parameters **config_object** (`configobj.ConfigObj`) – a Config object

LoadPreferences ()

Load the current preferences and fills the text controls.

OnCancel (*event*)

Closes the dialog without modifications.

Parameters **event** (*Event*) – GUI event.

OpenConfig (*event*)

Opens config file.

Parameters **event** (*Event*) – GUI event.

ReloadConfig (*event*)

Opens config file.

Parameters *event (Event)* – GUI event.

SavePreferences (*event*)
Save the preferences.

Parameters *event (Event)* – GUI Event.

class `dialogs.ProjectAuthenticationDialog` (*parent, title, project_id*)
A dialog for project authentication.

OnOk (*event*)
Called on OK button press.

class `dialogs.ProjectSelectDialog` (*parent*)
A dialog for selecting a project.

Parameters *parent (wx.Frame)* – Parent frame.

OnCancel (*event*)
Handles “Cancel” button presses.

Parameters *event (Event)* – GUI Event.

OnProjectAdd (*event*)
Shows a modal dialog for adding a new project.

Parameters *event (Event)* – GUI Event.

OnProjectDelete (*event*)
Handles the selection of a project. Starts a `wos.CURRENT_PROJECT`, if necessary. Shows a dialog of the selected project.

Parameters *evt (Event)* – GUI Event.

OnProjectEdit (*event*)
Shows a modal dialog for adding a new project.

Parameters *event (Event)* – GUI Event.

OnProjectSelect (*event*)
Handles the selection of a project.

Starts a `wos.CURRENT_PROJECT`, if necessary. Shows a dialog of the selected project.

Parameters *event (Event)* – GUI Event.

OnSelectionChange (*event*)
Event handler for selection change of the listbox.

UpdateProjects (*company_id=1*)
Fetches all projects from the database, based on the company.

Parameters *company_id (Integer)* – A company id, the owner of the projects.

Returns The total number of projects.

Type Integer

class `dialogs.ProjectSelectedDialog` (*parent, project_id*)
A dialog for project selection confirmation.

OnOk (*event*)
Event handler for OK button press.

Parameters *event (wx.Event)* – GUI event.

class `dialogs.SendProgressBar` (*parent, title, ypos*)

Implements file send progress bar...

class `dialogs.UpdateDialog` (*title, url, *args, **kwargs*)

A Dialog which notifies about a software update. Contains the URL which the user can click on.

Parameters

- **title** (*String*) – Title of the dialog.
- **url** (*String*) – URL of the update.

OnOk (*event*)

Event handler for OK button press.

Parameters **event** (`wx.Event`) – GUI event.

UrlHandler (*event*)

Event handler for URL text press.

Parameters **event** (`wx.Event`) – GUI event.

`dialogs.show_modal_and_destroy` (*class_, parent, params=None*)

Used to show modal and destroy afterwards.

Note: The implementation is kind of ugly, but guarantees a safe execution of the dialog without memory leaks and with all exceptions logged.

Parameters

- **class** (*type*) – The type of dialog to show.
- **parent** (`wx.Window`) – The parent `wx.Window` of this object.
- **params** (*Dictionary.*) – The params to give for `__init__` call.

Returns The modal result value.

Return type Integer

1.5 DiWaCS module

Created on 8.5.2012

author neriksso

class `diwacs.EventList` (*parent, *args, **kwargs*)

A Frame which displays the possible event titles and handles the event creation.

CheckVisibility (*selection*)

Checks the visibility.

HideNow ()

Method to hide the event list.

OnEnter (*event*)

Event handler for pressing ENTER button.

Parameters **event** (`wx.Event`) – The `EVT_ON_TEXT_EVENT` event.

OnFocusLost (*event*)

On focus lost event handler.

OnSelection (*event*)
On selection event handler.

OnText (*event*)
On text event handler.

ShowNow ()
Method to show the event list.

class diwacs.**GraphicalUserInterface**
WOS Application Frame.

DisableDirectoryButton ()
Used to disable the project directory button when project has been unselected.

Note: There should be no need for this as the software should always start a new project after the old one ends. But for the mid state to be legitimate this is still usable.

DisableSessionButton ()
Used to disable the needed buttons after session has been stopped.

Note: Does not actually disable the session button, only the session state of the button.

EnableDirectoryButton ()
Used to enable the project directory button when project has been selected.

EnableSessionButton ()
Used to enable the needed buttons after session has been started.

InitUICore ()
Inits the Core UI (`guitemplates.GUItemplate.InitUI()`) and binds the functionality.

OnAboutBox (*event*)
About dialog.

Parameters *event* (*Event*) – GraphicalUserInterface Event.

OnEventButton (*event*)
Event Button handler.

Parameters *event* (*Event*) – GraphicalUserInterface Event.

OnExit (*event*)
Exits program.

Parameters *event* (*Event*) – GraphicalUserInterface Event

OnFocus (*event*)
Event handler for gained focus.

Parameters *event* (`wx.Event`) – GUI event.

OnIconify (*event*)
Window minimize event handler. Should toggle the minimized state of the application.

Parameters *evt* (*Event*) – GraphicalUserInterface Event.

OnInfoBtn (*event*)
Handles the pressing of Web-information button.
Directs the user to web-storage website/help.

OnMBBtn (*event*)

Handles the pressing of meetings browser button.

Directs the user to web-storage website/mb.

OnPreferences (*event*)

Preferences dialog event handler.

Parameters **event** (*Event*) – GraphicalUserInterface Event.

OnProjectChanged ()

Project selected event handler.

OnSession (*event*)

Session button pressed.

The user either desires to start a new session or end an existing one.

Parameters **event** (*Event*) – GraphicalUserInterface Event.

OnTaskBarActivate (*event*)

Taskbar activate event handler.

Parameters **event** (*Event*) – GraphicalUserInterface Event.

OnTaskBarClose (*unused_event*)

Taskbar close event handler.

Parameters **evt** (*Event*) – GraphicalUserInterface Event.

OnWABtn (*event*)

Handles the pressing of Web-application button.

Directs the user to web-storage website.

OpenProjectDir (*event*)

Opens project directory in windows explorer.

Parameters **event** (*Event*) – The GraphicalUserInterface event.

SelectNode (*event*)

Handles the selection of a node, start remote control.

Note: For future use.

Parameters **event** (*Event*) – GraphicalUserInterface Event

SelectProjectDialog (*event*)

Select project event handler.

Parameters **event** (*Event*) – GraphicalUserInterface Event.

SetProjectName (*name*)

Set the project text. For example “No Project Selection”.

Note: Requires None explicitly when the purpose is to set default label because writing SetProjectName(None) is more informative than SetProjectName()

Parameters **name** (*String*) – The name of the project to set as label.

Shift (*event*)

Caroussel Shift function.

Parameters `event` (*Event*) – GraphicalUserInterface Event.

UpdateScreens (*update*)

Called when screens need to be updated and redrawn.

Parameters `update` (*Boolean*) – Pubsub needs one param, therefore it is called update.

`diwacs.main` (*profile*)

Main function.

Warning The profiler has been pre-calibrated using the development machine so this should be changed for other development environments that wish to profile the execution of the diwacs system.

THIS ONLY WORKS WHEN `diwavars.DEBUG` HAS BEEN ENABLED.

Remember to disable it from release binaries.

Parameters `profile` (*Boolean*) – should the call be profiled?

1.6 DiWaVars module

DiWaCS Variables

author neriksso

`diwavars.add_logger_initializer` (*logger_initializer*)

For initializing the loggers from main.

Parameters `logger_initializer` (*function*) – The logger initializer to add to initialize chain.

`diwavars.add_logger_level_setter` (*logger_level_setter*)

For setting application logger level globally.

Parameters `logger_level_setter` (*function*) – The logger level setter to add to level set chain.

`diwavars.print_to_status_box` (*line*)

A function that get's called to print text into the `status_box`. This forwards the function call to the registered function (registered via `register_status_box_callback()`).

Parameters `value` (*String*) – The text to print to the `status_box`.

`diwavars.register_status_box_callback` (*state_func*, *print_func*)

Register a function for changing the state of `status_box` and a function for printing data into the `status_box`.

Parameters

- **state_func** (*Function(Integer)*) – A function that get's called with the new value of `status_box` when the value changes.
- **print_func** (*Function(String)*) – A function that get's called to print text into the `status_box`.

`diwavars.set_blank_cursor` (*value*)

Set the blank cursor variable.

`diwavars.set_config` (*config*)

Set the CONFIG global...

`diwavars.set_default_cursor` (*value*)

Set the default cursor variable.

`diwavars.set_run_cmd` (*value*)

Update the RUN_CMD setting.

Parameters *value* (*Boolean*) – Desired value.

`diwavars.set_running()`

Set the currently running flag as true.

Causes other modules to redirect their stdout and stderr streams to files.

`diwavars.set_using_diwa_profile(value)`

Set variable defining is a profile in use.

`diwavars.update_audio(audio)`

Update the global Audio variable.

`diwavars.update_camera_vars(url, user, passwd)`

Update the global variables that control the camera settings.

`diwavars.update_config_loader(config_loader)`

Set the CONFIG loader function...

`diwavars.update_database_vars(address=None, name=None, type_=None, user=None, password=None)`

Update the global database settings.

`diwavars.update_keys(modifier=91, key=164)`

Update the key combination to stop remote controlling.

Parameters

- **modifier** (*Integer*) – The key to hold.
- **key** (*Integer*) – The key to press while holding modifier key.

`diwavars.update_padfile(padurl)`

Set the padfile address.

`diwavars.update_pgm_group(new_group)`

Update the PGM group for this node.

`diwavars.update_responsive(responsive)`

Update the global responsive setting.

`diwavars.update_status_box(value)`

A function that get's called with the new value of status_box when the value changes. This forwards the function call to the registered function (registered via `register_status_box_callback()`).

Parameters *value* (*Integer*) – The new value of status box.

`diwavars.update_storage(storage)`

Update the address of storage.

Parameters *storage* (*String*) – The new address of storage.

`diwavars.update_variable(name, value)`

Set ANY global value in diwavars.py into **value** (literal_eval).

EXAMPLE:

```
diwavars.update_variable('AUDIO', 'False')
```

Parameters

- **name** (*String*) – The name of the global.
- **value** (*String*) – The new value of the global embedded into a string.

```
diwavars.update_windows_version()
```

Updates the current version information to variables:

- WINDOWS_MAJOR
- WINDOWS_MINOR

1.7 Filesystem module

Created on 17.5.2013

author neriksso

```
filesystem.copy_file_to_project(filepath, project_id)
```

Copy file to project dir and return new filepath in project directory.

Parameters

- **filepath** (*String*) – The file path.
- **project_id** (*Integer*) – Project id from database.

Returns The path for this file in project directory or empty string.

Return type String

```
filesystem.copy_to_temporary_directory(filepath)
```

Copy a file to temporary folder.

Parameters **filepath** (*String*) – The file path.

```
filesystem.create_project_directory(dir_name)
```

Creates a project directory, if one does not exist in the file system

Parameters **dir_name** (*String*) – Name of the directory

```
filesystem.delete_directory(path)
```

Deletes a directory.

Returns Weather the function was successful or not.

Return type String

```
filesystem.get_current_wallpaper(win)
```

Try to get the current wallpaper image path.

Parameters **win** (*Tuple of Integers*) – Windows version (Major, Minor).

Returns Wallpaper image path if it can find it.

Return type String

```
filesystem.get_file_extension(path)
```

Returns the file extension of a file

Parameters **path** (*String*) – The file path.

Return type String

```
filesystem.get_node_image(node)
```

Searches for a node's image in STORAGE.

Parameters **node** (*Integer*) – The node id.

`filesystem.open_file(filepath)`

Opens a file path.

Parameters `filepath` (*String*) – The file path.

`filesystem.save_screen(filepath)`

Saves the background image of the desktop.

Parameters `filepath` (*String*) – The filepath for the saved image.

`filesystem.screen_capture(path, node_id)`

Take a screenshot and store it in project folder.

Parameters

- **path** (*String*) – Path to the project folder.
- **node_id** (*Integer*) – NodeID

`filesystem.search_file(filename, search_path, case_sensitive=True)`

Search file in a given path.

Parameters

- **filename** (*String*) – The file name.
- **search_path** (*String*) – The search path.

Returns The path to the file.

Return type `String`

`filesystem.test_storage_connection()`

Try to access \StorageProjects

Returns Does the path exist.

Return type `Boolean`

1.8 Graphical Design module

Created on 6.6.2013

author neriksso

synopsis This file represents graphical designs of some GUI elements in DiWaCS.

class `graphicaldesign.BlackOverlay(pos, size, parent, text)`

Represents all black frame without a mouse.

OnFocusLost (*evt*)

Event handler for focus losing of the window.

Parameters `evt` (`wx.Event`) – The focus lost event.

SetText (*button_modifier=None, button=None*)

Sets the text that appears on the black overlay.

Parameters

- **button_modifier** (*String*) – The button name that should be held down.
- **button** (*String*) – The button name that should be pressed when the modifier key is held down.

class `graphicaldesign.DropTarget` (*window, parent, i*)
 Implements drop target functionality to receive files, bitmaps and text.

OnData (*x, y, d*)
 Handles drag/dropping files/text or a bitmap.

Parameters

- **x** (*Integer*) – The x coordinate of the drop-location.
- **y** (*Integer*) – The y coordinate of the drop-location.
- **d** – The data of drop.

class `graphicaldesign.EventListTemplate` (*parent, *args, **kwargs*)
 Represents an event list menu.

GetProgramIcon (*icon*)
 Fetches gui icons.

Parameters **icon** (*String*) – The icon file name.

Return type `wx.Image`

class `graphicaldesign.GUItemplate` (**args, **kwargs*)
 Represents the main GUI window graphical template.

Parameters

- **parent** (`wx.Window`) – Parent frame.
- **id** (*Integer*) – ID of the new Frame.
- **title** (*String*) – Title for the frame, default = EmptyString.
- **pos** (`wx.Point`) – Position of the new frame.
- **size** (`wx.Size`) – Size of the new frame.
- **style** (*long*) – Style flags for the new frame.
- **name** (*String*) – Name of the new frame.

AlignCenterTop ()
 Aligns frame to Horizontal center and vertical top.

ConnectionErrorHandler (*error*)
 Show connection error handler dialog.

GetProgramIcon (*icon*)
 Fetches a GUI icon.

Parameters **icon** (*String*) – The icon file name.

Return type `wx.Image`

HideScreens ()
 Hides all screens.

InitScreens ()
 Inits Screens.

InitUI (*node_id*)
 UI initializing.

Parameters **node_id** (*Integer*) – The id of current swnp node (self).

OnExit (*event*)

Exits program.

Parameters *event* (*Event*) – GUI Event

SelectNode (*evt*)

Handles the selection of a node, prototype.

Parameters *evt* (*Event*) – GUI Event

class graphicaldesign.**MySplashScreen** (*parent=None*)
Create a splash screen widget.

class graphicaldesign.**NodeScreen** (*node, parent*)
Represents a bitmap with node id.

EmptyScreen ()

Make this screen EmptyScreen.

ReloadAs (*node*)

Reload the content of this bitmap.

SetNodeVars ()

Sets NodeScreens variables.

static update_bitmaps ()

Load the static bitmaps for hidden and wallpaperless screens. This caches them in memory to be used later without IO calls.

class graphicaldesign.**SysTray** (*parent*)
Taskbar Icon class.

Parameters *parent* (*wx.Frame*) – Parent frame

CreateMenu ()

Create systray menu.

ShowMenu (*event*)

Show popup menu.

Parameters *event* (*Event*) – GUI event.

ShowNotification (*title, message*)

Start a thread to show the notification.

Parameters

- **title** (*Unicode*) – Title to display in the balloon.
- **message** (*Unicode*) – Message to display in the balloon (max 255 chars).

1.9 Macro module

author neriksso

synopsis macro.py defines a few user input functions.

macro.GetKeydown (*code*)

Check if the key with keycode is held down.

Parameters *code* (*Integer*) – Keycode of the key.

class `macro.HardwareInput`
Docstring here.

class `macro.Input`
Docstring here.

class `macro.Input_I`
Docstring here.

class `macro.KeyBdInput`
Docstring here.

class `macro.MacroPoint`
Stores the x and y components of coordinates.

Attribute `x` `c_ulong`

Attribute `y` `c_ulong`

class `macro.MouseInput`
Docstring here.

`macro.click()`
Send a mouse click_type: LeftButton down, LeftButton up.

`macro.get_mouse_position()`
Return the current position of the mouse.

Returns The position of the mouse.

Return type `MacroPoint`

`macro.get_sendkeys(code)`
Returns a character for a key code.

Parameters `code` (*Integer*) – The character code.

`macro.hold()`
Send a mouse hold: LeftButton down.

`macro.key_press(event, kcode)`
Used to send a single virtual keycode to the system.

Parameters

- **event** (`wx.Event`) – Captured key event.
- **kcode** (*Integer*) – Keycode.

`macro.middle_click()`
Send a mouse middle click_type: MiddleButton down, MiddleButton up.

`macro.middle_hold()`
Send a mouse middle click_type: MiddleButton down.

`macro.middle_release()`
Send a mouse middle click_type: MiddleButton up.

`macro.move(pos_x, pos_y)`
move the cursor for pos_x amount in horizontal direction and pos_y amount in vertical direction.

Parameters

- **pos_x** (*Integer*) – Amount to move in horizontal direction.
- **pos_y** (*Integer*) – Amount to move in vertical direction.

`macro.move_to(pos_x, pos_y)`
move the mouse cursor to point (pos_x, pos_y) on screen.

Parameters

- **pos_x** (*Integer*) – X coordinate of the desired position.
- **pos_y** (*Integer*) – Y coordinate of the desired position.

`macro.release()`
Send a mouse release_type: LeftButton up.

`macro.release_all_keys()`
Reset every keycode state to UP state.

`macro.right_click()`
Send a mouse right click_type: RightButton down, RightButton up.

`macro.right_hold()`
Send a mouse right hold: RightButton down.

`macro.right_release()`
Send a mouse right release_type: RightButton up.

`macro.send_input(intype, data, flags, scan=0, mouse_data=0)`
send_input sends virtual user input.

Parameters

- **intype** (*String*) – Input type, either 'mouse_input' for mouse input or 'key_input' for keyboard input.
- **data** (*Integer or (Integer, Integer)*) – Input data, keycode to input or a tuple of (x, y) for mouse.
- **flags** (*Integer*) – Input flags, used to separate keyup and keydown events.
- **scan** (*Integer*) – Input scancode. More info in: <http://en.wikipedia.org/wiki/Scancode>
- **mouse_data** (*Integer*) – Represents additional information about mouse events for example wheel amount.

`macro.slide(difference_x, difference_y)`
slide the mouse for difference_x amount in horizontal direction and difference_y amount in vertical direction.

Parameters

- **difference_x** (*Integer*) – The amount to slide in horizontal direction.
- **difference_y** (*Integer*) – The amount to slide in vertical direction.

`macro.slide_to(target_x, target_y, speed='normal')`
Slides the mouse to point (target_x, target_y)

Parameters

- **target_x** (*Integer*) – The target X coordinate.
- **target_y** (*Integer*) – The target Y coordinate.
- **speed** (*String*) – The speed of motion 'slow', 'normal' or 'fast'.

1.10 Modelsbase module

Created on 31.6.2013

author neriksso

note Requires `sqlalchemy`

synopsis Defines and constructs the SQL alchemy Base class.

exception `modelsbase.ItemAlreadyExistsException` (*message*)

When the item already exists in the database, you need to use get method instead of constructor.

class `modelsbase.MethodMixin`

A base class for all our DiWa models.

Defines some common methods / use cases of SQLAlchemy.

delete ()

Delete an object of this class from the database.

classmethod `delete_many` (*instances*)

Delete objects of this class from the database.

classmethod `get` (*method*, **filters*)

Parameters *method* (*String*) –

Valid values are:

- all - This returns a list of matching objects.
- count - This returns an integer which represents the count of matching objects.
- delete - This deletes all the matching objects from the database.
- exists - This returns boolean informing weather the an object match was found from the database.
- first - This returns the first matching object.
- last - This returns the last matching object.
- one - This returns the object if it exists and raises an exception if it doesn't or if there's more than one instance of the desired object.

Additional parameters may be specified to filter results.

classmethod `get_by_id` (*id_=1*)

Gets the instance of model by ID.

Parameters *id* (*Integer*) – ID of the desired model.

classmethod `id_ordering` (*instance*)

Key function for id ordering.

update ()

Posts updates to this object into the database.

Returns Success value.

Return type Boolean

classmethod `update_many` (*instances*)

Posts updates to these objects into the database.

Returns Success value.

Return type Boolean

`modelsbase.connect_to_database(expire=False)`

Connect to the database and return a Session object.

Parameters `expire` (*Boolean*) – Parameter passed to session maker as `expire_on_commit`.

Returns Session.

Return type `sqlalchemy.orm.session.Session`

`modelsbase.create_all()`

Create tables to the database.

`modelsbase.update_database()`

Update the database connection engine.

Note: This only works when `DB_STRING` is completely defined by the log reader as otherwise the `create_engine` call would cause an exception.

1.11 Models module

Created on 23.5.2012

author neriksso

note Requires `sqlalchemy`

synopsis Defines and constructs the SQL alchemy Base class.

class `models.Action(name)`

A class representation of a action. A file action uses this to describe the action.

Field:

- `id` (`sqlalchemy.schema.Column(Integer)`) - ID of the action, used as primary key in database table.
- `name` (`sqlalchemy.schema.Column(String)`) - Name of the action (Max 50 characters).

Parameters `name` (*String*) – Name of the action.

class `models.Activity(project, session=None)`

A class representation of an activity.

Fields:

- `id` (`sqlalchemy.schema.Column(Integer)`) - ID of activity, used as primary key in database table.
- `session_id` (`sqlalchemy.schema.Column(Integer)`) - ID of the session activity belongs to.
- `session` (`sqlalchemy.orm.relationship`) - Session relationship.
- `project_id` (`sqlalchemy.schema.Column(Integer)`) - ID of the project activity belongs to.
- `project` (`sqlalchemy.orm.relationship`) - Project relationship.
- `active` (`sqlalchemy.schema.Column(Boolean)`) - Boolean flag indicating that the project is active.

Parameters

- **project** (`models.Project`) – Project activity belongs to.
- **session** (`models.Session`) – Optional session activity belongs to.

class `models.Company` (*name*)

A class representation of a company.

Fields:

- `id` (`sqlalchemy.schema.Column(Integer)`) - ID of the company, used as primary key in database table.
- `name` (`sqlalchemy.schema.Column(String)`) - Name of the company (Max 50 characters).

Parameters `name` (`String`) – The name of the company.

class `models.Computer` (*name, ip, mac, screens, responsive, pgm_group, wos_id*)

A class representation of a computer.

Fields:

- `id` (`sqlalchemy.schema.Column(Integer)`) - ID of computer, used as primary key in database table.
- `name` (`sqlalchemy.schema.Column(String)`) - Name of the computer.
- `ip` (`sqlalchemy.schema.Column(Integer)`) - Internet Protocol address of the computer (Defined as unsigned).
- `mac` (`sqlalchemy.schema.Column(String)`) - Media Access Control address of the computer.
- `time` (`sqlalchemy.schema.Column(DateTime)`) - Time of the last network activity from the computer.
- `screens` (`sqlalchemy.schema.Column(SmallInteger)`) - Number of screens on the computer.
- `responsive` (`sqlalchemy.schema.Column(SmallInteger)`) - The responsive value of the computer.
- `user_id` (`sqlalchemy.schema.Column(Integer)`) - ID of the user currently using the computer.
- `user` (`sqlalchemy.orm.relationship`) - The current user.
- `wos_id` (`sqlalchemy.schema.Column(Integer)`) - Network node ID, usually the last part of IP address (X.X.X.Y).

classmethod `get_most_recent_by_mac` (*mac_address*)

Retrieve a computer by it's hardware identifier.

classmethod `time_ordering` (*computer*)

Key function for time ordering.

class `models.Event` (*session_id, title='', description=''*)

A class representation of Event. A simple note with timestamp during a session.

Fields:

- `id` (`sqlalchemy.schema.Column(Integer)`) - ID of the event, used as primary key in database table.

- `title (sqlalchemy.schema.Column(String))` - Title of the event (Max 40 characters).
- `desc (sqlalchemy.schema.Column(String))` - More in-depth description of the event (Max 500 characters).
- `time (sqlalchemy.schema.Column(DateTime))` - Time the event took place.
- `session_id (sqlalchemy.schema.Column(Integer))` - ID of the session this event belongs to.
- `session (sqlalchemy.orm.relationship)` - Session this event belongs to.

class `models.File` (*path, project_id=None*)

A class representation of a file.

Fields:

- `id (sqlalchemy.schema.Column(Integer))` - ID of the file, used as primary key in database table.
- `path (sqlalchemy.schema.Column(String))` - Path of the file on DiWa (max 255 chars).
- `project_id (sqlalchemy.schema.Column(Integer))` - ID of the project this file belongs to.
- `project (sqlalchemy.orm.relationship)` - Project this file belongs to.

class `models.FileAction` (*file_, action, session=None, computer=None, user=None*)

A class representation of a file action.

Fields:

- `id (sqlalchemy.schema.Column(Integer))` - ID of the FileAction, used as primary key in the database table.
- `file_id (sqlalchemy.schema.Column(sqlalchemy.types.Integer))` - ID of the file this FileAction affects.
- `file (sqlalchemy.orm.relationship)` - The file this FileAction affects.
- `action_id (sqlalchemy.schema.Column(Integer))` - ID of the action affecting the file.
- `action (sqlalchemy.orm.relationship)` - Action affecting the file.
- `action_time (sqlalchemy.schema.Column(DateTime))` - Time the action took place on.
- `user_id (sqlalchemy.schema.Column(Integer))` - ID of the user performing the action.
- `user (sqlalchemy.orm.relationship)` - User performing the action.
- `computer_id (sqlalchemy.schema.Column(Integer))` - ID of the computer user performed the action on.
- `computer (sqlalchemy.orm.relationship)` - Computer user performed the action on.
- `session_id (sqlalchemy.schema.Column(Integer))` - ID of the session user performed the action in.
- `session (sqlalchemy.orm.relationship)` - Session user performed the action in.

Parameters

- **file** (`models.File`) – The file which is subjected to the action.
- **action** (`models.Action`) – The action which is applied to the file.
- **session** (`models.Session`) – The session in which the FileAction took place on.

- **computer** (`models.Computer`) – The computer from which the user performed the action.
- **user** (`models.User`) – The user performing the action.

class `models.Project` (*name, directory, company, password*)

A class representation of a project.

Fields:

- `id` (`sqlalchemy.schema.Column(Integer)`) - ID of project, used as primary key in database table.
- `name` (`sqlalchemy.schema.Column(String)`) - Name of the project (Max 50 characters).
- `company_id` (`sqlalchemy.schema.Column(Integer)`) - ID of the company that owns the project.
- `company` (`sqlalchemy.orm.relationship`) - The company that owns the project.
- `dir` (`sqlalchemy.schema.Column(String)`) - Directory path for the project files (Max 255 characters).
- `password` (`sqlalchemy.schema.Column(String)`) - Password for the project (Max 40 characters).
- `members` (`sqlalchemy.orm.relationship`) - The users that work on the project.

Parameters

- **name** (`String`) – Name of the project.
- **directory** (`String`) – The location of project on disc.
- **company** (`models.Company`) – The owner of the project.
- **password** (`String`) – The project password.

class `models.Session` (*project, previous_session=None*)

A class representation of a session.

Fields:

- `id` (`sqlalchemy.schema.Column(Integer)`) - ID of session, used as primary key in database table.
- `name` (`sqlalchemy.schema.Column(String)`) - Name of session (Max 50 characters).
- `project_id` (`sqlalchemy.schema.Column(Integer)`) - ID of the project the session belongs to.
- `project` (`sqlalchemy.orm.relationship`) - The project the session belongs to.
- `starttime` (`sqlalchemy.schema.Column(DateTime)`) - Time the session began, defaults to `now()`.
- `endtime` (`sqlalchemy.schema.Column(DateTime)`) - The time session ended.
- `previous_session_id` (`sqlalchemy.schema.Column(Integer)`) - ID of the previous session.
- `previous_session` (`sqlalchemy.orm.relationship`) - The previous session.
- `participants` (`sqlalchemy.orm.relationship`) - Users that belong to this session.
- `computers` (`sqlalchemy.orm.relationship`) - Computers that belong to this session.

Parameters `project` (`models.Project`) – The project for the session.

AddUser (`user`)

Add users to a session.

Parameters `user` (`models.User`) – User to be added into the session.

GetLastChecked ()

Fetch `last_checked` field.

Returns `last_checked` field (None before `models.Session.start()` is called).

Return type `datetime.datetime` or None

Start ()

Start a session. Set the `last_checked` field to current `DateTime`.

class `models.User` (`name`, `company`, `email=None`, `title=None`, `department=None`)

A class representation of a user.

Note Currently not used anywhere.

Fields:

- `id` (`sqlalchemy.schema.Column(Integer)`) - ID of the user, used as primary key in database table.
- `name` (`sqlalchemy.schema.Column(String)`) - Name of the user (Max 50 characters).
- `email` (`sqlalchemy.schema.Column(String)`) - Email address of the user (Max 100 characters).
- `title` (`sqlalchemy.schema.Column(String)`) - Title of the user in the company (Max 50 characters).
- `department` (`sqlalchemy.schema.Column(String)`) - Department of the user in the company (Max 100 characters).
- `company_id` (`sqlalchemy.schema.Column(Integer)`) - Company id of the employing company.
- `company` (`sqlalchemy.orm.relationship`) - Company relationship.

Parameters

- **name** (`String`) – Name of the user.
- **company** (`models.Company`) – The employer.

1.12 Setup module

Created on 8.5.2012

author nick26

synopsis This file is used to compile a DiWaCS.exe file out of the python project using py2exe and setuptools packages available at: pypi.python.org/pypi/setuptools

1.13 Models state

Created on 4.7.2013

author neriksso

exception `state.SessionChangeException`

A stub for new Exception that just had a different type to be catchable in its own right.

class `state.State` (*parent*)

Used to represent the state of the client.

All the graphical buttons etc have been removed from here and they are part of the main `GraphicalUserInterface` class right now. Likewise that class should minimize making direct changes to the current status of the software and only interpret user input.

append_swnp_data (*new_data*)

Append data to current data value for `swnp.Node`

Parameters *new_data* (*String*) – Value to be added

destroy ()

Part of the shutdown routine, closes all the threads under this.

end_current_project ()

End the current project.

end_current_session ()

End the current session.

get_random_responsive ()

Get a random node amongst all the responsive nodes.

get_swnp_data ()

Returns the data value for `swnp.Node`

handle_file_send (*filenames*, *dialog_parameters=None*)

Sends a file link to another node.

First parses all the files and folder structure, then confirms weather the users wishes to add the items to project before beginning the copy routine.

The copy routine first creates all the needed sub-folders and then sums up all the file sizes to be copied. Then it will update the dialog in the beginning/end of every file transaction and whenever there's been more than 1 second from the last update dialog update. Assuming the `dialog_parameters` parameter has been given.

The progress dialog, if supplied, is updated as follows:

- If there's less than `DEF_FILES (40)` files the dialog will not be shown or updated.
- If the data size sum is less than `DEF_SIZE (2 MB)` the dialog will not be shown or updated.
- Title will contain the total percentage of data transfer.
- Message will contain the percentage of current file transfer.
- Progress bar is set to percent [0, 100] of the total data transfer.

Parameters

- **filenames** (*List of String*) – All the files/folders to be copied.

- **dialog_parameters** (*dict*) – The progress dialog to create by `show_modal_and_destroy`, initialization parameters in a dictionary.

initialize ()

Finish the initialization (2-stage init).

Note As this is not so essential, we could just stick it up to the `__init__` but there might be something that needs to be done in between the `__init__` and these calls here.

message_handler (*message*)

Message handler for received messages.

Parameters *message* (*String*) – Received message.

on_project_selected ()

Event handler for project selection in the client.

on_session_changed (*desired_state*)

Event handler for session change in the client.

remove_from_swnp_data (*old_data*)

Removes data value from current data value for `swnp.Node`

Parameters *old_data* (*String*) – Old data value

remove_observer ()

Docstring.

send_pop_clipboard (*target_node_id*)

Sends a command to another node that they should restore their old clipboard content and send the over-written content back to this node.

Parameters *target_node_id* (*Integer*) – The ID of the node that should perform the operation.

send_push_clipboard (*target_node_id*)

Sends a command to another node that they should save their clipboard content and set the current content to what this node has on its clipboard at this moment.

Parameters *target_node_id* (*Integer*) – The ID of the node that should perform the operation.

set_current_project (*project_id*)

Start current project loop.

Parameters *project_id* (*Integer*) – The project id from database.

set_current_session (*session_id*)

Set current session.

Parameters *session_id* (*Integer*) – a session id from database.

set_observer ()

Set an observer for file changes in project directory and and observer for image uploads by camera in scan folder.

set_responsive ()

Set the current node as responsive.

set_swnp_data (*data*)

Set data value for `swnp.Node`

Parameters *data* (*String*) – New data value

start_audio_recorder ()

Starts the audio recorder thread.

start_current_project_thread()

Start current project loop.

start_current_session_thread()

Start current project loop.

start_new_session()

Start a new session.

stop_responsive()

Stop being responsive.

swnp_send(*node*, *message*)

Sends a message to the node.

Parameters

- **node** (*String*) – The node for which to send a message.
- **message** (*String*) – The message.

state.create_config()

Creates a config file.

This actually just copies the default one from installation folder to the ~wos settings folder.

state.initialization_test()

Used to test that we have are good to go.

At this time only includes test_connection() from controller, but more tests could be added here.

state.load_config()

Loads a config file, creating it if it does not exists.

1.14 SWNP module

Created on 30.4.2012

author neriksso

class `swnp.Message` (*tag*, *prefix*, *payload*)

A class representation of a Message.

Messages are divided into three parts: tag, prefix, payload. Messages are encoded to json for transmission.

Parameters

- **tag** (*String*) – tag of the message.
- **prefix** (*String*) – prefix of the message.
- **payload** (*String*) – payload of the message.

static from_json (*json_dict*)

Return a message from json.

Parameters `json_dict` (*json*) – The json.

Returns Initializes a message from JSON object.

Return type `swnp.Message`.

static to_dict (*msg*)

Return a message in a dict.

Parameters `msg` (`swnp.Message`) – The message.

Returns Dictionary representation of the message.

Return type Dict

class `swnp.Node` (`node_id`, `screens`, `name=None`, `data=None`)

A class representation of a node in the network.

Parameters

- **node_id** (*Integer*) – Node id.
- **screens** (*Integer*) – Amount of visible screens.
- **name** (*String*) – The name of the node.

data

Returns data.

get_age ()

Return the elapsed time since last refresh.

refresh ()

Updates the timestamp.

class `swnp.SWNP` (`pgm_group`, `screens=0`, `name=None`, `context=None`, `error_handler=None`)

The main class of swnp.

This class has the required ZeroMQ bindings and is responsible for communicating with other instances.

Warning: Only one instance per computer
--

Parameters

- **pgm_group** (*Integer*) – The Multicast Group this node wants to be a part of.
- **screens** (*Integer*) – The number of visible screens. Defaults to 0.
- **name** (*String*) – The name of the instance.
- **context** (`zmq.Context`) – ZeroMQ context to use.
- **error_handler** (`wos.CONN_ERR_TH`) – Error handler for the init constructor.

close ()

Closes all connections and exits.

do_ping ()

Send a PING message to the network.

find_node (`node_id`)

Search the node list for a specific node.

Parameters `node_id` (*Integer*) – The id of the searched node.

Return type `swnp.Node`

get_list ()

Returns a list of all nodes

Return type list

get_screen_list ()

Returns a list of screens nodes.

Return type list.

ping_handler (*payload*)

A handler for PING messages. Sends update_screens, if necessary.

Parameters **payload** (*String*) – The payload of a PING message.

ping_routine (*error_handler*)

A routine for sending PING messages at regular intervals.

send (*tag, prefix, message*)

Send a message to the network.

Parameters

- **tag** (*String*) – The tag of the message; recipient.
- **prefix** (*String*) – The prefix of the message.
- **message** (*String*) – The payload of the message.

set_name (*name*)

Sets the name for the instance.

Parameters **name** (*String*) – New name of the instance.

set_responsive (*responsive*)

Sets the responsive flag for the instance.

Parameters **responsive** (*Integer*) – New number of screens.

set_screens (*screens*)

Sets the number of screens for the instance.

Parameters **screens** (*Integer*) – New number of screens.

shutdown ()

Shuts down all connections, no exit.

static start_sub_routine (*target, routine, name, args*)

A wrapper for starting up subroutine threads.

Parameters

- **target** (*threading.Thread*) – Variable that contains the current thread for routine.
- **routine** – The routine to run.
- **name** (*String*) – Name of the routine.
- **args** (*List*) – Arguments for the routine.

Returns The thread of subroutine.

Return type *threading.Thread*

sub_routine (*sub_urls*)

Subscriber routine for the node ID.

Parameters **sub_urls** (*List of Strings*) – Subscribing URLs.

sub_routine_sys (*sub_urls*)

Subscriber routine for the node ID.

Parameters **sub_urls** (*List of Strings*) – Subscribing URLs.

sys_handler (*msg*)

Handler for “SYS” messages.

Parameters **msg** (*swnp.Message*) – The received message.

timeout_routine()

Routine for checking node list and removing nodes with timeout.

update_pgm_group(*new_pgm_group*)

This updates the PGM group on the fly.

Parameters

- **new_pgm_group** – New PGM Group value.
- **new_pgm_group** – Integer

1.15 Testing module

Created on 20.5.2013

author Kristian

class `testing.CallAbsorber`

Substitute for GUIs.

class `testing.TestAudioRecorder` (*methodName='runTest'*)

Test audio recorder module.

setUp()

Set up the audio recorder helpers for testing.

tearDown()

Stub to add cleaners in.

test_record()

Test recording functionality of AudioRecorder.

class `testing.TestDiwa`

Container for unittest cases.

run (*result, debug=False*)

Run the unittest.

class `testing.TestDocumentation` (*methodName='runTest'*)

Test that every Python function has been documented.

setUp()

Stub to add helpers in.

tearDown()

Stub to add cleaners in.

test_documentation()

Test that most of the code has been documented.

Note The algorithm that calculates the documentation percentage is not perfect but kind of works. It could be improved by using actual parser (and pylint even does the same) but this makes it an actual testcase.

This also prints out the missed lines where there should have been documentation (doc-strings) and prints the total percentage of the project documented.

This test fails if the percentage is lower than a hard-coded expected value. That value defaults to 95% at this moment.

```
class testing.TestFilesystem (methodName='runTest')
    Test filesystem module.

    setUp ()
        Stub to add helpers in.

    tearDown ()
        Stub to add cleaners in.

    test_searchfile ()
        Test searchfile function.

class testing.TestUtils (methodName='runTest')
    Test utils module.

    setUp ()
        Stub to add helpers in.

    tearDown ()
        Stub to add cleaners in.

    test_iterislast ()
        Test IterIsLast function.
```

1.16 Threads package

Set of threading functionality.

1.16.1 threads.audiorecorder module

Created on 5.6.2013

author neriksso

```
class threads.audiorecorder.AudioRecorder (parent)
    A thread for capturing audio continuously. It keeps a buffer that can be saved to a file. By convention AudioRecorder is usually written in mixed case even as we prefer upper case for threading types.

    Parameters parent (diwacs.GraphicalUserInterface) – Parent of the thread.

    find_input_device ()
        Find a microphone device.

    open_mic_stream ()
        Opens the stream object for microphone.

    run ()
        Continuously record from the microphone to the buffer.

        The size should be limited at diwavars.MAX_LENGTH constant. The implementation keeps only the most recent data in the case that there's too much data to store.

    save (event_id, path)
        Save the buffer to a file.

    stop ()
        Stop the audio recorder thread.
```

1.16.2 threads.checkupdate module

Created on 5.6.2013

author neriksso

class threads.checkupdate.CHECK_UPDATE

Thread for checking version updates.

static get_pad()

Returns the padfile object using PAD_URL setting.

Returns A Filelike object with additional methods geturl(), info() and getcode().

run()

Returns weather the update checking was successful.

Return type Boolean

show_dialog(url)

Shows the dialog that prompts the user to download newer version of the software.

Parameters url (*String*) – URL address of the new version.

1.16.3 threads.common module

Created on 5.6.2013

author neriksso

1.16.4 threads.connectionerror module

Created on 5.6.2013

author neriksso

class threads.connectionerror.CONNECTION_ERROR_THREAD(parent)

Thread for checking connection errors.

Parameters parent (*wx.Frame*) – Parent object.

run()

Starts the thread.

1.16.5 threads.contextmenu module

Created on 27.6.2013

author neriksso

class threads.contextmenu.ContextMenuFailure(*self*, *EventType* type=wxEVT_NULL, *int* winid=0)

Represents a failure of CMFH initialization.

class threads.contextmenu.SEND_FILE_CONTEX_MENU_HANDLER(*parent*, *context*, *send_file*, *handle_file*)

Thread for OS context menu actions like file sending to other node.

Parameters

- **context** (*zmq.Context*) – ZeroMQ Context for creating sockets.

- **send_file** (*Function*) – Sends files.
- **handle_file** (*Function*) – Handles files.

run ()
Starts the thread.

stop ()
Stops the thread.

1.16.6 threads.current module

Created on 27.6.2013

author neriksso

class threads.current.**CURRENT_PROJECT** (*swnp*)

Thread for transmitting current project selection. When user selects a project, an instance is started. When a new selection is made, by any DiWaCS instance, the old instance is terminated.

Parameters

- **project_id** (*Integer*) – Project id from the database.
- **swnp** (*swnp.SWNP*) – SWNP instance for sending data to the network.

run ()
Starts the thread.

class threads.current.**CURRENT_SESSION** (*swnp*)

Thread for transmitting current session id, when one is started by the user. When the session is ended, by any DiWaCS instance, the instance is terminated.

Parameters

- **session_id** (*Integer*) – Session id from the database.
- **swnp** (*swnp.SWNP*) – SWNP instance for sending data to the network.

run ()
Starts the thread.

1.16.7 threads.diwathread module

Created on 5.6.2013

author neriksso

class threads.diwathread.**DIWA_THREAD** (*target=None, name=None, args=(), kwargs=None*)

Doc string here.

remove_self ()
Removes self from the thread list, this should be used only when the thread is sure to die soon.

stop ()
Stop the thread.

static stop_all ()
Stop all program threads except the calling one.

stop_is_set ()
Is the thread supposed to stop.

exception `threads.diwathread.TimeoutException (message)`
Represents a thread timeout event.

1.16.8 threads.inputcapture module

Created on 5.6.2013

author neriksso

class `threads.inputcapture.INPUT_CAPTURE (parent, swnp)`
Thread for capturing input from mouse/keyboard.

Parameters

- **parent** (GUI) – Parent instance.
- **swnp** (`swnp.SWNP`) – SWNP instance for sending data to the network.

hook ()
Add the input hooks to the system.

on_keyboard_event (*event*)
Called when keyboard events are received.

on_mouse_event (*event*)
Called when mouse events are received.

- WM_MOUSEFIRST = 0x200
- WM_MOUSEMOVE = 0x200
- WM_LBUTTONDOWN = 0x201
- WM_LBUTTONUP = 0x202
- WM_LBUTTONDBLCLK = 0x203
- WM_RBUTTONDOWN = 0x204
- WM_RBUTTONUP = 0x205
- WM_RBUTTONDBLCLK = 0x206
- WM_MBUTTONDOWN = 0x207
- WM_MBUTTONUP = 0x208
- WM_MBUTTONDBLCLK = 0x209
- WM_MOUSEWHEEL = 0x20A
- WM_MOUSEHWHEEL = 0x20E

reset_mouse_events ()
Clear the mouse event queue.

run ()
Starts the thread.

stop ()
Stops the thread.

unhook ()
Remove the input hooks from the system.

class `threads.inputcapture.MOUSE_CAPTURE` (*parent*, *swnp*)

A thread for capturing mouse movements and sending them to remote controlled systems.

Parameters

- **parent** (`diwacs.GraphicalUserInterface`) – The main GUI.
- **swnp** (`swnp.SWNP`) – The network handler.

parse_mouse_events ()

Routine that constantly parses mouse events in the queue.

`threads.inputcapture.set_capture` (*value*)

Set's the capture value for threads.

Parameters **value** (*Boolean*) – Is the capture on.

1.16.9 threads.worker module

Created on 27.6.2013

author neriksso

class `threads.worker.SNAPSHOT_THREAD` (*path*)

Worker thread for taking snapshot.

Parameters **path** (*String*) – File path where to store the snapshot.

run ()

Worker procedure for storing the snapshot.

Warning: This object has a timeout of 1 minute. So consider terminating the thread on shutdown if it's hanging.

class `threads.worker.WORKER_THREAD` (*parent*)

Worker thread for non-UI jobs.

Parameters **parent** – The GUI object.

static add_project_registry_entry (*reg_type*)

Adds “Add to project” context menu item to registry. The item will be added to Software-Classes<reg_type>, where <reg_type> can be e.g. ‘*’ for all files or ‘Folder’ for folders.

Parameters **reg_type** (*String*) – Registry type.

static add_registry_entry (*name*, *node_id*)

Adds a node to registry.

Parameters

- **name** (*String*) – Node name.
- **id** (*Integer*) – Node id.

check_responsive ()

Determine the responsive node.

create_event (*title*)

Create a new event.

Parameters **title** (*String*) – Title of the event.

parse_config (*config_object*)
Handles config file settings.

static remove_all_registry_entries ()
Removes all related registry entries.

run ()
Run the worker thread.

1.17 Utils module

Created on 17.5.2013

author neriksso

utils.DottedIPToInt (*dotted_ip*)
Transforms a dotted IP address to Integer.

Parameters **dotted_ip** (*String*) – The IP address.

Returns The IP address.

Return type Integer

utils.GetLocalIPAddress (*target*)
Used to get local Internet Protocol address.

Returns The current IP address.

Return type string

utils.GetMacForIp (*ip*)
Returns the mac address for an local IP address.

Parameters **ip** (*String*) – IP address

utils.IterIsLast (*iterable*) → generates (item, islast) pairs.
Generates pairs where the first element is an item from the iterable source and the second element is a boolean flag indicating if it is the last item in the sequence.

Parameters **iterable** (*iterable*) – The iterable element.

utils.MapNetworkShare (*letter, share=None*)
Maps the network share to a letter.

Parameters

- **letter** (*String*) – The letter for which to map.
- **share** (*String*) – The network share, defaults to None which unmaps the letter.

utils.get_encrypted_directory_name (*name, hashed_password*)
Returns the encrypted name for project directory.

utils.hash_password (*password*)
Hashes the provided password.

CHAPTER
TWO

BUGS

Bug	Description	Status
Sample bug	Description for sample	Open / Closed / Will not be fixed

FEATURES

Feature	Description
Project	User can add, edit and select a project
Session	User can start, end and continue sessions
Event	User can tag an interesting event during a session
File Monitoring	Users' file actions are monitored during a session. It includes opening files.

LICENSE

European Union Public Licence

22. 1.1

EUPL © the European Community 2007

This European Union Public Licence (the “EUPL”) applies to the Work or Software (as defined below) which is provided under the terms of this Licence. Any use of the Work, other than as authorised under this Licence is prohibited (to the extent such use is covered by a right of the copyright holder of the Work).

The Original Work is provided under the terms of this Licence when the Licensor (as defined below) has placed the following notice immediately following the copyright notice for the Original Work:

Licensed under the EUPL V.1.1

or has expressed by any other mean his willingness to license under the EUPL.

4.1 1. Definitions

In this Licence, the following terms have the following meaning:

- **The Licence:** This Licence.
- **The Original Work or the Software:** The software distributed and/or communicated by the Licensor under this Licence, available as Source Code and also as Executable Code as the case may be.
- **Derivative Works:** The works or software that could be created by the Licensee, based upon the Original Work or modifications thereof. This Licence does not define the extent of modification or dependence on the Original Work required in order to classify a work as a Derivative Work; this extent is determined by copyright law applicable in the country mentioned in Article 15.
- **The Work:** The Original Work and/or its Derivative Works.
- **The Source Code:** The human-readable form of the Work which is the most convenient for people to study and modify.
- **The Executable Code:** Any code which has generally been compiled and which is meant to be interpreted by a computer as a program.
- **The Licensor:** The natural or legal person that distributes and/or communicates the Work under the Licence.
- **Contributor(s):** Any natural or legal person who modifies the Work under the Licence, or otherwise contributes to the creation of a Derivative Work.
- **The Licensee or “You”:** Any natural or legal person who makes any usage of the Software under the terms of the Licence.

- **Distribution and/or Communication:** Any act of selling, giving, lending, renting, distributing, communicating, transmitting, or otherwise making available, on-line or off-line, copies of the Work or providing access to its essential functionalities at the disposal of any other natural or legal person.

4.2 2. Scope of the rights granted by the Licence

The Licensor hereby grants You a world-wide, royalty-free, non-exclusive, sublicensable licence to do the following, for the duration of copyright vested in the Original Work:

- use the Work in any circumstance and for all usage,
- reproduce the Work,
- modify the Original Work, and make Derivative Works based upon the Work,
- communicate to the public, including the right to make available or display the Work or copies thereof to the public and perform publicly, as the case may be, the Work,
- distribute the Work or copies thereof,
- lend and rent the Work or copies thereof,
- sub-license rights in the Work or copies thereof.

Those rights can be exercised on any media, supports and formats, whether now known or later invented, as far as the applicable law permits so.

In the countries where moral rights apply, the Licensor waives his right to exercise his moral right to the extent allowed by law in order to make effective the licence of the economic rights here above listed.

The Licensor grants to the Licensee royalty-free, non exclusive usage rights to any patents held by the Licensor, to the extent necessary to make use of the rights granted on the Work under this Licence.

4.3 3. Communication of the Source Code

The Licensor may provide the Work either in its Source Code form, or as Executable Code. If the Work is provided as Executable Code, the Licensor provides in addition a machine-readable copy of the Source Code of the Work along with each copy of the Work that the Licensor distributes or indicates, in a notice following the copyright notice attached to the Work, a repository where the Source Code is easily and freely accessible for as long as the Licensor continues to distribute and/or communicate the Work.

4.4 4. Limitations on copyright

Nothing in this Licence is intended to deprive the Licensee of the benefits from any exception or limitation to the exclusive rights of the rights owners in the Original Work or Software, of the exhaustion of those rights or of other applicable limitations thereto.

4.5 5. Obligations of the Licensee

The grant of the rights mentioned above is subject to some restrictions and obligations imposed on the Licensee. Those obligations are the following:

Attribution right: the Licensee shall keep intact all copyright, patent or trademarks notices and all notices that refer to the Licence and to the disclaimer of warranties. The Licensee must include a copy of such notices and a copy of the Licence with every copy of the Work he/she distributes and/or communicates. The Licensee must cause any Derivative Work to carry prominent notices stating that the Work has been modified and the date of modification.

Copyleft clause: If the Licensee distributes and/or communicates copies of the Original Works or Derivative Works based upon the Original Work, this Distribution and/or Communication will be done under the terms of this Licence or of a later version of this Licence unless the Original Work is expressly distributed only under this version of the Licence. The Licensee (becoming Licensor) cannot offer or impose any additional terms or conditions on the Work or Derivative Work that alter or restrict the terms of the Licence.

Compatibility clause: If the Licensee Distributes and/or Communicates Derivative Works or copies thereof based upon both the Original Work and another work licensed under a Compatible Licence, this Distribution and/or Communication can be done under the terms of this Compatible Licence. For the sake of this clause, “Compatible Licence” refers to the licences listed in the appendix attached to this Licence. Should the Licensee’s obligations under the Compatible Licence conflict with his/her obligations under this Licence, the obligations of the Compatible Licence shall prevail.

Provision of Source Code: When distributing and/or communicating copies of the Work, the Licensee will provide a machine-readable copy of the Source Code or indicate a repository where this Source Code will be easily and freely available for as long as the Licensee continues to distribute and/or communicate the Work.

Legal Protection: This Licence does not grant permission to use the trade names, trademarks, service marks, or names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the copyright notice.

4.6 6. Chain of Authorship

The original Licensor warrants that the copyright in the Original Work granted hereunder is owned by him/her or licensed to him/her and that he/she has the power and authority to grant the Licence.

Each Contributor warrants that the copyright in the modifications he/she brings to the Work are owned by him/her or licensed to him/her and that he/she has the power and authority to grant the Licence.

Each time You accept the Licence, the original Licensor and subsequent Contributors grant You a licence to their contributions to the Work, under the terms of this Licence.

4.7 7. Disclaimer of Warranty

The Work is a work in progress, which is continuously improved by numerous contributors. It is not a finished work and may therefore contain defects or “bugs” inherent to this type of software development.

For the above reason, the Work is provided under the Licence on an “as is” basis and without warranties of any kind concerning the Work, including without limitation merchantability, fitness for a particular purpose, absence of defects or errors, accuracy, non-infringement of intellectual property rights other than copyright as stated in Article 6 of this Licence.

This disclaimer of warranty is an essential part of the Licence and a condition for the grant of any rights to the Work.

4.8 8. Disclaimer of Liability

Except in the cases of wilful misconduct or damages directly caused to natural persons, the Licensor will in no event be liable for any direct or indirect, material or moral, damages of any kind, arising out of the Licence or of the use of

the Work, including without limitation, damages for loss of goodwill, work stoppage, computer failure or malfunction, loss of data or any commercial damage, even if the Licensor has been advised of the possibility of such damage. However, the Licensor will be liable under statutory product liability laws as far such laws apply to the Work.

4.9 9. Additional agreements

While distributing the Original Work or Derivative Works, You may choose to conclude an additional agreement to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or services consistent with this Licence. However, in accepting such obligations, You may act only on your own behalf and on your sole responsibility, not on behalf of the original Licensor or any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against such Contributor by the fact You have accepted any such warranty or additional liability.

4.10 10. Acceptance of the Licence

The provisions of this Licence can be accepted by clicking on an icon “I agree” placed under the bottom of a window displaying the text of this Licence or by affirming consent in any other similar way, in accordance with the rules of applicable law. Clicking on that icon indicates your clear and irrevocable acceptance of this Licence and all of its terms and conditions.

Similarly, you irrevocably accept this Licence and all of its terms and conditions by exercising any rights granted to You by Article 2 of this Licence, such as the use of the Work, the creation by You of a Derivative Work or the Distribution and/or Communication by You of the Work or copies thereof.

4.11 11. Information to the public

In case of any Distribution and/or Communication of the Work by means of electronic communication by You (for example, by offering to download the Work from a remote location) the distribution channel or media (for example, a website) must at least provide to the public the information requested by the applicable law regarding the Licensor, the Licence and the way it may be accessible, concluded, stored and reproduced by the Licensee.

4.12 12. Termination of the Licence

The Licence and the rights granted hereunder will terminate automatically upon any breach by the Licensee of the terms of the Licence.

Such a termination will not terminate the licences of any person who has received the Work from the Licensee under the Licence, provided such persons remain in full compliance with the Licence.

4.13 13. Miscellaneous

Without prejudice of Article 9 above, the Licence represents the complete agreement between the Parties as to the Work licensed hereunder.

If any provision of the Licence is invalid or unenforceable under applicable law, this will not affect the validity or enforceability of the Licence as a whole. Such provision will be construed and/or reformed so as necessary to make it valid and enforceable.

The European Commission may publish other linguistic versions and/or new versions of this Licence, so far this is required and reasonable, without reducing the scope of the rights granted by the Licence. New versions of the Licence will be published with a unique version number.

All linguistic versions of this Licence, approved by the European Commission, have identical value. Parties can take advantage of the linguistic version of their choice.

4.14 14. Jurisdiction

Any litigation resulting from the interpretation of this License, arising between the European Commission, as a Licensor, and any Licensee, will be subject to the jurisdiction of the Court of Justice of the European Communities, as laid down in article 238 of the Treaty establishing the European Community.

Any litigation arising between Parties, other than the European Commission, and resulting from the interpretation of this License, will be subject to the exclusive jurisdiction of the competent court where the Licensor resides or conducts its primary business.

4.15 15. Applicable Law

This Licence shall be governed by the law of the European Union country where the Licensor resides or has his registered office. This licence shall be governed by the Belgian law if: - a litigation arises between the European Commission, as a Licensor, and any Licensee; - the Licensor, other than the European Commission, has no residence or registered office inside a European Union country.

4.16 Appendix

“Compatible Licences” according to article 5 EUPL are:

- GNU General Public License (GNU GPL) v. 2
- Open Software License (OSL) v. 2.1, v. 3.0
- Common Public License v. 1.0
- Eclipse Public License v. 1.0
- Cecill v. 2.0

USER INTERFACE



Figure 5.1: The UI of DiWaCS; Several icons for different functions.

The screen icons identify different screens nodes. The user can drop files on to these icons, causing the dropped files to be opened in the specific node. The arrows control the carousel of nodes, and are visible only if more than three nodes are connected. The drop-down list in holds recently viewed files in the selected project.

Table 5.1: Icons explained

Icon	Description
Briefcase	Select a project
Clock	Start / End a session
Folder	Open project directory
Note	Create an Event note
Circle	Hide the application
Cross	Exit the application

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

a

`add_file`, 3

c

`controller.activity`, 4
`controller.common`, 4
`controller.computer`, 5
`controller.handlers`, 6
`controller.project`, 7
`controller.session`, 8

d

`dialogs`, 9
`diwacs`, 12
`diwavars`, 15

f

`filesystem`, 17

g

`graphicaldesign`, 18

m

`macro`, 20
`models`, 24
`modelsbase`, 23

s

`send_file_to`, 3
`state`, 29
`swnp`, 31

t

`testing`, 34
`threads.audiorecorder`, 35
`threads.checkupdate`, 36
`threads.common`, 36
`threads.connectionerror`, 36
`threads.contextmenu`, 36
`threads.current`, 37
`threads.diwathread`, 37
`threads.inputcapture`, 38

`threads.worker`, 39

u

`utils`, 40

- Action (class in models), 24
- Activity (class in models), 24
- add_computer() (in module controller.computer), 5
- add_computer_to_session() (in module controller.computer), 5
- add_event() (in module controller.session), 8
- add_file (module), 3
- add_file_to_project() (in module controller.project), 7
- add_logger_initializer() (in module diwavars), 15
- add_logger_level_setter() (in module diwavars), 15
- add_or_update_activity() (in module controller.activity), 4
- add_project() (in module controller.project), 7
- add_project_registry_entry() (threads.worker.WORKER_THREAD static method), 39
- add_registry_entry() (threads.worker.WORKER_THREAD static method), 39
- AddProjectDialog (class in dialogs), 9
- AddUser() (models.Session method), 28
- Align_or_Top() (graphicaldesign.GUIItem template method), 19
- append_swnp_data() (state.State method), 29
- AudioRecorder (class in threads.audiorecorder), 35
- BlackOverlay (class in graphicaldesign), 18
- CallAbsorber (class in testing), 34
- check_password() (in module controller.project), 7
- check_responsive() (threads.worker.WORKER_THREAD method), 39
- CHECK_UPDATE (class in threads.checkupdate), 36
- CheckVisibility() (diwacs.EventList method), 12
- ChooseDiwaProfileDialog (class in dialogs), 9
- click() (in module macro), 21
- close() (swnp.SWNP method), 32
- CloseError, 10
- Company (class in models), 25
- Computer (class in models), 25
- connect_to_database() (in module modelsbase), 24
- CONNECTION_ERROR_THREAD (class in threads.connectionerror), 36
- ConnectionErrorDialog (class in dialogs), 10
- ConnectionErrorHandler() (graphicaldesign.GUIItem template method), 19
- ContextMenuFailure (class in threads.contextmenu), 36
- controller.activity (module), 4
- controller.common (module), 4
- controller.computer (module), 5
- controller.handlers (module), 6
- controller.project (module), 7
- controller.session (module), 8
- copy_file_to_project() (in module filesystem), 17
- copy_to_temporary_directory() (in module filesystem), 17
- create_all() (in module modelsbase), 24
- create_config() (in module state), 31
- create_event() (threads.worker.WORKER_THREAD method), 39
- create_file_action() (in module controller.project), 7
- create_project_directory() (in module filesystem), 17
- CreateMenu() (graphicaldesign.SysTray method), 20
- CURRENT_PROJECT (class in threads.current), 37
- CURRENT_SESSION (class in threads.current), 37
- data (swnp.Node attribute), 32
- delete() (modelsbase.MethodMixin method), 23
- delete_directory() (in module filesystem), 17
- delete_many() (modelsbase.MethodMixin class method), 23
- delete_record() (in module controller.common), 4
- DeleteProjectDialog (class in dialogs), 10
- destroy() (state.State method), 29
- dialogs (module), 9
- DisableDirectoryButton() (diwacs.GraphicalUserInterface method), 13
- DisableSessionButton() (diwacs.GraphicalUserInterface method), 13
- DIWA_THREAD (class in threads.diwathread), 37
- diwacs (module), 12
- diwavars (module), 15
- do_ping() (swnp.SWNP method), 32
- DottedIPToInt() (in module utils), 40
- DropTarget (class in graphicaldesign), 18
- edit_project() (in module controller.project), 7

EmptyScreen() (graphicaldesign.NodeScreen method), 20

EnableDirectoryButton() (diwacs.GraphicalUserInterface method), 13

EnableSessionButton() (diwacs.GraphicalUserInterface method), 13

end_current_project() (state.State method), 29

end_current_session() (state.State method), 29

end_session() (in module controller.session), 8

ErrorDialog (class in dialogs), 10

Event (class in models), 25

EventList (class in diwacs), 12

EventListTemplate (class in graphicaldesign), 19

Exit() (dialogs.ChooseDiwaProfileDialog method), 10

File (class in models), 26

FileAction (class in models), 26

filesystem (module), 17

find_input_device() (threads.audiorecorder.AudioRecorder method), 35

find_node() (swnp.SWNP method), 32

from_json() (swnp.Message static method), 31

get() (modelsbase.MethodMixin class method), 23

get_active_activity() (in module controller.activity), 4

get_active_computers() (in module controller.computer), 6

get_active_project() (in module controller.project), 7

get_active_responsive_nodes() (in module controller.computer), 6

get_active_session() (in module controller.session), 8

get_age() (swnp.Node method), 32

get_by_id() (modelsbase.MethodMixin class method), 23

get_current_wallpaper() (in module filesystem), 17

get_encrypted_directory_name() (in module utils), 40

get_file_extension() (in module filesystem), 17

get_latest_event_id() (in module controller.session), 8

get_list() (swnp.SWNP method), 32

get_most_recent_by_mac() (models.Computer class method), 25

get_mouse_position() (in module macro), 21

get_node_image() (in module filesystem), 17

get_or_create() (in module controller.common), 5

get_pad() (threads.checkupdate.CHECK_UPDATE static method), 36

get_project_id_by_activity() (in module controller.project), 8

get_projects_by_company() (in module controller.project), 8

get_random_responsive() (state.State method), 29

get_screen_list() (swnp.SWNP method), 32

get_sendkeys() (in module macro), 21

get_session_id_by_activity() (in module controller.session), 9

get_swnp_data() (state.State method), 29

GetKeydown() (in module macro), 20

GetLastChecked() (models.Session method), 28

GetLocalIPAddress() (in module utils), 40

GetMacForIp() (in module utils), 40

GetProgramIcon() (graphicaldesign.EventListTemplate method), 19

GetProgramIcon() (graphicaldesign.GUITemplate method), 19

GetResult() (dialogs.ConnectionErrorDialog method), 10

graphicaldesign (module), 18

GraphicalUserInterface (class in diwacs), 13

GUITemplate (class in graphicaldesign), 19

handle_file_send() (state.State method), 29

HardwareInput (class in macro), 20

hash_password() (in module utils), 40

HideNow() (diwacs.EventList method), 12

HideScreens() (graphicaldesign.GUITemplate method), 19

hold() (in module macro), 21

hook() (threads.inputcapture.INPUT_CAPTURE method), 38

id_ordering() (modelsbase.MethodMixin class method), 23

init_sync_project_directory() (in module controller.project), 8

initialization_test() (in module state), 31

initialize() (state.State method), 30

InitScreens() (graphicaldesign.GUITemplate method), 19

InitUI() (graphicaldesign.GUITemplate method), 19

InitUICore() (diwacs.GraphicalUserInterface method), 13

Input (class in macro), 21

INPUT_CAPTURE (class in threads.inputcapture), 38

Input_I (class in macro), 21

is_project_file() (in module controller.project), 8

ItemAlreadyExistsException, 23

IterIsLast() (in module utils), 40

key_press() (in module macro), 21

KeyBdInput (class in macro), 21

last_active_computer() (in module controller.computer), 6

ListDatabaseProfiles() (dialogs.ChooseDiwaProfileDialog static method), 10

load_config() (in module state), 31

LoadPreferences() (dialogs.PreferencesDialog method), 10

macro (module), 20

MacroPoint (class in macro), 21

main() (in module add_file), 3

- main() (in module diwacs), 15
- main() (in module send_file_to), 3
- MapNetworkShare() (in module utils), 40
- Message (class in swnp), 31
- message_handler() (state.State method), 30
- MethodMixin (class in modelsbase), 23
- middle_click() (in module macro), 21
- middle_hold() (in module macro), 21
- middle_release() (in module macro), 21
- models (module), 24
- modelsbase (module), 23
- MOUSE_CAPTURE (class in threads.inputcapture), 38
- MouseInput (class in macro), 21
- move() (in module macro), 21
- move_to() (in module macro), 21
- MySplashScreen (class in graphicaldesign), 20
- Node (class in swnp), 32
- NodeScreen (class in graphicaldesign), 20
- on_keyboard_event() (threads.inputcapture.INPUT_CAPTURE method), 38
- on_mouse_event() (threads.inputcapture.INPUT_CAPTURE method), 38
- on_project_selected() (state.State method), 30
- on_session_changed() (state.State method), 30
- OnAboutBox() (diwacs.GraphicalUserInterface method), 13
- OnAdd() (dialogs.AddProjectDialog method), 9
- OnCancel() (dialogs.DeleteProjectDialog method), 10
- OnCancel() (dialogs.PreferencesDialog method), 10
- OnCancel() (dialogs.ProjectSelectDialog method), 11
- OnClose() (dialogs.AddProjectDialog method), 9
- OnComboBox() (dialogs.ChooseDiwaProfileDialog method), 10
- OnData() (graphicaldesign.DropTarget method), 19
- OnEnter() (diwacs.EventList method), 12
- OnEventButton() (diwacs.GraphicalUserInterface method), 13
- OnExit() (diwacs.GraphicalUserInterface method), 13
- OnExit() (graphicaldesign.GUITemplate method), 19
- OnFocus() (diwacs.GraphicalUserInterface method), 13
- OnFocusLost() (diwacs.EventList method), 12
- OnFocusLost() (graphicaldesign.BlackOverlay method), 18
- OnIconify() (diwacs.GraphicalUserInterface method), 13
- OnInfoBtn() (diwacs.GraphicalUserInterface method), 13
- OnMBBtn() (diwacs.GraphicalUserInterface method), 13
- OnOk() (dialogs.DeleteProjectDialog method), 10
- OnOk() (dialogs.ProjectAuthenticationDialog method), 11
- OnOk() (dialogs.ProjectSelectedDialog method), 11
- OnOk() (dialogs.UpdateDialog method), 12
- OnPreferences() (diwacs.GraphicalUserInterface method), 14
- OnProjectAdd() (dialogs.ProjectSelectDialog method), 11
- OnProjectChanged() (diwacs.GraphicalUserInterface method), 14
- OnProjectDelete() (dialogs.ProjectSelectDialog method), 11
- OnProjectEdit() (dialogs.ProjectSelectDialog method), 11
- OnProjectSelect() (dialogs.ProjectSelectDialog method), 11
- OnSelection() (diwacs.EventList method), 12
- OnSelectionChange() (dialogs.ProjectSelectDialog method), 11
- OnSession() (diwacs.GraphicalUserInterface method), 14
- OnTaskBarActivate() (diwacs.GraphicalUserInterface method), 14
- OnTaskBarClose() (diwacs.GraphicalUserInterface method), 14
- OnText() (dialogs.AddProjectDialog method), 9
- OnText() (diwacs.EventList method), 13
- OnWABtn() (diwacs.GraphicalUserInterface method), 14
- open_file() (in module filesystem), 17
- open_mic_stream() (threads.audiorecorder.AudioRecorder method), 35
- OpenConfig() (dialogs.PreferencesDialog method), 10
- OpenProjectDir() (diwacs.GraphicalUserInterface method), 14
- parse_config() (threads.worker.WORKER_THREAD method), 39
- parse_mouse_events() (threads.inputcapture.MOUSE_CAPTURE method), 39
- ping_handler() (swnp.SWNP method), 32
- ping_routine() (swnp.SWNP method), 33
- PreferencesDialog (class in dialogs), 10
- print_to_status_box() (in module diwavars), 15
- Project (class in models), 27
- PROJECT_EVENT_HANDLER (class in controller.handlers), 6
- ProjectAuthenticationDialog (class in dialogs), 11
- ProjectSelectDialog (class in dialogs), 11
- ProjectSelectedDialog (class in dialogs), 11
- refresh() (swnp.Node method), 32
- refresh_computer() (in module controller.computer), 6
- refresh_computer_by_wos_id() (in module controller.computer), 6
- register_status_box_callback() (in module diwavars), 15
- release() (in module macro), 22
- release_all_keys() (in module macro), 22
- ReloadAs() (graphicaldesign.NodeScreen method), 20
- ReloadConfig() (dialogs.PreferencesDialog method), 10
- remove_all_registry_entries() (threads.worker.WORKER_THREAD static method), 40

`remove_from_swnp_data()` (state.State method), 30
`remove_observer()` (state.State method), 30
`remove_self()` (threads.diwathread.DIWA_THREAD method), 37
`reset_mouse_events()` (threads.inputcapture.INPUT_CAPTURE method), 38
`right_click()` (in module macro), 22
`right_hold()` (in module macro), 22
`right_release()` (in module macro), 22
`run()` (testing.TestDiwa method), 34
`run()` (threads.audiorecorder.AudioRecorder method), 35
`run()` (threads.checkupdate.CHECK_UPDATE method), 36
`run()` (threads.connectionerror.CONNECTION_ERROR_THREAD method), 36
`run()` (threads.contextmenu.SEND_FILE_CONTEXT_MENU_HANDLER method), 37
`run()` (threads.current.CURRENT_PROJECT method), 37
`run()` (threads.current.CURRENT_SESSION method), 37
`run()` (threads.inputcapture.INPUT_CAPTURE method), 38
`run()` (threads.worker.SNAPSHOT_THREAD method), 39
`run()` (threads.worker.WORKER_THREAD method), 40

`save()` (threads.audiorecorder.AudioRecorder method), 35
`save_screen()` (in module filesystem), 18
`SavePreferences()` (dialogs.PreferencesDialog method), 11
`screen_capture()` (in module filesystem), 18
`search_file()` (in module filesystem), 18
`SelectDiwaProfile()` (dialogs.ChooseDiwaProfileDialog method), 10
`SelectNode()` (diwacs.GraphicalUserInterface method), 14
`SelectNode()` (graphicaldesign.GUITemplate method), 20
`SelectProjectDialog()` (diwacs.GraphicalUserInterface method), 14
`send()` (swnp.SWNP method), 33
`SEND_FILE_CONTEXT_MENU_HANDLER` (class in threads.contextmenu), 36
`send_file_to` (module), 3
`send_input()` (in module macro), 22
`send_pop_clipboard()` (state.State method), 30
`send_push_clipboard()` (state.State method), 30
`SendProgressBar` (class in dialogs), 11
`Session` (class in models), 27
`SessionChangeException`, 29
`set_blank_cursor()` (in module diwavars), 15
`set_capture()` (in module threads.inputcapture), 39
`set_config()` (in module diwavars), 15
`set_current_project()` (state.State method), 30
`set_current_session()` (state.State method), 30

`set_default_cursor()` (in module diwavars), 15
`set_name()` (swnp.SWNP method), 33
`set_node_name()` (in module controller.common), 5
`set_node_screens()` (in module controller.common), 5
`set_observer()` (state.State method), 30
`set_responsive()` (state.State method), 30
`set_responsive()` (swnp.SWNP method), 33
`set_run_cmd()` (in module diwavars), 15
`set_running()` (in module diwavars), 16
`set_screens()` (swnp.SWNP method), 33
`set_swnp_data()` (state.State method), 30
`set_using_diwa_profile()` (in module diwavars), 16
`SetNodeVars()` (graphicaldesign.NodeScreen method), 20
`SelectName()` (diwacs.GraphicalUserInterface method), 14
`SetNode()` (graphicaldesign.BlackOverlay method), 18
`setUp()` (testing.TestAudioRecorder method), 34
`setUp()` (testing.TestDocumentation method), 34
`setUp()` (testing.TestFilesystem method), 35
`setUp()` (testing.TestUtils method), 35
`Shift()` (diwacs.GraphicalUserInterface method), 14
`show_dialog()` (threads.checkupdate.CHECK_UPDATE method), 36
`show_modal_and_destroy()` (in module dialogs), 12
`ShowMenu()` (graphicaldesign.SysTray method), 20
`ShowNotification()` (graphicaldesign.SysTray method), 20
`ShowNow()` (diwacs.EventList method), 13
`shutdown()` (swnp.SWNP method), 33
`slide()` (in module macro), 22
`slide_to()` (in module macro), 22
`SNAPSHOT_THREAD` (class in threads.worker), 39
`Start()` (models.Session method), 28
`start_audio_recorder()` (state.State method), 30
`start_current_project_thread()` (state.State method), 30
`start_current_session_thread()` (state.State method), 31
`start_new_session()` (in module controller.session), 9
`start_new_session()` (state.State method), 31
`start_sub_routine()` (swnp.SWNP static method), 33
`State` (class in state), 29
`state` (module), 29
`stop()` (threads.audiorecorder.AudioRecorder method), 35
`stop()` (threads.contextmenu.SEND_FILE_CONTEXT_MENU_HANDLER method), 37
`stop()` (threads.diwathread.DIWA_THREAD method), 37
`stop()` (threads.inputcapture.INPUT_CAPTURE method), 38
`stop_all()` (threads.diwathread.DIWA_THREAD static method), 37
`stop_is_set()` (threads.diwathread.DIWA_THREAD method), 37
`stop_responsive()` (state.State method), 31
`sub_routine()` (swnp.SWNP method), 33
`sub_routine_sys()` (swnp.SWNP method), 33

SWNP (class in swnp), 32
 swnp (module), 31
 swnp_send() (state.State method), 31
 sys_handler() (swnp.SWNP method), 33
 SysTray (class in graphicaldesign), 20

 tearDown() (testing.TestAudioRecorder method), 34
 tearDown() (testing.TestDocumentation method), 34
 tearDown() (testing.TestFilesystem method), 35
 tearDown() (testing.TestUtils method), 35
 test_connection() (in module controller.common), 5
 test_documentation() (testing.TestDocumentation method), 34
 test_iterislast() (testing.TestUtils method), 35
 test_record() (testing.TestAudioRecorder method), 34
 test_searchfile() (testing.TestFilesystem method), 35
 test_storage_connection() (in module filesystem), 18
 TestAudioRecorder (class in testing), 34
 TestDiwa (class in testing), 34
 TestDocumentation (class in testing), 34
 TestFilesystem (class in testing), 34
 testing (module), 34
 TestUtils (class in testing), 35
 threads.audiorecorder (module), 35
 threads.checkupdate (module), 36
 threads.common (module), 36
 threads.connectionerror (module), 36
 threads.contextmenu (module), 36
 threads.current (module), 37
 threads.diwathread (module), 37
 threads.inputcapture (module), 38
 threads.worker (module), 39
 time_ordering() (models.Computer class method), 25
 timeout_routine() (swnp.SWNP method), 33
 TimeoutException, 37
 to_dict() (swnp.Message static method), 31

 unhook() (threads.inputcapture.INPUT_CAPTURE method), 38
 unset_activity() (in module controller.activity), 4
 update() (modelsbase.MethodMixin method), 23
 update_audio() (in module diwavars), 16
 update_bitmaps() (graphicaldesign.NodeScreen static method), 20
 update_camera_vars() (in module diwavars), 16
 update_config_loader() (in module diwavars), 16
 update_database() (in module modelsbase), 24
 update_database_vars() (in module diwavars), 16
 update_keys() (in module diwavars), 16
 update_many() (modelsbase.MethodMixin class method), 23
 update_padfile() (in module diwavars), 16
 update_pgm_group() (in module diwavars), 16
 update_pgm_group() (swnp.SWNP method), 34

 update_responsive() (in module diwavars), 16
 update_status_box() (in module diwavars), 16
 update_storage() (in module diwavars), 16
 update_variable() (in module diwavars), 16
 update_windows_version() (in module diwavars), 16
 UpdateDialog (class in dialogs), 12
 UpdateProjects() (dialogs.ProjectSelectDialog method), 11
 UpdateScreens() (diwacs.GraphicalUserInterface method), 15
 UrlHandler() (dialogs.UpdateDialog method), 12
 User (class in models), 28
 utils (module), 40

 WORKER_THREAD (class in threads.worker), 39