



Vibration & Geotechnical Monitoring

Vibration Monitoring

VIBRA Series - Vibration Monitoring

With a Profound VIBRA system you can easily monitor vibrations, which may cause damage to buildings and sensitive equipment or cause nuisance to persons. Vibrations can be caused by traffic, pile driving, demolition work or blasting.

Setting up the system on site is easy: attach the 3-dimensional sensor to the structure to be monitored, switch on the system and start measuring. During measuring the VIBRA displays the current vibration values of the 3 directions including frequency, the maxima, besides date, time, remaining battery capacity, available memory. The VIBRA can be left unattended to operate continuously for weeks.

The system is robust, lightweight, portable and battery-operated. At the same time, the system provides a fully continuous and automatic registration of the vibration peak values up to a month.



Geotechnical Monitoring



Intelligent Sensor (IS) System

The Profound Intelligent Sensor-system is an effective tool for precision monitoring in the geotechnical field. Real-time measuring data on your PC enable you to monitor your project remotely.

Just one network cable interconnects the 'Intelligent Sensors', whereby the distance between measurement points can be hundreds of metres.

Typical applications include monitoring of settlements and pore pressures, as well as load monitoring and strain measurements. Different types of measurements from sensors such as Groundwater level, Inclinoimeters, Load cells, Potentiometers, Pore pressure sensors, Pressure sensors, Vibrating wire sensors, Liquid Level sensors (Profound IS-LLS) can easily be combined in one network.

All relevant parameters, like sensor type, calibration and scale factors can be stored in the memory of the IS-sensor.

You only have to set the measuring frequency in the network PC and the PC will collect the measurements accordingly.

BAT®-system - Accurate Groundwater Monitoring

The patented BAT - Groundwater Monitoring System represents an innovative and proven technology for groundwater monitoring and testing. For over twentyfive years the BAT-system has been successfully used in a great number of groundwater monitoring projects worldwide.

With the BAT®-system you measure accurately and efficiently the pore pressure, keep track of pressure fluctuations in the soil, have a fully digital system which stores the data in the internal memory of the BAT®-sensor, download results to a PC for further analysis, can also directly read out pore pressures determine the permeability of the soil (with an additional set), collect accurate groundwater samples (with an additional set)

The BAT-system is multi-purpose and flexible. You decide when and what to measure. You can either measure manually or continuously. The system enables you to follow the progress of your project remotely. Through a GSM-link you can download the measurement results where and when you like, enabling you to analyse the measurement data on your own PC. The pressure sensor is easily retrievable and can be used over and over.

