

Cooperative Multicast Scheduling with Random Network Coding in WiMAX



Jin Jin, Baochun Li,
Department of Electrical Computer Engineering
University of Toronto

WiMAX MBS

WiMAX MBS

WiMAX MBS

WiMAX MBS

WiMAX MBS

next generation infrastructure to broadcast data

WiMAX MBS

WiMAX MBS

next generation infrastructure to broadcast data

IEEE 802.11j/802.11m

WiMAX MBS

next generation infrastructure to broadcast data

IEEE 802.11j/802.11m

Problem with current multicast scheduling

WiMAX MBS

next generation infrastructure to broadcast data

IEEE 802.11j/802.11m

Problem with current multicast scheduling

no ARQ & HARQ

WiMAX MBS

next generation infrastructure to broadcast data
IEEE 802.11j/802.11m

Problem with current multicast scheduling

no ARQ & HARQ
single channel, single path

WiMAX MBS

next generation infrastructure to broadcast data
IEEE 802.11j/802.11m

Problem with current multicast scheduling

no ARQ & HARQ
single channel, single path
under-utilize spectrum due to user/channel diversity

WiMAX MBS

next generation infrastructure to broadcast data
IEEE 802.11j/802.11m

Problem with current multicast scheduling

no ARQ & HARQ
single channel, single path
under-utilize spectrum due to user/channel diversity

How to properly select a multicast rate?

Observation

Observation

Users can help each other (cooperation)

aim to exploit diversity and cooperative gain

cooperative communication is not well studied in MBS

Observation

Users can help each other (cooperation)

- aim to exploit diversity and cooperative gain

- cooperative communication is not well studied in MBS

Adoption of OFDMA in WiMAX

- concurrent transmissions without interference

- channel diversity gain

- multi-path, multi-hop transmission

Observation

Users can help each other (cooperation)

aim to exploit diversity and cooperative gain

cooperative communication is not well studied in MBS

Adoption of OFDMA in WiMAX

concurrent transmissions without interference

channel diversity gain


multi-path, multi-hop transmission

Can we take advantage of all potential benefits and design a multicast scheduling protocol to tightly integrate to WiMAX MBS?


Multicast Scheduling

Study from a new perspective

Multiple hops, multiple paths, multiple channels
Network Coding to mitigate the overhead



Conventional Multicast Scheme



Cooperative Multicast Scheme

Any Challenges?

Any Challenges?

How to dynamically assign relays?

Any Challenges?

How to dynamically assign relays?

How to apply random network coding?

Any Challenges?

How to dynamically assign relays?

How to apply random network coding?

How to allocate channels?

Any Challenges?

How to dynamically assign relays?

How to apply random network coding?

How to allocate channels?

How to allocate power?

Any Challenges?

How to dynamically assign relays?

How to apply random network coding?

How to allocate channels?

How to allocate power?

How to tightly integrate with WiMAX protocol?

Our Contribution :

Cooperative Multicast Scheduling with Random Network Coding

Optimization

Greedy Optimization Frame Work

time-slotted WiMAX MBS

optimal multicast rate

efficient cooperative communication schedule

proportional fairness criteria

$$\max_{R(t)} \sum_{i \in \zeta} \frac{U_i(t)}{\bar{r}_i(t)}$$

Subject to:

$$U_i(t) = S_{m,i}(t)R_m(t) + \sum_{g \in \zeta} R_{gi}(t)$$

$$0 \leq R_{gi}(t) \leq C_{gi}(t)$$

$$R_{gi}(t) \leq \max\left\{0, \frac{B_g(t) - B_i(t)}{T}\right\}$$

$$\sum_{g \in \zeta} R_{gi}(t) \leq \sum_{h=1}^{t-1} R(h) - \frac{B_i(t)}{T} + (1 - S_{m,i}(t))R_m(t)$$

Protocol Design

Protocol Design

BS: encode, broadcast ratelessly, use optimal rate

Protocol Design

BS: encode, broadcast ratelessly, use optimal rate

RS: recode in the middle, random push

Protocol Design

BS: encode, broadcast ratelessly, use optimal rate

RS: recode in the middle, random push

Receiver: collect coded blocks, decode

Protocol Design

BS: encode, broadcast ratelessly, use optimal rate

RS: recode in the middle, random push

Receiver: collect coded blocks, decode

Is it helpful?


Protocol Design

BS: encode, broadcast ratelessly, use optimal rate

RS: recode in the middle, random push

Receiver: collect coded blocks, decode

Is it helpful?




Protocol Design

BS: encode, broadcast ratelessly, use optimal rate

RS: recode in the middle, random push

Receiver: collect coded blocks, decode

Is it helpful?



Throughput vs. Number of MSs


Protocol Design

BS: encode, broadcast ratelessly, use optimal rate


RS: recode in the middle, random push

Receiver: collect coded blocks, decode

Is it helpful?



Throughput vs. Number of MSs




Protocol Design

BS: encode, broadcast ratelessly, use optimal rate


RS: recode in the middle, random push

Receiver: collect coded blocks, decode

Is it helpful?



Throughput vs. Number of MSs



Multicast Rate vs. Number of MSs

Limited Bandwidth Resources

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Solve it by maximum weighted bipartite matching

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Solve it by maximum weighted bipartite matching

Exploit spectrum reuse

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Solve it by maximum weighted bipartite matching

Exploit spectrum reuse

$$I_{ki} = \begin{cases} 1 & \text{If node } i \text{ is in interference zone of node } k \\ 0 & \text{Otherwise} \end{cases}$$

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Solve it by maximum weighted bipartite matching

Exploit spectrum reuse

$$I_{ki} = \begin{cases} 1 & \text{If node } i \text{ is in interference zone of node } k \\ 0 & \text{Otherwise} \end{cases}$$

$$\sum_{i \in \zeta, i \neq k} I_{ki} \sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall k \in \zeta$$

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Solve it by maximum weighted bipartite matching

Exploit spectrum reuse

$$I_{ki} = \begin{cases} 1 & \text{If node } i \text{ is in interference zone of node } k \\ 0 & \text{Otherwise} \end{cases}$$

$$\sum_{i \in \zeta, i \neq k} I_{ki} \sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall k \in \zeta$$

$$\sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall i \in \zeta$$

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Solve it by maximum weighted bipartite matching

Exploit spectrum reuse

$$I_{ki} = \begin{cases} 1 & \text{If node } i \text{ is in interference zone of node } k \\ 0 & \text{Otherwise} \end{cases}$$

$$\sum_{i \in \zeta, i \neq k} I_{ki} \sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall k \in \zeta$$

$$\sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall i \in \zeta$$

$$\left(1 - \left(1 - \frac{1}{G}\right)^G\right)$$

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Solve it by maximum weighted bipartite matching

Exploit spectrum reuse

$$I_{ki} = \begin{cases} 1 & \text{If node } i \text{ is in interference zone of node } k \\ 0 & \text{Otherwise} \end{cases}$$

$$\sum_{i \in \zeta, i \neq k} I_{ki} \sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall k \in \zeta$$

$$\sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall i \in \zeta$$

Solve it by randomized rounding, $(1 - (1 - \frac{1}{G})^G)$ approximation guarantee

Limited Bandwidth Resources

$$\sum_{g \in \zeta} \sum_{i \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi$$

$$U_i = S_{m,i} R_m + \sum_{g \in \zeta} \sum_{n \in \chi} K_{gi}^{(n)} R_{gi}^{(n)}$$

Solve it by maximum weighted bipartite matching

Exploit spectrum reuse


$$I_{ki} = \begin{cases} 1 & \text{If node } i \text{ is in interference zone of node } k \\ 0 & \text{Otherwise} \end{cases}$$

$$\sum_{i \in \zeta, i \neq k} I_{ki} \sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall k \in \zeta$$


$$\sum_{g \in \zeta} K_{gi}^{(n)} \leq 1 \quad \forall n \in \chi, \forall i \in \zeta$$

Solve it by randomized rounding, $(1 - (1 - \frac{1}{G})^G)$ approximation guarantee

How Efficient are the channel allocated?



Throughput vs. Number of MSs



Throughput vs. Number of Sub-channels


Power Allocation

When power on relays are high constrained


$$\sum_{n \in \chi} \sum_{i \in \zeta} S_{gi}^{(n)} \leq P_g \quad \forall g \in \zeta$$

$$0 \leq \omega_{gi}^{(n)} \leq C_{gi}^{(n)} = \frac{BW}{\bar{r}_i} \cdot \log_2 \left(1 + \frac{S_{gi}^{(n)}}{\sigma_{gi}^{(n)}} \right)$$

Solve the problem by solving the dual problem



Throughput vs. Power



Throughput vs. Number of Sub-channels

Conclusion

Conclusion

Our framework offers salient improvement

Conclusion

Our framework offers salient improvement

✓

Cooperative Communication

Conclusion

Our framework offers salient improvement

✓

Cooperative Communication

✓

Diversity gain

Conclusion

Our framework offers salient improvement

- ✓ Cooperative Communication
- ✓ Diversity gain
- ✓ Rateless Properties

Conclusion

Our framework offers salient improvement

- ✓ Cooperative Communication
- ✓ Diversity gain
- ✓ Rateless Properties
- ✓ Tightly Integrate with WiMAX

Conclusion

Our framework offers salient improvement

- ✓ Cooperative Communication
- ✓ Diversity gain
- ✓ Rateless Properties
- ✓ Tightly Integrate with WiMAX

Lead to the future design in WiMAX

Thank you!

more information:

<http://iqua.ece.toronto.edu/~jinjin>