

Diya Jain
COP 4530

Program 1

// C++ Program to print sum of numbers from 1 to 4

```
#include <iostream>
```

```
using namespace std;
```

```
int main() {
```

```
    int i = 1;
```

```
    int sum = 0;
```

```
    // do...while loop from 1 to 4
```

```
    do {
```

```
        sum = sum + i;
```

```
        ++i;
```

```
    }
```

```
    while (i <= 4);
```

```
    cout << sum << " ";
```

```
    return 0;
```

```
}
```

Program 2

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
int main() {
```

```
    string my_str;
```

```
    cout << "Enter a command: ";
```

```
    getline(cin, my_str);
```

```
    while (my_str != "exit")
```

```
    {
```

```
        cout << "You entered: " + my_str + "\n";
```

```
        cout << "Enter a command: ";
        getline(cin, my_str);
    }
    cout << "Bye";
}
```

Program 3

```
#include <iostream>
```

```
using namespace std;
```

```
int main()
{
    int number;
    cout << "Enter a number: ";
    cin >> number;

    while (number < 0)
    {
        cout << "Number must be greater than 0. Try again.\n";
        cout << "Enter a number: ";
        cin >> number;
    }

    cout << "You entered: \n " << number ;
    cout << "\nContinue (y/n):";

    return 0;
}
```