PARTICIPANT GUIDE

Build. Test. Improve.

A quick guide to using VeryJudgyCat for Automathon 2.0.

01 LOG IN	02 BUILD	03 UPLOAD	04 RUN
Use your team code and password.	Follow the round statement in n8n.	Download and upload your workflow JSON.	Try samples before a scored attempt.

What you need

A laptop or desktop screen at least 1024 pixels wide, your team code and password, the website address from the organisers, and a working n8n workflow.

Before you start

Open the site and sign in. When a round opens, its problem statement appears automatically. If you see Not open yet, wait for the organisers to open the round.

Your challenge

Read the complete statement and use the exact webhook paths, request fields and response fields it specifies. You may use your own supported node layout; you do not need to copy a reference workflow.

Your AI key

If your workflow uses an AI model, use your own valid API key and a model available to that key. Model calls consume your quota even for free sample runs.

From n8n to the judge

1 Build and export

Build your workflow in n8n. In the workflow menu, choose the three dots and Download to save the workflow as a JSON file. Export the whole workflow, including the required webhook nodes.

2 Upload or paste

On the site, use Upload file and choose the JSON, or select Paste JSON and press Check this JSON. Read the pre-check messages. If there is an error, fix your workflow in n8n, download a fresh JSON file, and upload it again.

3 Fill the requested credentials

The Credentials section lists what your workflow needs. Enter the requested key fields. Simulated accounts say nothing is needed for them. Do not paste a key into your workflow nodes or share it with another team; use a restricted or disposable key and rotate it after the event.

4 Run samples first

Press Run samples (free). The visible tests show input, expected behavior and your output. Samples do not use a scored attempt, but do use any model tokens your workflow calls. There is a two-minute wait between sample runs.

5 Run a scored attempt

When ready, press Run attempt and confirm. You have three scored attempts per round. Each runs the samples and hidden tests; your best eligible finished attempt counts. A rejected workflow or an unavailable model can use an attempt, so check the free samples first.

6 Read your results

The page shows the visible sample results and an aggregate count of hidden tests passed. Expand a sample to inspect it. Your runs and best score remain in the history on the page.

If something goes wrong

My workflow is not accepted

Check the message above the credential fields. Confirm all required webhooks exist, are enabled, use the stated paths and POST method, and that your n8n nodes are supported. Fix the workflow, then export and upload it again.

The run is queued

A test machine is busy or unavailable. Leave the page open and wait; do not repeatedly submit. If the queue does not move, tell an organiser your team code and run number.

Model unavailable or key rejected

Check the model selected in your n8n model node and the key you entered. Your provider may not offer that model to your key. Choose a supported model in n8n, export again, and retry with a sample.

Key rate-limited

Your provider temporarily limited requests. Wait or use a key with suitable quota. A scored attempt still rate-limited after retries is refunded and will not count.

Judge-side failure

If the site reports that the judge could not complete a run, show the message and run number to an organiser. A judge-side failed attempt is refunded; it does not count against your three.

I need help

Share the team code, run number and a description of the error with an organiser. Never send your API key in chat or include it in screenshots.

Quick reminder

Free samples check the visible cases. Scored attempts include the hidden cases. Your best eligible scored attempt counts.