

Multidimensional subwavelength position sensing using a semiconductor laser with optical feedback

Seth D. Cohen,^{1,*} Andrés Aragonese,² Damien Rontani,¹ M. C. Torrent,² Cristina Masoller² and Daniel J. Gauthier¹

¹*Duke University, Physics Department, BOX 90305, Durham, NC, 27708, USA*

²*Departament de Física i Enginyeria Nuclear, Universitat Politècnica de Catalunya, Colom 11, 08222 Barcelona, Spain*

**Corresponding author: sdc18@phy.duke.edu*

Compiled September 18, 2013

We demonstrate experimentally how to harness quasi-periodic dynamics in a semiconductor laser with dual optical feedback for measuring subwavelength changes in each arm of the cavity simultaneously. We exploit the multi-frequency spectrum of quasi-periodic dynamics and show that independent frequency shifts are mapped uniquely to two-dimensional displacements of the arms in the external cavity. Considering a laser diode operating at telecommunication wavelength $\lambda \approx 1550$ nm, we achieve an average nanoscale resolution of approximately 9.8 nm ($\sim \lambda/160$). © 2013 Optical Society of America

OCIS codes: (280.3420) Remote sensing and sensors, Laser sensors; (250.5960) Semiconductor lasers.

The extreme sensitivity of semiconductor lasers with optical feedback has been studied for its applications to sensors [1]. For example, the subwavelength sensitivity to changes in the external cavity length of the feedback has triggered the development of laser-feedback interferometry, also referred as self-mixing interferometry [2–4], where displacements and vibrations are measured with subwavelength resolution by tracking changes in the laser intensity. Other approaches have used changes in the relaxation-oscillation frequency [5]. These laser-based approaches usually lead to the extraction of a single observable, thus restricting sensing or imaging to one dimension (1D). As a consequence, to image or sense complex objects in 2D or 3D, such laser-based systems require scanning and sequential 1D acquisitions.

Recently, a subwavelength 2D position sensor was realized using a high-speed nonlinear feedback system comprising a radio-frequency ($\lambda \sim 10^{-2}$ m) wave-chaotic cavity [6]. It was demonstrated that the 2D position of an object inside the cavity could be determined with subwavelength precision using a linear map that uniquely associates frequency shifts in the quasi-periodic spectrum of the dynamics with the object position [6]; this method does not require sequential scanning to deduce 2D information. An open question is whether these frequency shifts can also occur in the optical domain, thus allowing for the development of novel laser feedback-based devices with the capability for subwavelength, nanoscale, multidimensional position sensing.

In this Letter, we demonstrate experimentally, using a semiconductor laser with quasi-periodic dynamics induced by external optical feedback from a cavity with two arms (referred to as T-cavity), the existence of frequency shifts in the spectrum, similar to those found in Ref. [6]. We unveil a quadratic mapping between these frequency shifts with independent, subwavelength translations of each arm of the T-cavity. We show that our

Fig. 1. (Color online) Two-delay all-optical feedback system for multi-dimensional subwavelength sensing. The output of a laser diode (LD, Sumitomo SLT4416-DP) passes through a polarization control (PC), a 90/10 optical coupler (OC), an optical attenuator (OA), and separates using a 50/50 beam splitter (BS). The feedback strength is set so that it reduces the laser threshold by $\sim 1\%$. The optical field propagates along two separate paths with time delays $\tau_{x,y}$. Piezoelectric transducers (PZT_{*x,y*}, Burleigh PZO-015) translate mirrors M_{*x,y*} by $\Delta_{x,y}$ and change feedback delay $\tau_{x,y}$. After an optical isolator (OI), detection is performed using a 12 GHz photodetector (PD, New Focus 1544-B) and a 40 GS/s, 8 GHz analog bandwidth, high-speed digital oscilloscope (OSC, Agilent DSO90804A).

approach leads to a highly sensitive detection scheme for 2D nanoscale translations.

Our experimental setup is shown in Fig. 1. A single-mode semiconductor laser operating at $\lambda = 1550.8$ nm is subjected to a dual optical feedback with two arms of lengths x and y , respectively. The propagation distances along each path result in two different time delays, $\tau_x \sim 55.5$ ns and $\tau_y \sim 55.6$ ns, with feedback strengths $\eta_{x,y}$ approximately equal and controlled simultaneously

by a single variable optical attenuator placed before the beam splitter (see Fig. 1). A polarization controller is used to ensure coherent feedback to the laser (verified using L-I curves [7]). Our setup is reminiscent of previous experiments with T-cavity optical feedback [8–10].

The relative values of the time delays are controlled using two piezoelectric transducers (PZT_{*x,y*}) that move the positions of the mirrors on a nanoscale by $\Delta_x \ll x$ and $\Delta_y \ll y$, respectively. To estimate the transducers displacements as a function of the applied voltages, we calibrate them via interferometry. Based on our calibration measurements, the translations per applied voltages to PZT_{*x,y*} are 29.2 ± 0.1 nm/V and 45.8 ± 0.2 nm/V, respectively. We note that this calibration does not include either the hysteresis or nonlinear response of the PZTs under applied voltages. To reduce the effects of the PZT nonlinearity and hysteresis, we bias them at 50 V (out of a total range of 0 – 150 V) and scan them by at most 3 V about this value. Based on the manufacturers specification, we estimate that the deviation from linearity is at most 0.3% for our experiment and hence we ignore these behaviors in the analysis described below.

We carefully adjust the feedback strength such that the optical intensity displays quasi-periodic oscillations in time. This occurs when the feedback strength is about $\sim 2\%$, consistent with previous reports of feedback-induced quasi-periodicity [11, 12]. A typical optical intensity time series is displayed in Fig. 2a. It shows a fast oscillatory signal with slow modulation of its amplitude. The frequency spectrum of the quasi-periodic signal is given in Fig. 2b. Within the 8 GHz bandwidth of our oscilloscope, it reveals multiple clusters of frequency peaks ranging from ~ 1 GHz to ~ 7 GHz (additional clusters above 8 GHz may be present but are not visible without suitable measurement equipments). The fourth cluster concentrates the largest amount of spectral power because it lies in the vicinity of the relaxation oscillation frequency measured to be ~ 6.5 GHz for pumping current $I = 23.6$ mA. The peak in the i th cluster with the maximum spectral power is denoted by f_i . In Fig. 2c-d, we show zoomed regions on the spectrum, highlighting f_2 and f_4 , respectively. We investigate the relative frequency shifts Δf_i to the values of f_i due to subwavelength translations $\Delta_{x,y} \ll \lambda$ of each arm of the dual optical feedback. These translations induce changes in the time delays denoted by $\Delta\tau_{x,y} = 2\Delta_{x,y}/c$, where c is the speed of light in free space.

We track the frequencies of the quasi-periodicity as $\tau_{x,y}$ are changed simultaneously by translating the positions of mirrors M_{*x,y*}. For this, we use computer-controlled, high-voltage power supplies connected to PZT_{*x,y*}. The piezoelectric transducers are translated by steps of ~ 10 nm within an approximative $100 \text{ nm} \times 100 \text{ nm}$ 2D grid. Over this subwavelength region of interest, the dynamics remains quasi-periodic. Over substantially larger regions, we observe that the dynamics bifurcates to a new behavior or undergoes frequency hopping. At each point of the grid, we measure the frequency shifts

Fig. 2. (Color online) Experimental quasi-periodic dynamics generated by a semiconductor laser with dual optical feedback. (a) Temporal evolution of $v(t)$ generated by the photo-detector and proportional to the intensity of the optical field. The pump current is $I = 23.6$ mA (the threshold is $I_{th} \sim 8.0$ mA), $\tau_x \approx 55.5$, $\tau_y \approx 55.6$ ns (corresponding to $\Delta_{x,y} = 0$), and $\sim 2\%$ of optical intensity fed back in the laser cavity. (b) Power spectral density (PSD) of $v(t)$ in the quasi-periodic regime showing four frequency clusters, each labelled by their central frequency f_i , $i = 1, \dots, 4$ ($f_1 = 1.07$ GHz, $f_2 = 2.13$ GHz, $f_3 = 5.42$ GHz, and $f_4 = 6.49$ GHz). (c)-(d) Zooms on the structures of the second and fourth labeled frequency clusters later used for subwavelength sensing.

Δf_i associated with each frequency f_i of the four labeled clusters.

The nanoscale modification to the cavity induced by the transducer leads to observed frequency shifts Δf_i on a kilohertz scale, which is orders of magnitude smaller compared to frequencies f_i . To resolve such fine variations, we use the trigger skew on our digital oscilloscope, so that the amount of time that the oscilloscope waits between its initial triggering and the acquisition of a waveform is $t_{\text{skew}} = 5 \mu\text{s}$. Using a large trigger skew causes small frequency shifts Δf_i to be observed as visible phase shifts $\Delta\varphi_i = \Delta f_i \cdot t_{\text{skew}}$ across the oscilloscope's delayed acquisition window.

Using this approach, measurements of Δf_i have a resolution set by the jitter of the waveform. To reduce the effect of jitter, we acquire (for each point of the 2D grid) a waveform $\bar{v}(t)$ resulting from the average of 500 time series. The averaging is realized in real time using the oscilloscope. We find that averaging over 500 time-series measurements optimizes the trade-off between noise-reduction in the measurement and the inevitable drift in the apparatus due to temperature fluctuations. Better thermal shielding in future experiments will minimize this non-ideal behavior. To successfully average

Fig. 3. (Color online) Experimental manifold associated with the quasi-periodic frequency shifts (a) Δf_2 and (b) Δf_4 as a function of $\Delta_{x,y}$. The 2D manifolds are fitted with quadratic functions with coefficients for (a): $a_{00|2} = -17.3784 \pm 1.0834$ kHz, $a_{01|2} = -0.0691 \pm 0.0358$ kHz·nm⁻¹, $a_{10|2} = 1.2458 \pm 0.0562$ kHz·nm⁻¹, $a_{11|2} = 0.0058 \pm 0.0005$ kHz·nm⁻², $a_{02|2} = -0.0041 \pm 0.0003$ kHz·nm⁻², $a_{20|2} = -0.0095 \pm 0.0009$ kHz·nm⁻² and for (b): $a_{00|4} = -67.7941 \pm 3.2683$ kHz, $a_{01|4} = 1.2050 \pm 0.1079$ kHz·nm⁻¹, $a_{10|4} = 1.8789 \pm 0.1694$ kHz·nm⁻¹, $a_{11|4} = 0.0093 \pm 0.0014$ kHz·nm⁻², $a_{02|4} = -0.0127 \pm 0.0010$ kHz·nm⁻², and $a_{20|4} = -0.0140 \pm 0.0026$ kHz·nm⁻².

over quasi-periodic waveforms, the trigger height v_{trig} must also be tuned so that the oscilloscope triggers only on the maxima of largest amplitudes, corresponding to regions of the quasi-periodic signal for which the incommensurate frequencies add constructively. Other triggering values, such as $v_{\text{trig}} = 0$ V, will cause the averaged waveforms to collapse to zero because of the non-periodic nature of the quasi-periodic signal. Using a calibrated quasi-periodic waveform generated by a stable function generator (Agilent E8267D with 10^{-3} Hz frequency resolution), our frequency-resolving protocol yields a ± 3 kHz frequency resolution.

We monitor the quasi-periodic frequency shifts Δf_i as a function of (Δ_x, Δ_y) . We approximate them using a nonlinear least-square regression to a model of a four-tone quasi-periodic signal of the averaged data from the delayed acquisition window of the oscilloscope

$$\bar{v}(t) \approx \sum_{1 \leq i \leq 4} A_i \sin[2\pi(f_i + \Delta f_i)(t - t_{\text{skew}})], \quad (1)$$

where A_i , Δf_i are the parameters estimated via regression and f_i are measured directly with the oscilloscope to achieve approximately 100 kHz resolution (using time-series with $\sim 5.25 \times 10^5$ points).

As an example, we plot Δf_2 and Δf_4 as a function of (Δ_x, Δ_y) over the entire 2D position grid in Figs. 3a-b. Interestingly, we do not observe a near-planar evolution of the frequency shifts similar to those observed in Ref. [6]. Our two-delay optical system produces frequency shifts that are mapped onto a smooth manifold with non-zero curvature.

The two manifolds exhibit different ranges of varia-

tions and levels of curvature, thus suggesting independent (and thus invertible) frequency shifts as a function of the PZT's translations. To demonstrate independence and inversion, we propose to fit the nonlinear map $(\Delta f_2, \Delta f_4) \rightarrow (\Delta_x, \Delta_y)$ by quadratic bivariate functions

$$\Delta f_{2,4}(\Delta_x, \Delta_y) = \sum_{0 \leq i+j \leq 2} a_{ij|2,4} \Delta_x^i \Delta_y^j, \quad (2)$$

where the values of the fitted coefficients $a_{ij|2,4}$ obtained via regression are given in the caption of Fig. 3. The fitted functions of Eq. (2) are numerically invertible so that predicted values for $\Delta_{x,y}$ can be related to a given measure of frequency shifts $\Delta f_{2,4}$. The root-mean square differences between the predicted and actual subwavelength translations realized by PZT_{*x,y*} are 12.3 nm and 6.8 nm, respectively. This gives an average resolution of 9.8 nm $\sim \lambda/160$. The maximum error between the experimental map and the fit are $\varepsilon_{x,\text{max}} = 27.5$ nm ($\sim \lambda/60$) and $\varepsilon_{y,\text{max}} = 22.7$ nm ($\sim \lambda/70$), which sets a bound on the achievable resolution. In our experiments, the frequency shifts associated with $\Delta f_{2,4}$ yield the best 2D resolution. A lower bound for the dynamic range for our system, given by the ratio between the observed range and resolution, is ~ 10 on the $100 \text{ nm} \times 100 \text{ nm}$ grid [as we define it, the dynamic range is ~ 100 nm (maximum observed range in each direction) / ~ 10 nm (resolution)].

We conjecture that room temperature fluctuations (which are not controlled in our experiment) are the main source of errors in our measurements. They induce erratic changes of the path lengths of each arm in the cavity, thus affecting the frequencies f_i with parasitic frequency shifts. Hence, the manifolds displayed in Fig. 3 can be used only once as calibration measurements to then infer an unknown subwavelength trajectory on the $100 \text{ nm} \times 100 \text{ nm}$ grid. Within a ~ 5 min time period, which corresponds to the typical time scale for the drift in our apparatus, we realize back-to-back acquisitions of 81 calibration points followed by 32 trajectory points. Using the calibration points, we realize the mapping to then recover the shape of the trajectory with an average 2D resolution of $\sim \lambda/160$ (for details, see Ref. [13]). Beyond the 5-min time window, temperature fluctuations prevent us to infer arbitrary sub-wavelength positions from the calibration.

In summary, we have presented the foundation for realizing a 2D position sensor with nanometer resolution using a quasi-periodic optical field generated by a semiconductor laser with optical feedback. To the best of our knowledge, this is the first experimental study of a T-cavity optical feedback for subwavelength multidimensional position sensing based on frequency shifts in the quasi-periodic dynamics spectrum. In Ref. [6], Cohen *et al.* hypothesize that their technique for subwavelength position sensing may be scalable to nanoscale using optical feedback. Our work shows that the physical mechanism responsible for subwavelength sensing in the RF domain, independent quasi-periodic frequency shifts, remains true in the optical domain, thus laying the foun-

dation for an all-optical implementation of their setup.

In the future, we envision several directions of dynamical phenomenon. Similar to Ref. [6], the delayed feedback of the optical system can be coupled into a wave-chaotic optical cavity [14] such that it interacts with a contained subwavelength scatterer. In its present form, our system may also be used as a multidimensional sensor similar to those developed for monitoring of chemical concentrations [15] or nano-particles [16]. Lastly, the Hopf frequency of a semiconductor laser with feedback has been studied with respect to the external cavity length [11]; developing theories for the quasi-periodic frequencies in a T-cavity subject to small delay changes may give deeper insight into our observations.

S.D.C, D.R, and D.J.G gratefully acknowledge the financial support of the U.S. Office of Naval Research grant # N00014-07-0734. A.A., M.C.T., and C.M. gratefully acknowledge the financial support of grant # FA8655-12-1-2140 from EOARD, # FIS2012-37655-C02-01 from the Spanish MCI, and # 2009 SGR 1168 from the Generalitat de Catalunya. C. M. also acknowledges support from the ICREA Academia program.

References

1. J. Ohtsubo, *Semiconductor Lasers: Stability, Instability and Chaos*, Springer (2006).
2. S. Donati, G. Giuliani, and S. Merlo, IEEE J. Quantum Electron. **31**, 113 (1995).
3. D. M. Kane and K. A. Shore, *Unlocking dynamical diversity: optical feedback effects in semiconductor lasers*, Chap. 7, Wiley (2005).
4. U. Zabit, R. Atashkhoeei, T. Bosch, S. Royo, F. Bony and A. D. Rakic, Opt. Lett. **35**, 1278 (2010).
5. E. Lacot, R. Day, J. Pinel, and F. Stoeckel, Opt. Lett. **26**, 1483 (2001).
6. S. Cohen, H. Cavalcante, and D. J. Gauthier, Phys. Rev. Lett. **107**, 254103 (2011).
7. J. Mink and B. H. Verbeek, Appl. Phys. Lett. **48**, 745 (1986).
8. Y. Liu and J. Ohtsubo, Opt. Lett. **19**, 448 (1994).
9. M. J. Bunner, A. Kittel, J. Parisi, I. Fischer, and W. Elsässer, Europhys. Lett. **42**, 353 (1998).
10. F. Rogister, D. W. Sukow, A. Gavrielides, P. Mégret, O. Deparis, and M. Blondel, Opt. Lett. **25**, 808 (2000).
11. J. Mørk, B. Tromborg, and J. Mark, IEEE J. Quantum Electron. **28**, 93 (1992).
12. C. Masoller, Phys. Rev. A **50**, 2569 (1994).
13. S. D. Cohen, PhD Thesis, Duke University (2013).
14. T. Gensty, K. Becker, I. Fischer, W. Elsässer, C. Degen, P. Debernardi, and G. P. Bava, Phys. Rev. Lett. **94**, 233901 (2005).
15. B. E. DeMartini, J. F. Rhoads, M. A. Zielke, K. G. Owen, S. W. Shaw, and K. L. Turner, Appl. Phys. Lett. **93**, 054102 (2008).
16. H.-Y. Lin, C.-H. Huang, C.-C. Huang, Y.-C. Liu, and L.-K. Chau, Opt. Lett. **37**, 3969 (2011).