



# **Network Vulnerability Assessment"**

Version 1.0

*Djamali Ali bakar*

February 10, 2025

# Network Vulnerability Assessment"

Djamali Ali bakar

February 9, 2025

Prepared by: Djamali Ali bakar Lead Auditors:

## Table of Contents

- Table of Contents
- Protocol Summary
- Disclaimer
- Risk Classification
- Audit Details
  - Scope
  - Roles
- Executive Summary
  - Issues found
- Findings
  - High
    - \* [H-1] Storing the password on-chain makes it visible to anyone and no longer private
    - \* [H-2] `PasswordStore::setPassword` has no access controls, meaning a non-owner could change the password
  - Informational
    - \* [I-1] The `PasswordStore::getPassword` natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect.

## Protocol Summary

PasswordStore is a protocol dedicated to store and retrieval of a user's passwords. The protocol is designed to be used by a single user, and is not designed to be used by multiple users. Only the owner should be able to set and access this password.

## Disclaimer

The YOUR\_NAME\_HERE team makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

## Risk Classification

		Impact		
		High	Medium	Low
Likelihood	High	H	H/M	M
	Medium	H/M	M	M/L
	Low	M	M/L	L

We use the CodeHawks severity matrix to determine severity. See the documentation for more details.

## Audit Details

### Scope

''' .src/ PasswordStore.sol '''

## Roles

- Owner: The user who can set the password and read the password.
- Outsides: No one else should be able to set or read the password.

## Executive Summary

*Add some notes about how the audit went, types of things you found, etc. We spend X hours with Z auditors using Y tools. etc*

## Issues found

Severity	Number of issues found
High	2
Medium	0
Low	0
Info	1
Total	3

## Findings

### High

#### [H-1] Storing the password on-chain makes it visible to anyone and no longer private

**Description:** All data stored on chain is public and visible to anyone. The `PasswordStore::s_password` variable is intended to be hidden and only accessible by the owner through the `PasswordStore::getPassword` function.

I show one such method of reading any data off chain below.

**Impact:** Anyone is able to read the private password, severely breaking the functionality of the protocol.

**Proof of Concept:** The below test case shows how anyone could read the password directly from the blockchain. We use foundry's cast tool to read directly from the storage of the contract, without being the owner.

```
make anvil make deploy cast storage 1 --rpc-url http://127.0.0.1:8545  
0x6d7950617373776f72644000000000000000000000000000000000000000000014 cast parse-bytes32-  
string 0x6d7950617373776f72644000000000000000000000000000000000000000000014 myPassword
```

**Recommended Mitigation:** Due to this, the overall architecture of the contract should be rethought. One could encrypt the password off-chain, and then store the encrypted password on-chain. This would require the user to remember another password off-chain to decrypt the stored password. However, you're also likely want to remove the view function as you wouldn't want the user to accidentally send a transaction with this decryption key.

**[H-2] PasswordStore::setPassword has no access controls, meaning a non-owner could change the password**

**Description:** The `PasswordStore : : setPassword` function is set to be an `external` function, however the purpose of the smart contract and function's natspec indicate that `This function allows only the owner to set a new password.`

```
''js function setPassword(string memory newPassword) external { // @Audit - There are no Access
Controls. s_password = newPassword; emit SetNewPassword();}''
```

**Impact:** Anyone can set/change the stored password, severely breaking the contract's intended functionality

**Proof of Concept:** Add the following to the PasswordStore.t.sol test file:

```
''js function test_anyone_can_set_password(address randomAddress) public { vm.assume(randomAddress  
!= owner); vm.startPrank(randomAddress); string memory expectedPassword = "myNewPassword";  
passwordStore.setPassword(expectedPassword);
```

```
1    vm.startPrank(owner);
2    string memory actualPassword = passwordStore.getPassword();
3    assertEquals(actualPassword, expectedPassword);
4 }
```

， ， ，

**Recommended Mitigation:** Add an access control conditional to `PasswordStore::setPassword`.

```
'''is if(msg.sender != s.owner){ revert PasswordStore_NotOwner();}'''
```

## Informational

**[I-1] The PasswordStore::getPassword natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect.**

**Description:** ''' / @notice This allows only the owner to retrieve the password. @> \* @param newPassword The new password to set. \*/ function getPassword() external view returns (string memory) {} '''

The `PasswordStore::getPassword` function signature is `getPassword()` while the natspec says it should be `getPassword(string)`.

**Impact:** The natspec is incorrect

**Recommended Mitigation:** Remove the incorrect natspec line

'''diff / @notice This allows only the owner to retrieve the password. - \* @param newPassword The new password to set. \*/ '''