

KDC-168U

| | | |
|----|--------------------------------------|---------------------------------------|
| FM | Frequency Range (Frequency step) | 87.9MHz - 107.9MHz (200kHz) |
| | Usable Sensitivity S/N:26dB | 8.2dBf (0.71μV/75Ω) |
| | Quieting Sensitivity DIN S/N 46dB | 17.2dBf (2.0μV/75Ω) |
| | Frequency Response (±3.0dB) | 30Hz-15kHz |
| | S/N | 64.0dB(MONO) |
| | Stereo Separation | 40dB(1kHz) |
| AM | Frequency Range (Frequency step) | 530kHz - 1700kHz (10kHz) |
| | Usable Sensitivity S/N:20dB | 29dBμ (28.2μv) |
| CD | Laser Diode | GaAlAs |
| | Digital Filter(D/A) | 8 Times OverSampling |
| | Spindle Speed | 500~200rpm (CLV) |
| | Wow & Flutter | Below Measurable Limit |
| | Frequency Response | 20Hz-20kHz(±1dB) |
| | Total Harmonic Distortion | 0.01%(1kHz) |
| | S/N Ratio (dB) | 105dB(1kHz) |
| | Dynamic Range | 90dB |
| | Channel Separation | 85dB |
| | MP3 Decode | Compliant with MPEG-1/2 Audio Layer-3 |
| | WMA Decode | Compliant with WINDOWS MEDIA AUDIO |
| | AAC Decode | - |

| | | |
|----------------------------------|--|--|
| | WAV Decode | - |
| Preout Level(mV)/Load-Unbalanced | | 2500mV/10kΩ(CD) |
| Preout Impedance(Ω) | | ≤600Ω |
| Speaker Impedance(Ω) | | 4-8Ω |
| USB I/F | USB | USB 1.1 / 2.0 Full Speed |
| | File System | FAT12 / 16 / 32 |
| | Maximum Supply current | DC5V(DC logo) 1A |
| | MP3 decode | Compliant with MPEG-1/2 Audio Layer-3 |
| | WMA decode | Compliant with Windows Media Audio |
| | AAC Decode | - |
| | WAV Decode | Linear-PCM |
| | FLAC Decode | FLAC file (Up to 48kHz/16bit) |
| AUX Input | Frequency Response | 20~20KHz ±3dB |
| | Input Maximum Voltage | 1000mV |
| | Input Impedance | 30KΩ |
| AMP | Maximum Power | 50wx4 |
| | Full Bandwidth Power (at less than 1%THD) | 22wx4 |
| TONE | Bass | 100Hz ±8dB |
| | Middle | 1kHz ±8dB |
| | Treble | 12.5kHz ±8dB |
| GENE | Operating voltage (10.5~16v allowable) | 14.4V |
| | Maximum Current Consumption | 10A |
| | Operational Temperature Range | -10°C to +60°C |
| | Installation Size (W) (H) (D) | 182(mm) 7-3/16(in) 53(mm) 2-1/16(in) 158(mm) 6-1/4(in) |
| | Net Weight (Trim plate and Mounting sleeve: Included) | 1.3(kg) 2.9(lbs) |

email address

Subscribe

KENWOOD

CAR ENTERTAINMENT

Communications
Smart Headsets

Car Audio

eXcelon Reference
eXcelon
Navigation & Multimedia
Cameras
Receivers
Amplifiers
Speakers & Subwoofers
Accessories

Support

eXcelon Motorsports

Receivers
Amplifiers
Speakers

Marine

Receivers
Cameras
Amplifiers
Speakers
Accessories

Motorsports

Receivers
Cameras
Amplifiers
Speakers
Accessories

Motorcycle

Receivers
Cameras
Amplifiers
Speakers