

Module 08


"New Features in C# 6.0"



Agenda



- ▶ **Introduction**
- ▶ Namespace-level Features
- ▶ Expression-level Features
- ▶ Statement-level Features
- ▶ Member Declaration Features
- ▶ Scrapped Features for C# 6.0 (*If Time Permits...*)
- ▶ Lab 8
- ▶ Discussion and Review



What is new in C# 6.0?

WINCUBATE

"Less code!" 😊

... but no major additions in terms of languages features

However..

.NET Compiler Platform (Formerly known as "Roslyn")



- ▶ Project running at Microsoft for more than 4 years
 - Reimplementation of C# and VB.NET compilers
- ▶ Provides an syntax tree representation of programs
- ▶ "Compiler-as-a-Service"
- ▶ At Build 2014 Microsoft announced the open-sourcing of the C# and VB.NET compilers
 - Everyone can "fork" the compiler, but...

▶ Contains a really useful Diagnostic Analyzer API



Agenda



- ▶ Introduction
- ▶ **Namespace-level Features**
- ▶ Expression-level Features
- ▶ Statement-level Features
- ▶ Member Declaration Features
- ▶ Scrapped Features for C# 6.0 (*If Time Permits...*)
- ▶ Lab 8
- ▶ Discussion and Review





Static Usings

- Static members can now be imported with **using static**
 - Rules similar to using extension methods

```
using static System.Console;

class Program
{
    static void Main(string[] args)
    {
        WriteLine( "Hello, World!" );
    }
}
```

- Extension methods are static methods, but intended as instance members

```
using static System.Linq.Enumerable;
...
IEnumerable<int> numbers = Range( 0, 100 ); // OK!
var query = Where( numbers, i => i % 2 == 0 ); // Not OK!
```



Agenda



- Introduction
- Namespace-level Features
- **Expression-level Features**
- Statement-level Features
- Member Declaration Features
- Scrapped Features for C# 6.0 (*If Time Permits...*)
- Lab 8
- Discussion and Review





Null-conditional Operator

- ▶ C# 6.0 introduces a new null-conditional operator `?.`
 - Also known as the "Elvis operator" ☺
 - Works for reference types and nullable types

```
Person p = ...;
string s = p?.FullName; // Full name (or null if person == null)
```

- ▶ Right-hand side only evaluated if left-hand side is not null
 - Propagates null through expression
- ▶ Interacts brilliantly with the null-coalescing operator `??`

```
string s = p?.FullName ?? "No name";
```

- ▶ Resolves the well-known design flaw for events
 - Note: `.Invoke()` must be explicitly applied for delegates



String Interpolation

- ▶ C# 6.0 offers easier formatting of strings

```
public class Person
{
    public string FirstName { get; set; }
    public string LastName { get; set; }

    public string FullName
    {
        get
        {
            return $"{FirstName} {LastName}";
        }
    }
}
```

- ▶ Very flexible
 - Works with virtually any expression
 - Respects usual formatting controls





nameof Expressions

- ▶ The **nameof** operator provides "reflection-style" access to the name of the syntactical structure

```
public void Add( Person p )
{
    if( p == null )
    {
        throw new ArgumentNullException( nameof( p ) );
    }
    _persons.Add(p);
}
```

- ▶ Works with more elaborate dotted names

```
Console.WriteLine( nameof( Person.FullName ) );
```

- ▶ Continues the trend of Caller Info Attributes of C# 5.0
 - Eases implementation of **INotifyPropertyChanged** etc.



Index Initializers

- ▶ Index initializers are now provided for collection initializers

```
var lineUp = new Dictionary<int, Person>
{
    [19] = new Person { FirstName = "Kim", LastName = "Aabech" },
    [11] = new Person { FirstName = "Jesper", LastName = "Lange" },
    [14] = new Person { FirstName = "Ahmed", LastName = "Yasin" }
};
```

- ▶ Intended for scenarios such as **JsonObject** initialization

```
var json = new JsonObject {
    ["FirstName"] = FirstName,
    ["LastName"] = LastName,
    ["Age"] = Age
};
```

- ▶ **Note:**
 - {...} maps to the **Add()** method
 - [...] = ... maps to the underlying indexer



Add() Extension Methods



- Collection initializer syntax is now extensible via extension methods

```
public static class QueueExtensions
{
    public static void Add<T>(this Queue<T> queue, T t)
    {
        queue.Enqueue(t);
    }
}
```

```
var persons = new Queue<Person>
{
    new Person { FirstName = "Kim", LastName = "Aabech" },
    new Person { FirstName = "Jesper", LastName = "Lange" },
    new Person { FirstName = "Ahmed", LastName = "Yasin" }
};
```



Agenda



- Introduction
- Namespace-level Features
- Expression-level Features
- **Statement-level Features**
- Member Declaration Features
- Scrapped Features for C# 6.0 (*If Time Permits...*)
- Lab 8
- Discussion and Review

Exception Filters



- ▶ Exception filters facilitates the handling of exceptions matching a specific type and/or predicate

```
var from = Bank.CreateAccount(100);
var to = Bank.CreateAccount(100);

try
{
    Bank.TransferFunds(from, 200, to);
}
catch (InsufficientFundsException e) when (e.Account?.IsVIP == true)
{
    // Handle VIP account
}
```

- ▶ Distinct clauses can match same exception type but with different conditions



await in catch and finally



- ▶ C# 6.0 now allows **await** inside
 - catch
 - finally

```
try
{
    Bank.TransferFunds(from, 200, to);
}
catch (InsufficientFundsException e) when (e.Account?.IsVIP == true)
{
    // Handle VIP account
    await logger.LogExceptionAsync(e);
}
finally
{
    await logger.LogAsync("Completed processing of accounts");
}
```





Agenda

- Introduction
- Namespace-level Features
- Expression-level Features
- Statement-level Features
- **Member Declaration Features**
- Scrapped Features for C# 6.0 (*If Time Permits...*)
- Lab 8
- Discussion and Review



Auto-property Initializers

- Initializers can now be supplied for the automatic properties introduced in C# 3.0

```
public class Person
{
    public string FirstName { get; set; } = "Jens";
    public string LastName { get; set; } = "Jensen";
    public int Age { get; set; } = 0;
}
```

- Equivalent to initializers on fields
 - ...but doesn't use setter!
 - Run before constructors
 - Cannot refer to **this** because happen before object is fully constructed
- Note: Structs still cannot have initializers!



Getter-only Auto-properties



- ▶ Moreover, the automatic properties can now be getter- or setter-only

```
public class StockChangedEventArgs : EventArgs
{
    public string Ticker { get; }
    public double StockValue { get; }
    public DateTime Timestamp { get; } = DateTime.Now;
}
```

- ▶ This is a really important mechanism for putting mutable and immutable data types on equal terms!
- ▶ Underlying field is created as **readonly**
 - Can still be assigned from the constructor
 - ... but elsewhere not!
- ▶ Note: Can still have initializers!



Expression-bodied Members



- ▶ All functionality-based members can have expression bodies
 - Methods
 - Properties
 - Indexers

```
public class Person
{
    public string FirstName { get; set; } = "Jens";
    public string LastName { get; set; } = "Jensen";
    public int Age { get; set; } = 0;

    public string FullName => $"{FirstName} {LastName}";

    public override string ToString() =>
        $"{Name} is {Age} year{(Age == 1 ? "" : "s")} old";
}
```



Agenda



- Introduction
- Namespace-level Features
- Expression-level Features
- Statement-level Features
- Member Declaration Features
- **Scrapped Features for C# 6.0 (If Time Permits...)**
- Lab 8
- Discussion and Review



Scrapped Features for C# 6.0



- **Beware! Many articles, videos, blog posts etc. are no longer current...!**
- Contrary to what you might read, the following features have all been scrapped from C# 6.0
 - Parameterless Constructors for Structs
 - Primary Constructors
 - Declaration Expressions
 - **var** return value (and **out var**)
 - **IEnumerable** with **params**
 - Event Initializers
 - Binary Literals and Numeric Separators
 - ...



Scrapped: Parameterless Constructors for Structs



- Until the very(!) last minute we could define parameterless constructors for structs...

```
struct Point
{
    public Point()
    {
        X = -1;
        Y = -1;
    }

    public int X { get; set; }
    public int Y { get; set; }

    public override string ToString() => $"({X},{Y})";
}
```



Scrapped: Primary Constructors



- Primary constructors were for a very long time hyped as one of the major additions of C# 6.0


```
struct Point( int x, int y )
{
    public int X { get; set; } = x;
    public int Y { get; set; } = y;

    public override string ToString() => $"({x},{Y})";
}
```

- But – alas – scrapped!




Scrapped: Declaration Expressions




- ▶ Allows variable declaration inside of expressions

```
string s = "Yay!";  
if (int.TryParse(s, out var result))  
{  
    Console.WriteLine( result );  
}
```

- ▶ Very many other uses for the construct




Scrapped: **var** return value and **out var**




- ▶ Automatically inferred types for return values and output parameters

```
var ComputeQuery( int speed, string make )  
{  
    var query = from c in cars  
                where c.Speed >= speed && c.Make == make  
                orderby c.Speed  
                select new { c.Make, c.Color };  
  
    return query;  
}
```

- ▶ Would have been essential to anonymous types!





Scrapped: **IEnumerable** with **params**




- ▶ A minor "clean-up" to the **params** modifier was planned – but unfortunately scrapped!

```
IEnumerator<int> GetPrimeFactors( params IEnumerable<int> numbers)
{
    return numbers
        .SelectMany(i => PrimeHelper.GetPrimeFactors(i))
        .Distinct();
}
```





Scrapped: Event Initializers



- ▶ Event initializers for object initializers

```
StockPublisher p1 = new StockPublisher
{
    Ticker = "MSF",
    StockChanged += ( sender, e ) =>
        Console.WriteLine( $"{e.Ticker} is priced at {e.StockValue:f2}")
}
```



Scrapped: Binary Literals and Numeric Separators



- ▶ Event initializers for object initializers

```
public enum FileAttributes
{
    ReadOnly = 0b00_00_00_00_00_00_01, // 0x0001
    Hidden = 0b00_00_00_00_00_00_10, // 0x0002
    System = 0b00_00_00_00_00_01_00, // 0x0004
    Directory = 0b00_00_00_00_00_10_00, // 0x0010
    Archive = 0b00_00_00_00_01_00_00, // 0x0020
    Device = 0b00_00_00_00_10_00_00, // 0x0040
    Normal = 0x00_00_00_01_00_00_00, // 0x0080
    Temporary = 0b00_00_00_10_00_00_00, // 0x0100
    SparseFile = 0b00_00_01_00_00_00_00, // 0x0200
    ReparsePoint = 0b00_00_10_00_00_00_00, // 0x0400
    Compressed = 0b00_01_00_00_00_00_00, // 0x0800
    Offline = 0b00_10_00_00_00_00_00, // 0x1000
    NotContentIndexed = 0b01_00_00_00_00_00_00, // 0x2000
    Encrypted = 0b10_00_00_00_00_00_00 // 0x4000
}
```

Lab 8: Write Less Code in C# 6.0



- ▶ Lab 8.1



Discussion and Review



- ▶ Introduction
- ▶ Namespace-level Features
- ▶ Expression-level Features
- ▶ Statement-level Features
- ▶ Member Declaration Features
- ▶ Scrapped Features for C# 6.0 (*If Time Permits...*)

