Mechanistic Analysis of Over-Squashing and Attention Dilution in Hybrid GNNs

How far should a graph model listen? Large social graphs, two knobs, first results

---

Collin McDevitt, Dhawal Dixit, Andy Jiang


Supervisor: Dr. Greg Green MS Applied Data Science capstone

November 2026

Outline


1. The question
2. Why social graphs
3. Measures
4. The knob problem
5. Pipeline
6. Results so far
7. Running now
8. Roadmap

Message passing: a game of telephone



- A graph neural network (GNN) updates each node from its **neighbours**
- One layer = one hop. With L layers a node hears at most L hops away
- Far information is **relayed** node by node, and mixed with everything else on the way


Over-squashing: many voices through one bridge



- Everything B knows must reach A through **one edge**
- Each node stores a fixed-size vector, so the messages get **compressed and lost**
- This is over-squashing (Alon & Yahav 2021; Topping et al. 2022)
- A narrow bridge = high **effective resistance** between A and B


Attention: a direct line, but too many voices

Direct line




- Graph transformers let every node **look at every node**
- No relay, no bridge to squeeze through

Dilution



- Attention is split among **all** nodes; most are irrelevant
- The useful signal drowns: attention dilution

Task range: how far must a node listen?



- **Short range**: friends are enough
- **Long range**: needs friends of friends of friends
- Measured from the trained model (Bamberger et al., ICML 2025):

$$\rho_v = \frac{\sum_u I_{vu}\, d(v,u)}{\sum_u I_{vu}}$$

I_{vu}: how much u's input moves v's output; d: hops


- Average distance a node "listens" to

Research question

Question

Do **graph structure** (bottlenecks) and **task range** predict how far a model's attention should reach?

- Too short a reach ⇒ over-squashing
- Too long a reach ⇒ dilution
- Measures explain *why*: Jacobian, attention entropy, range



Deliverable: a **phase diagram** (sketch, no data)

Why social graphs?

- **Small world**: most users are 3–6 hops apart
- **Hubs**: a few accounts have very many links
- So a few hops already reach huge crowds: both failure modes are likely
- Real tasks: content labels, user activity

A gap in the benchmarks

- **LRGB**: vision, chemistry and quantum-chemistry graphs (Dwivedi et al. 2022)
- **ECHO**: synthetic long-diameter graphs and molecules (Miglior et al., ICLR 2026)
- **No social graphs** in either

Older Peptides, river and tree experiments: appendix.

Datasets (SNAP) and real targets

Dataset	Graph	Target	Mean deg.	Eff. diam.
twitch-gamers	168,114 users, 6.8M mutual follows	`mature` (explicit content, binary)	11.6	5.8
reddit-body	35,776 subreddits, 124,330 links	`LIWC_Money` (regression)	4.3	5.7
twitch-de	9,498 users, 153,138 edges	`mature`	22.9	3.0
higgs-follow	35,593 users, 528,532 follows	`active_after`: active after the Higgs news (4 Jul 2012)	16.7	3.7

- `activate_passive`: same Higgs label, scored only on the $\sim$11% of users with **no earlier activity**, so any signal must come from neighbours
- reddit target: neighbours add the most (ridge R^2 0.108 own $\rightarrow$ 0.185 with 4 hops)

Degree, diameter: means over test subgraphs. Higgs retweet / reply layers before the cutoff: too sparse (mean degree 1.4 / 0.16).

Effective resistance collapses to degree

$$R(u,v) = (e_u - e_v)^\top L^+ (e_u - e_v)$$

- Low R: many wide paths. High R: a bottleneck
- On large, well-connected graphs (von Luxburg, Radl & Hein 2014):

$$R(u,v) \;\to\; \tfrac{1}{d_u} + \tfrac{1}{d_v}$$

- So R mostly measures degree, not bottlenecks
- We use **excess resistance**

$$R_{\text{ex}}(u,v) = R(u,v) - \left(\tfrac{1}{d_u} + \tfrac{1}{d_v}\right)$$

Graph	$\rho_S\left(R,\ \frac{1}{d_u}+\frac{1}{d_v}\right)$	mean R_{ex}
twitch-gamers	0.90	0.39
reddit	0.77	0.49
twitch-de	0.998	0.02
higgs-follow	0.98	0.09
higgs-retweet	0.07	–

ρ_S: Spearman correlation, on test subgraphs. Only the very sparse retweet layer escapes the collapse.

Three model measures

Jacobian sensitivity

$$J(u, v) = \left\| \frac{\partial h_v^{(L)}}{\partial h_u^{(0)}} \right\|_F$$

- Does v's output move when u's input moves?
- Over-squashing: J **decays** with hops and resistance

Attention entropy

$$\tilde{H} = \frac{-\sum_j a_{ij} \log a_{ij}}{\log N} \in [0, 1]$$

- $\tilde{H} \approx 1$: attention spread evenly over everyone
- High entropy = **dilution**
- Exact for softmax; implicit rows for Performer

Range


$$\rho_v = \frac{\sum_u I_{vu}\, d(v, u)}{\sum_u I_{vu}}$$

- How far the trained model listens
- Node level, from the Jacobian (Bamberger et al. 2025)
- Distance in hops or (excess) resistance

The hybrid model and its α knob

$$x' = x + (1-\alpha)\,\mathrm{Norm}\big(\mathrm{MPNN}(x)\big) + \alpha\,\mathrm{Norm}\big(\mathrm{Attn}(x)\big)$$

- $\alpha = 0$: pure message passing $\alpha = 1$: pure attention (GraphGPS-like, Rampášek et al. 2022)
- Plan: sweep α and find the best mix per graph and task



But: as built, training could undo α. Next slide.

Why α did nothing: the norms absorb it

BatchNorm has a learnable scale γ: $\mathrm{Norm}(h) = \gamma\,\hat{h} + \beta$


$$(1-\alpha)\,\mathrm{Norm}(h_{\text{loc}}) + \alpha\,\mathrm{Norm}(h_{\text{glb}}) = \underbrace{(1-\alpha)\gamma_{\text{loc}}}_{\text{learned}}\,\hat{h}_{\text{loc}} + \underbrace{\alpha\,\gamma_{\text{glb}}}_{\text{learned}}\,\hat{h}_{\text{glb}} + \dots$$

- Training can rescale either branch freely
- Any α strictly between 0 and 1 gives the **same** model family
- α only changed the starting point, not the model

Fix 1: affine-free α

Remove the learnable scale from the branch norms (`branch_affine=false`). Now α is a real, fixed weight.

Fix 2: the attention radius k




$k = \infty$: the whole graph

- Attention may only look at nodes **within k hops**
- $k = 0$: pure message passing; $k = \infty$: full attention
- Larger k: shortcuts past bottlenecks (less over-squashing)
- . . . but more nodes per softmax (more dilution)
- The best k *is* the trade-off we study
- Learned weights **cannot undo** it

Related architectures: DRew (Gutteridge et al. 2023, k-hop rewiring), Shortest Path Networks (Abboud et al. 2022), Graphormer's distance bias (Ying et al. 2021). Our contribution: the radius as a *diagnostic* knob, read with the measures.

From a SNAP file to a measured model



- **Subgraph mode** (so far): train and test inside each part
- **Full-graph mode** (now): parts only pick the labelled nodes; the model sees the **whole graph**
- **No leakage** on Higgs: inputs are follow degree and activity counts *before* the cutoff only

Models and baselines

Baselines

- **MLP**: own features only, no graph
- **GCN**: plain message passing

Hybrid

- Local branch: GCN-normalised message passing (GINE in the first sweep; its sum was unstable on hubs)
- Global branch: attention
- Branch norms without learnable scale

Three kinds of attention

- **Exact softmax**: small graphs
- **Performer** (FAVOR+): linear cost, for $k = \infty$ on big graphs (Choromanski et al. 2021)
- **Radius-masked softmax**: only pairs within k hops

Metric: test AUROC (binary targets), mean $\pm$ std over split and model seeds

Colab notebooks

Notebook	What it does	Status
`00_quickstart`	one short run, end-to-end check	**done**
`01_fetch_datasets`	download, parse, structure stats (S0)	**done**
`02_s2_<dataset>`	first α sweep, one notebook per dataset	**done** (Higgs)
`03_s2_results`	collect runs into tables and α curves	built
`04_higgs_affine_alpha`	affine-free α sweep, 500-node subgraphs	**done**
`05_higgs_radius`	radius sweep, 500-node subgraphs	**running**
`06_higgs_full_graph`	full-graph α and radius sweeps	**running**
`07_higgs_planted`	planted long-range targets	**being built**

Each notebook mounts Drive, clones the repo and resumes: finished runs are skipped, interrupted runs continue from their checkpoint.

Higgs, first sweep: nothing beats the MLP


Model	Test AUROC
MLP (no graph)	**0.687** $\pm$ 0.000
GCN	0.684 $\pm$ 0.000
$\alpha = 1$	0.677 $\pm$ 0.003
$\alpha = 0.5$	0.669 $\pm$ 0.026
$\alpha = 0.75$	0.666 $\pm$ 0.019
$\alpha = 0$	0.652 $\pm$ 0.034
$\alpha = 0.25$	0.648 $\pm$ 0.003

higgs-follow, `active_after`, 2k-node subgraphs, 3 seeds

- Setup: GINE local branch, Performer attention, flawed α (learnable norm scales)
- The graph adds nothing over own features
- GINE's sum aggregation was **unstable on hubs**

$\Rightarrow$ Fix the knob (affine-free), switch to a GCN-normalised local branch

Higgs, affine-free α: still no gain over the MLP



Mean ± std, 3 split seeds × 2 model seeds. `active_after` $\alpha = 0, .25, .5$: 4 of 6 runs (Drive error).

- Notebook 04: 500-node subgraphs, exact softmax attention
- MLP 0.710 / 0.664; GCN 0.706 / 0.661
- Hybrids: 0.691–0.700 / 0.642–0.663
- No graph model beat the MLP, on either target
- α barely matters

Diagnosis: cutting the graph removed the signal

Part size	Edges kept	Users	Own only	+ neighbours (full)	+ neighbours (in part)
500	32%	all	0.672	**0.690**	0.673
500	32%	passive	0.677	**0.705**	0.690
2000	47%	all	0.694	**0.707**	0.700

Logistic regression on own features + 1- and 2-hop neighbour averages, split by METIS part; test AUROC.

- There *is* a neighbour signal: real but modest, larger for passive users
- Inside 500-node parts only 32% of edges survive, and most of the signal goes with them

Takeaway

On small-world social graphs, subgraph training throws away the edges the models need. So: **train on the full graph**.

Full-graph sweeps on Higgs running

Design

- Whole 35.6k-node graph for message passing and attention; parts only pick labelled nodes
- α **sweep**: $\alpha \in \{0, .25, .5, .75, 1\}$, affine-free, Performer
- **Radius sweep**: $k \in \{0, 1, \infty\}$ ($k = 2$: 299M pairs, does not fit)
- $+$ MLP, GCN; both targets; 3 split $\times$ 2 model seeds
- Also running: radius sweep on 500-node subgraphs (expected to share the subgraph problem)

What would support the thesis

- Graph models **beat the MLP** once the edges are back
- The gain is larger on `activate_passive`
- The best k is **between** 0 and ∞, and entropy rises with k

Results pending

Full-graph α and radius sweeps.

Planted targets: a known range on a real graph being built

- Keep the real graph and features; **plant** a signal z_u with known range k
- `shell_mean(k)`: predict the mean of z_u over nodes *exactly* k hops away (sanity)
- `retrieve(k)`: fetch the value of the node k hops away whose key matches your query (main test)
- Higgs, $k = 1$–3; MLP, GCN, MPNN, attention, hybrid, radius 1 ($k = 4$: 97% of graph in reach)

Caveat: small world (effective diameter ≈3.7, mean degree ≈30), so $k \geq 3$ is close to the whole graph.

What would support the thesis

- Measured range **tracks** planted k (validates the measure)
- The best radius **grows with** k
- MP fails `retrieve` at large k; full attention loses to dilution

Results pending

Planted-target sweep (S3).

Roadmap

Phase	What	Status
S0	Social data, subgraphs, structure stats (excess resistance)	**done**
S1	Performer attention + node-level models	**done**
S2	Sweeps on real targets (now on the full graph)	**running**
S3	Planted targets with known range k	**being built**
S4	Phase diagram: structure $\times$ task range $\rightarrow$ best setting	planned
S5	Graph foundation model (GFM) benchmark	planned
S6	Benchmark release and final writeup	planned

Cut order if time is short: GraphAny, then Higgs multilayer analysis, then packaging polish. S1–S4 are never cut.

Where it leads: phase diagram, GFMs, benchmark

S4 Phase diagram

- x: excess resistance
- y: task range (planted k)
- Colour: best α / radius
- Overlay: attention entropy

S5 Do GFMs reach far enough?

- Fixed-backbone GFMs **under-reach** when task range differs from training (Gutteridge, Bronstein & Dong 2026; MP only)
- Test **GraphPFN** (Eremeev et al., ICML 2026), maybe GraphAny, on planted tasks; measure their range
- NodeGround: tuned GNNs still beat GFMs; no long-range analysis

S6 Benchmark

- First long-range benchmark on **social** graphs
- Released as generator code + node indices + seeds
- Rebuilt from public SNAP files

Takeaways

- GNNs pass messages hop by hop: far information is **squashed**; attention reaches far but **dilutes**
- Social graphs are small-world with hubs, and no long-range benchmark covers them
- Resistance collapses to degree there, so we use **excess resistance**
- The α knob could be undone by the norms: fixed (affine-free) and joined by the **attention radius** k
- On Higgs, no graph model beat the MLP yet: subgraph cuts removed most of the neighbour signal
- Now: full-graph sweeps and planted targets with known range; then the phase diagram, GFMs and a benchmark

References i

- U. Alon, E. Yahav. On the Bottleneck of Graph Neural Networks and its Practical Implications. *ICLR*, 2021.
- J. Topping, F. Di Giovanni, B. P. Chamberlain, X. Dong, M. M. Bronstein. Understanding Over-Squashing and Bottlenecks on Graphs via Curvature. *ICLR*, 2022.
- F. Di Giovanni, L. Giusti, F. Barbero, G. Luise, P. Liò, M. M. Bronstein. On Over-Squashing in Message Passing Neural Networks: The Impact of Width, Depth, and Topology. *ICML*, 2023.
- M. Black, Z. Wan, A. Nayyeri, Y. Wang. Understanding Oversquashing in GNNs through the Lens of Effective Resistance. *ICML*, 2023.
- U. von Luxburg, A. Radl, M. Hein. Hitting and Commute Times in Large Random Neighborhood Graphs. *JMLR*, 15, 2014.
- J. Bamberger, B. Gutteridge, et al. On Measuring Long-Range Interactions in Graph Neural Networks. *ICML*, 2025.
- L. Rampášek, M. Galkin, V. P. Dwivedi, A. T. Luu, G. Wolf, D. Beaini. Recipe for a General, Powerful, Scalable Graph Transformer. *NeurIPS*, 2022.
- K. Choromanski et al. Rethinking Attention with Performers. *ICLR*, 2021.
- B. Gutteridge, X. Dong, M. M. Bronstein, F. Di Giovanni. DRew: Dynamically Rewired Message Passing with Delay. *ICML*, 2023.
- R. Abboud, R. Dimitrov, İ. İ. Ceylan. Shortest Path Networks for Graph Property Prediction. *LoG*, 2022.
- C. Ying et al. Do Transformers Really Perform Bad for Graph Representation? *NeurIPS*, 2021.

References ii

- V. P. Dwivedi et al. Long Range Graph Benchmark. *NeurIPS Datasets and Benchmarks*, 2022.
- L. Miglior, M. Tolloso, A. Gravina, D. Bacciu. Can You Hear Me Now? A Benchmark for Long-Range Graph Propagation. *ICLR*, 2026. arXiv 2512.17762.
- B. Gutteridge, M. M. Bronstein, X. Dong. Can Graph Foundation Models Generalize Over Architecture? *GRaM Workshop, ICLR*, 2026. arXiv 2603.22984.
- D. Eremeev et al. GraphPFN. *ICML*, 2026. arXiv 2509.21489.
- J. Lee, D. Lee, M. Jeong, J. Yoo. NodeGround: A Node Classification Benchmark in the Graph Foundation Model Era. arXiv 2609.39673, 2026.
- J. Tönshoff, M. Ritzert, E. Rosenbluth, M. Grohe. Where Did the Gap Go? Reassessing the Long-Range Graph Benchmark. *TMLR*, 2024.
- S. Kumar, W. L. Hamilton, J. Leskovec, D. Jurafsky. Community Interaction and Conflict on the Web. *WWW*, 2018.
- M. De Domenico, A. Lima, P. Mougel, M. Musolesi. The Anatomy of a Scientific Rumor. *Scientific Reports*, 3, 2013.
- B. Rozemberczki, R. Sarkar. Twitch Gamers: a Dataset for Evaluating Proximity Preserving and Structural Role-based Node Embeddings. arXiv 2101.03091, 2021.
- B. Rozemberczki, C. Allen, R. Sarkar. Multi-Scale Attributed Node Embedding. *Journal of Complex Networks*, 9(2), 2021.
- C. Klingler, K. Schulz, M. Herrnegger. LamaH-CE: LArge-SaMple DAta for Hydrology and Environmental Sciences for Central Europe. *Earth System Science Data*, 13, 2021.

Appendix: background experiments

- Earlier work, before the move to social graphs. Kept as background
- **Peptides-func** (LRGB molecules): pilot replication, rebuilt-hybrid calibration (G0)
- **Reddit pilot**: virtual node vs SAGE by hop band
- **Untrained demos**: the measures behave as theory predicts
- **Synthetic trees**: message passing fails a 4-hop query
- **LamaH-CE rivers**: does upstream growth predict the hybrid's gain?

These used the old α-blend (with learnable norm scales), so their α curves inherit the knob problem.

Peptides-func: data and the old plan

- 15,535 molecules; ≈151 nodes, diameter ≈57 (Dwivedi et al. 2022)
- 10-label graph classification, macro AP
- RWSE positional encoding (20 steps)
- Near-trees, so $R \approx$ hops: "resistance beats hops" cannot be shown here
- Bamberger et al. find it short-range

Gate G0

- Rebuilt 4-layer hybrid, $\alpha = 0.5$, seed 0
- Must reach test AP ≥ 0.652 (the pilot GPS value)
- Result: 0.6259, not passed
- No further Peptides GPU work

Pilot LRGB replication on Peptides-func [pilot]

Model	Val AP	Test AP	Published
GPS	0.6702	**0.6518**	0.6535
GCN	0.6545	**0.6263**	≈0.686

- RWSE, 200 epochs (patience 40), 1 seed
- GPS reproduces the published value
- GCN is 0.06 short of Tönshoff et al.'s tuned value: a partial replication
- G0's 0.652 threshold comes from this GPS run

Pilot mechanistic notebook [pilot]

Jacobian vs resistance (log-log slope, 240 pairs)

	GINE	Transf.	GPS
slope	-1.76	-0.48	-0.81
r	-0.78	-0.41	-0.69
test AP	0.54	0.27	0.24

Entropy vs size (400 graphs)


- Raw H rises for both models ($r = +0.88$, $+0.91$)
- $H/\log N$ rises *only for GPS* ($r = +0.60$), not for the transformer ($r = -0.09$)

Caveats: not citable as results

- 30 epochs, 1 seed; the attention models did not train
- Atom codes passed through `nn.Linear`; no positional encoding
- Entropy computed on head-averaged attention

Nine bugs were fixed afterwards in `gnn_mech`

Gate G0 calibration on Colab: below threshold



`pilot_equivalence.yaml`: 4 layers, $\alpha = 0.5$, seed 0, 404,654 params, T4, $\approx$19 s/epoch

- Best val AP 0.6281 at epoch 142 (stopped at 182); **test AP 0.6259**, 0.026 short of 0.652
- Loss keeps falling to 0.009 while val AP plateaus near 0.62 from epoch 90: overfitting
- Measurements not saved: the Hessian graph range ran out of memory on the T4


Pilot Reddit: virtual node vs SAGE by hop band [pilot]

Hop	n	SAGE	VMN	Cut
1	1,454	16,808	14,808	12%
2	17,876	90,056	56,115	38%
3	7,269	194,509	95,359	51%
4	613	207,113	77,806	62%
$\geq$5	57	326,334	62,993	81%

Mean test MSE over 100 seeds (raw units). Distance split by BFS from an anchor.


- The gain from a global shortcut (virtual node) grows with distance
- Caveats
  - Only VMN had an input projection (unfair baseline)
  - The target (character count) is almost a function of the node's own features
  - "Far" is confounded with "out of distribution"

Demo 1: Jacobian decays with hops [illustrative, untrained]



MP loses ≈3–10× per hop and is exactly 0 beyond L hops. Attention is flat at $\approx 1/N$. The $\alpha = 0.5$ hybrid follows the local curve for 2–3 hops, then settles on a floor half as high.

Demo 2: attention dilution with graph size [illustrative, untrained]



Entropy lies on $\log N$ ($H/\log N \geq 0.995$). Sensitivity to sources $\geq$6 hops away falls exactly as $1/N$, e.g. global: 6.8×10^{-2} at $N = 16$ and 2.1×10^{-3} at $N = 512$.

Demo 3: range-measure sanity on a 150-node path [illustrative, untrained]

Model (untrained)	Node-level range, hops (mean / max)	Graph-level Hessian range
Local $\alpha = 0$ (5 layers)	0.67 / 0.69 (≤ 5 ✓)	undefined (ReLU-only)
Hybrid $\alpha = 0.5$	18.7 / 25.8	not run
Global $\alpha = 1$	34.3 / 47.0	not run
GCN (6 layers, GELU)	0.89 / 0.89	17.7

- The node-level range respects the receptive field and grows once attention is mixed in
- The Hessian range reaches ≈18 hops, far past GCN's 6-hop reach: pooling plus a nonlinear head couples all pairs

$\Rightarrow$ Models are compared using the **node-level** range

Synthetic tree sweep v1: MP fails the 4-hop query


Model	Near	Far	Balanced
MP ($\alpha = 0$)	0.0036	1.0094	0.5065
$\alpha = 0.25$	**0.0024**	0.0129	**0.0077**
$\alpha = 0.50$	0.0074	0.0147	0.0110
$\alpha = 0.75$	0.0050	**0.0122**	0.0086
Attn ($\alpha = 1$)	0.0093	0.0189	0.0141

Test MSE; predicting zero gives 1. Trees of 63/127 nodes; 4 marked nodes at 1 hop, 4 at 4 hops; the root query picks near or far.

- MP solves the 1-hop query but fails the 4-hop one, though 4 hops lie inside its 8-layer reach
- Every hybrid solves it, and beats pure attention
- Confounded: different target draws, mean aggregation for a sum target, attention-only hop bias, unequal parameter counts

River experiment: setup

- LamaH-CE: 32 upstream gauge trees, 5–35 nodes (Klingler et al. 2021)
- Predict discharge 1/3/7 days ahead; inputs: weather, or weather + flow
- GRU encoder (90 days) $\rightarrow$ 8 spatial layers: $(1-\alpha)\,\mathrm{LN}(\mathrm{MP}) + \alpha\,\mathrm{LN}(\mathrm{Attn})$
- Baselines: outlet-only GRU, upstream pooling, persistence
- 72 fits, 3 seeds, $\approx$28.5 GPU-h
- Hypothesis: faster upstream growth $V(r)$ means a larger gain over MP




$V(r)$: upstream nodes within r hops. It saturates at N.

River held-out results: the α curve (test NRMSE, lower is better)

Model	Weather	Weather+flow
MP ($\alpha = 0$)	0.2666	0.1691
$\alpha = 0.25$	0.2628	0.1722
$\alpha = 0.5$	0.2489	0.1706
$\alpha = 0.75$	**0.2409**	0.1716
Attention ($\alpha = 1$)	0.2426	0.1713
Upstream pooling	0.2437	**0.1689**
Outlet-only GRU	0.2600	0.1696

- **Weather only**: $\alpha = 0.75$ is best, 9.6% better than MP
- But only 0.7% better than attention and 1.1% better than pooling: the gain comes mostly from *global access*
- **Weather+flow**: no gain; every $\alpha > 0$ is slightly worse than MP, pooling is best
- Mean NSE in the weather regime is negative (-0.30 at $\alpha = 0.75$)

River α curves per held-out outlet



Top: weather (most outlets improve up to $\alpha \geq 0.5$; the largest graph, 499, does not). Bottom: weather+flow (flat).


River context ablation: a hint of over-squashing

Weather	Full	Radius 2	Radius 0
MP ($\alpha = 0$)	0.2666	0.2673	**0.2584**
$\alpha = 0.75$	**0.2409**	0.2695	0.2741
Attention	**0.2426**	0.2583	0.2791

Held-out test NRMSE, mean over horizons. Radius r: dynamic inputs kept only within r hops.

- MP does *better* when upstream inputs are hidden
- Attention and the hybrid use upstream context: NRMSE about 13% and 12% lower than at radius 0
- Consistent with over-squashing, but also with optimisation or parameter effects
- The ablation masks inputs; it does not rewire the graph

River growth → gain hypothesis: not supported




Held-out, weather, $\alpha = 0.75$, 3-day horizon. Positive = hybrid better than the reference.

Outlet	Nodes	$V(2)$	Gain vs MP
444	9	3	+13.1%
609	7	5	+18.8%
452	8	6	+26.2%
519	11	9	+2.9%
499	29	13	−4.4%

Gain averaged over seeds and horizons

- The fastest-growing outlet (499) gains *least*
- Spearman $\rho(V(2), \text{gain})$ is -0.70 vs MP (1- and 3-day) but $+0.90$ vs attention: **the sign flips with the reference**
- $n = 5$; leave-one-group-out ranges span both signs (-1.0 to $+0.5$)
- 27 development outlets, adjusted for size, depth and area: $\rho \approx 0$ for weather vs MP
- A graph-conditioned α selector is 2.3% *worse* than a fixed α

River cost vs α



Model	Active params	s/epoch
MP	355,715	52.9
Hybrid	490,979	80.1–80.6
Attention	291,299	54.2
Pooling	26,627	15.0
Outlet GRU	22,403	10.7

Training time only, RTX 3080 Laptop GPU

- A hybrid takes $\approx 1.5\times$ the time per epoch of either endpoint
- Pooling matches the best hybrid with $\approx 5\%$ of the parameters