

TCP/IP and OSI Models

Project Overview

This project explored and compared the OSI (Open Systems Interconnection) and TCP/IP models, fundamental frameworks in computer networking. The goal was to understand how each model structures data transmission and enables communication between devices across networks.

- **Understand Layer Functions:** Learn the roles of each layer in both models and their interaction during data transfer.
- **Analyze Encapsulation/De-encapsulation:** Study how data is packaged going down the layers and unpacked on the receiving end.
- **Compare Models:** Highlight differences such as OSI's 7 layers versus TCP/IP's 4–5 layers, with OSI offering clearer learning and troubleshooting structure.
- **Map Protocols:** Identify where protocols like HTTP, FTP, DNS, TCP, and IP fit within each model's layers.
- **Network Troubleshooting:** Apply layering concepts to diagnose issues effectively using tools like Wireshark.
- **Recognize Similarities and Usage:** Understand that both models use layered encapsulation, but TCP/IP is more practical and widely used in real networks.

Description

The TCP/IP model and the OSI model are foundational frameworks in computer networking. They define the structured steps for transmitting data between devices in a network. TCP/IP is a practical model that addresses specific communication challenges and relies on standardized protocols. In contrast, OSI serves as a comprehensive, protocol-independent framework designed to encompass various network communication methods.

Recommendations

- Understand the function of each layer in both models
- Use OSI for learning and conceptual clarity
- Use TCP/IP for practical implementation and real-world networking
- Map protocols to the appropriate layers (e.g., HTTP to Application layer)
- Apply security measures at each layer.
- Use packet analyzers (like Wireshark) to study how data flows through the layers
- Optimize network troubleshooting by isolating issues layer-by-layer

References

<https://www.fortinet.com/resources/cyberglossary/tcp-ip-model-vs-osi-model>
<https://www.geeksforgeeks.org/computer-networks/difference-between-osi-model-and-tcp-ip-model/>
<https://docs.oracle.com/cd/E19683-01/806-4075/ipov-10/index.html>
<https://www.imperva.com/learn/application-security/osi-model/>
<https://www.geeksforgeeks.org/computer-networks/how-data-encapsulation-de-encapsulation-works/>

Details

Data communication is a process or act in which we can send or receive data. Understanding the fundamental structures of networking is crucial for anyone working with computer systems and communication. For data communication two models are available, the OSI (Open Systems Interconnection) Model, and the TCP/IP (Transmission Control Protocol/Internet Protocol) Model.

These models work as frameworks for organizing and understanding how data moves from one device to another across networks. While both models aim to achieve similar goals, they differ in their approach, layer organization, and practical application within computer networking.

OSI Model

The Open Systems Interconnection (OSI) model describes seven layers that computer systems use to communicate over a network. Each layer of the OSI model interacts with the layer directly above and below it, encapsulating and transmitting data in a structured manner. The modern Internet is not based on OSI, but on the simpler TCP/IP model. However, the OSI 7-layer model is still widely used, as it helps visualize and communicate how networks operate.

The OSI 7 Layers:

1. Physical Layer:

The Physical Layer manages the hardware connection between devices, handling cables, signals, and data transmission.

It covers modulation, bit synchronization, and the movement of raw bits using technologies like Fiber Optics and Wi-Fi.

2. Data Link Layer:

The Data Link Layer enables node-to-node communication with error detection, correction, and MAC address handling. It includes two sublayers: LLC and MAC.

Examples: Ethernet (LANs), PPP (direct links), and error control mechanisms.

3. Network Layer:

The Network Layer handles routing, forwarding, and IP addressing, determining the best path for data delivery.

Key protocols: IP (addressing/routing), ICMP (error reporting), and RIP (routing updates).

4. Transport Layer:

The Transport Layer provides end-to-end communication services for applications. It ensures complete data transfer, error recovery, and flow control between hosts. This layer segments and reassembles data for efficient transmission and provides reliability with error detection and correction mechanisms.

Protocols at this layer include Transmission Control Protocol (TCP) and User Datagram Protocol (UDP).

5. Session Layer:

The Session Layer manages connections between devices—establishing, maintaining, and ending sessions. It supports checkpointing and recovery, allowing interrupted sessions to resume.

Examples: RPC, NetBIOS, and SQL session management help ensure organized, reliable communication

6. Presentation Layer:

The Presentation Layer translates data between the application and network formats, ensuring compatibility between systems.

It handles data formatting, encryption, and compression—enabling secure, efficient, and readable data exchange across networks (e.g., ASCII to EBCDIC conversion).

7. Application Layer:

The Application Layer connects end-user applications to network services, enabling functions like resource sharing, file access, and network management.

Examples: HTTP (web), FTP (file transfer), SMTP (email), and DNS (domain name resolution) ensure effective communication between users and servers.

TCP/IP model

The Transmission Control Protocol/Internet Protocol (TCP/IP) model came before the Open Systems Interconnection (OSI) model, and it has five layers:

1. Application layer.

The application layer is where data originates on the sender's side. Applications are used to create the data. A web browser, for example, is used to generate the data that gets sent through the rest of the layers, assisted by the Domain Name System (DNS), which associates web domain names with their Internet Protocol (IP) addresses.

2. Transport layer.

In the transport layer, the data gets encoded so it can be transported through the internet using either the User Datagram Protocol (UDP) or TCP.

3. Network access layer.

In the network access layer, the data gets a header and a trailer, and these tell the data where to go. This information is then conveyed to the network interface layer.

4. Network interface layer.

At the network interface layer, the packet of data gets formatted and prepared to be transported and routed through the network.

5. Hardware layer:

On the hardware layer, the data is turned into something that can be sent to and read by a computer or other device. For example, the IEEE 802.3 protocol is used to convert data into what is used in an Ethernet connection.

Encapsulation in OSI Model:

Encapsulation is the process of adding headers (and sometimes trailers) to data as it moves **down the OSI layers** before transmission:

1. *Application, Presentation, Session Layers*: No extra information is added—just raw data.
2. *Transport Layer*: Splits data into segments/datagrams (TCP = segments, UDP = datagrams) and adds headers (e.g., port numbers, sequence).
3. *Network Layer*: Adds IP header → creates packets.
4. *Data Link Layer*: Adds MAC header + trailer (for error checking) → forms frames.
5. *Physical Layer*: Converts frames into bits for transmission.

Encapsulation in TCP/IP Model:

Follows the same process as OSI, but:

- *Application Layer in TCP/IP* = OSI Layers 5–7 combined.
- *Network Access Layer* = OSI Layers 1–2 combined.

De-Encapsulation

De-encapsulation is the reverse process at the receiver's end:

1. *Physical Layer*: Receives bits → converts to frames.
2. *Data Link Layer*: Removes MAC header/trailer → passes packet.
3. *Network Layer*: Removes IP header → passes segment/datagram.
4. *Transport Layer*: Removes transport header → sends data to Application Layer (via Session/Presentation if using OSI logic).

Similarities Between OSI Model and TCP/IP Model

- Both are logical models that define how data is transmitted across a network.
- Use layered architecture, with each layer handling specific functions.
- Both use encapsulation to package data with headers/trailers for proper transmission