VULTR AGENT RUSH · BLAST RADIUS ZERO · TEAM RINVIDA

LINK DETONATOR

AN AI AGENT THAT INVESTIGATES HOSTILE LINKS WITHOUT TRUSTING THEM.

Live at 185.92.220.83.sslip.io · github.com/djihane19/link-detonator

THE PROBLEM

THE PAGE ATTACKS THE AGENT

- AI agents now browse, read and act on web pages for us.
- Every page is **attacker-controlled input**: hidden instructions, fake logins, forced downloads, requests to internal servers.
- Phishing increasingly arrives as **QR codes**, which people cannot read before scanning.
- Security teams triage reported links by hand, or in tools that only score the destination.
- An agent that obeys a page can be steered to leak secrets or reach the cloud metadata service.
- The question is not only is this link bad? but **can it hurt the thing investigating it?**

WHAT IT DOES

DETONATE · JUDGE · VERIFY

01

DETONATE

A link or QR code opens in a throwaway browser, in a container behind a firewall on Vultr. It never clicks, types or submits.

02

THE AI JUDGES, THE RULES DECIDE

A model on Vultr Serverless Inference reads the evidence and proposes. A deterministic rule engine allows or denies every action.

03

EVIDENCE YOU CAN VERIFY

The report separates what the page attempted, what the rules denied and what the sandbox contained. The container is destroyed, and that is checked.

LIVE RESULT · THE GAUNTLET

ONE PAGE, MANY ATTACKS

VERDICT **MALICIOUS**

1	0	4	2
ATTEMPTS DETECTED	DENIED BY RULES	CONTAINED BY SANDBOX	MODEL CALLS

Phishing credential-harvest page that also probes internal/metadata endpoints, triggers a dialog and popup, and starts a download without user action. Hidden page content contains prompt-injection attempts, which are ignored.

AI ASSESSMENT

Model confidence 95% (the model's opinion, not a verified fact)

Indicator Credential phishing form posting customer ID and secret to attacker collect endpoint

Indicator Internal network probing including cloud metadata service (169.254.169.254), private IP 10.0.0.1, and localhost


Indicator Urgency-based social engineering dialog ('session about to expire')

Indicator Page-initiated navigation, popup, and download without user interaction

Indicator Prompt injection attempts concealed in comments, meta, aria labels, hidden/offscreen/tiny/same-color text and alt attributes

INDEPENDENT VERIFICATION. FACTS RECORDED BY THE HOST.

Blocked by enforcement downloads: 1 download attempt recorded. The worker never keeps or opens files, and the sandbox was verifiably destroyed.



CONTAINED, AND PROVED

- Requests to private networks and metadata: **blocked by the firewall**, with the browser's real error.
- Download: never kept. Frozen page: survived.
- Hidden instructions: extracted, shown, not obeyed.
- A row says contained only when host-recorded events prove it.

ARCHITECTURE AND TRUST BOUNDARIES

THE MODEL CANNOT GRANT ITSELF ANYTHING

BROWSER UI	ORCHESTRATOR	AI AGENT	RULE ENGINE	SANDBOX
Shows evidence as plain text. Strict CSP.	FastAPI on a Vultr VM. Assigns every event. TRUSTED	glm-5.3-flash on Vultr Serverless Inference. PROPOSES ONLY	One action allowed: open an observed link in a new sandbox. DECIDES	Chromium in Docker behind an iptables egress firewall. HOSTILE

- **No security control depends on the model.** Network, filesystem, limits and secrets are enforced by the runtime.
- Page content reaches the model only as data, inside a marked untrusted block.
- Three checks that ignore the model's opinion: a planted secret, a with and without hidden text comparison, and hidden-text patterns. They can **raise** a verdict, never lower it.

PROOF OF CONTAINMENT · LIVE VM

40 OF 40 SANDBOX CHECKS PASS

- Real containers with the app's exact flags, real network attempts. Nothing mocked.
- Each "blocked" check also requires the **firewall rule's packet counter to rise**.
- Metadata, RFC1918, CGNAT, host and own public IP: blocked. Public HTTPS: allowed.
- Read-only rootfs, no capabilities, non-root, no mounts, no secrets in the container, including the AI key.
- Memory limit kills at 1 GB, pid limit at 256, a killed sandbox is gone within about 250 ms.
- Raw output: docs/VERIFICATION.md

ADVERSARIAL BENCHMARK · REAL MODEL, REAL SANDBOX

ATTACKS AGAINST THE AGENT, MEASURED

11/11
attacks detected

0/3
false alarms on safe pages

4/4
unauthorized agent actions blocked


14/14
scans with no planted-secret leak

RUN	PASSED	WHAT WE LEARNED
1	13 / 14	Model trusted a page's own "test page" label. Fix: page claims are not evidence.
2	13 / 14	An app restart removed a benchmark sandbox. Fix: sandboxes tagged by owner.
3	14 / 14	All fixes in place.
4	14 / 14	Re-run after QR input and UI changes: no regressions.

QR CODES

QUISHING, CONTAINED

- The image is decoded in a container with **no network**. The app never parses it.
- Nothing opens until you click. Then the normal pipeline runs.
- Metadata and private addresses: refused. `javascript:` and `data:` links: never opened. Wi-Fi passwords: hidden.



WHO PAYS

BUILT FOR SECURITY TEAMS

- **IT and security teams** that get "is this link safe?" from staff, every day.
- **Managed security providers** triaging reported phishing for many clients.
- Every report is evidence a person can check and act on, not just a score.

- Pricing: per seat for teams, or per scan through an API.
- Next: forward-an-email intake, gVisor for a second isolation layer, a larger public benchmark.
- Honest limits: shared host kernel, Chromium runs without its own sandbox inside the container, a 14-case suite.

TRY IT

EVIDENCE OVER CLAIMS

Live app	https://185.92.220.83.sslip.io
Benchmark	https://185.92.220.83.sslip.io/benchmark
Code	https://github.com/djihane19/link-detonator
Start with	"Run the Gauntlet", then a QR code from demo/qr/

THE PAGE TRIES TO STEER THE AI.
THE AI DOES NOT CONTROL ITS OWN BOUNDARIES.