



Unix System

my_irc

Contact b-psu-330@epitech.eu



Table des matières

| | |
|------------------------|---|
| Administrative details | 2 |
| Subject | 3 |
| Constraints | 5 |
| Forbidden functions | 6 |
| Allowed functions | 7 |



Administrative details

- The sources must be turned-in on the SVN repository
- Turn-in :
`svn+ssh ://kscm@koala-rendus.epitech.net/myirc-promotion-login_x`
- Your binaries shall be compiled by one (and only one!) Makefile.
- The server binary shall be named `server`
- The client binary shall be named `client`
- This project must be done in groups of two.
- Your report should contain a `auteur` file with the logins to each group member, separated by `' ; '`



Subject

- The aim of this project is to realise a IRC client / server.



Indices

For those who do not know IRC, it is a kind of CHAT, or a chat system in real time, which manages discussion groups called "channel", and also allows file exchanges.

- the communication network will be through TCP sockets.
- Your server will accept multiple simultaneous connections.



Attention, the use of fork is prohibited. So you should imperatively use **select**

- You may refer to the already existing code, it's a rough draft server. It is available as a guide with the subject.



However, it is strictly forbidden to make a simple copy / paste of the provided code. This will be considered as an element of cheating.

- Your server must not be blocking (the provided code is blocking)



Only one **select** is allowed in your project



Indices

This has nothing to do with non-blocking sockets, which are prohibited (so do not use `fcntl(s, O_NONBLOCK)`)

- Your server and your client will manage the following command :
 - `/server _host_ [:_port_]` : connects to a server
 - `/nick _nickname_` : defines the nickname of the user in the channel
 - `/list [string]` : list the channels available on the server. Displays only the channels containing the string "string" if it is specified.
 - `/join _channel_` : joins a channel on server
 - `/part _channel_` : leave the channel
 - `/users` : display the users connected to the channel (display the nicknames of course)
 - `_message_` : sends a message to all users connected to the channel.



- /msg _nickname_ _message_ : sends a message to a specific user
- /send_file _nickname_ _file_ : sends a file to a user.
- /accept_file _nickname_ : accepts the reception of a file from a user from the channel.



Constraints

Your code will not only be non-blocking, but will also **use** "turning round" tampons to secure and optimize the sending as the receiving of the various commands and responses.

It is your responsibility to produce a "clean" code, checking absolutely every error and every case that could cause problems. Otherwise, we will have no difficulty making your server inoperable (and therefore non-functional).



Indices `man nc + Ctrl-D`

Your client may be graphic. You have the possibility to use a graphics library (GTK, SDL, ...) as it is a C library or C++.

However, the network portion must imperatively be achieved through the C library functions... (no QtNetwork for example).



Forbidden functions

- fork



Allowed functions

- the C library