

# Mathematics Behind VAR

## 1 Motivations

A Vector Autoregression (VAR) model is a type of autoregressive model which aim to predict the next value in a sequence by measuring the previous values and are used in time series data of the like that we're looking in to.

A VAR model is an extension of this that models multiple variables and looks at the relationships between them.

In a VAR model all variables are modelled as if they influence eachother equally

## 2 Process

For each time step, the model has one equation for each variable within the system, so in our case there will be 8 equations at each time step. Below I give an example of the equations for a VAR model with 2 variables,

$$y_{1,t} = c_1 + \phi_{11,1}y_{1,t-1} + \phi_{12,1}y_{2,t-1} + e_{1,t}$$

$$y_{2,t} = c_2 + \phi_{21,1}y_{1,t-1} + \phi_{22,1}y_{2,t-1} + e_{2,t}$$

where,

$y_{i,t}$  is the  $t$ th observation of the  $i$ th variable

$c_i$  is a constant

$\phi_{ii,l}$  captures the influence of the  $l$ th lag variable of  $y_i$  on itself

$\phi_{ij,l}$  captures the influence of the  $l$ th lag variable of  $y_j$  on  $y_i$

$e_{i,t}$  are white noise processes that maybe be related

The goal is to estimate parameters for each equation so as to minimise,

$$\sum e_{i,t}^2$$

### 2.1 Lag Variable

Lag variables are key to the VAR model. It is a previous observation of the variable in question and allows us to predict our next value dependent on those we have already seen if there is such a relation between the current values and those we have encountered previously.

### **3 How and why we're using the VAR model**

For our project, we're using the VAR model as a baseline. It's appropriate for our data as it's a model that is commonly used for time series and it is also a lot simpler than the models we're going to delve into later. This gives us a good starting point for comparison when it comes to how long it takes to run and the amount of memory it takes.