
AI Prompt Transcript



New Bot

i thought (3) where to look first across the catalog , would be the most pressing because it directly translates to missed opportunities and my reasons for thinking so are as follows
1. what doesean to have a lot of users come and browse products, without making a purchase? i think it translates to either not having products attracting interest resulting in weak conversions. so, in such cases, it may be important to distinguish discovery of products, pricing, availability, and product-information issues, lack of popular variants (like colour or size).
2. identify products that are unavailable when the interest in them may be rising. this should need an investigation instead of automatically suggesting an order quantity.

New Bot

You're right to push that — I was optimizing for *cash left on the table today* (our 41% OOS), but your framing is the better operating system: **attention first is the diagnosis layer**, and restock/CRM are actions that should only fire after we know *why* interest isn't becoming a sale.

Your two reasons land. A browse-heavy, buy-light session isn't one problem — it's a mix of weak discovery, price friction, thin info, missing colour/size, or true stockout — and without that split we either restock the wrong SKU or discount something that never had intent. Rising interest on an unavailable style should open an **investigation queue** (is demand real, substitutable, seasonal, or a listing bug?), not an auto PO.

I'd revise the rank to: **(1) where to look first**, **(2) restock which SKUs and how fast** (only after intent is classified and rising-OOS cases are reviewed), **(3) who to target and with what**. Beacon's job becomes triage: score products by intent vs conversion, tag the failure mode, and route "rising interest + unavailable" to a buyer review card instead of a blind reorder.

i would infact combine (1) and (2). the second point of my explanation above nudges me towards the conclusion that, if we are to do some kind of interest based (maybe, include seasonality) demand forecasting, then the strength of interest and the extrapolation of a possible loss (in case of lack of inventory) would define the urgency of restocking naturally. what is your feedback on this as an online seller?

my main issue with demand forecasting is that i will have to synthesize a lot of dimensions in the user browsing dataset that i am going to create and the problem will be that i wont know if the solution did not work for the problem or the data did not mimic the reality. can you figure out how a senior data analyst approach this problem? what kind of data will mimic a rasonable catalog interaction.

New Bot

As a seller I'd combine them the way you describe: **restock urgency = strength of intent × expected lost margin if we stay OOS**, with seasonality as a multiplier, not a separate system. That keeps "where to look" and "what to reorder" as one queue sorted by dollars at risk — as long as rising-interest OOS still opens a **review** before the PO, not an auto-buy.

Senior-analyst move for your "model vs synthetic data" fear: **never train and score on the same fiction**. Keep a hidden ground truth (you already have `true_demand` / `lost_sales` in `demand/ground_truth.json`) and only expose Beacon to `daily_metrics` (sales, stock, PV, cart, wishlist, alerts). Then run three checks: (1) does the model recover lost sales on held-out SKU-days, (2) do observables obey real catalog invariants (funnel PV≫cart≫wishlist, size curves peaked mid-range, OOS boosts alerts not sales), (3) ablate one mechanism at a time — if realism fails, fix the generator; if realism holds and scores fail, fix the model.

Reasonable interaction data for Allbirds looks like SKU-day rows with session→PDP→size/colour select→cart/wishlist/BIS alert, **censored sales = min(demand, stock)**, sibling-size substitution when a size holes out, and seasonal bumps by subcategory — which is basically the path your `allbirds_pv_generator.py` is already on; harden it with those invariants and a locked eval split so you always know which side broke.

New Bot

yes, thats the idea behind keeping true_demand, which i want to keep hidden during training. the way i think it can be modelled is by factoring the contributions from both seasonality and trend to the base for each sku. base is just randomly generated constant for the avg number of units for that sku units sold/day. always take the floor value of what we have in the ground_truth.json. i am also adding small amount of noise so that the numbers truely look random over days. modify the generator script to follow the checks and invariants.

New Bot

Updated `allbirds_pv_generator.py` and regenerated `demand/`. Demand is now `true_demand = floor(Poisson(base × seasonality × trend × noise))` with a per-SKU constant base (Zipf + mid-size weight), subcategory seasonality, integer stock, and censored sales.

Hard invariant checks run at the end of every generate: floored GT counts, sales=min(demand,stock), OOS⇒no sales, BIS only on lost-sales, funnel PV≥cart≥wishlist≥pricedrop, mid-size ≥ extremes. Full 90-day run: all PASS (318k latent units, ~3.7% lost).

One design call: pure `floor(mean)` zeroed the long tail, so I wrapped the mean in a Poisson draw before flooring — same structure you described, but days actually look random. Say if you want strict floor-only instead and I'll swap it.

no, i did not think that flooring small values will take out the long tail. lets keep the values as is.

New Bot

Got it — flooring was my overreach. Reverted to continuous `true_demand = base × seasonality × trend × noise` (long tail kept as fractional values) and regenerated `demand/`. All invariants still PASS, including a check that fractional demand is actually present.

Yesterday 9:38 PM

there is some issue with the json format in daily_metrics.json. i have the following error JSONDecodeError: Unterminated string starting at: line 2182300 column 5 (char 82833698)

New Bot

That error is almost always a **truncated copy** of a huge pretty-printed JSON (unterminated string mid-file), not bad schema — the source `demand/daily_metrics.json` on disk validates clean (837k rows).

I rewrote the outputs as **compact JSON** (~491MB) plus streaming **`daily_metrics.jsonl`** / **`ground_truth.jsonl`**, and the generator now writes those by default. Prefer the `.jsonl` in Colab (`pd.read_json(..., lines=True)`), or re-copy the compact `.json` if you need the array form.

still some malformed identifier

JSONDecodeError: Extra data: line 2 column 1 (char 577)

New Bot

That's the `.jsonl` file — `json.load` reads the first object, then chokes on line 2 ("Extra data … char 577"). Use `demand/daily_metrics.json` with `json.load`, or keep the `.jsonl` and stream it:

```
import pandas as pd
df = pd.read_json("daily_metrics.jsonl", lines=True)
```

New Bot

i am trying to load the data with
metrics = pd.read_json("daily_metrics.jsonl", lines=True)
truth = pd.read_json("ground_truth.jsonl", lines=True)

try these yourself and fix the issues with the json structure

New Bot

I ran your exact loads on `demand/` — both succeed: `metrics` (837000×17), `truth` (837000×16). Line-by-line audit also found **0** malformed rows, so the JSONL structure itself is fine.

I rewrote both `.jsonl` / `.json` through pandas (canonical records) and added much smaller parquet twins: `daily_metrics.parquet` (5.6MB) and `ground_truth.parquet` (8.6MB). If Colab still errors, you're likely on a stale/truncated upload — reload from disk or use `pd.read_parquet(...)`.

Yesterday 10:25 PM

in cell 22 of the notebook, i have defined three product categories
category 1:
availability risk - currently unavailable but customer interest is rising (search, signing for availabe notfications)

category 2:
discovery opportunity - product searches appears poorly served by the available catalog attributes (no further action post search).

category3:
needs investigation - lot of product searches and fat inventory, but no actions on the skus.

review the formulas and the math and tell me if i am missing something. the data is sparse, thats why i am using log scale

New Bot

Quick read on the math: `log1p` on sparse counts is the right move. The main hole is a **ground-truth leak** — window agg still pulls `true_demand` / `lost_sales`, and `A_score` multiplies `r_lost`, so ranking isn't "observables only" even though the membership mask is.

Vs your definitions: **A** should also require rising **BIS / notify-me** (`r_bi` / `intent_trend`), not only `pv_trend` + stockout. **B** matches "high search, weak post-search action" only half-way — add low `cart_per_view` *and* low wishlist/sales given high PV; size-gap alone isn't "no further action." **C** in the notebook (high wl/bi/pdalert + low sales / ambiguous stock) is almost the opposite of what you just said — that one wants **high PV + fat stock (low stockout) + near-zero actions** (no cart/wishlist/BIS).

For sparse trends, replace `(r-p)/clip(p,1)` with `log1p(r)-log1p(p)` so a 0→3 bump doesn't look like a 200% surge. Also make A/B/C mutually exclusive (priority A→B→C) or you'll double-count the same OOS hero SKU. I can patch cell formulas if you want.

write an analysis script to create these three product categories. persist output in a file. i should be able to read the file using pandas.

New Bot

Script is at `analyze_product_categories.py`. It builds A/B/C from observables only (no ground truth), uses `log1p` trends, and enforces A→B→C priority.

New Bot

now, i want to build the market intelligence around this product category data. think of the application as a RAG and we are building a poc for an orchestration framework (think langchain) which uses this RAG to answer the merchant queries. we are not going to use a tokenizer or an LLM. but the application will mimic that it understands queries (predefined queries) and will use the product_categories to answer them (in pre-defined format). folloiwng are couple of examples of such questions and the logic to retrieve the rows from the category file.

Q. which products should i restock first?
high intent + unavailable product -> many notify-when-available subscriptions, but stock is zero. -> investigate replenishment and expected availability.

Q. which products are well stocked, but have no sales?
demand exists, but shoppers cannot find the product -> search queries show demand, but the right products are not ranked higher. -> investigate search relevance, filters, and catalog attributes that are used for relevance boosting.

Q. which products people are not buying because they are expensive?
high interest + possible price resistance -> users add them to wishlist or cart, and subscribe for price-drop notifications, but conversion remains slow. -> investigate pricing and check if similar products (similar product type) with similar price have conversion.

Q. which priducts have high traffic, but no sales?
high traffic + weak interest (no actions) -> product receives visits but few action signals (like add to cart, wishlist or subscribe for price-drop notification). -> investigate broken product page, product relevance.

does this make sense to you? ask questions if it does not?
can you recommend queries like these which are useful to you as a merchant, are not implicitely available from shopify and can be answered using the data we have curated.

New Bot

Yes — a fake-LLM router over predefined queries into ranked rows from `product_categories` (+ light joins to metrics) is a solid PoC. One tension: **Q2 vs Q4** both read as "in stock, no sales" — I'd split them cleanly as **findability** (high search/PV elsewhere in the type, this SKU buried / attribute gap) vs **PDP failure** (this product gets the visits, still no cart/wishlist/price-drop). Also: we don't have raw search strings, only PV/intent proxies — say that in the answer template so the merchant doesn't think we're reading Google queries.

Useful extras Shopify orders won't give you, that our curated signals can answer: (1) **who to BIS-notify first** among OOS styles, (2) **price resistance vs subcategory peers** (high pdalert+wishlist, slow sales, peer converts at similar price), (3) **cart but no buy while in stock** (checkout/friction), (4) **size-run holes** (intent on missing UK sizes), (5) **dead stock** (fat inventory + flat/falling PV + no actions), (6) **rising-star before it sells out** (steep intent trend, still available — protect inventory).

Quick checks before I scaffold the orchestrator: answer format = short diagnosis + top-N product table from the parquet? And is the "query understanding" just keyword/intent → one of these handlers (no embeddings)? If yes, I'll wire that next.

suggest me few templates. i will choose the best suited

New Bot

Here are **6 query templates** — pick the ones you want wired:

1. Restock first
`intent: restock`
Match: A / high `u_stockout|catalog_size_gap` + rising interest + BIS
Answer: "Expedite replenishment for {n} styles with rising intent while unavailable." + top-N by `A score`

`intent: findability`

Match: fat stock + weak on-product actions + high subcategory PV peers / size-gap
Answer: "Shoppers look in this category but don't engage these in-stock styles — likely ranking/filters/attributes."
Cols: product_name, r_pv, r_actions, catalog_size_gap, subcategory
Action: search relevance, filters, attribute boosts.

3. PDP / traffic waste (high traffic, no actions)
`intent: pdp_weak`
Match: C — high `r_pv`, low stockout, low actions
Answer: "High visits, almost no cart/wishlist/alerts — page or relevance issue."
Cols: product_name, r_pv, r_actions, action_per_view, r_stockout, C_score
Action: audit PDP, media, sizing, broken ATC.

4. Price resistance
`intent: price`
Match: high `r_wl+r_ca+r_pdalert`, low `r_sales`, in stock; compare peer conversion in same subcategory/price band
Answer: "Interest without conversion; peers at ~£{p} convert better/worse."
Cols: product_name, price, r_pdalert, r_wl, r_sales, subcategory, peer_sales_rate
Action: pricing test / promo / compare similar type.

5. Dead stock
`intent: dead_stock`
Match: high `mean_stock`, flat/negative `pv_trend`, low actions
Answer: "Capital tied in styles shoppers aren't engaging."
Cols: product_name, mean_stock, pv_trend, r_actions, r_sales
Action: markdown, bundle, or delist.

6. Protect rising stars
`intent: rising_star`
Match: strong `interest_trend`, still available (low stockout), healthy actions
Answer: "Intent rising and still in stock — guard inventory before it becomes an A."
Cols: product_name, interest_trend, r_actions, r_stockout, r_sales
Action: raise reorder point / ads on winners.

Each template shares one shell: `{headline}` → `{why_it_matters}` → `{top_n_table}` → `{recommended_action}`. Tell me which numbers (e.g. 1,3,4,6) and your top-N (5/10/15).

keep N=5 and add all 6 queries

New Bot

Wired all **6 queries at N=5** into a tiny LangChain-shaped PoC (keyword router → retriever → fixed answer shell). No tokenizer/LLM.

Run: `python run_merchant_rag.py` (or `python -m merchant_rag.cli -q "which products should i restock first?"`). Answers persisted at `demand/merchant_answers.json` — also readable with `pd.json_normalize(answers, "products")` after `json.load`.

we have calculated the loss over days because of missed opportunities. that should be in the result. i think it naturally translates to urgency

New Bot

Agreed — **missed-opportunity loss is the urgency**. I joined 60d/14d `lost_units` and `lost_revenue` (£) onto `product_categories`, and restock now ranks by that loss (interest only boosts, doesn't gate).

Top restock answer now leads with ~£57k / 408u lost on Runner Chelsea Protect, then Piper

New Bot

Top restock answer now leads with ~£57k / 408u lost on Runner Chelsea / Retest, then Apex (~£3.8k), then Cruiser Jersey (~£1.2k). Same loss fields show up on the other 5 query payloads in `demand/merchant_answers.json`.

Today 7:11 AM

one issue i realize in the intent data is missing funnel, because our view is demand centric and not shopper centric. i would like the data for a shopper to reflect their journey, like, search -> product view -> visit skus -> add to wishlist -> maybe subscribe to price-drop notification -> maybe return and buy. this is only one example and there can be many such shopper journeys. i would like to change the script as
1. generate N=10000 shoppers belonging to one of the following archetype (casual, comparer, decisive, deal-hunter, size-constrained and out-of-stock disappoints, wishlist-fillers)
2. each shopper has a session (variable session lengths) over the simulation window
3. each session is a sequence of events, drawn conditionally. we have defined the events like add-to-cart, add-to-wishlist, subscribe-to-out-of-stock-alerts, etc
4. some events lead to purchases (add realistic delay for conversion)

review the genertor script and then plan these changes. lets review the plan first and then implement

New Bot

Agreed on the gap. Current `allbirds_pv_generator.py` is demand-first: it draws SKU-day `true_demand`, reverse-infers `latent_shoppers = demand / conversion`, then independently Poisson-samples PV / cart / wishlist / alerts. So funnel totals look ordered, but there is no shopper, no session, no path dependence, and no delayed buy after a wishlist or BIS alert.

Proposed plan (review before code):

1. Keep catalog load, Zipf/size/seasonality as attraction weights, and (s,S) stock + sibling substitution.
2. Add N=10k shoppers with archetypes (casual, comparer, decisive, deal-hunter, size-constrained / OOS-disappointed, wishlist-filler), each with preference biases and transition probs.
3. Over the window, each shopper gets 1..K sessions of variable length; a session is a conditional event chain, e.g. `search → product_view → sku_view → {add_to_cart | wishlist | bis_alert | price_drop | bounce}`, with archetype-specific branches.
4. Purchases fire from cart / revisit / alert callbacks with a lag (hours–days), censored by stock at buy time; lost demand is "wanted but OOS," not a free-floating SKU-day Poisson.
5. Outputs: `shoppers` + `sessions` + `events` (journey grain), then roll up to today's `daily_metrics` / `ground_truth` so Beacon and the RAG PoC keep working.

Open choices before we implement: (a) extend this script vs new `shopper_journey_generator.py`, (b) archetype mix weights, (c) whether Beacon's primary training grain stays SKU-day or also trains on events. Prefer extend-in-place with a `--mode shopper` flag unless anyone wants a clean split.

write a new script. i would like to compare the two generated datasets and look for gaps.
the decisive shopper type should be least in the mix (say, 5% users convert), remaining you can adjust between 6-20% each.
training should be on the new dataset. am i missing something for (c)?
do not extend in-place.copy the functions that you need. this is a standalone script that runs once and is decoupled from the beacon application. so, do not worry about writing it in optimal way

New Bot

Locked in: new standalone script (copy what we need from the old generator), decisive ~5%, other archetypes in the 6–20% band, train on the shopper data.

New Bot

One more gap worth naming: delayed conversions and multi-session returns need a stable `shopper_id` across days, plus stock state at the buy timestamp (not just "session day"). If that matches what you meant, say go and I'll write the new script.

yes, we need a unique shopper identifier across days. think of this as their system generated uuid, stored in their app/browser cookie. do not worry about authenticated/unauthenticated users

New Bot

Got it. `shopper_id` = opaque UUID cookie, stable across sessions and days, no auth split. Ready to write the standalone generator when you say go.

implement

New Bot

On it — writing a new standalone shopper-journey generator next to the old one, with UUID shoppers, archetype mix, sessions/events, delayed buys, plus a SKU-day rollup for comparison.

Writing `shopper_journey_generator.py` now; I'll ping the room when the smoke run lands.

Done. New standalone script: `shopper_journey_generator.py` (old generator untouched).

Full run under `demand_shopper/` (90d / 10k): 10,000 UUID shoppers (decisive 5%, others 19% each), 217,860 sessions, 993,792 events, 126,537 successful purchases (mostly delayed: 118,632 vs 7,905 same-session), 4,589 OOS-blocked. Also wrote journey rollups `daily_metrics` / `ground_truth` (journey-derived fields — not interchangeable with old `true_demand` / `lost_sales`) plus shoppers/sessions/events.

Smoke copy at `demand_shopper_smoke/`. Ready to compare against `demand/` whenever you want.

Today 8:33 AM

did you rename or replace the columns. i'm getting key error in the notebook, cell 5
KeyError: "['true_demand', 'effective_demand', 'potential_sales', 'actual_sales', 'lost_sales', 'conversion', 'latent_shoppers'] not in index"

New Bot

Yes — I renamed them on purpose. The shopper `ground_truth` is journey-derived, not the old Poisson fields, so those old keys are gone.

Mapping for the notebook merge:

old	new
`true_demand`	`journey_demand`
`lost_sales`	`lost_units`
`actual_sales`	`sales`
`potential_sales` / `effective_demand` / `conversion` / `latent_shoppers`	dropped (no direct equivalent)

Also: load `ground_truth.jsonl` / `daily_metrics.jsonl` (or the `.parquet`s), not the old `.json` names — and `availability` is still there.

Want me to patch `allbirds_notebook.ipynb` cell 5+ to the new column names?

New Bot

Yes — I renamed them on purpose. The shopper `ground_truth` is journey-derived, not the old Poisson fields, so those old keys are gone.

Mapping for the notebook merge:

old	new
`true_demand`	`journey_demand`
`lost_sales`	`lost_units`
`actual_sales`	`sales`
`potential_sales` / `effective_demand` / `conversion` / `latent_shoppers`	dropped (no direct equivalent)

Also: load `ground_truth.jsonl` / `daily_metrics.jsonl` (or the `.parquet` s), not the old `.json` names — and `availability` is still there.

Want me to patch `allbirds_notebook.ipynb` cell 5+ to the new column names?

yes

New Bot

Patching the notebook for the shopper columns and jsonl/parquet loaders now.

Notebook patched. `allbirds_notebook.ipynb` now merges `journey_demand` / `lost_units` / `purchase_attempts` / `strong_oos_intents` (old keys gone). Backup at `allbirds_notebook.ipynb.bak`.

Set cwd to `demand_shopper` before running cell 5 — it prefers parquet, falls back to jsonl. Substitution section is now OOS-intent by size, since there is no day-vector inflow anymore.

refactor the remaning cells

New Bot

Scanning the notebook for cells that still need the shopper-journey refactor.

On it — finishing the leftover renames, cleaning §9, and adding a shopper/session/event block so the rest of the notebook matches the new grain.

Remaining cells refactored in `allbirds_notebook.ipynb`.

- Leftover `true_total` → `journey_total`
- New §2 shopper grain: loads shoppers/sessions, streams events for funnel + same-session vs delayed purchases (events stay out of a full DataFrame)
- Old §9 cleaned into **OOS Intent Pressure**; sections renumbered through 13
- Exec summary prints shopper/session/event counts when those files are in cwd

Still run with cwd = `demand_shopper`.

Today 9:07 AM

the correlation between availability of the sku and the sales or add-to-cart events are very low. is it because the availability data is skewed towards available

New Bot

New Bot

Scanning the notebook for cells that still need the shopper-journey refactor.

On it — finishing the leftover renames, cleaning §9, and adding a shopper/session/event block so the rest of the notebook matches the new grain.

Remaining cells refactored in `allbirds_notebook.ipynb`.

- Leftover `true_total` → `journey_total`
- New §2 shopper grain: loads shoppers/sessions, streams events for funnel + same-session vs delayed purchases (events stay out of a full DataFrame)
- Old §9 cleaned into **OOS Intent Pressure**; sections renumbered through 13
- Exec summary prints shopper/session/event counts when those files are in cwd

Still run with cwd = `demand_shopper`.

Today 9:07 AM

the correlation between availability of the sku and the sales or add-to-cart events are very low. is it because the availability data is skewed towards available

New Bot

Yes — mostly the skew. In `demand_shopper`, `availability` is almost binary: ~96.7% of SKU-days sit at exactly 1, ~3.3% at exactly 0, nothing in between. Pearson needs variance on both sides, so a near-constant "in stock" flag barely correlates with anything.

Two extra twists: sales are sparse even when available (most in-stock days still have `sales=0`), and cart/PV still fire on OOS days (mean cart is actually a bit higher OOS), so `corr(availability, add_to_cart)` can sit near zero or slightly negative. The real availability effect shows up as hard censoring — sales go to 0 when `stock_start=0` — not as a smooth linear correlation.

lets increase the number of users to 50k and add a fixed number of sales daily (skus will differ). start with 2000 sale events every day. regenerate the data

New Bot

Updating the generator for 50k shoppers plus a 2,000 sales/day floor, then regenerating `demand_shopper`.

This will take a bit — 50k shoppers over 90 days is heavier than the last run. I'll post counts and sales/day when `demand_shopper` is rewritten.

Today 9:35 AM

New Bot

`demand_shopper` regenerated: 50k shoppers, `--daily-sales 2000` floor.

90d run: 1.09M sessions, ~5.0M events, 621k successful purchases. Sales/day min=2000, mean≈6905, max=7549 (0 days below floor). Injection only filled Jul 1–3; after that organic volume alone cleared 2k/day across varying SKUs.

Old Poisson generator untouched. Re-run the notebook with cwd= `demand_shopper` — availability skew should ease a bit with denser sales.