

بينو ميروني للصناعات الخشبية والمعدنية
القطعة 49 ب 50
المنطقة الصناعية السادسة
اكتوبر GZ
مصر
معرف الضريبة: 205119999

رقم عرض السعر 2026/0017728

مندوب المبيعات
(Mohamed Hashim A.Karim Mahmoud (Kaeser Sales

تاريخ عرض السعر:
27 سبتمبر , 2026

#	الوصف	(PART # (BARCODE	الكمية	سعر الوحدة	المبلغ
1	ضاغط حلزوني كيزر CSDX 145/10	CSDX145/10	1.00 وحدات	1,989,000.0000	L.E 1,989,000.00
المبلغ دون الضريبة					L.E 1,989,000.00
ضريبة القيمة المضافة					L.E 278,460.00
الإجمالي					L.E 2,267,460.00

الخيارات

الوصف	سعر الوحدة
[1010121019081] ضاغط حلزوني كيزر ASK 40/11	L.E 714,600.00
[10101310138920010] ضاغط حلزوني كيزر SC3 BSD 83/125	L.E 1,404,000.00

الشروط العامة

الارتباط : يوم من تاريخ تقديم العرض .

التوريد : بضاعة حاضرة تخضع لاسبقية البيع او الحجز النقدي

الدفع : 100% عند الاستلام نقداً أو بشيك مقبول الدفع بإسم (شركة تكنولوجيا الهواء المضغوط - الحجار مصر)


علماً بأن بيانات حساب شركة الحجار كالتى:

البيان : رقم حساب البنك الاهلى المصرى (جارى مدين)

رقم الحساب: 1923070362172300024.

IBAN: EG400003019230703621723000240

الأدارة و الفرع الرئيسي : ك 28 طريق القاهرة - الأسكندرية الصحراوي - أبو رواش - الجيزة ت : 35391986 - 02 - ف : 35391990 - 02
فرع 6 أكتوبر : مجمع علي الدين - مبني أ محل 34 - مدينه 6 أكتوبر - الجيزة ت : 38838329 - 02 - ف : 38838944 - 02
فرع العاشر من رمضان : مجمع نجوم الصفاء الأردنيه - مبني أ ت : 4351065 - 055 - ف : 4371205 - 055



التسليم : مخازننا بأبورواش .

الضمان : 12 شهر من تاريخ التشغيل او 14 شهر من تاريخ الفاتورة ايهما اقرب بشرط اتباع تعليمات شركتنا الخاصة بغرفة محطة الهواء المضغوط و التركيب حيث ان الاشراف علي التركيب و التشغيل مجانا

• نحيط سيادتكم علما بان لدينا مركز خدمة متخصص يضم نخبة من المهندسين والفنيين الأكفاء للقيام بأعمال الصيانة اللازمة وقطع الغيار الأصلية متوفرة لدينا

ملحوظة الشركة تتبع نظام الدفعات المقدمة بالنسبة للخصم (1%) أرباح تجارية وصناعية وذلك بموجب الخطاب رقم 56173 بتاريخ 01/01/2026

Compressor

KAESER rotary screw compressor

Type: CSDX 145 (air-cooled)


Maximum cost-efficiency

The **CSDX 145** meets your operational needs perfectly: User-friendly and easy to maintain, it operates quietly and efficiently to deliver a cost-effective and dependable source of quality compressed air. These attributes are the result of many innovative solutions in areas such as the airend, compressor controller, Super Premium Efficiency (IE4) motor, cooling and ventilation, silencing, and an integrated KAESER axial centrifugal separator with an electronic ECO-DRAIN condensate drain.

Technical specifications (performance parameters at **10,0 bar working pressure**, relating to the overall system, including fans. In accordance with ISO 1217:2009, Annexe C.)

Flow rate at 10,0 bar (g)	12,80 m³/min
Electrical power consumption, complete system at 10,0 bar (g)	86,3 kW
Max. gauge pressure	10,00 bar
Drive motor efficiency at full load	95,6 %
Drive motor efficiency class	IE4
Drive motor rated power	75,0 kW
Drive motor speed	2982 1/min
Drive motor protection rating	IP 55
Power supply	400V / 3 / 50Hz
Electrical grid, country-compliant	Ja
Mains voltage tolerance, upper	10 %
Mains voltage tolerance, lower	-10 %
Sound pressure level	71 dB(A)

Specifications subject to change without notice.



Technical specifications - Type: CSDX 145

Compressed air discharge temperature above ambient temperature (at +20 °C, 30% rel. humidity)	6 K
Ambient temperature (max./min.)	45 °C / 3 °C
Max. usable hot air volume	11000 m³/h
Comp. air connection	G 2 1/2
Cooling oil fill volume	54,5 l
Compressor cooling oil type	KAESER FLUID ROTARY S-46
Dimensions (W x D x H)	2100 mm x 1280 mm x 1950 mm
Weight	1890 kg
Specifications subject to change without notice.	

Available options

Filter monitoring	Standard
Cooling air filter mat	Nein
MODULATING CONTROL	Nein
Bolt-down machine feet	Nein
Equipped with heat recovery	Nein
Compressor cooling oil type	KAESER FLUID ROTARY S-46

Project planning note:

- Please note that additional compressed air treatment components may be required for your proposal. Compressed air always contains a certain amount of solid matter/particulates, moisture and residual oil content (hydrocarbons in aerosol/vapour form). Depending on the application, a certain degree of treatment may be required (see ISO 8573). We would be pleased to advise you further on this matter.
- As per EMC Directive 2014/30/EU, this product is not suitable for use in residential areas.

Compressor

KAESER Rotary Screw Compressor


Type: ASK 40 (air-cooled)

Powerful and service-friendly

The **ASK 40** is a true class leader when it comes to impressive performance. This has been achieved through continued air end development, further optimisation of the SIGMA PROFILE rotors and low-speed operation. Compared with previous models, these enhancements have enabled free-air delivery to be increased by as much as 16 %. The use of a premium efficiency IE4 motor, the inbuilt SIGMA CONTROL 2 compressor controller, and Kaeser's unique cooling system also contribute to the efficiency of these versatile compressors.

Technical data (performance at **10,0 bar operating pressure**, referenced to the complete system, incl. fan, per ISO 1217:2009 Annex C.)

Free air delivery at 10,0 bar(g)	3,52 m³/min
Overall power consumption at 10,0 bar(g)	26,9 kW
Max. operating pressure	11,00 bar
Motor efficiency, full load	92,7 %
Motor efficiency class	IE4
Rated motor power	22,0 kW
Motor speed	2960 1/min
Motor protection	IP 55
Electrical connection	400V / 3 / 50Hz
Compressed air discharge temperature above ambient (at +20 °C, 30% rel. humidity)	7 K
Sound pressure level	69 dB(A)
Subject to alteration without notice!	



Technical data - Type: ASK 40

Max. useable hot air volume	5000 m ³ /h
Compressed air connection	G 1 1/4
Cooling oil charge	11 l
Compressor cooling oil grade	SIGMA FLUID S-570
Dimensions (L x B x H)	800 mm x 1110 mm x 1530 mm
Weight	525 kg
Subject to alteration without notice!	

Available options

- Adjustable machine mounts
- Modulating control
- Equipped with heat recovery
- Compressor cooling oil grade

Project planning note:

Please note that additional compressed air treatment components may be required for your proposal. Compressed air always contains some particulates/dust, moisture, and residual oil (hydrocarbons in aerosol/vapour form), and a certain degree of treatment is required depending on the application (see ISO 8573). We would be please to advise you further on this matter

Compressor

KAESER Rotary Screw Compressor

Type: BSD 83 (air cooled)


One-to-one drive: ultimate efficiency

The **BSD 83** is designed to meet the toughest of operational demands: User-friendly and easy to maintain, it operates quietly and efficiently to provide a cost-effective and dependable source of quality compressed air. These attributes are the result of many innovative solutions in such areas as airends, industrial PC controllers, high-efficiency motors, cooling and ventilating, sound attenuation, maintenance and servicing.

Technical data (performance at **10,0 bar operating pressure**, referenced to the complete system, incl. ventilator per ISO 1217:2009 Annex C.)

Free air delivery at 10,0 bar(g)	6,85 m³/min
Overall power consumption at 10,0 bar(g)	48,6 kW
Max. operating pressure	12,0 bar
Motor efficiency, full load	95,0 %
Motor efficiency class	IE4
Nominal motor power	45,0 kW
Motor speed	2960 1/min
Motor protection	IP 55
Electrical connection	400 V / 3 Ph / 50 Hz
Compressed air discharge temperature above ambient (at 20 °C; 30 % rel. humidity)	6 K
Sound pressure level	71 dB(A)

Subject to alteration without notice!



Technical data - Type: BSD 83

Max. useable hot air volume	8000 m ³ /h
Compressed air connection	G1½
Cooling oil charge	26/24 l
Compressor cooling oil grade	SIGMA FLUID S 570
Dimensions (L x B x H)	1590 mm x 1030 mm x 1700 mm
Weight	1060 kg
Subject to alteration without notice!	

Available options

- Optional filter monitoring package (standard on BSD range and above)
- Cooling air filter mat
- Modulating control
- Adjustable machine mounts
- Equipped with heat recovery
- Compressor cooling oil grade

Project planning note:

- Please note that additional compressed air treatment components may be required for your proposal. Compressed air always contains some particulates/dust, moisture, and residual oil (hydrocarbons in aerosol/vapour form), and a certain degree of treatment is required depending on the application (see ISO 8573). We would be please to advise you further on this matter. This product complies with EMC Class A (industrial) requirements.