

### (Kernel) Isolation – PV, HVM, OS-V technologies in Linux

Introduction and description of the isolation differences between HM, PV and OS-level virt. technologies.

Zdeněk Kubala Senior QA Engineer zkubala@suse.com @n1djz88

#### Paravirtualization

#### Paravirtualization (a.k.a. PV - Xen)

- Not kernel module, uses a hypervisor(domain 0)
- Guest OS has to be aware of the fact it is being paravirtualized(Kernel 3.0+).

 Hypervisor provides ABI to communicate and Guest OS calls it

#### Paravirtualization (a.k.a. PV)

- "No" Performance losses (direct access to resources)
- Faster boot Can boot kernel directly (no bootloader)
- Guests uses own kernel
- Isolation on the underlying OS processes could be secured by Apparmor/Selinux

# Hardware-assisted virtualization

### Hardware-assisted virtualization (a.k.a. HVM)

For example: KVM or Xen

Using "hypervisor" - guests are completely isolated

- binary translation to trap and virtualize nonvirtualized instructions => emulation
- Has own bootloder
- Has own kernel
- Not modified OS.

### Hardware-assisted virtualization (a.k.a. HVM)

- All resources are handled in-directly through emulation.
- Nowadays PVHVM can be used if OS supports it (Kernel 2.6.32+)

Needs CPU flags (Intel vmx | AMD svm)

## Operating-system-level virtualization

### Operating-system-level virt. (a.k.a. containers)

When we talk about containers we can think about a book in a shelf. There are multiple chapters in the book. Every chapter has a different "story" but they belong to the same piece of book.

\_\_-8-8\_\_-8-8-8\_8--8-8\_-8-8-8\_-8-8\_-8-8-8

### Operating-system-level virt. (a.k.a. containers)

- Sometimes called as "jail on steroids".
- Containers provide an additional layer of the security by isolating resources on a OS level
- Can be used together with apparmor/SELinux to enhance security

\_\_-8-8\_\_-8-8-8\_8--8-8\_-8-8-8\_-8-8\_-8-8-8

### Operating-system-level virt. (a.k.a. containers)

- Solves issues with shared libraries(multiple versions) and helps with keeping OS clean
- Easily destroyed
- Sharing the kernel with the host

# Differences between virtual machines & containers

### Differences between virt. machines & containers

- VMs are "heavier" to setup/start in general
- OS boot takes up to minutes (PV/HVM difference)
- HW isolation on a hypervisor level(HVM/PV/PVHVM)
- Qemu process represents virtual machine, storage backend involved

### Differences between virt. machines & containers

- Lightweight(MiB-"hundreds of MiB")
- Can be application oriented
- Isolation on an OS level process tree

- chroot \*1982
- OpenVZ \*2005
- lxc(lxd) \*2008
- docker \*2013
- systemd-nspawn \*2013

**chroot** \*1982

- partial file system isolation
- nested virtualization

#### **OpenVZ** \*2005

- file system isolation
- disk quotas (ZFS)
- IO limiting
- memory limits
- cpu quotas
- network isolation
- partial nested virtualization
- live migration
- root isolation

#### **lxc(lxd)** \*2008

- file system isolation
- partial disk quotas (lvm/btrfs)
- partial IO limiting (btrfs)
- memory limits
- cpu quotas
- network isolation
- partial nested virtualization
- root isolation

#### **docker** \*2013

- file system isolation
- IO limiting (since 1.10)
- memory limits
- cpu quotas
- network isolation
- partial nested virtualization
- root isolation (since 1.10)

#### systemd-nspawn \*2013

- file system isolation
- disk quotas
- partial IO limiting (systemd+Cgroups)
- memory limits (systemd+Cgroups)
- cpu quotas (systemd+Cgroups)
- network isolation
- nested virtualization
- root isolation

- PID namespace Process identifiers and capabilities
- UTS namespace Host and domain name
- MNT namespace File system access and structure

- IPC namespace -Process communication over shared memory
- NET namespace -Network access and structure
- USR namespace -User names and identifiers

Controls the location of the file system root

Cgroups

Resource protection(cpu usage, memory usage, io)

# When to choose containers and when vms

#### When to choose containers

testing a new application(from source - from the internet)

.-2-2\_--2<u>-2\_2-2---</u>2

 fast deployments - "iso" template for the application(or for whole cycle)

#### When to choose vms

 wider isolation(running in the process, access to resources is filtered/emulated HVM or through api/drivers PV)

\_\_-8-8\_\_-8-8\_8\_8--8-8-8-8-8

"sendboxes" for customers




#### Questions?

#### Sources:

https://en.wikipedia.org/wiki/Hardware-assisted\_virtualization https://en.wikipedia.org/wiki/Operating-system-level\_virtualization http://www.linux-magazine.com/Issues/2016/184/systemd-nspawn

> Zdeněk Kubala Senior QA Engineer zkubala@suse.com @n1djz88

### Thank you



Zdeněk Kubala Senior QA Engineer zkubala@suse.com @n1djz88

Join Us at www.opensuse.org

#### License

This slide deck is licensed under the Creative Commons Attribution-ShareAlike 4.0 International license.

It can be shared and adapted for any purpose (even commercially) as long as Attribution is given and any derivative work is distributed under the same license.

Details can be found at https://creativecommons.org/licenses/by-sa/4.0/

#### General Disclaimer

This document is not to be construed as a promise by any participating organisation to develop, deliver, or market a product. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. openSUSE makes no representations or warranties with respect to the contents of this document, and specifically disclaims any express or implied warranties of merchantability or fitness for any particular purpose. The development, release, and timing of features or functionality described for openSUSE products remains at the sole discretion of openSUSE. Further, openSUSE reserves the right to revise this document and to make changes to its content, at any time, without obligation to notify any person or entity of such revisions or changes. All openSUSE marks referenced in this presentation are trademarks or registered trademarks of SUSE LLC, in the United States and other countries. All third-party trademarks are the property of their respective owners.

#### Credits

Template Richard Brown rbrown@opensuse.org

Design & Inspiration openSUSE Design Team http://opensuse.github.io/branding-quidelines/