WORK ORDER HUB · TECHNICAL REFERENCE

PostgreSQL Data Model

Live schema inventory of every PostgreSQL table and view directly used by the application, across the application, Field Service, and d365crm mirror databases.

31	0	651
Tables	Views directly used	Columns documented

Generated 18 September 2026 at 09:14 IST

Schema metadata only · No record data

Inventory and scope

> **Scope:** This report combines live PostgreSQL catalog metadata with SQL references in the current API server and the maintained application data catalog. It excludes PostgreSQL system schemas and mirrored CRM objects that the app does not query. No table row data, credentials, hosts, or connection strings are included.

Application database

heliumdb 7 tables 0 views

1. `app.app_user` TABLE
2. `public.booking_notes` TABLE
3. `public.booking_writebacks` TABLE
4. `public.placeholder_jobs` TABLE
5. `public.schedule_blocks` TABLE
6. `public.sessions` TABLE
7. `public.users` TABLE

Field Service database

fieldservice 9 tables 0 views

1. `public.bookings` TABLE
2. `public.contact` TABLE
3. `public.customers` TABLE
4. `public.equipment` TABLE
5. `public.regions` TABLE
6. `public.technicians` TABLE
7. `public.work_order_products` TABLE
8. `public.work_order_services` TABLE
9. `public.work_orders` TABLE

d365crm mirror database

d365crm 15 tables 0 views

1. `crm.account` TABLE
2. `crm.bookableresource` TABLE
3. `crm.booking` TABLE
4. `crm.booking_notes` TABLE
5. `crm.bookingstatus` TABLE
6. `crm.cf_company` TABLE
7. `crm.cf_servicelocation` TABLE
8. `crm.cf_workordercustomerequipment` TABLE
9. `crm.contact` TABLE
10. `crm.msdyn_resourceterritory` TABLE
11. `crm.placeholder_jobs` TABLE
12. `crm.schedule_blocks` TABLE
13. `crm.systemuser` TABLE
14. `crm.territory` TABLE
15. `crm.workorder` TABLE

Object names, column types, nullability, defaults, and constraints were read from the live PostgreSQL catalogs on 18 September 2026 at 09:14 IST. “Views directly used” is zero in the current application; views present elsewhere in the CRM mirror are outside this app-used scope.

POSTGRESQL SOURCE

Application database

heliumdb · 7 tables · 0 views

TABLE

app.**app_user**

7
COLUMNS

#	Column	Type	Null	Key	Default
1	entra_oid	text	NO	PK	—
2	email	text	NO		—
3	display_name	text	YES		—
4	role	text	NO		'technician'::text
5	is_active	boolean	NO		true
6	created_at	timestamp with time zone	NO		now()
7	updated_at	timestamp with time zone	NO		now()

Constraints

PRIMARY KEY app_user_pkey
PRIMARY KEY (entra_oid)

TABLE

public.**booking_notes**

4
COLUMNS

#	Column	Type	Null	Key	Default
1	id	integer	NO	PK	nextval('booking_notes_id_seq'::regclass)
2	booking_id	text	NO	UQ	—
3	note	text	YES		—
4	updated_at	timestamp with time zone	NO		now()

Constraints

PRIMARY KEY booking_notes_pkey
PRIMARY KEY (id)

UNIQUE booking_notes_booking_id_key
UNIQUE (booking_id)

TABLE

public.**booking_writebacks**

10
COLUMNS

#	Column	Type	Null	Key	Default
1	id	integer	NO	PK	nextval('booking_writebacks_id_seq'::regclass)
2	booking_id	character varying(255)	NO		—
3	work_order_id	character varying(255)	YES		—
4	start_time	timestamp with time zone	YES		—
5	end_time	timestamp with time zone	YES		—
6	technician_id	character varying(255)	YES		—
7	status	character varying(32)	NO		'queued'::character varying
8	created_at	timestamp with time zone	NO		now()
9	synced_at	timestamp with time zone	YES		—
10	error	text	YES		—

Constraints

PRIMARY KEY booking_writebacks_pkey
PRIMARY KEY (id)

TABLE

public.**placeholder_jobs**

13
COLUMNS

#	Column	Type	Null	Key	Default
1	id	integer	NO	PK	nextval('placeholder_jobs_id_seq'::regclass)
2	technician_id	text	NO		—
3	title	text	NO		—
4	customer_name	text	YES		—
5	city	text	YES		—
6	state	text	YES		—
7	start_time	timestamp with time zone	NO		—
8	end_time	timestamp with time zone	NO		—
9	notes	text	YES		—
10	created_at	timestamp with time zone	NO		now()
11	status	text	YES		—
12	service_location_id	text	YES		—
13	color_index	smallint	YES		—

Constraints

CHECK `placeholder_jobs_status_check`
CHECK (status = ANY (ARRAY['Reminder Letter Sent'::text, 'Quoted – No Purchase Order'::text, 'Have Purchase Order'::text, 'Have Credit Card'::text, 'Cash in Advance'::text, 'Credit Hold'::text]))

PRIMARY KEY `placeholder_jobs_pkey`
PRIMARY KEY (id)

TABLE

public.schedule_blocks

9 COLUMNS

#	Column	Type	Null	Key	Default
1	id	integer	NO	PK	nextval('schedule_blocks_id_seq'::regclass)
2	technician_id	text	NO		—
3	block_type	text	NO		—
4	start_time	timestamp with time zone	NO		—
5	end_time	timestamp with time zone	NO		—
6	notes	text	YES		—
7	created_at	timestamp with time zone	NO		now()
8	title	text	YES		—
9	color_index	smallint	YES		—

Constraints

CHECK schedule_blocks_block_type_check
CHECK (block_type = ANY (ARRAY['drive_time'::text, 'pto'::text, 'custom'::text]))

PRIMARY KEY schedule_blocks_pkey
PRIMARY KEY (id)

TABLE

public.**sessions**

3
COLUMNS

#	Column	Type	Null	Key	Default
1	sid	character varying	NO	PK	—
2	sess	jsonb	NO		—
3	expire	timestamp without time zone	NO		—

Constraints

PRIMARY KEY sessions_pkey
PRIMARY KEY (sid)

TABLE

public.**users**

7
COLUMNS

#	Column	Type	Null	Key	Default
1	id	character varying	NO	PK	gen_random_uuid()
2	email	character varying	YES	UQ	—
3	first_name	character varying	YES		—
4	last_name	character varying	YES		—
5	profile_image_url	character varying	YES		—
6	created_at	timestamp with time zone	NO		now()
7	updated_at	timestamp with time zone	NO		now()

Constraints

PRIMARY KEY `users_pkey`
PRIMARY KEY (id)

UNIQUE `users_email_key`
UNIQUE (email)

POSTGRESQL SOURCE

Field Service database

fieldservice · 9 tables · 0 views

TABLE

public.**bookings**

23
COLUMNS

#	Column	Type	Null	Key	Default
1	booking_id	uuid	NO	PK	—
2	work_order_id	uuid	YES	FK	—
3	technician_id	uuid	YES	FK	—
4	booking_status	character varying(100)	YES		—
5	start_time	timestamp without time zone	YES		—
6	end_time	timestamp without time zone	YES		—
7	estimated_arrival_time	timestamp without time zone	YES		—
8	actual_arrival_time	timestamp without time zone	YES		—
9	actual_start_time	timestamp without time zone	YES		—
10	actual_end_time	timestamp without time zone	YES		—
11	duration_minutes	integer	YES		—
12	latitude	numeric(12,8)	YES		—
13	longitude	numeric(12,8)	YES		—
14	modified_on	timestamp without time zone	YES		—
15	crmstart_time	date	YES		—
16	crmend_time	date	YES		—
17	crmstarttime	time without time zone	YES		—
18	crmendtime	time without time zone	YES		—
19	modifiedon	date	YES		—
20	modifiedtime	time without time zone	YES		—
21	actualarrivaltime	character varying(50)	YES		—
22	actualarrival	date	YES		—
23	actualduration	integer	YES		—

Constraints

FOREIGN KEY bookings_technician_id_fkey
FOREIGN KEY (technician_id) REFERENCES technicians(technician_id)

FOREIGN KEY bookings_work_order_id_fkey
FOREIGN KEY (work_order_id) REFERENCES work_orders(work_order_id)

PRIMARY KEY bookings_pkey
PRIMARY KEY (booking_id)

TABLE

public.**contact**

16
COLUMNS

#	Column	Type	Null	Key	Default
1	contact_id	uuid	NO	PK	—
2	fullname	character varying(100)	YES		—
3	firstname	character varying(100)	YES		—
4	middlename	character varying(100)	YES		—
5	lastname	character varying(100)	YES		—
6	email	character varying(100)	YES		—
7	businessphone	character varying(100)	YES		—
8	homephone	character varying(100)	YES		—
9	mobilephone	character varying(100)	YES		—
10	street1	character varying(255)	YES		—
11	city	character varying(100)	YES		—
12	state	character varying(100)	YES		—
13	country	character varying(100)	YES		—
14	customer_id	uuid	YES	FK	—
15	created_on	timestamp without time zone	YES		—
16	modified_on	timestamp without time zone	YES		—

Constraints

FOREIGN KEY `contact_customer_id_fkey`
FOREIGN KEY (customer_id) REFERENCES customers(customer_id)

PRIMARY KEY `contact_pkey`
PRIMARY KEY (contact_id)

TABLE

public.**customers**

24
COLUMNS

#	Column	Type	Null	Key	Default
1	customer_id	uuid	NO	PK	—
2	customer_name	character varying(250)	YES		—
3	email	character varying(200)	YES		—
4	phone	character varying(50)	YES		—
5	address	text	YES		—
6	city	character varying(100)	YES		—
7	state	character varying(100)	YES		—
8	country	character varying(100)	YES		—
9	postal_code	character varying(30)	YES		—
10	accountnumberus	character varying(50)	YES		—
11	accountnumberuk	character varying(50)	YES		—
12	accountnumberin	character varying(50)	YES		—
13	accountnumbercn	character varying(50)	YES		—
14	contact_id	uuid	YES	FK	—
15	owner	character varying(100)	YES		—
16	industry	character varying(50)	YES		—
17	customergroupus	character varying(50)	YES		—
18	customergroupuk	character varying(50)	YES		—
19	customergroupin	character varying(50)	YES		—
20	customergroupcn	character varying(50)	YES		—
21	salesgroupus	character varying(50)	YES		—
22	salesgroupuk	character varying(50)	YES		—
23	salesgroupin	character varying(50)	YES		—
24	salesgroupcn	character varying(50)	YES		—

Constraints

FOREIGN KEY `customers_contact_id_fkey`
FOREIGN KEY (contact_id) REFERENCES contact(contact_id)

PRIMARY KEY `customers_pkey`
PRIMARY KEY (customer_id)

TABLE

public.**equipment**

10
COLUMNS

#	Column	Type	Null	Key	Default
1	equipmentid	uuid	NO	PK	—
2	name	character varying(200)	YES		—
3	serialnumber	character varying(50)	YES		—
4	lastcalibrationdate	date	YES		—
5	nextcalibrationdate	date	YES		—
6	calinterval	integer	YES		—
7	machinecapacity	character varying(50)	YES		—
8	calibrationdate	date	YES		—
9	work_order_id	uuid	YES	FK	—
10	modifiedon	date	YES		—

Constraints

FOREIGN KEY equipment_work_order_id_fkey
FOREIGN KEY (work_order_id) REFERENCES work_orders(work_order_id)

PRIMARY KEY equipment_pkey
PRIMARY KEY (equipmentid)

TABLE

public.**regions**

9
COLUMNS

#	Column	Type	Null	Key	Default
1	regionid_id	uuid	NO	PK	—
2	region	character varying(50)	YES		—
3	owner_name	character varying(200)	YES		—
4	owner_email	character varying(200)	YES		—
5	phone	character varying(50)	YES		—
6	is_active	boolean	YES		true
7	last_synced_at	timestamp without time zone	YES		now()
8	compamy	character varying(50)	YES		—
9	company	character varying(30)	YES		—

Constraints

PRIMARY KEY regions_pkey
PRIMARY KEY (regionid_id)

TABLE

public.technicians

10
COLUMNS

#	Column	Type	Null	Key	Default
1	technician_id	uuid	NO	PK	—
2	resource_name	character varying(200)	YES		—
3	user_email	character varying(200)	YES		—
4	phone	character varying(50)	YES		—
5	resource_type	character varying(50)	YES		—
6	is_active	boolean	YES		true
7	last_synced_at	timestamp without time zone	YES		now()
8	company	character varying(50)	YES		—
9	region	character varying(30)	YES		—
10	regionid_id	uuid	YES	FK	—

Constraints

FOREIGN KEY technicians_regionid_id_fkey
FOREIGN KEY (regionid_id) REFERENCES regions(regionid_id)

PRIMARY KEY technicians_pkey
PRIMARY KEY (technician_id)

TABLE

public.work_order_products

6
COLUMNS

#	Column	Type	Null	Key	Default
1	id	uuid	NO	PK	—
2	work_order_id	uuid	YES	FK	—
3	product_name	character varying(250)	YES		—
4	quantity	numeric(18,2)	YES		—
5	unit	character varying(50)	YES		—
6	line_status	character varying(100)	YES		—

Constraints

FOREIGN KEY work_order_products_work_order_id_fkey
FOREIGN KEY (work_order_id) REFERENCES work_orders(work_order_id)

PRIMARY KEY work_order_products_pkey
PRIMARY KEY (id)

TABLE

public.work_order_services

5
COLUMNS

#	Column	Type	Null	Key	Default
1	id	uuid	NO	PK	—
2	work_order_id	uuid	YES	FK	—
3	service_name	character varying(250)	YES		—
4	duration_minutes	integer	YES		—
5	line_status	character varying(100)	YES		—

Constraints

FOREIGN KEY `work_order_services_work_order_id_fkey`
FOREIGN KEY (work_order_id) REFERENCES work_orders(work_order_id)

PRIMARY KEY `work_order_services_pkey`
PRIMARY KEY (id)

TABLE

public.**work_orders**

31
COLUMNS

#	Column	Type	Null	Key	Default
1	work_order_id	uuid	NO	PK	—
2	work_order_number	character varying(100)	YES		—
3	title	character varying(250)	YES		—
4	customer_id	uuid	YES	FK	—
5	service_address	text	YES		—
6	priority	character varying(50)	YES		—
7	system_status	character varying(100)	YES		—
8	sub_status	character varying(100)	YES		—
9	incident_type	character varying(200)	YES		—
10	description	text	YES		—
11	created_on	timestamp without time zone	YES		—
12	modified_on	timestamp without time zone	YES		—
13	region	character varying(50)	YES		—
14	company	character varying(50)	YES		—
15	accountnumberin	character varying(50)	YES		—
16	accountnumbercn	character varying(50)	YES		—
17	contact_id	uuid	YES	FK	—
18	servicelocation	character varying(50)	YES		—
19	pricelistname	character varying(50)	YES		—
20	cf_projectname	character varying(50)	YES		—
21	cf_ponumber	character varying(50)	YES		—
22	cf_axserviceorderid	character varying(50)	YES		—
23	msdyn_addressname	character varying(350)	YES		—
24	city	character varying(50)	YES		—
25	state	character varying(50)	YES		—
26	postalcode	character varying(50)	YES		—
27	country	character varying(50)	YES		—
28	servicetype	character varying(100)	YES		—
29	approved	character varying(10)	YES		—
30	approvedon	date	YES		—
31	salesordernum	character varying(20)	YES		—

Constraints

FOREIGN KEY work_orders_contact_id_fkey
FOREIGN KEY (contact_id) REFERENCES contact(contact_id)

FOREIGN KEY work_orders_customer_id_fkey
FOREIGN KEY (customer_id) REFERENCES customers(customer_id)

PRIMARY KEY work_orders_pkey
PRIMARY KEY (work_order_id)

POSTGRESQL SOURCE

d365crm mirror database

d365crm · 15 tables · 0 views

TABLE

crm.**account**

43 COLUMNS

#	Column	Type	Null	Key	Default
1	accountid	uuid	NO	PK	—
2	name	text	YES		—
3	accountnumber	text	YES		—
4	telephone1	text	YES		—
5	emailaddress1	text	YES		—
6	address1_city	text	YES		—
7	address1_country	text	YES		—
8	address1_line1	text	YES		—
9	address1_line2	text	YES		—
10	address1_line3	text	YES		—
11	address1_postalcode	text	YES		—
12	address1_stateorprovince	text	YES		—
13	cf_accountnumbercn	text	YES		—
14	cf_accountnumberin	text	YES		—
15	cf_accountnumberuk	text	YES		—
16	cf_accountnumberus	text	YES		—
17	cf_administrationstoppedcn	text	YES		—
18	cf_administrationstoppedin	text	YES		—
19	cf_administrationstoppeduk	text	YES		—
20	cf_administrationstoppedus	text	YES		—
21	cf_calibrationintervalinmonths	integer	YES		—
22	cf_creditlimitcn	text	YES		—
23	cf_creditlimitin	text	YES		—
24	cf_creditlimituk	text	YES		—
25	cf_creditlimitus	text	YES		—
26	cf_customergroupcn	text	YES		—
27	cf_customergroupin	text	YES		—
28	cf_customergroupuk	text	YES		—
29	cf_customergroupus	text	YES		—
30	cf_salesgroupcn	text	YES		—
31	cf_salesgroupin	text	YES		—
32	cf_salesgroupuk	text	YES		—
33	cf_salesgroupus	text	YES		—
34	ownerid	uuid	YES		—
35	transactioncurrencyid	uuid	YES		—
36	primarycontactid	uuid	YES		—
37	statecode	integer	YES		—
38	statuscode	integer	YES		—
39	modifiedon	timestamp without time zone	YES		—
40	is_deleted	boolean	YES		false
41	deleted_on	timestamp without time zone	YES		—
42	raw_json	jsonb	YES		—
43	synced_on	timestamp without time zone	YES		now()

Constraints

PRIMARY KEY `account_pkey`
PRIMARY KEY (accountid)

TABLE

crm.bookableresource

52
COLUMNS

#	Column	Type	Null	Key	Default
1	bookableresourceid	uuid	NO	PK	—
2	calendarid	uuid	YES		—
3	cf_companystructure	uuid	YES	FK	—
4	cf_companystructurename	text	YES		—
5	cf_fsa_resource	text	YES		—
6	cf_resourceid	text	YES		—
7	cf_userbusinessunit	uuid	YES		—
8	cf_userbusinessunitname	text	YES		—
9	contactid	uuid	YES		—
10	createdon	timestamp without time zone	YES		—
11	modifiedon	timestamp without time zone	YES		—
12	msdyn_crewstrategy	integer	YES		—
13	msdyn_crewstrategyname	text	YES		—
14	msdyn_derivecapacity	boolean	YES		—
15	msdyn_derivecapacityname	text	YES		—
16	msdyn_displayonscheduleassistant	boolean	YES		—
17	msdyn_displayonscheduleassistantname	text	YES		—
18	msdyn_displayonscheduleboard	boolean	YES		—
19	msdyn_displayonscheduleboardname	text	YES		—
20	msdyn_enableappointments	integer	YES		—
21	msdyn_enableappointmentsname	text	YES		—
22	msdyn_enabledforfieldservicemobile	boolean	YES		—
23	msdyn_enabledforfieldservicemobilename	text	YES		—
24	msdyn_enabledripscheduling	boolean	YES		—
25	msdyn_enabledripschedulingname	text	YES		—
26	msdyn_enableoutlookschedules	integer	YES		—
27	msdyn_enableoutlookschedulesname	text	YES		—
28	msdyn_endlocation	integer	YES		—
29	msdyn_endlocationname	text	YES		—
30	msdyn_generictype	integer	YES		—
31	msdyn_generictypename	text	YES		—
32	msdyn_hourlyrate	numeric(17,4)	YES		—
33	msdyn_hourlyrate_base	numeric(17,4)	YES		—
34	msdyn_latitude	double precision	YES		—
35	msdyn_longitude	double precision	YES		—
36	msdyn_primaryemail	text	YES		—
37	msdyn_warehouse	uuid	YES		—
38	msdyn_warehousename	text	YES		—
39	name	text	YES		—
40	ownerid	uuid	YES		—
41	owningbusinessunit	uuid	YES		—

#	Column	Type	Null	Key	Default
42	resourcetype	integer	YES		—
43	statecode	integer	YES		—
44	statuscode	integer	YES		—
45	timezone	integer	YES		—
46	transactioncurrencyid	uuid	YES		—
47	userid	uuid	YES		—
48	useridname	text	YES		—
49	is_deleted	boolean	YES		false
50	deleted_on	timestamp without time zone	YES		—
51	raw_json	jsonb	YES		—
52	synced_on	timestamp without time zone	YES		now()

Constraints

FOREIGN KEY `fk_resource_company`
FOREIGN KEY (cf_companystructure) REFERENCES crm.cf_company(cf_companyid)

PRIMARY KEY `bookableresource_pkey`
PRIMARY KEY (bookableresourceid)

TABLE

crm.**booking**

23 COLUMNS

#	Column	Type	Null	Key	Default
1	bookableresourcebookingid	uuid	NO	PK	—
2	name	text	YES		—
3	starttime	timestamp without time zone	YES		—
4	endtime	timestamp without time zone	YES		—
5	duration	numeric(12,2)	YES		—
6	resource	uuid	YES	FK	—
7	bookingstatus	uuid	YES	FK	—
8	msdyn_workorder	uuid	YES	FK	—
9	createdon	timestamp without time zone	YES		—
10	modifiedon	timestamp without time zone	YES		—
11	is_deleted	boolean	YES		false
12	deleted_on	timestamp without time zone	YES		—
13	raw_json	jsonb	YES		—
14	synced_on	timestamp without time zone	YES		now()
15	msdyn_actualarrivaltime	timestamp without time zone	YES		—
16	msdyn_actualtravelduration	numeric(12,2)	YES		—
17	msdyn_estimatedtravelduration	numeric(12,2)	YES		—
18	cf_actualarrivaltime	text	YES		—
19	cf_endtime	text	YES		—
20	cf_durationschedule	numeric(12,2)	YES		—
21	cf_duration	numeric(12,2)	YES		—
22	cf_fieldnotes	text	YES		—
23	cf_internalfieldnotes	text	YES		—

Constraints

FOREIGN KEY `fk_booking_bookingstatus`
FOREIGN KEY (bookingstatus) REFERENCES crm.bookingstatus(bookingstatusid)

FOREIGN KEY `fk_booking_resource`
FOREIGN KEY (resource) REFERENCES crm.bookableresource(bookableresourceid)

FOREIGN KEY `fk_booking_workorder`
FOREIGN KEY (msdyn_workorder) REFERENCES crm.workorder(msdyn_workorderid)

PRIMARY KEY `booking_pkey`
PRIMARY KEY (bookableresourcebookingid)

TABLE

crm.**booking_notes**

4
COLUMNS

#	Column	Type	Null	Key	Default
1	id	integer	NO	PK	nextval('crm.booking_notes_id_seq'::regclass)
2	booking_id	text	NO	UQ	—
3	note	text	YES		—
4	updated_at	timestamp with time zone	NO		now()

Constraints

PRIMARY KEY booking_notes_pkey
PRIMARY KEY (id)

UNIQUE booking_notes_booking_id_key
UNIQUE (booking_id)

TABLE

crm.**bookingstatus**

26
COLUMNS

#	Column	Type	Null	Key	Default
1	bookingstatusid	uuid	NO	PK	—
2	name	text	YES		—
3	description	text	YES		—
4	status	integer	YES		—
5	statecode	integer	YES		—
6	statuscode	integer	YES		—
7	msdyn_fieldservicestatus	integer	YES		—
8	msdyn_optimizationmethod	integer	YES		—
9	msdyn_statuscompletesworkorder	boolean	YES		—
10	msdyn_statuscolor	character varying(20)	YES		—
11	msdyn_iconname	character varying(100)	YES		—
12	msdyn_internalflags	text	YES		—
13	ownerid	uuid	YES		—
14	owninguser	uuid	YES		—
15	owningteam	uuid	YES		—
16	owningbusinessunit	uuid	YES		—
17	createdby	uuid	YES		—
18	modifiedby	uuid	YES		—
19	transactioncurrencyid	uuid	YES		—
20	createdon	timestamp without time zone	YES		—
21	modifiedon	timestamp without time zone	YES		—
22	exchangerate	numeric(18,10)	YES		—
23	is_deleted	boolean	YES		false
24	deleted_on	timestamp without time zone	YES		—
25	raw_json	jsonb	YES		—
26	synced_on	timestamp without time zone	YES		now()

Constraints

PRIMARY KEY bookingstatus_pkey
PRIMARY KEY (bookingstatusid)

TABLE

crm.cf_company

26
COLUMNS

#	Column	Type	Null	Key	Default
1	cf_companyid	uuid	NO	PK	—
2	cf_name	text	YES		—
3	cf_areaid	text	YES		—
4	cf_parentcompanystructure	uuid	YES		—
5	ownerid	uuid	YES		—
6	owninguser	uuid	YES		—
7	owningteam	uuid	YES		—
8	owningbusinessunit	uuid	YES		—
9	createdby	uuid	YES		—
10	modifiedby	uuid	YES		—
11	createdonbehalfby	uuid	YES		—
12	modifiedonbehalfby	uuid	YES		—
13	createdon	timestamp without time zone	YES		—
14	modifiedon	timestamp without time zone	YES		—
15	overriddencreatedon	timestamp without time zone	YES		—
16	statecode	integer	YES		—
17	statuscode	integer	YES		—
18	importsequencenumber	integer	YES		—
19	versionnumber	bigint	YES		—
20	utcconversiontimezonecode	integer	YES		—
21	timezoneruleversionnumber	integer	YES		—
22	odata_etag	text	YES		—
23	is_deleted	boolean	YES		false
24	deleted_on	timestamp without time zone	YES		—
25	raw_json	jsonb	YES		—
26	synced_on	timestamp without time zone	YES		now()

Constraints

PRIMARY KEY `cf_company_pkey`
PRIMARY KEY (cf_companyid)

TABLE

crm.cf_servicelocation

33
COLUMNS

#	Column	Type	Null	Key	Default
1	cf_servicelocationid	uuid	NO	PK	—
2	cf_name	text	YES		—
3	cf_servicelocid	text	YES		—
4	cf_fsa_servicelocid	text	YES		—
5	cf_addressname	text	YES		—
6	cf_street1	text	YES		—
7	cf_street2	text	YES		—
8	cf_street3	text	YES		—
9	cf_city	text	YES		—
10	cf_state	text	YES		—
11	cf_zippostalcode	text	YES		—
12	cf_countryregion	text	YES		—
13	cf_customeraddressguid	uuid	YES		—
14	cf_specialinstructions	text	YES		—
15	cf_dontsendreminder	boolean	YES		—
16	cf_account	uuid	YES	FK	—
17	cf_serviceterritory	uuid	YES	FK	—
18	cf_servicecontact	uuid	YES		—
19	ownerid	uuid	YES		—
20	owninguser	uuid	YES		—
21	owningbusinessunit	uuid	YES		—
22	createdby	uuid	YES		—
23	modifiedby	uuid	YES		—
24	createdon	timestamp without time zone	YES		—
25	modifiedon	timestamp without time zone	YES		—
26	statecode	integer	YES		—
27	statuscode	integer	YES		—
28	utcconversiontimezonecode	integer	YES		—
29	timezoneruleversionnumber	integer	YES		—
30	is_deleted	boolean	YES		false
31	deleted_on	timestamp without time zone	YES		—
32	raw_json	jsonb	YES		—
33	synced_on	timestamp without time zone	YES		now()

Constraints

FOREIGN KEY `fk_cf_servicelocation_account`
FOREIGN KEY (cf_account) REFERENCES crm.account(accountid)

FOREIGN KEY `fk_servicelocation_territory`
FOREIGN KEY (cf_serviceterritory) REFERENCES crm.territory(territoryid)

PRIMARY KEY `cf_servicelocation_pkey`
PRIMARY KEY (cf_servicelocationid)

TABLE

crm.cf_workordercustomerequipment

37 COLUMNS

#	Column	Type	Null	Key	Default
1	cf_workordercustomerequipmentid	uuid	NO	PK	—
2	cf_name	text	YES		—
3	cf_serialnumber	text	YES		—
4	cf_fsa_serviceobject	text	YES		—
5	cf_serviceobjectid	text	YES		—
6	cf_calibrationdate	timestamp without time zone	YES		—
7	cf_lastcalibrationdate	timestamp without time zone	YES		—
8	cf_nextcalibrationdate	timestamp without time zone	YES		—
9	cf_calibrationstatus	integer	YES		—
10	cf_calibrationcondition	integer	YES		—
11	cf_calibraitoncondition	integer	YES		—
12	cf_calibrationnotes	text	YES		—
13	cf_calibraitonnotes	text	YES		—
14	cf_witness	text	YES		—
15	workorderid	uuid	YES	FK	—
16	accountid	uuid	YES	FK	—
17	servicelocationid	uuid	YES	FK	—
18	calibratedbyid	uuid	YES		—
19	customerequipmentid	uuid	YES		—
20	ownerid	uuid	YES		—
21	owninguser	uuid	YES		—
22	owningteam	uuid	YES		—
23	owningbusinessunit	uuid	YES		—
24	createdby	uuid	YES		—
25	modifiedby	uuid	YES		—
26	createdon	timestamp without time zone	YES		—
27	modifiedon	timestamp without time zone	YES		—
28	statecode	integer	YES		—
29	statuscode	integer	YES		—
30	importsequencenumber	integer	YES		—
31	versionnumber	bigint	YES		—
32	utcconversiontimezonecode	integer	YES		—
33	timezoneruleversionnumber	integer	YES		—
34	is_deleted	boolean	YES		false
35	deleted_on	timestamp without time zone	YES		—
36	raw_json	jsonb	YES		—
37	synced_on	timestamp without time zone	YES		now()

Constraints

FOREIGN KEY `fk_wocusteq_account`
FOREIGN KEY (accountid) REFERENCES crm.account(accountid)

FOREIGN KEY `fk_wocusteq_srvlocation`
FOREIGN KEY (servicelocationid) REFERENCES crm.cf_servicelocation(cf_servicelocationid)

FOREIGN KEY `fk_wocusteq_workorder`
FOREIGN KEY (workorderid) REFERENCES crm.workorder(msdyn_workorderid)

PRIMARY KEY `cf_workordercustomerequipment_pkey`
PRIMARY KEY (cf_workordercustomerequipmentid)

TABLE

crm.**contact**

15
COLUMNS

#	Column	Type	Null	Key	Default
1	contactid	uuid	NO	PK	—
2	fullname	text	YES		—
3	firstname	text	YES		—
4	lastname	text	YES		—
5	emailaddress1	text	YES		—
6	mobilephone	text	YES		—
7	telephone1	text	YES		—
8	parentcustomerid	uuid	YES	FK	—
9	statecode	integer	YES		—
10	statuscode	integer	YES		—
11	modifiedon	timestamp without time zone	YES		—
12	is_deleted	boolean	YES		false
13	deleted_on	timestamp without time zone	YES		—
14	raw_json	jsonb	YES		—
15	synced_on	timestamp without time zone	YES		now()

Constraints

FOREIGN KEY `fk_contact_account`
FOREIGN KEY (parentcustomerid) REFERENCES crm.account(accountid)

PRIMARY KEY `contact_pkey`
PRIMARY KEY (contactid)

TABLE

crm.**msdyn_resourceterritory**

24
COLUMNS

#	Column	Type	Null	Key	Default
1	msdyn_resourceterritoryid	uuid	NO	PK	—
2	msdyn_name	character varying(200)	YES		—
3	msdyn_resource	uuid	YES	FK	—
4	msdyn_territory	uuid	YES	FK	—
5	cf_companystructure	uuid	YES		—
6	cf_businessunit	uuid	YES		—
7	cf_resource	uuid	YES		—
8	statecode	integer	YES		—
9	statuscode	integer	YES		—
10	createdon	timestamp without time zone	YES		—
11	modifiedon	timestamp without time zone	YES		—
12	createdby	uuid	YES		—
13	modifiedby	uuid	YES		—
14	ownerid	uuid	YES	FK	—
15	owninguser	uuid	YES		—
16	owningteam	uuid	YES		—
17	owningbusinessunit	uuid	YES		—
18	utcconversiontimezonecode	integer	YES		—
19	timezoneruleversionnumber	integer	YES		—
20	cf_fsa_resourceterritory	text	YES		—
21	is_deleted	boolean	YES		false
22	deleted_on	timestamp without time zone	YES		—
23	raw_json	jsonb	YES		—
24	synced_on	timestamp without time zone	YES		CURRENT_TIMESTAMP

Constraints

FOREIGN KEY `fk_rt_owner`
FOREIGN KEY (ownerid) REFERENCES crm.systemuser(systemuserid)

FOREIGN KEY `fk_rt_resource`
FOREIGN KEY (msdyn_resource) REFERENCES crm.bookableresource(bookableresourceid)

FOREIGN KEY `fk_rt_territory`
FOREIGN KEY (msdyn_territory) REFERENCES crm.territory(territoryid)

PRIMARY KEY `msdyn_resourceterritory_pkey`
PRIMARY KEY (msdyn_resourceterritoryid)

TABLE

crm.placeholder_jobs

13
COLUMNS

#	Column	Type	Null	Key	Default
1	id	integer	NO	PK	—
2	technician_id	text	NO		—
3	title	text	NO		—
4	customer_name	text	YES		—
5	city	text	YES		—
6	state	text	YES		—
7	start_time	timestamp with time zone	NO		—
8	end_time	timestamp with time zone	NO		—
9	notes	text	YES		—
10	created_at	timestamp with time zone	NO		now()
11	status	text	YES		—
12	service_location_id	text	YES		—
13	color_index	smallint	YES		—

Constraints

PRIMARY KEY placeholder_jobs_pkey
PRIMARY KEY (id)

TABLE

crm.schedule_blocks

9 COLUMNS

#	Column	Type	Null	Key	Default
1	id	integer	NO	PK	nextval('crm.schedule_blocks_id_seq'::regclass)
2	technician_id	text	NO		—
3	block_type	text	NO		—
4	start_time	timestamp with time zone	NO		—
5	end_time	timestamp with time zone	NO		—
6	notes	text	YES		—
7	created_at	timestamp with time zone	NO		now()
8	title	text	YES		—
9	color_index	smallint	YES		—

Constraints

PRIMARY KEY schedule_blocks_pkey
PRIMARY KEY (id)

TABLE

crm.systemuser

88
COLUMNS

#	Column	Type	Null	Key	Default
1	systemuserid	uuid	NO	PK	—
2	fullname	text	YES		—
3	firstname	text	YES		—
4	middlename	text	YES		—
5	lastname	text	YES		—
6	title	text	YES		—
7	jobtitle	text	YES		—
8	domainname	text	YES		—
9	internalemailaddress	text	YES		—
10	windowsliveid	text	YES		—
11	personalemailaddress	text	YES		—
12	sharepointemailaddress	text	YES		—
13	mobilephone	text	YES		—
14	homephone	text	YES		—
15	address1_telephone1	text	YES		—
16	address1_fax	text	YES		—
17	address1_city	text	YES		—
18	address1_stateorprovince	text	YES		—
19	address1_postalcode	text	YES		—
20	address1_country	text	YES		—
21	address1_line1	text	YES		—
22	address1_line2	text	YES		—
23	address1_line3	text	YES		—
24	address1_composite	text	YES		—
25	address1_addressid	uuid	YES		—
26	address1_addresstypecode	integer	YES		—
27	businessunitid	uuid	YES		—
28	organizationid	uuid	YES		—
29	siteid	uuid	YES		—
30	queueid	uuid	YES		—
31	territoryid	uuid	YES		—
32	defaultmailbox	uuid	YES		—
33	mobileofflineprofileid	uuid	YES		—
34	parentsystemuserid	uuid	YES		—
35	calendarid	uuid	YES		—
36	cf_companystructure	uuid	YES		—
37	cf_maptoax	boolean	YES		—
38	cf_axemployeepersonnelnumber	text	YES		—
39	cf_warehouse	uuid	YES		—
40	cf_warehouseid	text	YES		—
41	cf_warehousename	text	YES		—
42	transactioncurrencyid	uuid	YES		—
43	exchangerate	numeric(18,10)	YES		—
44	ownerid	uuid	YES		—
45	createdby	uuid	YES		—
46	modifiedby	uuid	YES		—

#	Column	Type	Null	Key	Default
47	createdonbehalfby	uuid	YES		—
48	isdisabled	boolean	YES		—
49	disabledreason	text	YES		—
50	islicensed	boolean	YES		—
51	isintegrationuser	boolean	YES		—
52	issyncwithdirectory	boolean	YES		—
53	displayinserviceviews	boolean	YES		—
54	setupuser	boolean	YES		—
55	accessmode	integer	YES		—
56	caltype	integer	YES		—
57	invitestatuscode	integer	YES		—
58	incomingemaildeliverymethod	integer	YES		—
59	outgoingemaildeliverymethod	integer	YES		—
60	preferredemailcode	integer	YES		—
61	preferredphonecode	integer	YES		—
62	preferredaddresscode	integer	YES		—
63	emailrouteraccessapproval	integer	YES		—
64	userlicensetype	integer	YES		—
65	systemmanagedusertype	integer	YES		—
66	azureactivedirectoryobjectid	uuid	YES		—
67	azurestate	integer	YES		—
68	azuredeletedon	timestamp without time zone	YES		—
69	userpuid	text	YES		—
70	identityid	integer	YES		—
71	msdyn_botprovider	integer	YES		—
72	msdyn_bothandle	text	YES		—
73	msdyn_botapplicationid	text	YES		—
74	msdyn_botdescription	text	YES		—
75	msdyn_botendpoint	text	YES		—
76	msdyn_usertype	integer	YES		—
77	msdyn_agenttype	integer	YES		—
78	msdyn_capacity	integer	YES		—
79	msdyn_activeconversationlimit	integer	YES		—
80	msdyn_gdproptout	boolean	YES		—
81	createdon	timestamp without time zone	YES		—
82	modifiedon	timestamp without time zone	YES		—
83	versionnumber	bigint	YES		—
84	timezoneruleversionnumber	integer	YES		—
85	is_deleted	boolean	YES		false
86	deleted_on	timestamp without time zone	YES		—
87	raw_json	jsonb	YES		—
88	synced_on	timestamp without time zone	YES		now()

Constraints

PRIMARY KEY `systemuser_pkey`
PRIMARY KEY (systemuserid)

TABLE

crm.territory

30 COLUMNS

#	Column	Type	Null	Key	Default
1	territoryid	uuid	NO	PK	—
2	name	text	YES		—
3	description	text	YES		—
4	managerid	uuid	YES	FK	—
5	manageridname	text	YES		—
6	organizationid	uuid	YES		—
7	organizationidname	text	YES		—
8	createdon	timestamp without time zone	YES		—
9	modifiedon	timestamp without time zone	YES		—
10	createdby	uuid	YES		—
11	createdbyname	text	YES		—
12	modifiedby	uuid	YES		—
13	modifiedbyname	text	YES		—
14	statecode	integer	YES		—
15	statuscode	integer	YES		—
16	importsequencenumber	integer	YES		—
17	overriddencreatedon	timestamp without time zone	YES		—
18	timezoneruleversionnumber	integer	YES		—
19	utcconversiontimezonecode	integer	YES		—
20	versionnumber	bigint	YES		—
21	is_deleted	boolean	YES		false
22	deleted_on	timestamp without time zone	YES		—
23	raw_json	jsonb	YES		—
24	synced_on	timestamp without time zone	YES		now()
25	country	text	YES		—
26	city	text	YES		—
27	state_province	text	YES		—
28	parent_territory_id	uuid	YES		—
29	companystructureid	uuid	YES	FK	—
30	businessunit	uuid	YES		—

Constraints

FOREIGN KEY `fk_territory_company`
FOREIGN KEY (companystructureid) REFERENCES crm.cf_company(cf_companyid)

FOREIGN KEY `fk_territory_manager`
FOREIGN KEY (managerid) REFERENCES crm.systemuser(systemuserid)

PRIMARY KEY `territory_pkey`
PRIMARY KEY (territoryid)

TABLE

crm.workorder

41
COLUMNS

#	Column	Type	Null	Key	Default
1	msdyn_workorderid	uuid	NO	PK	—
2	msdyn_name	text	YES		—
3	msdyn_systemstatus	integer	YES		—
4	msdyn_substatus	uuid	YES		—
5	msdyn_serviceaccount	uuid	YES	FK	—
6	msdyn_billingaccount	uuid	YES	FK	—
7	cf_approvedby	uuid	YES	FK	—
8	cf_approvedon	timestamp without time zone	YES		—
9	cf_approveworkorder	boolean	YES		—
10	cf_axprojectid	text	YES		—
11	cf_axsalesorder	text	YES		—
12	cf_axserviceorderid	text	YES		—
13	cf_businessunit	uuid	YES		—
14	cf_companystructure	uuid	YES	FK	—
15	cf_contactperson	uuid	YES	FK	—
16	cf_ponumber	text	YES		—
17	cf_project	uuid	YES		—
18	cf_servicelocation	uuid	YES	FK, FK	—
19	exchangerate	numeric	YES		—
20	msdyn_address1	text	YES		—
21	msdyn_address2	text	YES		—
22	msdyn_address3	text	YES		—
23	msdyn_addressname	text	YES		—
24	msdyn_city	text	YES		—
25	msdyn_completedon	timestamp without time zone	YES		—
26	msdyn_country	text	YES		—
27	msdyn_phonenumber	text	YES		—
28	msdyn_postalcode	text	YES		—
29	msdyn_pricelist	uuid	YES		—
30	msdyn_serviceterritory	uuid	YES	FK	—
31	msdyn_stateorprovince	text	YES		—
32	msdyn_workordertype	uuid	YES		—
33	new_customerrequirement	text	YES		—
34	ownerid	uuid	YES		—
35	transactioncurrencyid	uuid	YES	FK	—
36	createdon	timestamp without time zone	YES		—
37	modifiedon	timestamp without time zone	YES		—
38	is_deleted	boolean	YES		false
39	deleted_on	timestamp without time zone	YES		—
40	raw_json	jsonb	YES		—
41	synced_on	timestamp without time zone	YES		now()

Constraints

FOREIGN KEY `fk_workorder_account`
FOREIGN KEY (msdyn_billingaccount) REFERENCES crm.account(accountid)

FOREIGN KEY `fk_workorder_approviguser`
FOREIGN KEY (cf_approvedby) REFERENCES crm.systemuser(systemuserid)

FOREIGN KEY `fk_workorder_company`
FOREIGN KEY (cf_companystructure) REFERENCES crm.cf_company(cf_companyid)

FOREIGN KEY `fk_workorder_contact`
FOREIGN KEY (cf_contactperson) REFERENCES crm.contact(contactid)

FOREIGN KEY `fk_workorder_currency`
FOREIGN KEY (transactioncurrencyid) REFERENCES crm.transactioncurrency(transactioncurrencyid)

FOREIGN KEY `fk_workorder_serviceaccount`
FOREIGN KEY (msdyn_serviceaccount) REFERENCES crm.account(accountid)

FOREIGN KEY `fk_workorder_servicelocation`
FOREIGN KEY (cf_servicelocation) REFERENCES crm.cf_servicelocation(cf_servicelocationid)

FOREIGN KEY `fk_workorder_srvlocation`
FOREIGN KEY (cf_servicelocation) REFERENCES crm.cf_servicelocation(cf_servicelocationid)

FOREIGN KEY `fk_workorder_territory`
FOREIGN KEY (msdyn_serviceterritory) REFERENCES crm.territory(territoryid)

PRIMARY KEY `workorder_pkey`
PRIMARY KEY (msdyn_workorderid)