



LeetCode 94 — Binary Tree Inorder Traversal

 <https://leetcode.com/problems/binary-tree-inorder-traversal/>

1. Problem Title & Link

Title: LeetCode 94: Binary Tree Inorder Traversal

Link: <https://leetcode.com/problems/binary-tree-inorder-traversal/>

2. Problem Statement (Short Summary)

Given the root of a binary tree, return its **inorder traversal**.

Traversal order:

➡ **Left → Node → Right**

3. Examples (Input → Output)

Example 1

Tree:

```
1
 \
  2
 /
3
```

Output:

[1,3,2]

Example 2

Input: root = []

Output: []

Example 3

Input:

```
1
 /
2
```

Output: [2,1]

4. Constraints

- $0 \leq \text{number of nodes} \leq 10^4$
- Node values can repeat



- Must follow strict inorder $L \rightarrow N \rightarrow R$
- Recursive depth = height of tree

5. Core Concept (Pattern / Topic)

★ DFS → Binary Tree Traversal (Inorder)

6. Thought Process (Step-by-Step)

✨ ✨ Approach 1: Recursive (easy & clean)

- Visit left subtree
- Visit node
- Visit right subtree

✨ ✨ Approach 2: Iterative with Stack (most common in interviews)

We manually simulate recursion:

- Push all left nodes
- Pop → record value
- Move to right child

✨ ✨ Approach 3: Morris Traversal (advanced, $O(1)$ space)

Make temporary threaded links (no stack, no recursion).

7. Visual / Intuition Diagram

Example Tree:

```
  1
 / \
2   3
```

Inorder Path:

Left → Node → Right

$2 \rightarrow 1 \rightarrow 3$

8. Pseudocode

```
result = []
stack = []
curr = root

while curr != null or stack not empty:
```



```
while curr != null:
    stack.push(curr)
    curr = curr.left

curr = stack.pop()
result.append(curr.val)
curr = curr.right

return result
```

9. Code Implementation

✓ Python

```
class Solution:
    def inorderTraversal(self, root):
        res, stack = [], []
        curr = root

        while curr or stack:
            while curr:
                stack.append(curr)
                curr = curr.left

            curr = stack.pop()
            res.append(curr.val)
            curr = curr.right

        return res
```

✓ Java

```
class Solution {
    public List<Integer> inorderTraversal(TreeNode root) {
        List<Integer> res = new ArrayList<>();
        Stack<TreeNode> stack = new Stack<>();
        TreeNode curr = root;

        while (curr != null || !stack.isEmpty()) {
            while (curr != null) {
                stack.push(curr);
                curr = curr.left;
            }
        }
    }
}
```



```
        curr = stack.pop();
        res.add(curr.val);
        curr = curr.right;
    }

    return res;
}
```

10. Time & Space Complexity

Time: $O(n)$

Each node visited exactly once.

Space:

- Recursion: $O(h)$
- Iteration using stack: $O(h)$
- Morris: **$O(1)$**

(h = tree height)

11. Common Mistakes / Edge Cases

- ✗ Returning preorder by mistake
- ✗ Forgetting to push left chain
- ✗ Not using while curr or stack
- ✗ Infinite loop: forgetting `curr = curr.right`

Edge cases:

- ✓ Empty tree
- ✓ Single node
- ✓ Left-only chain
- ✓ Right-only chain

12. Detailed Dry Run

Tree:

```
1
 \
 2
 /
```



3

Step	curr	stack	result
push 1	1→2	[1]	[]
push 2	2→3	[1,2]	[]
push 3	3→null	[1,2,3]	[]
pop 3	null	[1,2]	[3]
pop 2	right=null	[1]	[3,2]
pop 1	right visited	[]	[3,2,1]

Final: [1,3,2]

13. Common Use Cases

- BST inorder → sorted output
- Syntax tree traversal
- Building expression evaluators
- Validating BST correctness

14. Common Traps

- ⚠ Pushing right child too early
- ⚠ Wrong order of appending
- ⚠ Stack pop before finishing left chain
- ⚠ Using recursion when depth might exceed limit

15. Builds To (Related Problems)

- LC 144 — Preorder
- LC 145 — Postorder
- LC 98 — Validate BST
- LC 230 — Kth Smallest in BST



16. Alternate Approaches + Comparison

Approach	Time	Space	Notes
Recursion	$O(n)$	$O(h)$	Cleanest
Stack	$O(n)$	$O(h)$	Most used in interviews
Morris	$O(n)$	$O(1)$	Advanced

17. Why This Solution Works

Inorder traversal always processes the left subtree, then the root, then the right subtree.

The stack replicates this exact recursive behavior.

18. Variations / Follow-Up

- Do inorder **without recursion**
- Do inorder with **$O(1)$ space** (Morris)
- Inorder traversal of BST gives **sorted list**
- Find kth smallest using inorder