

Disk and partition ownership

ONTAP 9

NetApp July 12, 2023

This PDF was generated from https://docs.netapp.com/us-en/ontap/disks-aggregates/disk-partition-ownership-overview-concept.html on July 12, 2023. Always check docs.netapp.com for the latest.

Table of Contents

c and partition ownership	 1
isk and partition ownership	 1
bout automatic assignment of disk ownership	 1
Display disk and partition ownership	 2
Change settings for automatic assignment of disk ownership	 3
lanually assign disk ownership	 4
Manually assign ownership of partitioned disks overview	 5
et up an active-passive configuration on nodes using root-data partitioning	 8
et up an active-passive configuration on nodes using root-data-data partitioning	 11
Remove ownership from a disk	 13

Disk and partition ownership

Disk and partition ownership

You can manage the ownership of disks and partitions.

You can perform the following tasks:

Display disk and partition ownership

You can view disk ownership to determine which node controls the storage. You can also view the partition ownership on systems that use shared disks.

Change settings for automatic assignment of disk ownership

You can select a non-default policy for automatically assigning disk ownership or disable automatic assignment of disk ownership.

· Manually assign ownership of unpartitioned disks

If your cluster is not configured to use automatic disk ownership assignment, you must assign ownership manually.

· Manually assign ownership of partitioned disks

You can set the ownership of the container disk or the partitions manually or by using auto-assignment—just as you do for unpartitioned disks.

Remove a failed disk

A disk that has failed completely is no longer considered by ONTAP to be a usable disk, and you can immediately disconnect the disk from the shelf.

Remove ownership from a disk

ONTAP writes disk ownership information to the disk. Before you remove a spare disk or its shelf from a node, you should remove its ownership information so that it can be properly integrated into another node.

About automatic assignment of disk ownership

The automatic assignment of unowned disks is enabled by default. Automatic disk ownership assignments occur 10 minutes after system initialization and every five minutes during normal system operation.

When you add new disks to a system – for example, when replacing failed disks, responding to a low spares message, or adding capacity – the default auto-assignment policy assigns ownership of the disk to a node as a spare. You can disable automatic assignment or select a different auto-assignment policy using the storage disk option modify command.

The default auto-assignment policy is based on platform-specific characteristics, but it uses one of the following methods to assign disk ownership:

Assignment method	Effect on node assignments	Platforms
bay	Even-numbered bays are assigned to node A and odd-numbered bays to node B.	Entry-level systems in an HA configuration with a single, shared shelf.
shelf	All disks in the shelf are assigned to node A.	Entry-level systems in an HA configuration with one stack of two or more shelves, and MetroCluster configurations with one stack per node, two or more shelves.
split shelf	Disks on the left side of the shelf are assigned to node A and on the right side to Node B. Partial shelves on new systems are shipped from the factory with disks populated from the shelf edge toward the center.	AFF C190 systems and some MetroCluster configurations.
stack	All disks in the stack are assigned to node A.	Stand-alone entry-level systems and all other configurations.

If the default assignment method is not desirable in your environment, you can specify the bay, shelf, or stack assignment method using the -autoassign-policy parameter to the storage disk option modify command. Note the following rules:

- If you try to use the bay autoassign-policy for a non-entry level platform, it will fail.
- There is no corresponding non-default policy for specifying the split-shelf method.

You can also manage disk assignment manually using the storage disk assign command.

- If you disable auto-assignment, new disks are not available as spares until they are assigned to a node with the storage disk assign command.
- If you want disks to be auto-assigned and you have multiple stacks or shelves that must have different ownership, one disk must have been manually assigned on each stack or shelf so that automatic ownership assignment works on each stack or shelf.
- If auto-assignment is enabled and you manually assign a single drive to a node that isn't specified in the active policy, auto-assignment stops working and an EMS message is displayed.

Learn more about manually assigning disk ownership.

You can display the current auto-assignment settings with the storage disk option show command.

Display disk and partition ownership

You can view disk ownership to determine which node controls the storage. You can also view the partition ownership on systems that use shared disks.

Steps

1. Display the ownership of physical disks:

storage disk show -ownership

	_	Home		-	Home ID	Owner ID	DR
	aggr0_2 09 Pool0	node2	node2	-	2014941509	2014941509	-
	aggr0_2 09 Pool0	node2	node2	-	2014941509	2014941509	-
	aggr0_1 19 Pool0	node1	node1	-	2014941219	2014941219	-
1.0.3	- 19 Pool0	node1	node1	-	2014941219	2014941219	

2. If you have a system that uses shared disks, you can display the partition ownership:

storage disk show -partition-ownership

Owner ID				Root		Data	
Owner ID	Container	Containe	er				
1.0.0 - node1 1886742616 node1 1886742616 node1 1.0.1 - node1 1886742616 node1 1886742616 node1 1886742616 1.0.2 - node2 1886742657 node2 1886742657 node2	Disk	Aggregate	Root Owner	Owner ID	Data Owner	Owner ID	Owner
1886742616 1.0.1 - node1 1886742616 node1 1886742616 node: 1886742616 1.0.2 - node2 1886742657 node2 1886742657 node: 1886742657	Owner ID						
1886742616 1.0.1 - node1 1886742616 node1 1886742616 node: 1886742616 1.0.2 - node2 1886742657 node2 1886742657 node: 1886742657							
1886742616 1.0.1 - node1 1886742616 node1 1886742616 node: 1886742616 1.0.2 - node2 1886742657 node2 1886742657 node: 1886742657							
1.0.1 - node1 1886742616 node1 1886742616 node1 1886742616 1.0.2 - node2 1886742657 node2 1886742657 node2	1.0.0	-	node1	1886742616	node1	1886742616	node1
1886742616 1.0.2 - node2 1886742657 node2 1886742657 node2 1886742657	188674261	. 6					
1.0.2 - node2 1886742657 node2 1886742657 node2 1886742657	1.0.1	-	node1	1886742616	node1	1886742616	node1
1886742657	188674261	. 6					
	1.0.2	_	node2	1886742657	node2	1886742657	node2
1.0.3 - node2 1886742657 node2 1886742657 node2	188674265	7					
	1.0.3	_	node2	1886742657	node2	1886742657	node2

Change settings for automatic assignment of disk ownership

You can use the storage disk option modify command to select a non-default policy for automatically assigning disk ownership or to disable automatic assignment of disk ownership.

Learn about automatic assignment of disk ownership.

Steps

- 1. Modify automatic disk assignment:
 - a. If you want to select a non-default policy, enter:

```
storage disk option modify -autoassign-policy autoassign\_policy -node node\ name
```

- Use stack as the autoassign_policy to configure automatic ownership at the stack or loop level.
- Use shelf as the autoassign policy to configure automatic ownership at the shelf level.
- Use bay as the autoassign policy to configure automatic ownership at the bay level.
- b. If you want to disable automatic disk ownership assignment, enter:

```
storage disk option modify -autoassign off -node node name
```

2. Verify the automatic assignment settings for the disks:

storage disk option show

Manually assign disk ownership

Disks must be owned by a node before they can be used in a local tier (aggregate).

If your cluster is not configured to use automatic disk ownership assignment, you must assign ownership manually.

You cannot reassign ownership of a disk that is in use in a local tier.

Steps

1. Using the CLI, display all unowned disks:

```
storage disk show -container-type unassigned
```

2. Assign each disk:

```
storage disk assign -disk disk_name -owner owner_name
```

You can use the wildcard character to assign more than one disk at once. If you are reassigning a spare disk that is already owned by a different node, you must use the "-force" option.

Manually assign ownership of partitioned disks overview

Using the CLI, you can set the ownership of the container disk or the partitions manually or by using auto-assignment—just as you do for unpartitioned disks.



If a container disk fails in a half-populated shelf and is replaced, ONTAP will not auto-assign ownership. In this case, any assignment of new disks will need to be done manually. To make auto-assign work on half-populated shelves, place disks equally on lower half and 6 on far right bays to begin with. That is, 6 disks from bays 0-5 and 6 disks from bays 18-23. After the container disk is assigned in an ADP-configured system, ONTAP's software will handle any partitioning and partition assignments that are required, without user intervention.

You can perform the following tasks in the CLI:

Manually assign disks with root-data partitioning

For root-data partitioning, there are three owned entities (the container disk and the two partitions) collectively owned by the HA pair.

The container disk and the two partitions do not all need to be owned by the same node in the HA pair as long as they are all owned by one of the nodes in the HA pair. However, when you use a partition in a local tier (aggregate), it must be owned by the same node that owns the local tier.

Steps

1. Use the CLI to display the current ownership for the partitioned disk:

```
storage disk show -disk disk name -partition-ownership
```

2. Set the CLI privilege level to advanced:

```
set -privilege advanced
```

3. Enter the appropriate command, depending on which ownership entity you want to assign ownership for:

If you want to assign ownership for the	Use this command
Container disk	storage disk assign -disk disk_name -owner owner_name
Data partition	storage disk assign -disk disk_name -owner owner_name -data true
Root partition	storage disk assign -disk disk_name -owner owner_name -root true

If any of the ownership entities are already owned, then you must include the "-force" option.

Manually assign disks with root-data-data partitioning

For root-data-data partitioning, there are four owned entities (the container disk and the three partitions) collectively owned by the HA pair.

Root-data-data partitioning creates one small partition as the root partition and two larger, equally sized partitions for data.

About this task

Parameters must be used with the disk assign command to assign the proper partition of a root-data-data partitioned disk. You cannot use these parameters with disks that are part of a storage pool. The default value is "false".

- The -data1 true parameter assigns the "data1" partition of a root-data1-data2 partitioned disk.
- The -data2 true parameter assigns the "data2" partition of a root-data1-data2 partitioned disk.

Steps

1. Use the CLI to display the current ownership for the partitioned disk:

```
storage disk show -disk disk name -partition-ownership
```

2. Set the CLI privilege level to advanced:

```
set -privilege advanced
```

3. Enter the appropriate command, depending on which ownership entity you want to assign ownership for:

If you want to assign ownership for the	Use this command
Container disk	storage disk assign -disk disk_name -owner owner_name
Data1 partition	storage disk assign -disk disk_name -owner owner_name -data1 true
Data2 partition	storage disk assign -disk disk_name -owner owner_name -data2 true
Root partition	storage disk assign -disk disk_name -owner owner_name -root true

If any of the ownership entities are already owned, then you must include the "-force" option.

Set up an active-passive configuration on nodes using rootdata partitioning

When an HA pair is configured to use root-data partitioning by the factory, ownership of the data partitions is split between both nodes in the pair for use in an active-active configuration. If you want to use the HA pair in an active-passive configuration, you must update partition ownership before creating your data local tier (aggregate).

What you'll need

- You should have decided which node will be the active node and which node will be the passive node.
- Storage failover must be configured on the HA pair.

About this task

This task is performed on two nodes: Node A and Node B.

This procedure is designed for nodes for which no data local tier (aggregate) has been created from the partitioned disks.

Learn about advanced disk partitioning.

Steps

All commands are inputted at the cluster shell.

1. View the current ownership of the data partitions:

```
storage aggregate show-spare-disks
```

The output shows that half of the data partitions are owned by one node and half are owned by the other node. All of the data partitions should be spare.

cluster1::> storage aggrega	te show-	-spare-disks		
Original Owner: cluster1-01 Pool0 Partitioned Spares				
_			Local	
Local			Data	
Root Physical Disk Usable Size	Туре	RPM Checksum	Usable	
1.0.0	BSAS	7200 block	753.8GB	
0B 828.0GB 1.0.1 73.89GB 828.0GB	BSAS	7200 block	753.8GB	
1.0.5	BSAS	7200 block	753.8GB	

)B 828.0GB			
1.0.6	BSAS	7200 block	753.8GB
DB 828.0GB			
1.0.10	BSAS	7200 block	753.8GB
DB 828.0GB			
1.0.11	BSAS	7200 block	753.8GB
DB 828.0GB			
Original Owner: cluster1-0	02		
Pool0			
Partitioned Spares			
			Local
Local			
			Data
Root Physical			
Disk	Type	RPM Checksum	Usable
Jsable Size			
1 0 2			
1.0.2		7200 block	
1.0.2 DB 828.0GB	BSAS	7200 block	753.8GB
1.0.2 DB 828.0GB 1.0.3	BSAS		
1.0.2 DB 828.0GB 1.0.3 DB 828.0GB	BSAS BSAS	7200 block 7200 block	753.8GB 753.8GB
1.0.2 DB 828.0GB 1.0.3 DB 828.0GB 1.0.4	BSAS	7200 block 7200 block	753.8GB
1.0.2 DB 828.0GB 1.0.3 DB 828.0GB 1.0.4 DB 828.0GB	BSAS BSAS	7200 block 7200 block 7200 block	753.8GB 753.8GB 753.8GB
1.0.2 DB 828.0GB 1.0.3 DB 828.0GB 1.0.4 DB 828.0GB 1.0.7	BSAS BSAS	7200 block 7200 block 7200 block	753.8GB 753.8GB
1.0.2 DB 828.0GB 1.0.3 DB 828.0GB 1.0.4 DB 828.0GB	BSAS BSAS BSAS	7200 block 7200 block 7200 block 7200 block	753.8GB 753.8GB 753.8GB
1.0.2 DB 828.0GB 1.0.3 DB 828.0GB 1.0.4 DB 828.0GB 1.0.7 DB 828.0GB 1.0.7	BSAS BSAS	7200 block 7200 block 7200 block 7200 block	753.8GB 753.8GB 753.8GB
1.0.2 DB 828.0GB 1.0.3 DB 828.0GB 1.0.4 DB 828.0GB 1.0.7 DB 828.0GB	BSAS BSAS BSAS	7200 block 7200 block 7200 block 7200 block 7200 block	753.8GB 753.8GB 753.8GB
1.0.2 0B 828.0GB 1.0.3 0B 828.0GB 1.0.4 0B 828.0GB 1.0.7 0B 828.0GB 1.0.7 0B 828.0GB	BSAS BSAS BSAS	7200 block 7200 block 7200 block 7200 block 7200 block	753.8GB 753.8GB 753.8GB 753.8GB

2. Enter the advanced privilege level:

set advanced

3. For each data partition owned by the node that will be the passive node, assign it to the active node:

storage disk assign -force -data true -owner active_node_name -disk disk_name
You do not need to include the partition as part of the disk name.

You would enter a command similar to the following example for each data partition you need to reassign:

storage disk assign -force -data true -owner cluster1-01 -disk 1.0.3

4. Confirm that all of the partitions are assigned to the active node.

cluster1::*> storage aggreg	gate show	-spare-	-disks	
Original Owner: cluster1-01	_			
Pool0				
Partitioned Spares				
				Local
Local				
				Data
Root Physical	Ш	DDM	Clara la secon	TT 1- 1 -
Disk Usable Size	туре	RPM	Checksum	Usable
1.0.0	BSAS	7200	block	753.8GB
DB 828.0GB				
1.0.1	BSAS	7200	block	753.8GB
73.89GB 828.0GB				
1.0.2	BSAS	7200	block	753.8GB
B 828.0GB				
1.0.3	BSAS	7200	block	753.8GB
B 828.0GB				
1.0.4	BSAS	7200	block	753.8GB
B 828.0GB				
1.0.5	BSAS	7200	block	753.8GB
0B 828.0GB				
1.0.6	BSAS	7200	block	753.8GB
B 828.0GB	D C 3 C	7000	1- 1 1	752 225
1.0.7	BSAS	7200	DIOCK	753.8GB
DB 828.0GB 1.0.8	BSAS	7200	block	753.8GB
1.0.0 B 828.0GB	מאמם	1200	DIOCK	/33.0GB
1.0.9	BSAS	7200	block	753.8GB
DB 828.0GB	20110	, 200	2001	, 33 : 03D
1.0.10	BSAS	7200	block	753.8GB
0B 828.0GB				
1.0.11	BSAS	7200	block	753.8GB
B 828.0GB				
riginal Owner: cluster1-02)			
Pool0				
Partitioned Spares				
				Local
Local				
				Data
Root Physical				

Disk	Type	RPM Checksum	Usable
Usable Size			
1.0.8	BSAS	7200 block	0B
73.89GB 828.0GB			
13 entries were dis	played.		

Note that cluster1-02 still owns a spare root partition.

5. Return to administrative privilege:

```
set admin
```

6. Create your data aggregate, leaving at least one data partition as spare:

```
storage aggregate create new\_aggr\_name -diskcount number\_of\_partitions -node active\_node\_name
```

The data aggregate is created and is owned by the active node.

Set up an active-passive configuration on nodes using rootdata-data partitioning

When an HA pair is configured to use root-data-data partitioning by the factory, ownership of the data partitions is split between both nodes in the pair for use in an active-active configuration. If you want to use the HA pair in an active-passive configuration, you must update partition ownership before creating your data local tier (aggregate).

What you'll need

- You should have decided which node will be the active node and which node will be the passive node.
- Storage failover must be configured on the HA pair.

About this task

This task is performed on two nodes: Node A and Node B.

This procedure is designed for nodes for which no data local tier (aggregate) has been created from the partitioned disks.

Learn about advanced disk partitioning.

Steps

All commands are input at the cluster shell.

1. View the current ownership of the data partitions:

```
storage aggregate show-spare-disks -original-owner passive_node_name -fields local-usable-data1-size, local-usable-data2-size
```

The output shows that half of the data partitions are owned by one node and half are owned by the other node. All of the data partitions should be spare.

2. Enter the advanced privilege level:

set advanced

3. For each data1 partition owned by the node that will be the passive node, assign it to the active node:

storage disk assign -force -data1 -owner active_node_name -disk disk_name

You do not need to include the partition as part of the disk name

4. For each data2 partition owned by the node that will be the passive node, assign it to the active node:

storage disk assign -force -data2 -owner active_node_name -disk disk_name

You do not need to include the partition as part of the disk name

5. Confirm that all of the partitions are assigned to the active node:

storage aggregate show-spare-disks

cluster1::*> storage agg:	regate show	-spare-disks		
Original Owner: cluster1-	-01			
Partitioned Spares			Local	
Local			Data	
Root Physical			2404	
Disk	Type	RPM Checksum	Usable	
Usable Size				
1.0.0	DCAC	7200 block	752 OCD	
0B 828.0GB	BSAS	7200 DIOCK	/33.0GB	
1.0.1	BSAS	7200 block	753.8GB	
73.89GB 828.0GB				
1.0.2	BSAS	7200 block	753.8GB	
0B 828.0GB				
1.0.3	BSAS	7200 block	753.8GB	
0B 828.0GB 1.0.4	BSAS	7200 block	753.8GB	
0B 828.0GB	DOAG	,200 DIOCK	755.000	
1.0.5	BSAS	7200 block	753.8GB	
0B 828.0GB				
1.0.6	BSAS	7200 block	753.8GB	
·				

0B 828.0GB			
1.0.7	BSAS	7200 block	753.8GB
0B 828.0GB			
1.0.8	BSAS	7200 block	753.8GB
0B 828.0GB	Dava	7000 1-11-	752 0CD
1.0.9 0B 828.0GB	BSAS	7200 block	753.8GB
1.0.10	BSAS	7200 block	753.8GB
0B 828.0GB			
1.0.11	BSAS	7200 block	753.8GB
0B 828.0GB			
Original Owner: cluster1-02			
Pool0			
Partitioned Spares			
-			Local
Local			
			Data
Root Physical Disk	Птто	RPM Checksum	IIgablo
Usable Size	Type	KFM CHECKSUM	USADIE
1.0.8	BSAS	7200 block	0B
73.89GB 828.0GB			
13 entries were displayed.			

Note that cluster1-02 still owns a spare root partition.

6. Return to administrative privilege:

```
set admin
```

7. Create your data aggregate, leaving at least one data partition as spare:

```
storage aggregate create new\_aggr\_name -diskcount number\_of\_partitions -node active node name
```

The data aggregate is created and is owned by the active node.

8. Alternatively, you can use ONTAP's recommend aggregate layout which includes best practices for RAID group layout and spare counts:

```
storage aggregate auto-provision
```

Remove ownership from a disk

ONTAP writes disk ownership information to the disk. Before you remove a spare disk or

its shelf from a node, you should remove its ownership information so that it can be properly integrated into another node.

What you'll need

The disk you want to remove ownership from must meet the following requirements:

· It must be a spare disk.

You cannot remove ownership from a disk that is being used in an local tier (aggregate).

- It cannot be in the maintenance center.
- · It cannot be undergoing sanitization.
- · It cannot have failed.

It is not necessary to remove ownership from a failed disk.

About this task

If you have automatic disk assignment enabled, ONTAP could automatically reassign ownership before you remove the disk from the node. For this reason, you disable the automatic ownership assignment until the disk is removed, and then you re-enable it.

Steps

1. If disk ownership automatic assignment is on, use the CLI to turn it off:

```
storage disk option modify -node node_name -autoassign off
```

- 2. If needed, repeat the previous step for the node's HA partner.
- 3. Remove the software ownership information from the disk:

```
storage disk removeowner disk name
```

To remove ownership information from multiple disks, use a comma-separated list.

Example:

```
storage disk removeowner sys1:0a.23, sys1:0a.24, sys1:0a.25
```

- 4. If the disk is partitioned for root-data partitioning, remove ownership from the partitions:
 - a. For ONTAP 9.10.1 and later, enter:

```
storage disk removeowner -disk disk name
```

b. For ONTAP 9.9.1 and earlier, enter both commands:

```
storage disk removeowner -disk disk_name -root true storage disk removeowner -disk disk_name -data true
```

Both partitions are no longer owned by any node.

5. If you previously turned off automatic assignment of disk ownership, turn it on after the disk has been removed or reassigned:

storage disk option modify -node node_name -autoassign on

6. If needed, repeat the previous step for the node's HA partner.

Copyright information

Copyright © 2023 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.