

MegaDash Integration Spec

For: Dean's main Claude (resuming Ecom/Reserve/ItemPrep/Receiving edits)

Purpose: Wire each dept app to export a standard payload that MegaDash_v1.0.html can ingest.

Status: MegaDash is built and ready. The four processors need one small addition each.

What to add to each app

Each app needs one button and one function. That's it — nothing else changes.

1. The export button (add to the tab bar or settings panel)

html

```
<button class="export-btn" onclick="exportForDash()"> 📄 Export for Dashboard</button>
```

Style to match the app's existing button patterns. Suggest placing it in the top-right of the results area or alongside the Copy button.

2. The export function (add to the `<script>` block)

Replace `DEPT_KEY`, `APP_VERSION`, the `units` line, `goal` line, and the `tabs` array with the correct values for each app. Details per app are in the table below.

javascript

```

function exportForDash() {
  const payload = {
    dept:      "DEPT_KEY",          // see table below – must be lowercase
    shift:     currentShift,        // variable already exists in each app
    date:      new Date().toISOString().slice(0, 10),
    exportedAt: Date.now(),
    units:     TOTAL_UNITS_VALUE,   // see table below
    goal:      GOAL_VALUE,          // see table below (0 if no goal set)
    tabs:      TABS_ARRAY,         // see table below
    roster:    currentRoster.length, // .length of the roster array in each app
    version:   "APP_VERSION"        // e.g. "2.3"
  };

  // Option A – download as .json file (works today, no hosting needed)
  const blob = new Blob([JSON.stringify(payload, null, 2)], { type: 'application/json' });
  const url  = URL.createObjectURL(blob);
  const a    = document.createElement('a');
  a.href     = url;
  a.download = payload.dept + '_' + payload.date + '_export.json';
  a.click();
  URL.revokeObjectURL(url);

  // Option B – copy payload code to clipboard (for paste into MegaDash)
  navigator.clipboard.writeText(JSON.stringify(payload)).then(() => {
    showToast('Payload copied – paste into Shift Dashboard');
  }).catch(() => {
    showToast('Downloaded as .json – drag into Shift Dashboard');
  });
}

```

3. Per-app substitutions

App	DEPT_KEY	units value	goal value	tabs array
Ecom v2.3	"ecom"	replenTotal	replenGoal	[{label:"Replenishment",units:replenTotal}, {label:"Putaway",units:putawayTotal}]
		+ putawayTotal	+ putawayGoal	
Reserve v1.4	"reserve"	pickTotal + replenTotal	pickGoal + replenGoal	[{label:"Picking",units:pickTotal}, {label:"Replenishment",units:replenTotal}]

App	DEPT_KEY	units value	goal value	tabs array
ItemPrep v1.9	"itemprep"	$\frac{\text{ilrTotal} + \text{ccTotal}}{\text{ccTotal}}$	$\frac{\text{ilrGoal} + \text{ccGoal}}{\text{ccGoal}}$	<code>[{label:"Item Level Receive",units:ilrTotal},{label:Code",units:ccTotal}]</code>
Receiving v1.6	"receiving"	lpnTotal	lpnGoal	<code>[{label:"LPN Receive",units:lpn</code>

Note: The variable names above (`replenTotal`, `pickTotal`, etc.) are representative — substitute the actual variable names used in each app's JS. The values already exist; this is just exposing them.

4. Add MegaDash to the Menu

In `Menu_v1.5.html`, add a fifth card to the `.grid` div. The grid is currently `grid-template-columns: 1fr 1fr` — either expand to a 5th card or change to 3-col for the new row. ▶

html

```
<button class="card card-megadash" onclick="openApp('MegaDash_v1.0.html')">
  <span class="card-version">v1.0</span>
  <div class="card-icon">📊</div>
  <div class="card-name">Shift Dashboard</div>
  <div class="card-sub">Cross-Dept · Leadership</div>
</button>
```

Add matching styles to Menu CSS:

css

```
.card-megadash { border-color: #534AB7; }
.card-megadash:hover { background: #1a1530; box-shadow: 0 0 0 3px rgba(83,74,18); }
body.light .card-megadash:hover { background: #f0eeff; }
.card-megadash .card-name { color: #A89FE8; }
```

5. File placement

All files must be in the same folder:

```
Menu_v1.5.html  
Ecom_v2.3.html  
Reserve_v1.4.html  
ItemPrep_v1.9.html  
Receiving_v1.6.html  
MegaDash_v1.0.html ← new
```

MegaDash will navigate back to `Menu_v1.5.html` via the ← Menu button. No other pathing changes needed.

6. Future: OneDrive/hosted auto-load

When hosting is available (GitHub Pages or shared folder), the export function can POST the payload to a shared endpoint instead of downloading. MegaDash already has the ingest logic ready — only the transport changes. The payload format stays the same.