11/30/23, 9:15 PM about:blank



Developing Back-End Apps with Node.js and Express Module 1 Cheat Sheet: Introduction to Server-Side JavaScript

```
Package/Method Description
                                                                           Code Example
                  http package is
                  used for
                  establishing
                  remote
                  connections to
                  a server or to
                  create a server
                  which listens to
                  client.
                  createServer -
                                    8.8
                  Takes a
1. const http = require('http');
                                    2. const requestListener = function(req, res) {
                  which takes
                                         res.writeHead(200);
                                         res.end('Hello, World!');
                  request and
                                    5. }
                  response
                                    6. const port = 8080;
                  parameters,
                                    7. const server = http.createServer(requestListener);
                  where request
                                    8. console.log('server listening on port: '+ port);
                  is the handle to
                                    9. server.listen(port);
                  the request
                                  Copied!
                  from the client
                  and response is
                  the handle to be
                  sent to the
                  client.
                  new Date()
                  method returns
                                    2. 2
                                    3. 3
                  the current date
                  as an object.
                  You can invoke
                                    1. module.exports.getDate = function getDate() {
new Date()
                  methods on the
                                           let aestTime = new Date().toLocaleString("en-US", {timeZone: "Australia/Brisbane"});
                                    2.
                  date object to
                                    3.
                                           return aestTime;
                                    4. }
                  format it or
                  change the
                                  Copied!
                  timezone.
                                    2. 2
                                    3. 3
                  The import
                                    5.5
                                    6.6
                  statement is
                                    7. 7
                  used to import
                                    8.8
                  modules that
                  some other

    // addTwoNos.mjs

import()
                  module has
                                    2. function addTwo(num) {
                  exported. A file
                                         return num + 4;
                                    3.
                  that includes
                  reusable code
                                    5. export { addTwo };
                  is known as a
                                    6. // app.js
                                    7. import { addTwo } from './addTwoNos.mjs';
                  module.
                                    8. // Prints: 8
                                    9. console.log(addTwo(4));
                                  Copied!
                                    1. 1
require()
                  The built-in
                                    2. 2
                  NodeJS method
                  require() is
                  used to
                                    1. module.exports = 'Hello Programmers';
                                    2. let msg = require('./messages.js');
                  incorporate
                                    3. console.log(msg);
                  external
                  modules that
                                  Copied!
                  are included in
                  different files.
```

about:blank 1/2

11/30/23, 9:15 PM about:blank

The require() statement essentially reads and executes a JavaScript file before returning the export object.

Changelog

Date	Version	Changed by	Change Description
04-07-2022	1.0	Pallavi	Initial version created
18-10-2022	1.2	Sapthashree K S	Cheatsheet updated
17-11-2022	1.3	K Sundararajan	IDSN logo updated based on Beta feedback
29-11-2022	1.4	K Sundararajan	Minor upates based on Beta feedback
04-05-2023	1.5	K Sundararajan	Updated some codes based on reviews

© IBM Corporation 2022. All rights reserved.

about:blank 2/2