ER-001

Sample Qualification Report — Energized Optical Evaluation

Illustrative report format showing the output of the HLG proprietary optical evaluation platform.

Sample document. Values shown are illustrative placeholders used to demonstrate report structure and are not measured results for any product or program.

1. Article Under Evaluation

Field	Entry
Article	Heated laminated transparency, sample coupon
Conductor format	Embedded tungsten wire, single heated zone
Aperture	Representative sample section
Supply condition	Program-defined nominal voltage
Standard applied	HLG-QS-1724, Revision A

2. Test Conditions

- Ambient baseline, de-energized.
- Steady-state energized condition at nominal supply.
- Recovery measurement following power removal.
- Repeat power cycles to establish repeatability.
- Electrical, thermal, and optical measurements recorded throughout.

3. Reported Measurements

Measurement	Reported as
Optical distortion	Full-aperture map plus critical viewing zone extract
Dynamic optical stability	Change from ambient baseline at steady state
Thermal uniformity	Distribution across heated field and bus bar zones
Repeatability	Cycle-to-cycle variation across the tested sequence
Recovery	Return toward baseline after power removal

4. Report Contents Delivered

- Configuration and as-tested record with lot traceability.
- Imaging data and analysis outputs.
- Zone-resolved optical and thermal results.
- Cycle history and repeatability summary.
- Engineering observations and recommended follow-on evaluation.

5. How the Report Is Used

Engineering reports of this type support product qualification, supplier qualification, comparative benchmarking, prototype evaluation, failure investigation, and design verification. Program-specific reports are issued confidentially to the requesting organization.

This document is provided for engineering information. Descriptions reflect development and evaluation capabilities and are not statements of certification, approval, or guaranteed performance. Application-specific performance is established by test on representative samples.