



Name: _____ Cohort/Batch: _____ Date: _____ Score: _____

ASP.NET CORE PRACTICE SHEET - 10 CONCEPTUAL Q&A

10 Q&A on pipeline, DI lifetimes, Minimal API, auth, and testing

TOTAL: 10 QUESTIONS

Q1 What is the ASP.NET Core request pipeline and how do you add middleware?

Threat Model

Q6 How do you add JWT Bearer authentication to ASP.NET Core?

Observability

Q2 What are the three DI service lifetimes and what are captive dependency risks?

Architecture

Q7 What is the Options pattern in ASP.NET Core configuration?

Lifecycle

Q3 How does ASP.NET Core attribute routing work?

Configuration

Q8 What is Entity Framework Core and how does Add-Migration work?

Compliance

Q4 What is the difference between [FromBody], [FromQuery], and [FromRoute]?

Hardening

Q9 What are action filters in ASP.NET Core and what can they do?

Testing

Q5 What is Minimal API in ASP.NET Core 6+ and when should you use it?

SSO / IdP

Q10 How do you write integration tests for ASP.NET Core?

Tuning



ANSWER KEY & EXPLANATORY SOLUTIONS

Comprehensive verified answers, best-practice configs, security controls & reference

VERIFIED SOLUTIONS

A1 The pipeline is a chain of

Mitigation

The pipeline is a chain of middleware delegates in Program.cs. app.UseRouting(), app.UseAuthentication(), and app.UseAuthorization() must be in that order. app.Use(async (ctx, next) => {...; await next(ctx)}) inserts custom middleware.

A6 Call

Observability

Call builder.Services.AddAuthentication().AddJwtBearer(opts => {opts.TokenValidationParameters = new() {ValidIssuer=..., IssuerSigningKey=...}}). Add app.UseAuthentication() and app.UseAuthorization() in the pipeline. Protect endpoints with [Authorize].

A2 Singleton lives for the app lifetime.

Primitives

Singleton lives for the app lifetime. Scoped lives per HTTP request. Transient is created fresh each injection. A captive dependency occurs when a Singleton injects a Scoped service the Scoped service is never disposed correctly. ASP.NET Core detects this at startup.

A7 Define a class MySettings with properties.

Automation

Define a class MySettings with properties. Call builder.Services.Configure<MySettings>(builder.Configuration.GetSection("MySettings")). Inject IOptions<MySettings> (singleton snapshot), IOptionsSnapshot<MySettings> (scoped, reloads per request), or IOptionsMonitor (live).

A3 [Route('api/users')] on a controller and

Hardening

[Route('api/users')] on a controller and [HttpGet('{id:int}')] on an action define the full route template. Route constraints like :int, :guid, and :minlength(3) validate segments. [ApiController] enforces model binding and returns 400 on validation failure.

A8 EF Core is Microsoft's ORM. DbContext

Governance

EF Core is Microsoft's ORM. DbContext represents a session with the database. Define DbSet<T> properties for each entity. dotnet ef migrations add AddUserTable generates a migration C# file based on the difference between the model and the last migration.

A4 [FromBody] reads from the JSON request

Gotchas

[FromBody] reads from the JSON request body (only one per action). [FromQuery] reads query string parameters. [FromRoute] reads named route template segments. Without explicit attributes, [ApiController] infers: complex types from body, simple types from query/route.

A9 IActionFilter runs OnActionExecuting (before

Assessment

IActionFilter runs OnActionExecuting (before the action) and OnActionExecuted (after). Use them for logging, validation, or caching. [ResponseCache], [ValidateAntiForgeryToken] are built-in filters. Register globally in AddControllers(opts => opts.Filters.Add(...)).

A5 Minimal API uses lambda-based route handlers

Federation

Minimal API uses lambda-based route handlers (app.MapGet('/users/{id}', (int id) => ...)) instead of controllers. It is less structured but has lower overhead and works well for microservices or simple CRUD APIs where the MVC controller ceremony is unnecessary.

A10 Use WebApplicationFactory<Program> to spin

Optimization

Use WebApplicationFactory<Program> to spin up the app in-process. Call factory.CreateClient() to get an HttpClient that sends requests to the test server. Override services with factory.WithWebHostBuilder(b => b.ConfigureTestServices(...)). No real port is needed.