



Name: _____ Cohort/Batch: _____ Date: _____ Score: _____

DJANGO PRACTICE SHEET - 10 CONCEPTUAL Q&A

10 Q&A on MTV, ORM, views, authentication, and REST framework

TOTAL: 10 QUESTIONS

Q1 What is Django's MTV architecture and how does it map to Model MVC?

map to Model

Q6 How does Django's permission system work?

Observability

Q2 How does Django's ORM work and how do you create a migration?

Architecture

Q7 What is Django middleware and how does the request/response cycle work?

Lifecycle

Q3 What is the difference between an FBV and a CBV in Django?

Django

Q8 What is template inheritance in Django and how does it work?

Template

Q4 How does Django URL routing resolve a request to a view?

Routing

Q9 How does Django caching work and what backends are available?

Testing

Q5 What is Django REST Framework (DRF) and what does a serializer do?

API / IDP

Q10 How do you write tests in Django?

Tuning



ANSWER KEY & EXPLANATORY SOLUTIONS

Comprehensive verified answers, best-practice configs, security controls & reference

VERIFIED SOLUTIONS

A1 Model handles data and business logic. Template

Mitigation

Model handles data and business logic. Template renders HTML. View acts as the controller it processes requests, queries the Model, and returns a Template response. The URL dispatcher maps URL patterns to View functions or class-based views.

A6 Django auto-creates add, change, delete, view permissions

Permissions

Django auto-creates add, change, delete, view permissions for every model. @login_required or LoginRequiredMixin enforces authentication. @permission_required('app.can_publish') or PermissionRequiredMixin checks named permissions stored in the auth_permission table.

A2 Define model classes with fields (CharField, IntegerField, etc.)

Primitives

Define model classes with fields (CharField, IntegerField, ForeignKey). Run python manage.py makemigrations to generate migration files from model changes, then migrate to apply them. Django tracks applied migrations in the django_migrations table.

A7 Middleware classes wrap the view. process_request runs

Information

Middleware classes wrap the view. process_request runs before the view (returning a response short-circuits the rest). process_response runs after. Built-in middleware handles sessions, CSRF tokens, authentication, and security headers.

A3 A Function-Based View is a plain Python

Hardening

A Function-Based View is a plain Python function taking a request and returning a response simple and explicit. A Class-Based View inherits from View (or ListView, CreateView etc.) and overrides get()/post() methods, enabling reuse via mixins.

A8 A base template defines named {% block %}

Governance

A base template defines named {% block %} areas. Child templates extend it with {% extends 'base.html' %} and override blocks with their own content. The template engine replaces blocks at render time, enabling DRY layouts across pages.

A4 Django iterates urlpatterns in the root urls.py,

Gotchas

Django iterates urlpatterns in the root urls.py, testing each path() or re_path() pattern. include() delegates to a nested urls.py. Named groups or path converters (<int:pk>) capture parts of the URL and pass them as kwargs to the view.

A9 Django's cache framework uses a unified API

Assessment

Django's cache framework uses a unified API (cache.get/set/delete). Backends include in-memory (LocMemCache), Redis (django-redis), Memcached, and database. @cache_page(60*15) caches entire view responses; template fragment caching and low-level API give finer control.

A5 DRF adds API tools on top of

Federation

DRF adds API tools on top of Django. A Serializer converts model instances to Python dicts (for JSON responses) and validates incoming dicts back to model instances. ModelSerializer auto-generates fields from the model definition.

A10 Subclass django.test.TestCase (wraps each test in a transaction)

Optimization

Subclass django.test.TestCase (wraps each test in a transaction that rolls back). Use self.client.get('/url/') to simulate HTTP requests. APIClient (DRF) sends JSON requests. Use factories or fixtures to create test data. Run with python manage.py test.