



Name: _____ Cohort/Batch: _____ Date: _____ Score: _____

NESTJS PRACTICE SHEET - 10 CONCEPTUAL Q&A

10 Q&A on modules, DI, guards, pipes, interceptors, and testing

TOTAL: 10 QUESTIONS

Q1 How does NestJS's modular architecture work?

Threat Model

Q6 What is a NestJS exception filter and how does it standardize error responses?

Q2 How does NestJS's dependency injection container work?

Q7 What are NestJS interceptors used for?

Lifecycle

Q3 What are NestJS decorators and how do they work?

Configuration

Q8 How do you integrate TypeORM with NestJS?

Compliance

Q4 How do NestJS Pipes work and how do you validate request bodies?

Requesting

Q9 How does NestJS support microservice communication?

Testing

Q5 What are NestJS Guards and how do you implement RBAC?

RBAC? IDP

Q10 How do you write unit tests in NestJS?

Tuning



ANSWER KEY & EXPLANATORY SOLUTIONS

Comprehensive verified answers, best-practice configs, security controls & reference

VERIFIED SOLUTIONS

A1 A Module groups related controllers and providers.

Mitigation

A Module groups related controllers and providers. `@Module({imports, controllers, providers, exports})` defines its boundaries. The AppModule is the root. Feature modules import other modules and export providers they want to share with importers.

A2 Providers declared in a module's providers array

Primitives

Providers declared in a module's providers array are added to the DI container. NestJS resolves constructor injection by type token. Provider scope can be DEFAULT (singleton per module), REQUEST (new instance per request), or TRANSIENT (new per injection).

A3 Decorators are TypeScript metadata annotations. `@Get('/path')`

Decorators are TypeScript metadata annotations. `@Get('/path')` stores route metadata on the method. `@Body()`, `@Param()`, `@Query()` bind request data. NestJS's RouterExplorer reads this metadata at startup to register Express/Fastify routes automatically.

A4 Pipes transform or validate data before it

Gotchas

Pipes transform or validate data before it reaches the handler. Global ValidationPipe with `whitelist:true` strips undeclared properties and transforms payloads. class-validator decorators (`@IsEmail()`, `@MinLength(8)`) on DTO classes define validation rules.

A5 A Guard implements CanActivate. Return true to

Federation

A Guard implements CanActivate. Return true to allow or false to deny. `@UseGuards(RolesGuard)` applies it to a controller or method. The guard reads `@Roles('admin')` metadata via Reflector and checks the authenticated user's roles against the required roles.

A6 Implement ExceptionFilter, annotate with

Observability

Implement ExceptionFilter, annotate with `@Catch(MyException)`, and define `catch(exception, host)`. It intercepts thrown exceptions and returns a structured JSON error response. Register globally with `app.useGlobalFilters(new MyFilter())` for consistent API error shapes.

A7 Interceptors wrap request handling before and after.

Automation

Interceptors wrap request handling before and after. The `intercept(ctx, next)` method calls `next.handle()` which returns an Observable. Use RxJS operators to transform the response (map), measure execution time, add caching, or log requests and responses.

A8 Import TypeOrmModule.forRoot(options) in AppModule

Governance

Import `TypeOrmModule.forRoot(options)` in AppModule. Import `TypeOrmModule.forFeature([UserEntity])` in the feature module to get a repository. Inject `InjectRepository(UserEntity)` private `userRepo: Repository<UserEntity>` into services.

A9 NestJS microservices use ClientProxy to send messages.

Assessment

NestJS microservices use ClientProxy to send messages and emit events. Transport strategies include TCP, Redis, NATS, Kafka, and RabbitMQ. `@MessagePattern('pattern')` on a handler receives messages. Both request-response and event-driven patterns are supported.

A10 Use Test.createTestingModule({providers: [MyService]})

Optimization

Use `Test.createTestingModule({providers: [MyService, {provide: Repo, useValue: mockRepo}]})`. This creates a mini DI container. Call `module.get(MyService)` to retrieve the instance. Jest spies and mocks replace real dependencies.